

# Lecture 02 - Image Filtering


Prof. André Gustavo Hochuli

[gustavo.hochuli@pucpr.br](mailto:gustavo.hochuli@pucpr.br)

[aghochuli@ppgia.pucpr.br](mailto:aghochuli@ppgia.pucpr.br)



# Topics

- **Discussion of Practice 01**
- **Image Filtering**
  - **Convolution**
  - **Mean, Median, Gaussian Filters**
- **Practice**




# Image Filtering

- Image Enhancement
- Noise Reduction
- Mathematical Operations



# Convolution


- Slides a kernel (a.k.a convolution filter) in the entire image
- Transforming the pixel in the center of the kernel by the weights of its neighbors



# Mean Filter

- Replaces the center pixel with the mean of its neighborhood
- Spreads the outlier value to its neighbors
- Details are smoothed


```
kernel_size = (3,3)
im_blur = cv2.blur(im_einstein,kernel_size)
plot_sidebyside([im_einstein,im_blur],['Noisy','Mean Filter'],colormap='gray')
```



# Median Filter

- Replaces the center pixel with by a median of its neighborhood
- Preserves more details when compared to the mean filter


```
im_blur = cv2.medianBlur(im_einstein,3)  
plot_sidebyside([im_einstein,im_blur],['Noisy','Median Filter'],colormap='gray')
```



# Gaussian Filter

- Gaussian distribution of pixels
- The kernel is composed of probabilities
- Weighted Mean
- The standard deviation determines the blur degree

```
im_blur = cv2.GaussianBlur(im_einstein,(3,3),0)  
plot_sidebyside([im_einstein,im_blur],['Noisy','Gaussian Filter'],colormap='gray')
```






# Bilateral Filter

- Gaussian Distribution based
- Add Normalization Factors and Range Weight
- Preserve details

```
# Apply bilateral filter with d = 15,  
# sigmaColor = sigmaSpace = 75.  
im_blur = cv2.bilateralFilter(im_einstein,9,75,75)  
plot_sidebyside([im_einstein,im_blur],['Noisy','BiLateral Filter'],colormap='gray')
```






# Bilateral Filter

- Gaussian Distribution based (spacial and pixel intensity)
- Add Normalization Factors and Range Weight
- Preserve details

```
# Apply bilateral filter with d = 15,  
# sigmaColor = sigmaSpace = 75.  
im_blur = cv2.bilateralFilter(im_einstein,9,75,75)  
plot_sidebyside([im_einstein,im_blur],['Noisy','BiLateral Filter'],colormap='gray')
```



# Practice

[Link: Practice 02](#)