Queue

FIFO → First In First Out

push()
pop()
front()
size()
isEmpty()

Queue using linked list.

```
class Queue {
    private:
        LinkedList ll;
    public:
        push()
        pop()
        front()
        size()
        isEmpty()
}
```

Queue.
O(1) ← push()
O(1) ← pop()
O(1) ← front()

LL (with Tail ptr)
push at the end
delete at the beginning
return head value

push(1)
push(2)
push(3)
→ front() → 1
→ pop()
push(4)
pop()
pop()
pop()

Queue Using static Array

```
class Queue {
    private:
        int arr[100];

    public:
        .
        .
        .
        .
}
```

push(1)
push(2)
push(3)
→ front() → 1
→ pop()
push(4)
→ pop() front() → 2
pop() front() → 3
pop() rear() → 4
pop()

rear: 0 1 2 3


```
[ rear = rear+1 ]   X
→ [ rear = (rear+1) % 100 ]
```

front = front+1 X
→ front = (front+1) % 100 ✓



Reverse a Queue.

Queue: front → 4, 3, 1, 10, 2, 6

O/P: 6, 2, 10, 1, 3, 4

→ 4, 3, 1, 10, 2, 6

4, 3, 1, 10, 2, 6

6, 2, 10, 1, 3, 4

4, 3, 1, 10, 2, 6

6, 2, 10, 1, 3, 4

TC= O(n)
AS = O(n).

"1010"
$2^3\ 2^2\ 2^1\ 2^0$

$0*2^3 + 1*2^2 + 0*2^1 + 1*2^0 = 0+2+0+8 = 10$

Decimal	Binary
0	0000
1	0001
2	0010
3	0011
4	0100
5	0101
6	0110
7	0111
8	1000
9	1001
10	1010
11	1011
12	1100
13	1101
14	1110
15	1111

1 → 01
2 → 10
3 → 11
4 → 100
5 → 101
6 → 110
7 → 111
8 → 1000
9 → 1001
10 → 1010

value = 13

TC= O(log n)
AS = O(1)

BF: TC= O(n log n)
AS = O(1)

n = 10

Queue: 1, 10, 11, 100, 101, 110, 111, 1000, 1001, 1010, 1011

Ans: 1, 10, 11, 100, 101

TC = O(n)
AS = O(n) = O(n log n).

geeksforgeeks.

geeks ...

i/p: a a b c
o/p: a # b b

i/p: a a c b
o/p: a # c c

a a b c
a # b b

a a b c
a # c c

BF: TC= O(n)
AS = O(1)

i: 0 → n-1
j: 0 → i

a a b c b d d c a f
a # b b c

a → 2
b → 2
c → 1

a a b c b d d c a f
a # b b c c c # # f

a → 2 3
b → 2
c → 2
d → 2
f → 1

a, b, c, d, f