1, 2, 4, 8, 16 - - - - - (?)

n

assume $2^{n-1} = n$

$i = 2^{n-1} = n$

$n-1 = \log_2 n$

$\sqrt{n}$

$n = 10^6$

$\sqrt{n} = 10^3$ $\log n = 6$

Array:



→ Contiguous Memory Allocation.



index < n-1 > max

$x + 5^{th}$

Random Access: O(1)

→ Insert at the end : → O(1)

Insert at the beginning: O(n)

Insert at the middle: O(n)

Del from the end: O(1)

Del from the beginning: O(n)

Del from the middle: O(n)

Disadv.

→ Insertion from the beginning is costly

Adv.

1) Random access

2) Cache friendly

1
2
4
8
16
32
64
128
256

[5, 4, 2, 3] o/1 = 1

[0, -10, 1, 3, -20] o/1 = 2

[1, 2, 3, 4, 5] o/1 = 4

BF:

TC: $O(n^2)$

AS: O(1)

```
for (int i = 1; i < n-1; i++) {
    linear search for i
    if found, move ahead
    otherwise return i+1
}
return n+1;
```

Sorting: [-20, -10, 0, 1, 3]

[2, 3, 4, 5]

[-20, -10, 0, 1, 1, 2, 3, 5]

val = 2 to 4

TC: $O(n \log n + n) = O(n \log n)$

AS: O(1)

Hashing/Hashmap/Set

arr [-10, -10, 0, 5, 1, 1, 2, 3, 5]



o/1 = 4.

TC: O(n)

AS: O(n)

Binding Trick

o/1 = 4

Use the i^{th} bucket to store the info whether $(i+1)$ is present in the array or not.

TC: O(n)

AS: O(1)

---

rows:

cols:



---

zero+num=num2 → true
zero+num2=num → false



[5, 3, 2, 4, 6]

Subarrays:

[5, 3] [5, 3, 2] [5, 2, 4]

[4] [] [3, 5] [5, 2, 3]

Subsequence:

[5] [5, 3] [5, 2] [3, 4, 2]

[1, 2, 3, -2, 5] o/1 = 9 6/8/24 (?)

[-1, -3, -3, -5] o/1 = -1