print(i) i = 1 → n

Break the problem into smaller & smaller sub problems

print(1, n) → 1 → print(2, n)

```
void printTwoNth(int start, int n) {
  // base case ??
  cout << start << endl;
=> printTwoNth(start + 1, n);
}
```

n = 5

start = 1
start = 2
start = 3
start = 4
start = 5

1 2 3 4 5

print(n) → n print(n-1)

Tail Recursion

when the last call is the last thing your func does

a → b → c

fact(n) = n * fact(n-1)

Tower of Hanoi

n=1

A B C

n=2

A B C

n=3

A B C

(n, A, B, C) → (n-1, A, C, B) + 1 + (n-1, B, A, C)

n-1 disk from A to C

n=3
n-1=2
n-2=1
n

A B C

T(n) = 2T(n-1) + c

H = n

T(n) → c
T(n-1) → 2c
T(n-1) T(n-1) → 4c

c + 2c + 4c + 8c ---

n-times

a = c
b = 2
n = n

c(2^n - 1) / 2 - 1 = TC: O(2^n)

```
// TC: O(n)
// SC: O(n)
int towerOfHanoiOptimal(int n) {
  if (n == 0) {
    return 0;
  }

  // int result = towerOfHanoiOptimal(n - 1);
  // result++;
  // result += towerOfHanoiOptimal(n - 1);
  return 2*towerOfHanoiOptimal(n - 1) + 1;
}
```

a n=3 3
b n=2 1
c n=1 0
d n=0

Possible words from Phone Digits

[2, 3]

[2, 3, 4]

abc def ghi

[2, 3] → [2, 3]

[ad, ae, af
bd, be, bf
cd, ce, cf]

abc def ghi

[2, 3, 4]

count = 3*3*3 = 27
res = [adg, adh, adi ...]

[2,3,4]

[3,4] [4]

[] [] []

abc def

[2, 3]

count = 3*3 = 9
res = [ad, ae, af
bd, be, bf
cd, ce, cf]

```
void possibleWordsFromPhoneDigitsHelper(int i, vector<int> &arr, string &curr, vector<string> &mp){
    if(i == arr.size()){
        result.push_back(curr);
        return;
    }

    // 2 string word = mp[arr[i]];

    for(int ch : word ){
        curr.push_back(ch);
        possibleWordsFromPhoneDigitsHelper(i + 1, arr, curr, result);
        curr.pop_back();
    }
}
```

[2,3]

count = 3*3 = 9
res = [ad, ae, af ...]

i = 0 curr = abc
i = 1 curr = adf
i = 1 curr = def
i = 2 i = 2 i = 2

H = n

T(n) → c
T(n-1) T(n-1) T(n-1) T(n-1) → 4c
→ 4^n c

TC = O(4^n)

AS =