

# NLP - Fake news detection

Simbiat Musa    Georg F.K. Höhn

Ironhack

19 June 2025

# Project overview

## Given

- ▶ dataset of headlines annotated as fake (0) or real (1)

## Aim

- ▶ classify news headlines in unseen data (using machine learning)

## Deliverables

- ▶ Python pipeline (+ csv with model training results)
- ▶ csv with predictions for test set

Data overview

Methodology

Training results

Conclusion

## Data overview

- ▶ 34152 rows of annotated data
  - ▶ fake news: 17572
  - ▶ real news: 16580
- ▶ relatively balanced

## Word cloud for data annotated as real




Figure 1: Word cloud for real headlines



## Methodology



# Structure

- ▶ one main .py file for data exploration, model experimentation and output generation
- ▶ helper.py with functions for
  - ▶ cleaning strings
  - ▶ generate, print and save model evaluations (to csv)
  - ▶ removing stop words (not needed with TF-IDF vectoriser)
  - ▶ lemmatizer (currently not used)
  - ▶ huggingface pipeline for transformer models

# General pipeline

- ▶ EDA
- ▶ clean data (generate new columns)
- ▶ train-test split (20% test size)
- ▶ vectorise train and test sets
- ▶ train (and tune?) models
- ▶ compare based on test accuracy
- ▶ run best model(s) on target data and save
- ▶ (run best models of different types on target data and calculate inter-annotator agreement)

## Vectorisation

- ▶ TF-IDF
- ▶ GloVE (glove-wiki-gigaword-100)

## ML-algorithms

- ▶ Logistic Regression  
(`sklearn.linear_model.LinearRegression`)
- ▶ Random Forest  
(`sklearn.ensemble.RandomForestClassifier`)
- ▶ KNN (`sklearn.neighbors.KNeighborsClassifier`)
- ▶ XGBoost (`xgboost.XGBClassifier`)

# Regarding transformer models

- ▶ tried pipelines with
  - 1) jy46604790/Fake-News-Bert-Detect
  - 2) omykhailiv/bert-fake-news-recognition
- ▶ both performed abysmally: everything is fake, see result for 1
- ▶ over-sensitive? issue with our data pre-processing?




Figure 3: jy46604790/Fake-News-Bert-Detect

## Training results

model_id	params	acc_train	accuracy
logreg_lemma	miter=500	0.9209	0.9133
xgb_lemma	est=500,depth=100,lr=0.3, $\alpha$ =0.1	0.9963	0.9130
logreg_final	miter=500	0.9172	0.9084
logreg_1000	miter=1000	0.9172	0.9084
xgb_final	est=500,depth=100,lr=0.3, $\alpha$ =0.1	0.9899	0.9065
xgb	est=500,depth=200,lr=0.07, $\alpha$ =0.1	0.9896	0.9037
xgb_2	est=200,depth=0,lr=0.1	0.9896	0.9026
rndforest_lemma	est=300,minleaf=2	0.9409	0.9002
xgb_2	est=200,depth=50,lr=0.04	0.9407	0.8971
rndforest_final	est=300,minleaf=2	0.9382	0.8949
xgb_1	defaults	0.9002	0.8807
logreg_glove	miter=500	0.8689	0.8703
rndforest_2	est=300,depth=30	0.8677	0.8418
xgb_2	est=10,depth=50,lr=0.04	0.8611	0.8371
knn_3	k=3	0.9154	0.8172
knn_5	k=5	0.8829	0.8037
knn_3_lemma	k=3	0.8901	0.7993
knn_10	k=10	0.8158	0.7804
omykhailiv	defaults	0.5140	0.5166
jy46604790	defaults	0.5140	0.5166

- ▶ best performing: logistic regression model with lemmatized dataset
  - ▶ max-iterations did not seem to make a difference
- ▶ xgb and RandomForest very close by
  - ▶ but: high risk of overfitting
  - ▶ longer training times/higher complexity
- ▶ knn not performing very well
  - ▶ using lemmatized dataset actually leads to drop in accuracy

# Confusion matrices LogReg




Figure 4: Confusion matrix for logistic regression model




Figure 5: LogReg lemmatized



# Confusion matrices XGBoost




Figure 6: XGB model




Figure 7: XGB lemmatized

# Confusion matrices RandomForest




Figure 8: RandomForest




Figure 9: RandomForest lemmatized

# Confusion matrices KNN




Figure 10: KNN, k=3




Figure 11: KNN lemmatized

## Conclusion

- ▶ logistic regression model offers best performance

## Collaboration

- ▶ using py files to avoid notebook consistency issues with git
- ▶ # %: useful VS Code option for generating jupyter-like cells

## Outlook/reflection

- ▶ further experimentation with vectoriser settings
- ▶ actually implement lemmatisation (oops)
- ▶ some confusion in our raw performance results.csv
  - ▶ some RandomForest models seemed to perform better than final model, but probably due to earlier mistakes in preprocessing?
  - ▶ lesson: also note changes to preprocessing or cleanly reset logging files

Thanks for your attention!