

How to Solve a Linear System

Goran Flegar


Hartwig Anzt, Yen-Chen Chen, Terry Cojean, Jack Dongarra, Nick Higham, Pratik Nayak, Enrique S. Quintana-Ortí, Mike Tsai




- Real-world problem transformed into a linear system via:
 - PDE discretizations, graph representations
 - Large number of unknowns (1M+, full matrix 8TB)
 - Most matrix elements are zero



- Real-world problem transformed into a linear system via:
 - PDE discretizations, graph representations
 - Large number of unknowns (1M+, full matrix 8TB)
 - Most matrix elements are zero
- Possible approach: iterative methods
 - Krylov-subspace based linear solvers
 - SpMV
 - BLAS-1 operations
 - Sparse matrix formats & SpMV
 - accelerate each iteration of the solver
 - Preconditioners
 - reduce the number of iterations




- Real-world problem transformed into a linear system via:
 - PDE discretizations, graph representations
 - Large number of unknowns (1M+, full matrix 8TB)
 - Most matrix elements are zero
- Possible approach: iterative methods
 - Krylov-subspace based linear solvers
 - SpMV
 - BLAS-1 operations
 - Sparse matrix formats & SpMV
 - accelerate each iteration of the solver
 - Preconditioners
 - reduce the number of iterations
 - Special hardware (e.g. GPUs)
 - Probably not a good idea to implement everything from scratch...



- Real-world problem transformed into a linear system via:
 - PDE discretizations, graph representations
 - Large number of unknowns (1M+, full matrix 8TB)
 - Most matrix elements are zero
- Possible approach: iterative methods
 - Krylov-subspace based linear solvers
 - SpMV
 - BLAS-1 operations
 - Sparse matrix formats & SpMV
 - accelerate each iteration of the solver
 - Preconditioners
 - reduce the number of iterations
 - Special hardware (e.g. GPUs)
 - Probably not a good idea to implement everything from scratch...
 - Use a library instead:







- Real-world problem transformed into a linear system via:
 - PDE discretizations, graph representations
 - Large number of unknowns (1M+, full matrix 8TB)
 - Most matrix elements are zero
- Possible approach: iterative methods
 - Krylov-subspace based linear solvers
 - SpMV
 - BLAS-1 operations
 - Sparse matrix formats & SpMV
 - accelerate each iteration of the solver
 - Preconditioners
 - reduce the number of iterations
 - Special hardware (e.g. GPUs)
 - Probably not a good idea to implement everything from scratch...
 - Use a library instead:





The Ginkgo library

- Linear operator algebra library:
 - Matrix formats, preconditioners, (Krylov) solvers

Joint effort: Innovative Computing Lab at University of Tennessee, Knoxvile; Karlsruhe Institute of Technology; University Jaume I









The Ginkgo library

- Linear operator algebra library:
 - Matrix formats, preconditioners, (Krylov) solvers
- Goals:
 - Backends for various devices (executors)
 - Easy composability even when using building blocks from a different category (e.g. using a matrix or a solver as a preconditioner)
 - Easy extensibility
 - Support for matrix-free methods

Joint effort: Innovative Computing Lab at University of Tennessee, Knoxvile; Karlsruhe Institute of Technology; University Jaume I







Matrix-vector product

$$x = Ab$$

Matrix-vector product

Preconditioner

$$x = Ab$$

$$x = M^{-1}b$$

$$M \approx A$$

Matrix-vector product

Preconditioner

$$x = Ab$$

$$x = M^{-1}b$$

$$M \approx A$$
$$M^{-1} = \Pi(A)$$

Matrix-vector product

Preconditioner

Solver

Ax = b

$$x = Ab$$

$$x = M^{-1}b$$

$$M \approx A$$
$$M^{-1} = \Pi(A)$$

Matrix-vector product

Preconditioner

Solver

$$x = Ab$$

$$x = M^{-1}b$$

$$Ax = b$$
$$x = Sb$$

$$M \approx A$$
$$M^{-1} = \Pi(A)$$

$$S = A^{-1}$$

Matrix-vector product

Preconditioner

Solver

$$x = Ab$$

$$x = M^{-1}b$$

$$Ax = b$$
$$x = Sb$$

$$M \approx A$$
$$M^{-1} = \Pi(A)$$

$$S = A^{-1}$$
$$S = \Sigma(A)$$

Matrix-vector product

Preconditioner

Solver

$$x = Ab$$

$$x = M^{-1}b$$

$$Ax = b$$

$$x = Sb$$

$$M \approx A$$
$$M^{-1} = \Pi(A)$$

$$S = A^{-1}$$
$$S = \Sigma(A)$$

All of them can be expressed as:

applications of linear operators* (LinOp)

$$L: \mathbb{F}^m \to \mathbb{F}^n$$

* can be realized as a (non-linear) approximation



Matrix-vector product

Preconditioner

Solver

$$(x = Ab)$$

$$\boxed{x = M^{-1}b}$$

$$Ax = b$$

$$x = Sb$$

$$M \approx A$$

$$M^{-1} = \Pi(A)$$

$$S = A^{-1}$$
$$S = \Sigma(A)$$

All of them can be expressed as:

- applications of linear operators* (LinOp)
- (non-linear) transformations applied to linear operators (Factory)

$$L: \mathbb{F}^m \to \mathbb{F}^n$$

$$\Phi: \mathbb{L}^{mn}(\mathbb{F}) \to \mathbb{L}^{kl}(\mathbb{F})$$

* can be realized as a (non-linear) approximation

 Solving a symmetric positive definite linear system using the conjugate gradient (CG) solver, preconditioned with a block-Jacobi (BJ) preconditioner, with a system matrix stored in CSR format



- Solving a symmetric positive definite linear system using the conjugate gradient (CG) solver, preconditioned with a block-Jacobi (BJ) preconditioner, with a system matrix stored in CSR format
- 1. Read the system matrix operator, right hand side and initial guess from file, standard input, or use existing data from the application

- Solving a symmetric positive definite linear system using the conjugate gradient (CG) solver, preconditioned with a block-Jacobi (BJ) preconditioner, with a system matrix stored in CSR format
 - 1. Read the system matrix operator, right hand side and initial guess from file, standard input, or use existing data from the application
 - 2. Build the block-Jacobi preconditioner factory (no computation, binding parameters)

A_{CSR} b_D x_D

BJ

- Solving a symmetric positive definite linear system using the conjugate gradient (CG) solver, preconditioned with a block-Jacobi (BJ) preconditioner, with a system matrix stored in CSR format
- 1. Read the system matrix operator, right hand side and initial guess from file, standard input, or use existing data from the application
- 2. Build the block-Jacobi preconditioner factory (no computation, binding parameters)
- 3. Use the preconditioner factory to build the preconditioned conjugate gradient factory (no computation, binding parameters)

A_{CSR} b_D x_D

BJ

 CG_{BJ}

- Solving a symmetric positive definite linear system using the conjugate gradient (CG) solver, preconditioned with a block-Jacobi (BJ) preconditioner, with a system matrix stored in CSR format
- 1. Read the system matrix operator, right hand side and initial guess from file, standard input, or use existing data from the application

 $A_{CSR} b_D x_D$

2. Build the block-Jacobi preconditioner factory (no computation, binding parameters)

BJ

3. Use the preconditioner factory to build the preconditioned conjugate gradient factory (no computation, binding parameters)

- CG_{BJ}
- 4. Generate the solver operator from the system matrix using the solver factory (preprocessing needed for the solver and preconditioner)
- $S_A = CG_{BJ}(A_{CSR})$

- Solving a symmetric positive definite linear system using the conjugate gradient (CG) solver, preconditioned with a block-Jacobi (BJ) preconditioner, with a system matrix stored in CSR format
- 1. Read the system matrix operator, right hand side and initial guess from file, standard input, or use existing data from the application

 A_{CSR} b_D x_D

2. Build the block-Jacobi preconditioner factory (no computation, binding parameters)

BJ

3. Use the preconditioner factory to build the preconditioned conjugate gradient factory (no computation, binding parameters)

- CG_{BJ}
- 4. Generate the solver operator from the system matrix using the solver factory (preprocessing needed for the solver and preconditioner)
- $S_A = CG_{BJ}(A_{CSR})$


5. Solve the system (actual computation)

 $x_D = S_A b_D$


Example source code

```
int main() {
  // Instantiate a CUDA executor
  auto gpu = gko::CudaExecutor::create(0, gko::OmpExecutor::create());
  // Read data
  auto A = gko::read<gko::matrix::Csr<>>(std::cin, gpu);
  auto b = gko::read<gko::matrix::Dense<>>(std::cin, gpu);
  auto x = gko::read<gko::matrix::Dense<>>(std::cin, gpu);
  // Create the solver
  auto solver = gko::solver::Cg<>::build()
    .with preconditioner(
      gko::preconditioner::Jacobi<>::build().with_max_block_size(32).on(gpu))
    .with criteria(
        gko::stop::Iteration::build().with_max_iters(20u).on(gpu),
        qko::stop::ResidualNormReduction<>::build()
          .with_reduction_factor(1e-15).on(gpu))
    .on(gpu);
  // Solve system
  solver->generate(give(A))->apply(lend(b), lend(x));
  // Write result
  write(std::cout, lend(x));
```

Library features



Library features: extensibility




users can provide new matrices, solvers, preconditioners, stopping criteria, loggers

Without recompiling the library!



- Real-world problem transformed into a linear system via:
 - PDE discretizations, graph representations
 - Large number of unknowns (1M+, full matrix 8TB)
 - Most matrix elements are zero
- Possible approach: iterative methods
 - Krylov-subspace based linear solvers
 - SpMV
 - BLAS-1 operations
 - Sparse matrix formats & SpMV
 - accelerate each iteration of the solver
 - Preconditioners
 - reduce the number of iterations
 - Special hardware (e.g. GPUs)
 - Probably not a good idea to implement everything from scratch...
 - Use a library instead:





$$Ax = b, \ A \in \mathbb{R}^{n \times n}$$



$$Ax = b, A \in \mathbb{R}^{n \times n}$$

$$M^{-1}Ax = M^{-1}b$$

Replace the original system with an equivalent preconditioned system

$$Ax = b, A \in \mathbb{R}^{n \times n}$$

$$M^{-1}Ax = M^{-1}b$$

Replace the original system with an equivalent preconditioned system

$$M \approx A$$
 M^{-1} easy to compute

$$Ax = b, \ A \in \mathbb{R}^{n \times n}$$



$$M^{-1}Ax = M^{-1}b$$

Replace the original system with an equivalent preconditioned system

$$M \approx A$$

$$M \approx A$$
 M^{-1} easy to compute



Do not compute the preconditioned system matrix explicitly!

$$Ax = b, A \in \mathbb{R}^{n \times n}$$



$$M^{-1}Ax = M^{-1}b$$

Replace the original system with an equivalent preconditioned system

$$M \approx A$$

$$M^{-1}$$
 easy to compute



$$y := (M^{-1}A)x$$

Do not compute the preconditioned system matrix explicitly!

$$Ax = b, A \in \mathbb{R}^{n \times n}$$



$$M^{-1}Ax = M^{-1}b$$

Replace the original system with an equivalent preconditioned system

$$M \approx A$$





Do not compute the preconditioned system matrix explicitly!

$$y := (M^{-1}A)x$$

$$z := Ax$$

$$y := M^{-1}z$$

Preconditioner application

$$Ax = b, A \in \mathbb{R}^{n \times n}$$



$$M^{-1}Ax = M^{-1}b$$

Replace the original system with an equivalent preconditioned system

$$M \approx A$$

$$M^{-1}$$
 easy to compute



 $y := (M^{-1}A)x$

Do not compute the preconditioned system matrix explicitly!

Generate the preconditioner matrix, and store it in a form suitable for application

$$A \rightsquigarrow M^{-1}$$

Preconditioner setup

$$z := Ax$$

$$y := M^{-1}z$$

Preconditioner application

$$Ax = b, A \in \mathbb{R}^{n \times n}$$



$$M^{-1}Ax = M^{-1}b$$

Replace the original system with an equivalent preconditioned system

$$M \approx A$$

$$M^{-1}$$
 easy to compute




 $y := (M^{-1}A)x$

Do not compute the preconditioned system matrix explicitly!

Generate the preconditioner matrix, and store it in a form suitable for application

$$A \rightsquigarrow M^{-1}$$


Generation via factory



Linear operator application



Example: Block-Jacobi preconditioning



- Block-Jacobi preconditioning
 - Use only diagonal blocks for approximation


$$\operatorname{diag}(A) = [D_1, \dots, D_k]$$

$$M := \operatorname{diag}(D_1, \dots, D_k)$$

Anzt, Dongarra, Flegar, Quintana-Ortí, Variable-size batched Gauss—Jordan elimination for block-Jacobi preconditioning on graphics processors, ParCo


Benefits of block-Jacobi


- 56 matrices from SuiteSparse with inherent block structure
- MAGMA-sparse open source library
 - IDR solver
 - Supervariable agglomeration
 - Detects block structure of the matrix
- Improves the robustness of the solver



Benefits of block-Jacobi


- 56 matrices from SuiteSparse with inherent block structure
- MAGMA-sparse open source library
 - IDR solver
 - Supervariable agglomeration
 - Detects block structure of the matrix
- Improves the robustness of the solver
- Improves convergence of the solver









Complete solver runtime




Chebyshev3




nd24k




G3_circuit



bcsstk38



ship_003





Preconditioner is an approximation of the system matrix

- Applying a preconditioner inherently carries an error
- For block-Jacobi the relative error of z is usually around 0.01-0.1

$$z := M^{-1}y \approx A^{-1}y$$



Preconditioner is an approximation of the system matrix

- Applying a preconditioner inherently carries an error
- For block-Jacobi the relative error of z is usually around 0.01-0.1

$$z := M^{-1}y \approx A^{-1}y$$

Preconditioner application is memory bounded

- Most of the cost comes from reading the matrix from memory
- Idea: use lower precision to store the matrix

Preconditioner is an approximation of the system matrix

- Applying a preconditioner inherently carries an error
- For block-Jacobi the relative error of z is usually around 0.01-0.1

$$z := M^{-1}y \approx A^{-1}y$$

Preconditioner application is memory bounded

- Most of the cost comes from reading the matrix from memory
- Idea: use lower precision to store the matrix

Adaptive precision in inversion-based block-Jacobi:

- All computation is done in double precision
- Preconditioner matrix is stored in lower precision, with roundoff error "u"
- Frror bound:

$$\frac{||\delta z_i||}{||z_i||} \lesssim (c_i \kappa(D_i) u_d + u) \kappa(D_i)$$



Preconditioner is an approximation of the system matrix

- Applying a preconditioner inherently carries an error
- For block-Jacobi the relative error of z is usually around 0.01-0.1

$$z := M^{-1}y \approx A^{-1}y$$

Preconditioner application is memory bounded

- Most of the cost comes from reading the matrix from memory
- Idea: use lower precision to store the matrix

Adaptive precision in inversion-based block-Jacobi:

- All computation is done in double precision
- Preconditioner matrix is stored in lower precision, with roundoff error "u"
- Error bound:

$$\frac{||\delta z_i||}{||z_i||} \lesssim (c_i \kappa(D_i) u_d + u) \kappa(D_i)$$

Assuming the preconditioner block is relatively well conditioned

- The error is determined by the product of u, and the condition number
- Choose the precision for each block independently, such that at least 1 digit of the result is correct



Experimental results

Determining the precision:


$$\begin{cases} \text{fp16} & \text{if } 0 < \kappa_1(D_i) \le 10^2, \\ \text{fp32} & \text{if } 10^2 < \kappa_1(D_i) \le 10^6, \text{ and} \\ \text{fp64} & \text{otherwise,} \end{cases}$$

Experimental results

Determining the precision:

$$\begin{cases} \text{fp16} & \text{if } 0 < \kappa_1(D_i) \le 10^2, \\ \text{fp32} & \text{if } 10^2 < \kappa_1(D_i) \le 10^6, \text{ and} \\ \text{fp64} & \text{otherwise,} \end{cases}$$

% of diagonal blocks stored in each precision *:




* Prototype implementation in MATLAB, Results on 63 matrices from SuiteSparse

Experimental results


Determining the precision:

$$\begin{cases} \text{fp16} & \text{if } 0 < \kappa_1(D_i) \le 10^2, \\ \text{fp32} & \text{if } 10^2 < \kappa_1(D_i) \le 10^6, \text{ and} \\ \text{fp64} & \text{otherwise,} \end{cases}$$



Usually < 5% iteration increase

% of diagonal blocks stored in each precision *:



* Prototype implementation in MATLAB, Results on 63 matrices from SuiteSparse

Energy efficiency of adaptive precision block-Jacobi

Memory access is an order of magnitude more expensive than computation! [Shalf 2013]



Energy efficiency of adaptive precision block-Jacobi

Memory access is an order of magnitude more expensive than computation! [Shalf 2013]

Energy model assumptions:

- Accessing 1 bit of data has a cost of 1 (energy unit)
- Disregard energy cost of arithmetic operations
- Total energy cost of each iteration:

vector memory transfers +
$$\underbrace{(2n + n_z) \cdot \text{fp64} + (n + n_z) \cdot \text{int32}}_{\text{CSR-SpMV memory transfers}} + \underbrace{2n \cdot \text{fp64} + \sum_{i=1}^{N} m_i^2 \cdot \text{fpxx}_i}_{\text{preconditioner memory transfers}}$$

Energy efficiency of adaptive precision block-Jacobi


Memory access is an order of magnitude more expensive than computation! [Shalf 2013]

Energy model assumptions:

- Accessing 1 bit of data has a cost of 1 (energy unit)
- Disregard energy cost of arithmetic operations
- Total energy cost of each iteration:

$$\underbrace{14n \cdot \text{fp64}}_{\text{vector memory transfers}} + \underbrace{(2n + n_z) \cdot \text{fp64} + (n + n_z) \cdot \text{int32}}_{\text{CSR-SpMV memory transfers}} + \underbrace{2n \cdot \text{fp64} + \sum_{i=1}^{N} m_i^2 \cdot \text{fpxx}_i}_{\text{preconditioner memory transfers}}$$

Predicted energy savings of adaptive precision block-Jacobi:



Overflow and underflow

- Storing the block in lower precision can cause underflow or overflow in some values.
- This is not accounted for by the numerical analysis shown in the previous slides


Overflow and underflow

- Storing the block in lower precision can cause underflow or overflow in some values.
- This is not accounted for by the numerical analysis shown in the previous slides
- Two possible solutions:
 - 1. Check the condition number of the low precision block to verify there were no catastrophic overflows or underflows.




Overflow and underflow

- Storing the block in lower precision can cause underflow or overflow in some values.
- This is not accounted for by the numerical analysis shown in the previous slides
- Two possible solutions:
 - 1. Check the condition number of the low precision block to verify there were no catastrophic overflows or underflows.
 - 2. Use a custom storage format that preserves the number of exponent bits:





Initial GPU implementation






Sources of linear systems


- Real-world problem transformed into a linear system via:
 - PDE discretizations, graph representations
 - Large number of unknowns (1M+, full matrix 8TB)
 - Most matrix elements are zero
- Possible approach: iterative methods
 - Krylov-subspace based linear solvers
 - SpMV
 - BLAS-1 operations
 - Sparse matrix formats & SpMV
 - accelerate each iteration of the solver
 - Preconditioners
 - reduce the number of iterations
 - Special hardware (e.g. GPUs)
 - Probably not a good idea to implement everything from scratch...
 - Use a library instead:






































... leads to CSC



... leads to CSC




"Standard" approach

First things first

THERE IS NO "BEST" SPARSE MATRIX FORMAT / SpMV ALGORITHM



Maximum slowdown factor over fastest



```
3.2 1.2 0.4 2.7 1.3 4.1 0.1 2.7 Values (val)

0 2 2 0 1 3 0 3 Column indexes (colidx)

0 2 3 6 Row pointers (rowptr)

y := Ax
1 void SpMV_CSR(int m, int *rowptr, int *colidx, float *val, float *x, float *y)
```

```
void SpMV_CSR(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
for (int i = 0; i < m; ++i) {
   for (int j = rowptr[i]; j < rowptr[i+1]; ++j)
      y[i] += val[j] * x [ colidx[j] ];
}</pre>
```

~ cuSPARSE SpMV

```
3.2 1.2 0.4 2.7 1.3 4.1 0.1 2.7 Values (val)

0 2 2 0 1 3 0 3 Column indexes (colidx)

0 2 3 6 Row pointers (rowptr)

y := Ax
void SpMV_CSR(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
for (int i = 0; i < m; ++i) {
```

for (int j = rowptr[i]; j < rowptr[i+1]; ++j)</pre>

y[i] += val[j] * x [colidx[j]];

Load imbalance!


Bell & Garland '08

parallelize outer loop

~ cuSPARSE SpMV


Example


Freescale/transient



Example

* GTX 1080







Can we do better than HYB using CSR?

Example

* GTX 1080







Can we do better than HYB using CSR?

55x speedup

YES!

Flegar, Anzt, Overcoming Load Imbalance for Irregular Sparse Matrices, IA3'17

Flegar, Quintana-Ortí, Balanced CSR Sparse Matrix-Vector Product on Graphics Processors, Euro-Par'17

How to do it

```
void SpMV_CSR(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
   for (int i = 0; i < m; ++i) {
      for (int j = rowptr[i]; j < rowptr[i+1]; ++j)
        y[i] += val[j] * x [ colidx[j] ];
}
</pre>
```

```
void SpMV_CSR(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
    for (int i = 0; i < m; ++i) {
        for (int j = rowptr[i]; j < rowptr[i+1]; ++j)

            y[i] += val[j] * x [ colidx[j] ];
}

Merge the two loops into one.

void SpMV_CSR(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
    int row = -1, next_row = 0, nnz = rowptr[m];
    for (int i = 0; i < nnz; ++i) {
        while (i >= next_row) next_row = rowptr[++row+1];
        y[row] += val[i] * x[ colidx[i] ];
}
```

```
void SpMV_CSR(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
   for (int i = 0; i < m; ++i) {
     for (int j = rowptr[i]; j < rowptr[i+1]; ++j)</pre>
        y[i] += val[j] * x [ colidx[j] ];
    }
                               Merge the two loops into one.
  void SpMV_CSR(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
    int row = -1, next_row = 0, nnz = rowptr[m];
    for (int i = 0; i < nnz; ++i) {
        while (i >= next_row) next_row = rowptr[++row+1];
        y[row] += val[i] * x[ colidx[i] ];
 }}
                               Split the loop into equal chunks.
  const int T = thread_count;
  void SpMV_CSRI(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
    int row = -1, next_row = 0, nnz = rowptr[m];
    for (int k = 0; k < T; ++k) {
      for (int i = k*nnz / T; i < (k+1)*nnz / T; ++i) {
6
7
        while (i >= next_row) next_row = rowptr[++row+1];
        y[row] += val[i] * x[ colidx[i] ];
 | }}}
```

```
void SpMV_CSR(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
   for (int i = 0; i < m; ++i) {
      for (int j = rowptr[i]; j < rowptr[i+1]; ++j)</pre>
        y[i] += val[j] * x [ colidx[j] ];
    }
                               Merge the two loops into one.
  void SpMV_CSR(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
    int row = -1, next_row = 0, nnz = rowptr[m];
    for (int i = 0; i < nnz; ++i) {
        while (i >= next_row) next_row = rowptr[++row+1];
        y[row] += val[i] * x[ colidx[i] ];
 }}
                               Split the loop into equal chunks.
  const int T = thread_count;
  void SpMV_CSRI(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
3
    int row = -1, next_row = 0, nnz = rowptr[m];
   for (int k = 0; k < T; ++k) { Parallelize this!
5
      for (int i = k*nnz / T; i < (k+1)*nnz / T; ++i) {
6
7
        while (i >= next_row) next_row = rowptr[++row+1];
        y[row] += val[i] * x[ colidx[i] ];
 | }}}
```

```
void SpMV_CSR(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
   for (int i = 0; i < m; ++i) {
      for (int j = rowptr[i]; j < rowptr[i+1]; ++j)</pre>
        y[i] += val[j] * x [ colidx[j] ];
    }
                                Merge the two loops into one.
  void SpMV_CSR(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
    int row = -1, next_row = 0, nnz = rowptr[m];
    for (int i = 0; i < nnz; ++i) {
        while (i >= next_row) next_row = rowptr[++row+1];
        y[row] += val[i] * x[ colidx[i] ];
 }}
                               Split the loop into equal chunks.
  const int T = thread_count;
  void SpMV_CSRI(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
3
    int row = -1, next_row = 0, nnz = rowptr[m];
   for (int k = 0; k < T; ++k) { Parallelize this!}
5
      for (int i = k*nnz / T; i < (k+1)*nnz / T; ++i) {
6
7
        while (i >= next_row) next_row = rowptr[++row+1];
       y[row] += val[i] * x[ colidx[i] ];
 | }}}
```

Race conditions!

```
void SpMV_CSR(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
   for (int i = 0; i < m; ++i) {
      for (int j = rowptr[i]; j < rowptr[i+1]; ++j)
        y[i] += val[j] * x [ colidx[j] ];
    }
                                Merge the two loops into one.
  void SpMV_CSR(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
    int row = -1, next_row = 0, nnz = rowptr[m];
    for (int i = 0; i < nnz; ++i) {
        while (i >= next_row) next_row = rowptr[++row+1];
        y[row] += val[i] * x[ colidx[i] ];
 }}
                               Split the loop into equal chunks.
  const int T = thread_count;
  void SpMV_CSRI(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
3
    int row = -1, next_row = 0, nnz = rowptr[m];
   for (int k = 0; k < T; ++k) { Parallelize this!}
5
      for (int i = k*nnz / T; i < (k+1)*nnz / T; ++i) {
6
7
        while (i >= next_row) next_row = rowptr[++row+1];
        y[row] += val[i] * x[ colidx[i] ];
 }}}

    Use atomics

      Race conditions! • Accumulate partial
                         result in the registers
```

```
void SpMV_CSR(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
   for (int i = 0; i < m; ++i) {
      for (int j = rowptr[i]; j < rowptr[i+1]; ++j)
        y[i] += val[j] * x [ colidx[j] ];
    }
                                Merge the two loops into one.
  void SpMV_CSR(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
    int row = -1, next_row = 0, nnz = rowptr[m];
    for (int i = 0; i < nnz; ++i) {
        while (i >= next_row) next_row = rowptr[++row+1];
        y[row] += val[i] * x[ colidx[i] ];
 }}
                               Split the loop into equal chunks.
  const int T = thread_count;
  void SpMV_CSRI(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
3
    int row = -1, next_row = 0, nnz = rowptr[m];
   for (int k = 0; k < T; ++k) { Parallelize this!}
5
      for (int i = k*nnz / T; i < (k+1)*nnz / T; ++i) {
                                                               State between outer
6
7
        while (i >= next_row) next_row = rowptr[++row+1];
                                                               loop iterations!
        y[row] += val[i] * x[ colidx[i] ];
 | }}}

    Use atomics

      Race conditions! • Accumulate partial
                         result in the registers
```

```
void SpMV_CSR(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
    for (int i = 0; i < m; ++i) {
      for (int j = rowptr[i]; j < rowptr[i+1]; ++j)
4
        y[i] += val[j] * x [ colidx[j] ];
5
                                Merge the two loops into one.
  void SpMV_CSR(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
    int row = -1, next_row = 0, nnz = rowptr[m];
    for (int i = 0; i < nnz; ++i) {
        while (i >= next_row) next_row = rowptr[++row+1];
        v[row] += val[i] * x[ colidx[i] ];
 }}
                               Split the loop into equal chunks.
  const int T = thread_count;
  void SpMV_CSRI(int m, int *rowptr, int *colidx, float *val, float *x, float *y) {
3
    int row = -1, next_row = 0, nnz = rowptr[m];
    for (int k = 0; k < T; ++k) { Parallelize this!}
5
      for (int i = k*nnz / T; i < (k+1)*nnz / T; ++i) {
                                                               State between outer
6
7
        while (i >= next_row) next_row = rowptr[++row+1];
                                                               loop iterations!
        y[row] += val[i] * x[ colidx[i] ];
 }}}

    Use atomics

                                                              Precompute starting value
      Race conditions! • Accumulate partial
                                                             of "row" for each thread.
```

result in the registers

CUDA thread = 1 lane of a 32-wide SIMD unit (warp)




CUDA thread = 1 lane of a 32-wide SIMD unit (warp)

Spreading out threads causes strided memory access.



CUDA thread = 1 lane of a 32-wide SIMD unit (warp)


Spreading out threads causes strided memory access.






CUDA thread = 1 lane of a 32-wide SIMD unit (warp)

Spreading out threads causes strided memory access.




CUDA thread = 1 lane of a 32-wide SIMD unit (warp)

Spreading out threads causes strided memory access.




CUDA thread = 1 lane of a 32-wide SIMD unit (warp)

Spreading out threads causes strided memory access.




CUDA thread = 1 lane of a 32-wide SIMD unit (warp)

Spreading out threads causes strided memory access.




Performance of CSR-I

100 matrices from SuiteSparse




Speed-up / slowdown over cuSPARSE CSR





Speed-up / slowdown over cuSPARSE CSR



No format conversion!

- try both, and use the fastest later on!
- sometimes 1 cuSPARSE SpMV = 100 CSR-I SpMVs



CSR-I designed for irregular patterns



CSR-I designed for irregular patterns

How to measure irregularity?

Deviation of row lengths from the mean.



CSR-I designed for irregular patterns

How to measure irregularity?

Deviation of row lengths from the mean.

Is "5" regular or irregular?

Depends on the density of the matrix (mean #rows)



CSR-I designed for irregular patterns


How to measure irregularity?

Deviation of row lengths from the mean.

Is "5" regular or irregular?

Depends on the density of the matrix (mean #rows)

Scatter plot of speedup vs normalized std. dev.





CSR-I designed for irregular patterns


How to measure irregularity?

Deviation of row lengths from the mean.

Is "5" regular or irregular?


Depends on the density of the matrix (mean #rows)

Scatter plot of speedup vs normalized std. dev.





Combining both approaches





CSR-I designed for irregular patterns


How to measure irregularity?

Deviation of row lengths from the mean.

Is "5" regular or irregular?

Depends on the density of the matrix (mean #rows)

Scatter plot of speedup vs normalized std. dev.





CSR-I designed for irregular patterns


How to measure irregularity?

Deviation of row lengths from the mean.

Is "5" regular or irregular?


Depends on the density of the matrix (mean #rows)

Scatter plot of speedup vs normalized std. dev.






Combining both approaches





Outlook



Choosing the correct combination of

matrix format solver preconditioner

... requires expert knowledge or significant trial and error.

Design a tool that does it (semi-)automatically?



Thank you! Questions?


- Krylov-subspace based linear solvers
 - Performance depends on SpMV and Preconditioners
- Sparse matrix formats & SpMV
 - There is no "holy grail" best format depends on the problem
- Preconditioners
 - Accelerate the solution of the solver
 - Only an approximation, can use lower precision storage
- Do not implement from scratch, use a library. For example:



- github.com/ginkgo-project/ginkgo
- Open source license (BSD-3)
- Modern C++
- High performance GPU backend
- reference CPU implementation
- High performance CPU backend on the way

Slides:















github.com/gflegar/talks/tree/master/cmu_pittsburgh_2018_11

