

Scan Report

September 19, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone “Coordinated Universal Time”, which is abbreviated “UTC”. The task was “Full Network Scan – Complete Network”. The scan started at Sat Sep 19 16:34:33 2026 UTC and ended at Sat Sep 19 17:38:02 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1	Result Overview	2
2	Results per Host	2
2.1	192.168.1.1	2
2.1.1	Low general/tcp	2
2.2	192.168.1.128	3
2.3	192.168.1.129	3
2.4	192.168.1.130	3
2.5	192.168.1.131	4
2.5.1	Low general/icmp	4
2.5.2	Low general/tcp	4
2.6	192.168.1.132	5
2.6.1	Low general/icmp	5
2.7	192.168.1.135	6
2.7.1	Medium 8002/tcp	6
2.7.2	Low general/icmp	12
2.7.3	Low general/tcp	12
2.8	192.168.1.136	13
2.8.1	Low general/icmp	13
2.9	192.168.1.138	14
2.9.1	Low general/icmp	14
2.10	192.168.1.140	15
2.11	192.168.1.141	15
2.12	192.168.1.146	15

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
192.168.1.1 _gateway	0	0	0	1	0	0
192.168.1.128 192.168.1.128	0	0	0	0	0	0
192.168.1.129 192.168.1.129	0	0	0	0	0	0
192.168.1.130 192.168.1.130	0	0	0	0	0	0
192.168.1.131	0	0	0	2	0	0
192.168.1.132	0	0	0	1	0	0
192.168.1.135	0	0	3	2	0	0
192.168.1.136	0	0	0	1	0	0
192.168.1.138	0	0	0	1	0	0
192.168.1.140 192.168.1.140	0	0	0	0	0	0
192.168.1.141 192.168.1.141	0	0	0	0	0	0
192.168.1.146 192.168.1.146	0	0	0	0	0	0
Total: 12	0	0	3	8	0	0

Vendor security updates are not trusted.

Overrides are off. Even when a result has an override, this report uses the actual threat of the result.

Information on overrides is included in the report.

Notes are included in the report.

This report might not show details of all issues that were found.

Issues with the threat level “Log” are not shown.

Issues with the threat level “Debug” are not shown.

Issues with the threat level “False Positive” are not shown.

Only results with a minimum QoD of 70 are shown.

This report contains all 11 results selected by the filtering described above. Before filtering there were 170 results.

2 Results per Host

2.1 192.168.1.1

Host scan start Sat Sep 19 16:34:45 2026 UTC
Host scan end Sat Sep 19 17:34:43 2026 UTC

Service (Port)	Threat Level
general/tcp	Low

2.1.1 Low general/tcp

Low (CVSS: 2.6)
NVT: TCP Timestamps Information Disclosure
Summary
...continues on next page ...

...continued from previous page ...
The remote host implements TCP timestamps and therefore allows to compute the uptime.
Quality of Detection (QoD): 80%
Vulnerability Detection Result It was detected that the host implements RFC1323/RFC7323. The following timestamps were retrieved with a delay of 1 seconds in-between: Packet 1: 305236334 Packet 2: 305236437
Impact A side effect of this feature is that the uptime of the remote host can sometimes be computed.
Solution: Solution type: Mitigation To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime. To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled. The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment. See the references for more information.
Affected Software/OS TCP implementations that implement RFC1323/RFC7323.
Vulnerability Insight The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.
Vulnerability Detection Method Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported. Details: TCP Timestamps Information Disclosure OID:1.3.6.1.4.1.25623.1.0.80091 Version used: 2023-12-15T16:10:08Z

[\[return to 192.168.1.1 \]](#)

2.2 192.168.1.128

Host scan start Sat Sep 19 16:34:45 2026 UTC
Host scan end Sat Sep 19 16:38:01 2026 UTC

Service (Port)	Threat Level
----------------	--------------

2.3 192.168.1.129

Host scan start Sat Sep 19 16:34:45 2026 UTC
Host scan end Sat Sep 19 16:37:14 2026 UTC

Service (Port)	Threat Level
----------------	--------------

2.4 192.168.1.130

Host scan start Sat Sep 19 16:34:45 2026 UTC
Host scan end Sat Sep 19 16:37:16 2026 UTC

Service (Port)	Threat Level
----------------	--------------

2.5 192.168.1.131

Host scan start Sat Sep 19 16:34:45 2026 UTC
Host scan end Sat Sep 19 17:37:58 2026 UTC

Service (Port)	Threat Level
general/icmp	Low
general/tcp	Low

2.5.1 Low general/icmp

Low (CVSS: 2.1)
NVT: ICMP Timestamp Reply Information Disclosure
Summary The remote host responded to an ICMP timestamp request.
Quality of Detection (QoD): 80%
Vulnerability Detection Result The following response / ICMP packet has been received: - ICMP Type: 14 - ICMP Code: 0
Impact This information could theoretically be used to exploit weak time-based random number generators in other services.
Solution: Solution type: Mitigation Various mitigations are possible: - Disable the support for ICMP timestamp on the remote host completely - Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)
Vulnerability Insight The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.
Vulnerability Detection Method Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received. Details: ICMP Timestamp Reply Information Disclosure OID:1.3.6.1.4.1.25623.1.0.103190 Version used: 2025-01-21T05:37:33Z
References cert-bund: CB-K15/1514 cert-bund: CB-K14/0632 dfn-cert: DFN-CERT-2014-0658

[\[return to 192.168.1.131 \]](#)

2.5.2 Low general/tcp

Low (CVSS: 2.6)
NVT: TCP Timestamps Information Disclosure
Summary The remote host implements TCP timestamps and therefore allows to compute the uptime.
Quality of Detection (QoD): 80%
Vulnerability Detection Result It was detected that the host implements RFC1323/RFC7323. The following timestamps were retrieved with a delay of 1 seconds in-between: Packet 1: 1582036950 Packet 2: 1582037989
Impact A side effect of this feature is that the uptime of the remote host can sometimes be computed.
Solution: Solution type: Mitigation To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime. To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled. The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment. See the references for more information.
Affected Software/OS TCP implementations that implement RFC1323/RFC7323.
Vulnerability Insight The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.
Vulnerability Detection Method Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported. Details: TCP Timestamps Information Disclosure OID:1.3.6.1.4.1.25623.1.0.80091 Version used: 2023-12-15T16:10:08Z

[\[return to 192.168.1.131 \]](#)

2.6 192.168.1.132

Host scan start Sat Sep 19 16:34:47 2026 UTC
 Host scan end Sat Sep 19 16:36:58 2026 UTC

Service (Port)	Threat Level
general/icmp	Low

2.6.1 Low general/icmp

Low (CVSS: 2.1)
NVT: ICMP Timestamp Reply Information Disclosure
Summary The remote host responded to an ICMP timestamp request.
Quality of Detection (QoD): 80% ...continues on next page ...

Vulnerability Detection Result

- ICMP Type: 14

Impact

Solution:

Various mitigations are possible:

- ### Vulnerability Insight

Vulnerability Detection Method

Details: ICMP Timestamp Reply Information Disclosure

Version used: 2025-01-21T05:37:33Z

cert-bund: CB-K15/1514

cert-bund: CB-K14/0632

dfn-cert: DFN-CERT-2014-0658

2.7 192.168.1.135

```
Host scan start   Sat Sep 19 16:51:15 2026 UTC
Host scan end    Sat Sep 19 17:16:10 2026 UTC
```

2.7.1 Medium 8002/tcp

The remote SSL/TLS service is prone to a man-in-the-middle (MITM) vulnerability.

Vulnerability Detection Result

... continues on next page ...

...continued from previous page ...	
Impact	A remote, unauthenticated attacker may be able to inject an arbitrary amount of chosen plaintext into the beginning of the application protocol stream. This could allow an attacker to issue HTTP requests, or take action impersonating the user, among other consequences.
Solution:	Solution type: VendorFix Users should contact their vendors for specific patch information. General solution options are: - remove/disable renegotiation capabilities altogether from/in the affected SSL/TLS service - enable Safe/Secure renegotiation (RFC5746) for the affected SSL/TLS service
Affected Software/OS	The TLS protocol, and the SSL protocol 3.0 and possibly earlier, as used in Microsoft Internet Information Services (IIS) 7.0, mod_ssl in the Apache HTTP Server 2.2.14 and earlier, OpenSSL before 0.9.8l, GnuTLS 2.8.5 and earlier, Mozilla Network Security Services (NSS) 3.12.4 and earlier, multiple Cisco products, and other products.
Vulnerability Insight	The flaw exists because the remote SSL/TLS service does not properly associate renegotiation handshakes with an existing connection, which allows MITM attackers to insert data into HTTPS sessions, and possibly other types of sessions protected by TLS or SSL, by sending an unauthenticated request that is processed retroactively by a server in a post-renegotiation context, related to a 'plaintext injection' attack, aka the 'Project Mogul' issue.
Vulnerability Detection Method	Checks if the remote service allows to re-do the same SSL/TLS handshake (Renegotiation) over an existing / already established SSL/TLS connection. Details: SSL/TLS: Renegotiation MITM Vulnerability (CVE-2009-3555) OID:1.3.6.1.4.1.25623.1.0.117758 Version used: 2026-03-13T05:54:58Z
References	cert-bund: CB-K17/1878 cert-bund: CB-K17/1642 cert-bund: CB-K15/0637 dfn-cert: DFN-CERT-2017-1960 dfn-cert: DFN-CERT-2017-1722 dfn-cert: DFN-CERT-2015-0664 dfn-cert: DFN-CERT-2013-0321 dfn-cert: DFN-CERT-2012-1377 dfn-cert: DFN-CERT-2012-0828 dfn-cert: DFN-CERT-2012-0613 dfn-cert: DFN-CERT-2011-1720 dfn-cert: DFN-CERT-2011-1138 dfn-cert: DFN-CERT-2011-1137 dfn-cert: DFN-CERT-2011-0712 dfn-cert: DFN-CERT-2011-0700 dfn-cert: DFN-CERT-2011-0321 dfn-cert: DFN-CERT-2011-0193 dfn-cert: DFN-CERT-2011-0185 dfn-cert: DFN-CERT-2011-0181 dfn-cert: DFN-CERT-2011-0116 dfn-cert: DFN-CERT-2011-0021 dfn-cert: DFN-CERT-2011-0020 dfn-cert: DFN-CERT-2011-0019 dfn-cert: DFN-CERT-2010-1762 dfn-cert: DFN-CERT-2010-1731 dfn-cert: DFN-CERT-2010-1710 dfn-cert: DFN-CERT-2010-1702 dfn-cert: DFN-CERT-2010-1650 dfn-cert: DFN-CERT-2010-1647 dfn-cert: DFN-CERT-2010-1527 dfn-cert: DFN-CERT-2010-1500 dfn-cert: DFN-CERT-2010-1439 dfn-cert: DFN-CERT-2010-1424 dfn-cert: DFN-CERT-2010-1406 dfn-cert: DFN-CERT-2010-1405 dfn-cert: DFN-CERT-2010-1387 dfn-cert: DFN-CERT-2010-1385 dfn-cert: DFN-CERT-2010-1380
...continues on next page ...	

...continued from previous page ...

dfn-cert: DFN-CERT-2010-1368
dfn-cert: DFN-CERT-2010-1293
dfn-cert: DFN-CERT-2010-1227
dfn-cert: DFN-CERT-2010-1052
dfn-cert: DFN-CERT-2010-1009
dfn-cert: DFN-CERT-2010-1000
dfn-cert: DFN-CERT-2010-0899
dfn-cert: DFN-CERT-2010-0859
dfn-cert: DFN-CERT-2010-0833
dfn-cert: DFN-CERT-2010-0815
dfn-cert: DFN-CERT-2010-0775
dfn-cert: DFN-CERT-2010-0729
dfn-cert: DFN-CERT-2010-0725
dfn-cert: DFN-CERT-2010-0707
dfn-cert: DFN-CERT-2010-0705
dfn-cert: DFN-CERT-2010-0669
dfn-cert: DFN-CERT-2010-0639
dfn-cert: DFN-CERT-2010-0619
dfn-cert: DFN-CERT-2010-0618
dfn-cert: DFN-CERT-2010-0603
dfn-cert: DFN-CERT-2010-0586
dfn-cert: DFN-CERT-2010-0579
dfn-cert: DFN-CERT-2010-0562
dfn-cert: DFN-CERT-2010-0558
dfn-cert: DFN-CERT-2010-0544
dfn-cert: DFN-CERT-2010-0539
dfn-cert: DFN-CERT-2010-0525
dfn-cert: DFN-CERT-2010-0504
dfn-cert: DFN-CERT-2010-0498
dfn-cert: DFN-CERT-2010-0491
dfn-cert: DFN-CERT-2010-0488
dfn-cert: DFN-CERT-2010-0485
dfn-cert: DFN-CERT-2010-0456
dfn-cert: DFN-CERT-2010-0455
dfn-cert: DFN-CERT-2010-0451
dfn-cert: DFN-CERT-2010-0413
dfn-cert: DFN-CERT-2010-0411
dfn-cert: DFN-CERT-2010-0410
dfn-cert: DFN-CERT-2010-0407
dfn-cert: DFN-CERT-2010-0406
dfn-cert: DFN-CERT-2010-0405
dfn-cert: DFN-CERT-2010-0388
dfn-cert: DFN-CERT-2010-0370
dfn-cert: DFN-CERT-2010-0339
dfn-cert: DFN-CERT-2010-0303
dfn-cert: DFN-CERT-2010-0273
dfn-cert: DFN-CERT-2010-0201
dfn-cert: DFN-CERT-2010-0166
dfn-cert: DFN-CERT-2010-0050
dfn-cert: DFN-CERT-2010-0030
dfn-cert: DFN-CERT-2009-1833
dfn-cert: DFN-CERT-2009-1821
dfn-cert: DFN-CERT-2009-1820
dfn-cert: DFN-CERT-2009-1809
dfn-cert: DFN-CERT-2009-1805
dfn-cert: DFN-CERT-2009-1757
dfn-cert: DFN-CERT-2009-1755
dfn-cert: DFN-CERT-2009-1725
dfn-cert: DFN-CERT-2009-1719
dfn-cert: DFN-CERT-2009-1689
dfn-cert: DFN-CERT-2009-1688
dfn-cert: DFN-CERT-2009-1654
dfn-cert: DFN-CERT-2009-1653
dfn-cert: DFN-CERT-2009-1646
dfn-cert: DFN-CERT-2009-1643
dfn-cert: DFN-CERT-2009-1630
dfn-cert: DFN-CERT-2009-1623
dfn-cert: DFN-CERT-2009-1603
dfn-cert: DFN-CERT-2009-1602
dfn-cert: DFN-CERT-2009-1584
dfn-cert: DFN-CERT-2009-1578

Medium (CVSS: 5.0)
NVT: SSL/TLS: Renegotiation DoS Vulnerability (CVE-2011-1473, CVE-2011-5094)
Summary The remote SSL/TLS service is prone to a denial of service (DoS) vulnerability.
Quality of Detection (QoD): 70%
Vulnerability Detection Result The following indicates that the remote SSL/TLS service is affected: Protocol Version Successful re-done SSL/TLS handshakes (Renegotiation) over an ↪ existing / already established SSL/TLS connection ----- ↪----- TLSv1.0 10 TLSv1.1 10 TLSv1.2 10
Impact The flaw might make it easier for remote attackers to cause a DoS (CPU consumption) by performing many renegotiations within a single connection.
Solution: Solution type: VendorFix Users should contact their vendors for specific patch information. A general solution is to remove/disable renegotiation capabilities altogether from/in the affected SSL/TLS service.
Affected Software/OS Every SSL/TLS service which does not properly restrict client-initiated renegotiation.
Vulnerability Insight The flaw exists because the remote SSL/TLS service does not properly restrict client-initiated renegotiation within the SSL and TLS protocols. Note: The referenced CVEs are affecting OpenSSL and Mozilla Network Security Services (NSS) but both are in a DISPUTED state with the following rationale: > It can also be argued that it is the responsibility of server deployments, not a security library, to prevent or limit renegotiation when it is inappropriate within a specific environment. Both CVEs are still kept in this VT as a reference to the origin of this flaw.
Vulnerability Detection Method Checks if the remote service allows to re-do the same SSL/TLS handshake (Renegotiation) over an existing / already established SSL/TLS connection. Details: SSL/TLS: Renegotiation DoS Vulnerability (CVE-2011-1473, CVE-2011-5094) OID:1.3.6.1.4.1.25623.1.0.117761 Version used: 2026-03-13T05:54:58Z
References cert-bund: WID-SEC-2026-2904 cert-bund: WID-SEC-2026-0180 cert-bund: WID-SEC-2024-1591 cert-bund: WID-SEC-2024-0796 cert-bund: WID-SEC-2023-1435 cert-bund: CB-K17/0980 cert-bund: CB-K17/0979 cert-bund: CB-K14/0772 cert-bund: CB-K13/0915 cert-bund: CB-K13/0462 dfn-cert: DFN-CERT-2025-0933 dfn-cert: DFN-CERT-2017-1013 dfn-cert: DFN-CERT-2017-1012 dfn-cert: DFN-CERT-2014-0809 dfn-cert: DFN-CERT-2013-1928 dfn-cert: DFN-CERT-2012-1112

Medium (CVSS: 4.3)
NVT: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection
Product detection result cpe:/a:ietf:transport_layer_security:1.0 Detected by SSL/TLS: Version Detection (OID: 1.3.6.1.4.1.25623.1.0.105782)
Summary It was possible to detect the usage of the deprecated TLSv1.0 and/or TLSv1.1 protocol on this system.
Quality of Detection (QoD): 98%
Vulnerability Detection Result In addition to TLSv1.2+ the service is also providing the deprecated TLSv1.0 and ↪ TLSv1.1 protocols and supports one or more ciphers. Those supported ciphers c ↪an be found in the 'SSL/TLS: Report Supported Cipher Suites' (OID: 1.3.6.1.4.1 ↪.25623.1.0.802067) VT.
Impact An attacker might be able to use the known cryptographic flaws to eavesdrop the connection between clients and the service to get access to sensitive data transferred within the secured connection. Furthermore newly uncovered vulnerabilities in this protocols won't receive security updates anymore.
Solution: Solution type: Mitigation It is recommended to disable the deprecated TLSv1.0 and/or TLSv1.1 protocols in favor of the TLSv1.2+ protocols. Please see the references for more resources supporting you with this task.
Affected Software/OS - All services providing an encrypted communication using the TLSv1.0 and/or TLSv1.1 protocols - CVE-2023-41928: Kiloview P1 4G and P2 4G Video Encoder - CVE-2024-41270: Gorush v1.18.4 - CVE-2025-3200: Multiple products from Wiesemann & Theis
Vulnerability Insight The TLSv1.0 and TLSv1.1 protocols contain known cryptographic flaws like: - CVE-2011-3389: Browser Exploit Against SSL/TLS (BEAST) - CVE-2015-0204: Factoring Attack on RSA-EXPORT Keys Padding Oracle On Downgraded Legacy Encryption (FREAK)
Vulnerability Detection Method Checks the used TLS protocols of the services provided by this system. Details: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection OID:1.3.6.1.4.1.25623.1.0.117274 Version used: 2026-06-03T07:18:10Z
Product Detection Result Product: cpe:/a:ietf:transport_layer_security:1.0 Method: SSL/TLS: Version Detection OID: 1.3.6.1.4.1.25623.1.0.105782
References cert-bund: WID-SEC-2026-0180 cert-bund: WID-SEC-2023-1435 cert-bund: CB-K18/0799 cert-bund: CB-K16/1289 cert-bund: CB-K16/1096 cert-bund: CB-K15/1751 cert-bund: CB-K15/1266 cert-bund: CB-K15/0850 cert-bund: CB-K15/0764 cert-bund: CB-K15/0720 cert-bund: CB-K15/0548 cert-bund: CB-K15/0526 cert-bund: CB-K15/0509 cert-bund: CB-K15/0493 cert-bund: CB-K15/0384 cert-bund: CB-K15/0365 cert-bund: CB-K15/0364
...continues on next page ...

	...continued from previous page ...
cert-bund: CB-K15/0302	
cert-bund: CB-K15/0192	
cert-bund: CB-K15/0079	
cert-bund: CB-K15/0016	
cert-bund: CB-K14/1342	
cert-bund: CB-K14/0231	
cert-bund: CB-K13/0845	
cert-bund: CB-K13/0796	
cert-bund: CB-K13/0790	
dfn-cert: DFN-CERT-2020-0177	
dfn-cert: DFN-CERT-2020-0111	
dfn-cert: DFN-CERT-2019-0068	
dfn-cert: DFN-CERT-2018-1441	
dfn-cert: DFN-CERT-2018-1408	
dfn-cert: DFN-CERT-2016-1372	
dfn-cert: DFN-CERT-2016-1164	
dfn-cert: DFN-CERT-2016-0388	
dfn-cert: DFN-CERT-2015-1853	
dfn-cert: DFN-CERT-2015-1332	
dfn-cert: DFN-CERT-2015-0884	
dfn-cert: DFN-CERT-2015-0800	
dfn-cert: DFN-CERT-2015-0758	
dfn-cert: DFN-CERT-2015-0567	
dfn-cert: DFN-CERT-2015-0544	
dfn-cert: DFN-CERT-2015-0530	
dfn-cert: DFN-CERT-2015-0396	
dfn-cert: DFN-CERT-2015-0375	
dfn-cert: DFN-CERT-2015-0374	
dfn-cert: DFN-CERT-2015-0305	
dfn-cert: DFN-CERT-2015-0199	
dfn-cert: DFN-CERT-2015-0079	
dfn-cert: DFN-CERT-2015-0021	
dfn-cert: DFN-CERT-2014-1414	
dfn-cert: DFN-CERT-2013-1847	
dfn-cert: DFN-CERT-2013-1792	
dfn-cert: DFN-CERT-2012-1979	
dfn-cert: DFN-CERT-2012-1829	
dfn-cert: DFN-CERT-2012-1530	
dfn-cert: DFN-CERT-2012-1380	
dfn-cert: DFN-CERT-2012-1377	
dfn-cert: DFN-CERT-2012-1292	
dfn-cert: DFN-CERT-2012-1214	
dfn-cert: DFN-CERT-2012-1213	
dfn-cert: DFN-CERT-2012-1180	
dfn-cert: DFN-CERT-2012-1156	
dfn-cert: DFN-CERT-2012-1155	
dfn-cert: DFN-CERT-2012-1039	
dfn-cert: DFN-CERT-2012-0956	
dfn-cert: DFN-CERT-2012-0908	
dfn-cert: DFN-CERT-2012-0868	
dfn-cert: DFN-CERT-2012-0867	
dfn-cert: DFN-CERT-2012-0848	
dfn-cert: DFN-CERT-2012-0838	
dfn-cert: DFN-CERT-2012-0776	
dfn-cert: DFN-CERT-2012-0722	
dfn-cert: DFN-CERT-2012-0638	
dfn-cert: DFN-CERT-2012-0627	
dfn-cert: DFN-CERT-2012-0451	
dfn-cert: DFN-CERT-2012-0418	
dfn-cert: DFN-CERT-2012-0354	
dfn-cert: DFN-CERT-2012-0234	
dfn-cert: DFN-CERT-2012-0221	
dfn-cert: DFN-CERT-2012-0177	
dfn-cert: DFN-CERT-2012-0170	
dfn-cert: DFN-CERT-2012-0146	
dfn-cert: DFN-CERT-2012-0142	
dfn-cert: DFN-CERT-2012-0126	
dfn-cert: DFN-CERT-2012-0123	
dfn-cert: DFN-CERT-2012-0095	
dfn-cert: DFN-CERT-2012-0051	
dfn-cert: DFN-CERT-2012-0047	
dfn-cert: DFN-CERT-2012-0021	
...continues on next page ...	

...continued from previous page ...	
dfn-cert:	DFN-CERT-2011-1953
dfn-cert:	DFN-CERT-2011-1946
dfn-cert:	DFN-CERT-2011-1844
dfn-cert:	DFN-CERT-2011-1826
dfn-cert:	DFN-CERT-2011-1774
dfn-cert:	DFN-CERT-2011-1743
dfn-cert:	DFN-CERT-2011-1738
dfn-cert:	DFN-CERT-2011-1706
dfn-cert:	DFN-CERT-2011-1628
dfn-cert:	DFN-CERT-2011-1627
dfn-cert:	DFN-CERT-2011-1619
dfn-cert:	DFN-CERT-2011-1482

[\[return to 192.168.1.135 \]](#)

2.7.2 Low general/icmp

Low (CVSS: 2.1)	
NVT: ICMP Timestamp Reply Information Disclosure	
Summary The remote host responded to an ICMP timestamp request.	
Quality of Detection (QoD): 80%	
Vulnerability Detection Result The following response / ICMP packet has been received: - ICMP Type: 14 - ICMP Code: 0	
Impact This information could theoretically be used to exploit weak time-based random number generators in other services.	
Solution: Solution type: Mitigation Various mitigations are possible: - Disable the support for ICMP timestamp on the remote host completely - Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)	
Vulnerability Insight The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.	
Vulnerability Detection Method Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received. Details: ICMP Timestamp Reply Information Disclosure OID:1.3.6.1.4.1.25623.1.0.103190 Version used: 2025-01-21T05:37:33Z	
References cert-bund: CB-K15/1514 cert-bund: CB-K14/0632 dfn-cert: DFN-CERT-2014-0658	

[\[return to 192.168.1.135 \]](#)

2.7.3 Low general/tcp

Low (CVSS: 2.6)
NVT: TCP Timestamps Information Disclosure
Summary The remote host implements TCP timestamps and therefore allows to compute the uptime.
Quality of Detection (QoD): 80%
Vulnerability Detection Result It was detected that the host implements RFC1323/RFC7323. The following timestamps were retrieved with a delay of 1 seconds in-between: Packet 1: 479686 Packet 2: 479944
Impact A side effect of this feature is that the uptime of the remote host can sometimes be computed.
Solution: Solution type: Mitigation To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime. To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled. The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment. See the references for more information.
Affected Software/OS TCP implementations that implement RFC1323/RFC7323.
Vulnerability Insight The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.
Vulnerability Detection Method Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported. Details: TCP Timestamps Information Disclosure OID:1.3.6.1.4.1.25623.1.0.80091 Version used: 2023-12-15T16:10:08Z

[\[return to 192.168.1.135 \]](#)

2.8 192.168.1.136

Host scan start Sat Sep 19 16:34:45 2026 UTC
Host scan end Sat Sep 19 16:36:51 2026 UTC

Service (Port)	Threat Level
general/icmp	Low

2.8.1 Low general/icmp

Low (CVSS: 2.1)
NVT: ICMP Timestamp Reply Information Disclosure
Summary The remote host responded to an ICMP timestamp request.
Quality of Detection (QoD): 80% ...continues on next page ...

...continued from previous page ...
Vulnerability Detection Result The following response / ICMP packet has been received: - ICMP Type: 14 - ICMP Code: 0
Impact This information could theoretically be used to exploit weak time-based random number generators in other services.
Solution: Solution type: Mitigation Various mitigations are possible: - Disable the support for ICMP timestamp on the remote host completely - Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)
Vulnerability Insight The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.
Vulnerability Detection Method Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received. Details: ICMP Timestamp Reply Information Disclosure OID:1.3.6.1.4.1.25623.1.0.103190 Version used: 2025-01-21T05:37:33Z
References cert-bund: CB-K15/1514 cert-bund: CB-K14/0632 dfn-cert: DFN-CERT-2014-0658

[\[return to 192.168.1.136 \]](#)

2.9 192.168.1.138

Host scan start Sat Sep 19 16:34:45 2026 UTC
 Host scan end Sat Sep 19 16:36:51 2026 UTC

Service (Port)	Threat Level
general/icmp	Low

2.9.1 Low general/icmp

Low (CVSS: 2.1)
NVT: ICMP Timestamp Reply Information Disclosure
Summary The remote host responded to an ICMP timestamp request.
Quality of Detection (QoD): 80%
Vulnerability Detection Result The following response / ICMP packet has been received: - ICMP Type: 14 - ICMP Code: 0
Impact This information could theoretically be used to exploit weak time-based random number generators in other services.
Solution: Solution type: Mitigation ...continues on next page ...

...continued from previous page ...
Various mitigations are possible: - Disable the support for ICMP timestamp on the remote host completely - Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)
Vulnerability Insight The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.
Vulnerability Detection Method Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received. Details: ICMP Timestamp Reply Information Disclosure OID:1.3.6.1.4.1.25623.1.0.103190 Version used: 2025-01-21T05:37:33Z
References cert-bund: CB-K15/1514 cert-bund: CB-K14/0632 dfn-cert: DFN-CERT-2014-0658

[\[return to 192.168.1.138 \]](#)

2.10 192.168.1.140

Host scan start Sat Sep 19 16:34:45 2026 UTC
Host scan end Sat Sep 19 16:38:02 2026 UTC

Service (Port)	Threat Level
----------------	--------------

2.11 192.168.1.141

Host scan start Sat Sep 19 16:34:45 2026 UTC
Host scan end Sat Sep 19 16:38:02 2026 UTC

Service (Port)	Threat Level
----------------	--------------

2.12 192.168.1.146

Host scan start Sat Sep 19 16:34:45 2026 UTC
Host scan end Sat Sep 19 16:37:14 2026 UTC

Service (Port)	Threat Level
----------------	--------------