shield clips

CLIP1 CLIP2 CLIP3 CLIP4 CLIP5 CLIP30 CLIP31
CLIP6 CLIP7 CLIP8 CLIP9 CLIP10 CLIP27
CLIP11 CLIP12 CLIP13 CLIP14 CLIP15 CLIP28
CLIP16 CLIP17 CLIP18 CLIP19 CLIP20 CLIP29
CLIP21 CLIP22 CLIP23 CLIP24 CLIP25 CLIP26
(all GND)

Ext clock input

GND — 10nF C37 — 10nF C42 — GND
GND — 0 R6 — SG0
SMA J2 — 50_Ohms
IN_SEL
CLK_DIV

Clock from Kasli

J7 MMCX — GND — 50_Ohms

DDS_CLK

U_CLK_INPUT
CLK_INPUT.SchDoc

CK_SMA_IN
IN_SEL
CLK_DIV
INT_CLK_IN

DDS_CLKA0_P DDS_CLKA0_N DDS_CLKA1_P DDS_CLKA1_N DDS_CLKA2_P DDS_CLKA2_N DDS_CLKA3_P DDS_CLKA3_N DDS_CLKB0_P DDS_CLKB0_N DDS_CLKB1_P DDS_CLKB1_N DDS_CLKB2_P DDS_CLKB2_N DDS_CLKB3_P DDS_CLKB3_N

Output SMAs

GND — 10nF C11 — SG1
GND — 0 R64 — 10nF C25 — GND
SMA J3 — RF_OUT0 — 50_Ohms
GND — 10nF C31 — SG2
GND — 0 R65 — 10nF C32 — GND
SMA J4 — RF_OUT1 — 50_Ohms
GND — 10nF C33 — SG3
GND — 0 R74 — 10nF C34 — GND
SMA J5 — RF_OUT2 — 50_Ohms
GND — 10nF C35 — SG4
GND — 0 R75 — 10nF C41 — GND
SMA J6 — RF_OUT3 — 50_Ohms

ATT_CLK
ATT_LE
ATT_RSTn
ATT_S_IN
ATT_S_OUT

U_DDS_OUT_channel0
DDS_OUT_channel.SchDoc
U_DDS_OUT_channel1
DDS_OUT_channel.SchDoc
U_DDS_OUT_channel2
DDS_OUT_channel.SchDoc
U_DDS_OUT_channel3
DDS_OUT_channel.SchDoc

DAC_OUT_P DAC_OUT_N ATT_CLK RFSW_CTRL ATT_LE ATT_RSTn ATT_S_IN ATT_S_OUT

RFSW_CTRL0
RFSW_CTRL1
RFSW_CTRL2
RFSW_CTRL3

U_CTRL_LOGIC
CTRL_LOGIC.SchDoc

RFSW_CTRL0 RFSW_CTRL1 RFSW_CTRL2 RFSW_CTRL3
DDS_SDO[3..0] DDS_SDI[3..0] DDS_SCKI[3..0] DDS_CSn[3..0]
IN_SEL CLK_DIV
DDS_UPDATE[3..0] DDS_SYNC_CLK0 DDS_PLL_LOCK[3..0] SYNC_SMP_ERR[3..0]
DDS_Profile
DDS_I/O_RESET DDS_RESET LED[7..0]
ATT_CLK ATT_LE ATT_RSTn ATT_S_IN ATT_S_OUT
RE_DE[15..0]
IO0_CLK IO_A1 IO_A2 IO_A3 IO_A4 IO_A5 IO_A6 IO_A7
IO_B8_SCKI IO_B9 IO_B10 IO_B11 IO_B12 IO_B13 IO_B14 IO_B15
DDS_SYNC_CLKSEL DDS_SYNC_OUTEN DDS_SYNC_CLK_OUTEN

RE_DE[15..0]

LVDS_IFC_DDS.SchDoc U_LVDS_IFC

EEM A
IO0 IO1 IO2 IO3 IO4 IO5 IO6 IO7 LVDS0_P LVDS0_N LVDS1_P LVDS1_N LVDS7_P LVDS7_N
I2C_SDA I2C_SCL
RE_DE0 RE_DE1 RE_DE2 RE_DE3 RE_DE4 RE_DE5 RE_DE6 RE_DE7

SDA SCL

LVDS_IFC_DDS.SchDoc U_LVDS_IFC

EEM B
IO0 IO1 IO2 IO3 IO4 IO5 IO6 IO7 LVDS0_P LVDS0_N LVDS1_P LVDS1_N LVDS7_P LVDS7_N
I2C_SDA I2C_SCL
RE_DE8 RE_DE9 RE_DE10 RE_DE11 RE_DE12 RE_DE13 RE_DE14 RE_DE15

DDS_SYNC_CLKSEL DDS_SYNC_OUTEN

DDS_SYNC_CLK0 — 1k R31 — 100 R32 — 3V3_CLK2
P3V3_CLK2 — 1k R36 — 1k R39 — GND
C1 100nF — GND
C13 100nF — GND
IC4 FIN1101K8X: EN GND VCC GND

120R@100MHz
P3V3A — L8 — C45 1uF — GND — P3V3_CLK2

IC9

DDS0_SYNC_OUT_P DDS0_SYNC_OUT_N — 100 R68
CLK0 CLK0 CLK1 CLK1 CLK_SEL Q2
Q0 Q0 Q1 Q1 Q2
DDS0_SYNC_IN_P DDS0_SYNC_IN_N DDS1_SYNC_IN_P DDS1_SYNC_IN_N
SFOUTA0 SFOUTA1 OE0 OE1 OE2
SFOUTB0 SFOUTB1 OE3 OE4 OE5 VREF
Q3 Q3 Q4 Q4 Q5 Q5
DDS3_SYNC_IN_P DDS3_SYNC_IN_N DDS2_SYNC_IN_P DDS2_SYNC_IN_N FB_SYNC_P FB_SYNC_N
VDD VDDOA VDDOB
Si53304-B-GM

P3V3_CLK1 — GND — 120R@100MHz P3V3A — L13 — C86 1uF C89 100nF C90 100nF — P3V3_CLK1

IC16 FIN1101K8X: EN GND VCC GND — GND — P3V3_CLK2
R114 100 — C46 100nF — GND

LED0 LED1 LED2 LED3 LED4 LED5 LED6 LED7
R27 R28 R29 R30 R43 R44 R25 R26 — 1% 470
LD5A LD5B LD6A LD6B LD8A LD8B LD2A LD2B — BOT/TOP — Green/Red
DDS0 LEDs DDS1 LEDs DDS2 LEDs DDS3 LEDs

FTG1 FTG2 FTG3 FTG4

U_Supply_DDS
Supply_DDS.SchDoc
SDA SCL

Trace lengths matched within each of DDS_SYNC_CLK[3:0], DDS_UDPATE[3:0], RF_SW_CTRL[3:0], IO[15:11] (RF_SW ctrl lines), DDS_SYNC_IN[3:0], DDS_RESET[3:0], DDS_CLK[3:0]

Project/Equipment ARTIQ/SINARA

Document **3U DDS (URUKUL)** *Top entity*

Designer G.K.	
Drawn by G.K.	XX/XX/XXXX
Check.by	-
Last Mod. -	10.10.2017
File PCB_3U_DDS.schdoc	
Print Date 10.10.2017 01:01:12	Sheet 1 of 7

Warsaw Univeristy of Technology *ISE*
Nowowiejska 15/19

ARTIQ — Size A3 — Rev -

FSEN = 1 -> type 2 receiver with offset; hanging input causes L at the output



EEM Connector
All signals are LVDS, in case of Metlino VCC is 1.8V
I2C is 3.3V LVCMOS
P3V3_MP can handle up to 20mA
P12V0 current is up to 1A









Project/Equipment	ARTIQ/SINARA		
Document	**LVDS to LVTTL interface & EEM connector**	Designer G.K.	
		Drawn by G.K.	XX/XX/XXXX
		Check.by	-
		Last Mod. -	10.10.2017
		File LVDS_IFC_DDS.SchDoc	
		Print Date 10.10.2017 01:01:13	Sheet 2 of 7
Warsaw Univeristy of Technology *Nowowiejska 15/19*	*ISE*	ARTIQ	Size A3 / Rev -

FSEN = 1 -> type 2 receiver with offset; hanging input causes L at the output



EEM Connector
All signals are LVDS, in case of Metlino VCC is 1.8V
I2C is 3.3V LVCMOS
P3V3_MP can handle up to 20mA
P12V0 current is up to 1A









Project/Equipment	ARTIQ/SINARA		
Document	**LVDS to LVTTL interface & EEM connector**	Designer G.K.	
		Drawn by G.K.	XX/XX/XXXX
		Check.by	-
		Last Mod. -	10.10.2017
		File LVDS_IFC_DDS.SchDoc	
		Print Date 10.10.2017 01:01:13	Sheet 2 of 7
Warsaw Univeristy of Technology Nowowiejska 15/19	*ISE*	ARTIQ	Size A3 / Rev -



ADR: 1001 000







Power budget (max ratings):	AD9912 variant(mA)	AD9910 variant(mA)
P3V3:		
LVDS interface 4x	660	660
LVDS load 4x24mA	96	96
CPLD	100	100
Si53312-B-GM	240	240
Si453304	-	100
DDS AVDD3	4*(9,6+31)=133,6	4*29=116
DDS DVDDIO	4*3=12	4*11=44
TOTAL P3V3	1121	1246
TOTAL POWER	3.7	3.9
P1V8:		
DDS AVDD	4*(48+136)=736	4*110=440
DDS DVDD	4*246=984	4*222=888
TOTAL P1V8	1720	1328
TOTAL POWER	3,096	2.39
P5V0		
HMC542BLP4E	4*2.9=11.6	4*2.9=11.6
HMC349LP4C	4*3.5=14	4*3.5=14
TOTAL 5V0	25.6	25.6
TOTAL POWER	0,125	0,125
P7V0		
ERA-3XSM+	4*35=150	4*35=150
TOTAL POWER	1.05	1.05
DC/DC converter losses		
TPS62175 eff .95	0,05*(.27+0,026)*7,5=0.11	0,05*(.27+0,026)*7,5=0.11
LTM:3.6V eff .9	0.1*1,321*3,6=0,47	0,1*1,346*3,6=0,48
LTM:2V eff .87	0.13*1,721*2=0,44	0.13*1.328*2=0.34
LDO losses		
2V->1.8V	0.34	0,26
3.6V->3.3V	0.396	0.4
7.5V->7V	0,135	0,135
7.5V->5V	0,064	0,064
Total power from 12V	9.95W	9.05
Total current from 12V	0.83A	0.75A

P1V8A P2V0 P3V3 P3V3A P3V3_MP P3V6 P5V0A P7V0A P12V0 — TP10 TP11 TP12 TP13 TP14 TP15 TP16 TP17 TP18







Project/Equipment	ARTIQ/SINARA		
Document	**Power supply DC/DC & LDOs**	Designer G.K.	
		Drawn by G.K.	XX/XX/XXXX
		Check.by	-
		Last Mod. -	10.10.2017
		File Supply_DDS.SchDoc	
		Print Date 10.10.2017 01:01:13	Sheet 3 of 7
Warsaw Univeristy of Technology *Nowowiejska 15/19*	*ISE*	ARTIQ	Size A3 / Rev -


Jumpers R57/R59 and R58/C28 select between filter options
Jumper
Jumper
9912 devkit uses ADT2-1T-1P wich is footprint compatible
Digital Attenuator
IC3A
HMC542BLP4E
F clk max = 30MHz
ATT_LE
ATT_S_IN
ATT_S_OUT
ATT_CLK
ATT_RSTn
With about 1dBm out of the DDS, 0.5 dB insertion loss from the Balun, 0.5 dB from the lowpass, 1.5 dB from the attenuator, we need a 9dB T-pad to attenuate that before the ERA-3+ with 23 dB gain and P1dB of 13 dBm at our frequencies.
R137 power = 35mA^2*100 = 0.12W
Amplifier
23 dB gain and 13 dBm P1dB
ERA-3+
SPDT switch
IC23A
HMC349ALP4E
RFSW_CTRL
RF_OUT
Copyright WUT 2017
This documentation describes Open Hardware and is licensed under the CERN OHL v.1.1. You may redistribute and modify this documentation under the terms of the CERN OHL v.1.1. (http://ohwr.org/CERNOHL). This documentation is distributed WITHOUT ANY EXPRESS OR IMPLIED WARRANTY, INCLUDING OF MERCHANTABILITY, SATISFACTORY QUALITY AND FITNESS FOR A PARTICULAR PURPOSE. Please see the CERN OHL v.1.1 for applicable conditions.
Project/Equipment ARTIQ/SINARA
Document
Output stage : Attenuator, amplifier and filter
Designer G.K.
Drawn by G.K. XX/XX/XXXX
Check.by -
Last Mod. - 10.10.2017
File DDS_OUT_channel.SchDoc
Print Date 10.10.2017 01:01:14 Sheet 4 of 7
Warsaw Univeristy of Technology ISE
Nowowiejska 15/19
ARTIQ
Size A3 Rev -


Jumpers R57/R59 and R58/C28 select between filter options
Jumper
Jumper
9912 devkit uses ADT2-1T-1P wich is footprint compatible
ADT1-1WT+
1:1
TR1B
Digital Attenuator
IC3B
HMC542BLP4E
F clk max = 30MHz
With about 1dBm out of the DDS, 0.5 dB insertion loss from the Balun, 0.5 dB from the lowpass, 1.5 dB from the attenuator, we need a 9dB T-pad to attenuate that before the ERA-3+ with 23 dB gain and P1dB of 13 dBm at our frequencies.
PAT1220-C-9DB-T5
R137 power = 35mA^2*100 = 0.12W
ERA-3+
Amplifier
23 dB gain and 13 dBm P1dB
SPDT switch
IC23B
HMC349ALP4CE
RFSW_CTRL
RF_OUT
DC to 320MHz
Copyright WUT 2017
This documentation describes Open Hardware and is licensed under the CERN OHL v.1.1. You may redistribute and modify this documentation under the terms of the CERN OHL v.1.1. (http://ohwr.org/CERNOHL). This documentation is distributed WITHOUT ANY EXPRESS OR IMPLIED WARRANTY, INCLUDING OF MERCHANTABILITY, SATISFACTORY QUALITY AND FITNESS FOR A PARTICULAR PURPOSE. Please see the CERN OHL v.1.1 for applicable conditions.
Project/Equipment ARTIQ/SINARA
Document
Output stage : Attenuator, amplifier and filter
Designer G.K.
Drawn by G.K. XX/XX/XXXX
Check.by -
Last Mod. - 10.10.2017
File DDS_OUT_channel.SchDoc
Print Date 10.10.2017 01:01:14 Sheet 4 of 7
Warsaw Univeristy of Technology ISE
Nowowiejska 15/19
ARTIQ
Size A3 Rev -


50_Ohms
GND
C164C
C203C
R48C
C172C
C204C
R49C
C176C
C205C
R50C
C180C
C206C
R51C
C202C
C207C
Undefined
Jumpers R57/R59 and R58/C28 select between filter options
R57C
R59C
R58C
10nF
C28C
Jumper
FL2C
DC to 320MHz
DAC_OUT_N
DAC_OUT_P
49R9
R54C
R38C
100
R8C
9910 only
ADT1-1WT+
1:1
TR1C
SEC
PRI
9912 devkit uses ADT2-1T-1P wich is footprint compatible
Digital Attenuator
IC3C
ATT_LE
ATT_S_IN
ATT_S_OUT
ATT_CLK
ATT_RSTn
F clk max = 30MHz
LE
S_IN
S_OUT
CLK
RST
CONTROL INTERFACE
0.5dB
1dB
2dB
4dB
8dB
16dB
RF1
RF2
ACG1
ACG2
ACG3
ACG4
ACG5
ACG6
ACG7
NC
VCC
HMC542BLP4E
C14C
C15C
C16C
C17C
C18C
C19C
C20C
C36C
P5V0A
L7C
390R@100MHz
C21C
C22C
C23C
C24C
10uF
100nF
1nF
100pF
With about 1dBm out of the DDS, 0.5 dB insertion loss from the Balun, 0.5 dB from the lowpass, 1.5 dB from the attenuator, we need a 9dB T-pad to attenuate that before the ERA-3+ with 23 dB gain and P1dB of 13 dBm at our frequencies.
PAT1220-C-9DB-T5
IC17C
9dB
P7V0A
R137 power = 35mA^2*100 = 0.12W
R137C
C12C
C27C
1uF
0.5uH@200mA
L1C
TCCH-80+
IC5C
ERA-3+
C55C
C29C
Amplifier
23 dB gain and 13 dBm P1dB
SPDT switch
IC23C
RFC
EN
VCTL
VDD
HMC349ALP4CE
R138C
RFSW_CTRL
R20C
4k7
C38C
C39C
C40C
L6C
C49C
R2C
C50C
RF_OUT
R3C
R4C
R46C
R47C
Undefined
Copyright WUT 2017
This documentation describes Open Hardware and is licensed under the CERN OHL v.1.1. You may redistribute and modify this documentation under the terms of the CERN OHL v.1.1. (http://ohwr.org/CERNOHL). This documentation is distributed WITHOUT ANY EXPRESS OR IMPLIED WARRANTY, INCLUDING OF MERCHANTABILITY, SATISFACTORY QUALITY AND FITNESS FOR A PARTICULAR PURPOSE. Please see the CERN OHL v.1.1 for applicable conditions.
Project/Equipment ARTIQ/SINARA
Document
Output stage : Attenuator, amplifier and filter
Designer G.K.
Drawn by G.K.
XX/XX/XXXX
Check.by -
Last Mod. - 10.10.2017
File DDS_OUT_channel.SchDoc
Print Date 10.10.2017 01:01:15
Sheet 4 of 7
Warsaw Univeristy of Technology
Nowowiejska 15/19
ISE
ARTIQ
Size A3
Rev -


50_Ohms
GND
C164D
C203D
R48D
C172D
C204D
R49D
C176D
C205D
R50D
C180D
C206D
R51D
C202D
C207D
Undefined
Jumpers R57/R59 and R58/C28 select between filter options
R57D
R59D
Jumper
FL2D
DC to 320MHz
R58D
10nF
C28D
Jumper
DAC_OUT_N
DAC_OUT_P
49R9
R54D
R38D
9910 only
ADT1-1WT+
1:1
TR1D
SEC
PRI
9912 devkit uses ADT2-1T-1P wich is footprint compatible
Digital Attenuator
IC3D
ATT_LE
ATT_S_IN
ATT_S_OUT
ATT_CLK
ATT_RSTn
F clk max = 30MHz
LE
S_IN
S_OUT
CLK
RST
CONTROL INTERFACE
0.5dB
1dB
2dB
4dB
8dB
16dB
RF1
RF2
ACG1
ACG2
ACG3
ACG4
ACG5
ACG6
ACG7
VCC
NC
HMC542BLP4E
C36D
10nF
C14D
C15D
C16D
C17D
C18D
C19D
C20D
P5V0A
L7D
390R@100MHz
C21D
C22D
C23D
C24D
1uF
100nF
1nF
100pF
With about 1dBm out of the DDS, 0.5 dB insertion loss from the Balun, 0.5 dB from the lowpass, 1.5 dB from the attenuator, we need a 9dB T-pad to attenuate that before the ERA-3+ with 23 dB gain and P1dB of 13 dBm at our frequencies.
PAT1220-C-9DB-T5
IC17D
9dB
P7V0A
R137 power = 35mA^2*100 = 0.12W
R137D
C12D
C27D
0.5uH@200mA
L1D
TCCH-80+
IC5D
ERA-3+
C55D
C29D
Amplifier
23 dB gain and 13 dBm P1dB
SPDT switch
IC23D
RFC
EN
VCTL
VDD
HMC349ALP4CE
R138D
RFSW_CTRL
R20D
4k7
C38D
C39D
C40D
L6D
C49D
C50D
R2D
R3D
R4D
C47D
R46D
R45D
RF_OUT
Copyright WUT 2017
This documentation describes Open Hardware and is licensed under the CERN OHL v.1.1. You may redistribute and modify this documentation under the terms of the CERN OHL v.1.1. (http://ohwr.org/CERNOHL). This documentation is distributed WITHOUT ANY EXPRESS OR IMPLIED WARRANTY, INCLUDING OF MERCHANTABILITY, SATISFACTORY QUALITY AND FITNESS FOR A PARTICULAR PURPOSE. Please see the CERN OHL v.1.1 for applicable conditions.
Project/Equipment ARTIQ/SINARA
Document
Output stage : Attenuator, amplifier and filter
Designer G.K.
Drawn by G.K. XX/XX/XXXX
Check.by -
Last Mod. - 10.10.2017
File DDS_OUT_channel.SchDoc
Print Date 10.10.2017 01:01:15 Sheet 4 of 7
Warsaw Univeristy of Technology ISE
Nowowiejska 15/19
ARTIQ
Size A3
Rev -



Table 8. Default Power-Up Frequency Options for 1 GHz System Clock

Status Pin				SYSCLK Input Mode	Output Frequency (MHz)
S4	S3	S2	S1		
0	0	0	0	Xtal/PLL	0
0	0	0	1	Xtal/PLL	38.87939
0	0	1	0	Xtal/PLL	51.83411
0	0	1	1	Xtal/PLL	61.43188
0	1	0	0	Xtal/PLL	77.75879
0	1	0	1	Xtal/PLL	92.14783
0	1	1	0	Xtal/PLL	122.87903
0	1	1	1	Xtal/PLL	155.51758
1	0	0	0	Direct	0
1	0	0	1	Direct	38.87939
1	0	1	0	Direct	51.83411
1	0	1	1	Direct	61.43188
1	1	0	0	Direct	77.75879
1	1	0	1	Direct	92.14783
1	1	1	0	Direct	122.87903
1	1	1	1	Direct	155.51758

Project/Equipment	ARTIQ/SINARA
Document	9910 & 9912 DDS
Designer	G.K.
Drawn by	G.K. XX/XX/XXXX
Check.by	-
Last Mod.	- 10.10.2017
File	DDS_channel.SchDoc
Print Date	10.10.2017 01:01:15 Sheet 5 of 7
Warsaw Univeristy of Technology Nowowiejska 15/19	ISE
ARTIQ	Size A3 Rev -

separate RSET and loop filter components due to layout constraints

Clock Mode Select. Set to GND when connecting a crystal to the system clock input (Pin 27 and Pin 28). Pull up to 1.8 V when using either an oscillator or an external clock source.

System Clock Multiplier Loop Filter. When using the frequency multiplier to drive the system clock, an external loop filter must be constructed and attached to this pin. This pin should be pulled down to ground with 1 kΩ resistor when the system clock PLL is bypassed

Loop filter calculation:
Reference input frequency : 50MHz
PFD : 50MHz
multiplication factor: 20MHz
system clock frequency : 1GHz
desired phase margin: 65deg
Open loop BW: 1.6MHz

R=859R
Cs=522p
Cp=27p

Clock must be AC coupled

Power-Down. When this active high pin is asserted, the device becomes inactive and enters the full power down state. This pin has an internal 50 kΩ pull-down resistor.

PIN37 is not used but must be powered 1.8 or 3.3

Table 8. Default Power-Up Frequency Options for 1 GHz System Clock

Status Pin				SYSCLK	Output Frequency
S4	S3	S2	S1	Input Mode	(MHz)
0	0	0	0	Xtal/PLL	0
0	0	0	1	Xtal/PLL	38.87939
0	0	1	0	Xtal/PLL	51.83411
0	0	1	1	Xtal/PLL	61.43188
0	1	0	0	Xtal/PLL	77.75879
0	1	0	1	Xtal/PLL	92.14783
0	1	1	0	Xtal/PLL	122.87903
0	1	1	1	Xtal/PLL	155.51758
1	0	0	0	Direct	0
1	0	0	1	Direct	38.87939
1	0	1	0	Direct	51.83411
1	0	1	1	Direct	61.43188
1	1	0	0	Direct	77.75879
1	1	0	1	Direct	92.14783
1	1	1	0	Direct	122.87903
1	1	1	1	Direct	155.51758

Project/Equipment	ARTIQ/SINARA
Document	9910 & 9912 DDS
Designer	G.K.
Drawn by	G.K. XX/XX/XXXX
Check.by	-
Last Mod.	- 10.10.2017
File	DDS_channel.SchDoc
Print Date	10.10.2017 01:01:16 Sheet 5 of 7
Warsaw Univeristy of Technology Nowowiejska 15/19	ISE ARTIQ Size A3 Rev -

Clock Mode Select. Set to GND when connecting a crystal to the system clock input (Pin 27 and Pin 28). Pull up to 1.8 V when using either an oscillator or an external clock source.

separate RSET and loop filter components due to layout constraints

System Clock Multiplier Loop Filter. When using the frequency multiplier to drive the system clock, an external loop filter must be constructed and attached to this pin. This pin should be pulled down to ground with 1 kΩ resistor when the system clock PLL is bypassed

Loop filter calculation:
Reference input frequency : 50MHz
PFD : 50MHz
multiplication factor: 20MHz
system clock frequency : 1GHz
desired phase margin: 65deg
Open loop BW: 1.6MHz

R=859R
Cs=522p
Cp=27p

Clock must be AC coupled

Power-Down. When this active high pin is asserted, the device becomes inactive and enters the full power down state. This pin has an internal 50 kΩ pull-down resistor.

PIN37 is not used but must be powered 1.8 or 3.3

Table 8. Default Power-Up Frequency Options for 1 GHz System Clock

Status Pin				SYSCLK	Output Frequency
S4	S3	S2	S1	Input Mode	(MHz)
0	0	0	0	Xtal/PLL	0
0	0	0	1	Xtal/PLL	38.87939
0	0	1	0	Xtal/PLL	51.83411
0	0	1	1	Xtal/PLL	61.43188
0	1	0	0	Xtal/PLL	77.75879
0	1	0	1	Xtal/PLL	92.14783
0	1	1	0	Xtal/PLL	122.87903
0	1	1	1	Xtal/PLL	155.51758
1	0	0	0	Direct	0
1	0	0	1	Direct	38.87939
1	0	1	0	Direct	51.83411
1	0	1	1	Direct	61.43188
1	1	0	0	Direct	77.75879
1	1	0	1	Direct	92.14783
1	1	1	0	Direct	122.87903
1	1	1	1	Direct	155.51758

Project/Equipment ARTIQ/SINARA

Document **9910 & 9912 DDS**

Designer G.K.
Drawn by G.K. XX/XX/XXXX
Check.by -
Last Mod. - 10.10.2017
File DDS_channel.SchDoc
Print Date 10.10.2017 01:01:16 Sheet 5 of 7

Warsaw Univeristy of Technology ISE
Nowowiejska 15/19

ARTIQ

Size A3 Rev -



Table 8. Default Power-Up Frequency Options for 1 GHz System Clock

Status Pin				SYSCLK Input Mode	Output Frequency (MHz)
S4	S3	S2	S1		
0	0	0	0	Xtal/PLL	0
0	0	0	1	Xtal/PLL	38.87939
0	0	1	0	Xtal/PLL	51.83411
0	0	1	1	Xtal/PLL	61.43188
0	1	0	0	Xtal/PLL	77.75879
0	1	0	1	Xtal/PLL	92.14783
0	1	1	0	Xtal/PLL	122.87903
0	1	1	1	Xtal/PLL	155.51758
1	0	0	0	Direct	0
1	0	0	1	Direct	38.87939
1	0	1	0	Direct	51.83411
1	0	1	1	Direct	61.43188
1	1	0	0	Direct	77.75879
1	1	0	1	Direct	92.14783
1	1	1	0	Direct	122.87903
1	1	1	1	Direct	155.51758

Project/Equipment	ARTIQ/SINARA
Document	9910 & 9912 DDS
Designer	G.K.
Drawn by	G.K. XX/XX/XXXX
Check.by	-
Last Mod.	- 10.10.2017
File	DDS_channel.SchDoc
Print Date	10.10.2017 01:01:17 Sheet 5 of 7
Warsaw Univeristy of Technology Nowowiejska 15/19	ISE
ARTIQ	Size A3 Rev -



Project/Equipment	ARTIQ/SINARA
Document	Clock distribution and generation
Designer	G.K.
Drawn by	G.K. XX/XX/XXXX
Check.by	-
Last Mod.	- 10.10.2017
File	CLK_INPUT.SchDoc
Print Date	10.10.2017 01:01:17 Sheet 6 of 7
Warsaw Univeristy of Technology Nowowiejska 15/19	ISE
ARTIQ	Size A3 Rev -



Project/Equipment	ARTIQ/SINARA
Document	**CPLD logic & option switches**
Designer	G.K.
Drawn by	G.K. XX/XX/XXXX
Check.by	-
Last Mod.	- 10.10.2017
File	CTRL_LOGIC.SchDoc
Print Date	10.10.2017 01:01:17 Sheet 7 of 7
Author	*Warsaw Univeristy of Technology Nowowiejska 15/19*
Author	*ISE*
Author	ARTIQ
Size	A3
Rev	-


RF OUT 0
J3
IC5A
IC23A
IC17A
IC3A
LD5
RF OUT 1
J4
IC5B
IC23B
IC17B
IC3B
LD6
RF OUT 2
J5
IC5C
IC23C
IC17C
IC3C
LD8
RF OUT 3
J6
IC5D
IC23D
IC17D
IC3D
LD2
EXT CLK IN
J2
P2V0
INT CLK IN
J7
LD7
IC21
P5V0
P3V6
LD9
P5V0A
LD1
OSC1
IC2A
IC13A
IC2B
IC13B
IC2C
IC13C
IC2D
IC13D
P1V8A
TP0
TP2
TP4
TP1
TP3
P3V6
IC18
IC10
MODE
P3V3_MP
LD10
J8
JTAG
EEM A
J1B
EEM B
J1A
IC16
IC19
LD4
INT OSC
MMCX CLK
P3V3
IC9
P12V0
LD3
P3V3_MP
P2V0
P3V3A
IC7
IC11
IC15
IC22
3U DDS rev 1.0
WUT ISE 2017


IC14
IC4
IC1A
IC1B
IC6A
IC6B
IC8B
IC8A

RF OUT 0
J3
LD5
RF OUT 1
J4
LD6
RF OUT 2
J5
LD8
RF OUT 3
J6
LD2
EXT CLK IN
J2
LD7
P7V0
INT CLK IN
J7
IC5A
IC5B
IC5C
IC5D
IC23A
IC23B
IC23C
IC23D
IC17A
IC17B
IC17C
IC17D
IC3A
IC3B
IC3C
IC3D
IC21
IC20
P5V0
OSC1
LD9
P5V0A
P3V6
LD1
IC2A
IC2B
IC2C
IC2D
IC13A
IC13B
IC13C
IC13D
P1V8A
TP0
TP1
TP2
TP3
TP4
P3V6
IC18
IC10
MODE
ON
1 2 3 4
J8
P3V3_MP
GND
JTAG
EEM A
J1B
EEM B
J1A
IC16
IC19
LD4
INT OSC
MMCX CLK
P3V3
IC9
P12V0
LD3
P3V3_MP
P2V0
P3V3A
IC7
IC11
IC15
IC22
30
30

3U DDS rev 1.0 WUT ISE 2017













IC15

IC14

IC4

IC1B

IC1A

IC6B

IC6A

IC8B

IC8A