


Lvalues and Rvalues


```
int &y = 0;  
int x = y;  
const SymOp &s1= SymOp();
```

Lvalue denotes an object whose resource cannot be reused and are generally the names of objects.

Rvalues are objects that cannot be reused.
Usually they are temporary/soon to be destroyed.



Lvalues and Rvalues



```
int &y = 0;  
int x = y;  
const SymOp &s1= SymOp();
```

Lvalue denotes an object whose resource cannot be reused and are generally the names of objects.

0


y

Rvalues are objects that cannot be reused.
Usually they are temporary/soon to be destroyed.

Lvalue Reference vs. Rvalue Reference

```
void apply_sym(const SymOp& op, Structure& struc);  
Structure apply_sym(const SymOp& op, const Structure &struc);  
Structure apply_sym(const SymOp& op, Structure &&struc);
```

void apply_sym(const SymOp& op, Structure& struc);
Applies symmetry operation, op, in a non-const way
using struc as a bound lvalue reference.
Hint look for single &.




Lvalue Reference vs. Rvalue Reference


```
void apply_sym(const SymOp& op, Structure& struc);  
Structure apply_sym(const SymOp& op, const Structure &struc);  
Structure apply_sym(const SymOp& op, Structure &&struc);
```

void apply_sym(const SymOp& op, Structure& struc);
Applies symmetry operation, op, in a non-const way
using struc as a bound lvalue reference.
Hint look for single &.

function



user




Lvalue Reference vs. Rvalue Reference


```
void apply_sym(const SymOp& op, Structure& struc);  
Structure apply_sym(const SymOp& op, const Structure &struc);  
Structure apply_sym(const SymOp& op, Structure &&struc);
```

void apply_sym(const SymOp& op, Structure& struc);
Applies symmetry operation, op, in a non-const way
using struc as a bound lvalue reference.
Hint look for single &.

function



user




Lvalue Reference vs. Rvalue Reference


```
void apply_sym(const SymOp& op, Structure& struc);  
Structure apply_sym(const SymOp& op, const Structure &struc);  
Structure apply_sym(const SymOp& op, Structure &&struc);
```

void apply_sym(const SymOp& op, Structure& struc);
Applies symmetry operation, op, in a non-const way
using struc as a bound lvalue reference.
Hint look for single &.

function



user




Lvalue Reference vs. Rvalue Reference

```
void apply_sym(const SymOp& op, Structure& struc);  
Structure apply_sym(const SymOp& op, const Structure &struc);  
Structure apply_sym(const SymOp& op, Structure &&struc);
```

Structure apply_sym(const SymOp& op, const Structure
&struc);

Applies symmetry operation, op, in a secure way using struc
as a bound const lvalue reference.

Hint look for single & and const.




Lvalue Reference vs. Rvalue Reference

```
void apply_sym(const SymOp& op, Structure& struc);  
Structure apply_sym(const SymOp& op, const Structure &struc);  
Structure apply_sym(const SymOp& op, Structure &&struc);
```

Structure apply_sym(const SymOp& op, const Structure
&struc);

Applies symmetry operation, op, in a secure way using struc
as a bound const lvalue reference.

Hint look for single & and const.



Lvalue Reference vs. Rvalue Reference

```
void apply_sym(const SymOp& op, Structure& struc);  
Structure apply_sym(const SymOp& op, const Structure &struc);  
Structure apply_sym(const SymOp& op, Structure &&struc);
```


Structure apply_sym(const SymOp& op, const Structure
&struc);

Applies symmetry operation, op, in a secure way using struc
as a bound const lvalue reference.

Hint look for single & and const.

function

user




Lvalue Reference vs. Rvalue Reference

```
void apply_sym(const SymOp& op, Structure& struc);  
Structure apply_sym(const SymOp& op, const Structure &struc);  
Structure apply_sym(const SymOp& op, Structure &&struc);
```

Structure apply_sym(const SymOp& op, Structure &&struc);
Applies symmetry operation, op, in a potentially non-const way using struc as a bound rvalue reference.

Hint look for double &&.




Lvalue Reference vs. Rvalue Reference

```
void apply_sym(const SymOp& op, Structure& struc);  
Structure apply_sym(const SymOp& op, const Structure &struc);  
Structure apply_sym(const SymOp& op, Structure &&struc);
```

Structure apply_sym(const SymOp& op, Structure &&struc);
Applies symmetry operation, op, in a potentially non-const way using struc as a bound rvalue reference.

Hint look for double &&.




Lvalue Reference vs. Rvalue Reference

```
void apply_sym(const SymOp& op, Structure& struc);  
Structure apply_sym(const SymOp& op, const Structure &struc);  
Structure apply_sym(const SymOp& op, Structure &&struc);
```

Structure apply_sym(const SymOp& op, Structure &&struc);
Applies symmetry operation, op, in a potentially non-const way using struc as a bound rvalue reference.

Hint look for double &&.




Lvalue Reference vs. Rvalue Reference

```
void apply_sym(const SymOp& op, Structure& struc);  
Structure apply_sym(const SymOp& op, const Structure &struc);  
Structure apply_sym(const SymOp& op, Structure &&struc);
```

Structure apply_sym(const SymOp& op, Structure &&struc);
Applies symmetry operation, op, in a potentially non-const way using struc as a bound rvalue reference.

Hint look for double &&.



Rules

- Cannot bind rvalue reference to lvalue or lvalue reference
- Cannot bind non-const lvalue reference to rvalue or rvalue reference