

深圳市达妙科技有限公司

电机模组选型表

类型	电机型号	额定扭矩 (Nm)	峰值扭矩 (Nm)	空载转速 (rpm)	额定转速 (rpm)	减速比	尺寸 直径*高度 (mm)	重量 (g)	供电电压 (V)	建议供电范围 (V)	额定相电流 (A)	峰值相电流 (A)	额定功率 (W)	极对数	槽数	通信方式	编码器类型	驱动配置 方式	相间电阻 (Ω)	相间电感 (uH)	电感值 (mH)	转动惯量 (Kg*m^2)	齿轮系数	扭矩系数 (Nm/A)	额定最大电流 (A)	默认 PMAx (rad)	默认 VMAx (rad/s)	默认 TMAx (Nm)	速度常数
关节电机 DM-J-定子直径+减速比+编码器数量+通信方式	DM-J3507-2EC	0.8	3	460	150	7	46*37.9	约150	24	15-30	2.4	8.3	12.6	14	24	CAN、CANFD	磁编，双编	内置	0.8	235	0.0037	8.70E-06	1	0.5439	10.261194	12.566	50	5	106.4341497
	DM-J4310-2EC V1.1	3	7	200	120	10	57*46	约300	24	15-32	3.7	7.2	37.7	14	24	CAN、CANFD	磁编，双编	内置	0.85	345	0.0045	1.80E-05	1	0.945	10.261194	12.5	30	10	87.51252308
	DM-J4310-2EC V1.1 (48V)	3	7	400	120	10	57*46	约300	48	15-52	3.7	7.2	37.7	14	24	CAN、CANFD	磁编，双编	内置	0.85	345	0.0045	1.80E-05	1	0.945	10.261194	12.5	30	10	87.51252308
	DM-J4310P-2EC	3.5	12.5	200	120	10	57*49.05	约325	24	15-32	4.9	20	44.0	14	24	CAN、CANFD	磁编，双编	内置	0.58	320	0.0042	1.90E-05	1	0.882	20.522388	12.5	30	10	93.76341759
	DM-J4310P-2EC (48V)	3.5	12.5	450	120	10	57*49.05	约325	48	15-52	4.8	20	44.0	14	24	CAN、CANFD	磁编，双编	内置	0.58	320	0.0042	1.90E-05	1	0.882	20.522388	12.5	30	10	93.76341759
	DM-J4340-2EC	9	27	52.5	36	40	57*53.3	约362	24	15-32	3	8	33.9	14	24	CAN、CANFD	磁编，双编	内置	0.88	360	0.00485	2.00E-05	1	4.074	10.261194	12.5	8	28	81.19718637
	DM-J4340-2EC (48V)	9	27	100	36	40	57*53.3	约362	48	15-52	2.5	9	33.9	14	24	CAN、CANFD	磁编，双编	内置	0.88	360	0.00485	2.00E-05	1	4.074	10.261194	12.5	8	28	81.19718637
	DM-J4340P-2EC	9	27	52.5	36	40	57*56.5	约375	24	15-32	3	8	33.9	14	24	CAN、CANFD	磁编，双编	内置	0.88	360	0.00485	2.00E-05	1	4.074	10.261194	12.5	8	28	81.19718637
	DM-J4340P-2EC (48V)	9	27	100	36	40	57*56.5	约375	48	15-52	2.5	9	33.9	14	24	CAN、CANFD	磁编，双编	内置	0.88	360	0.00485	2.00E-05	1	4.074	10.261194	12.5	8	28	81.19718637
	DM-J6006-2EC	4	11	226@24V 392.8@48V	150	6	76*36.5	约335	24-48	15-52	5.96	17.6	62.8	14	24	CAN、CANFD	磁编，双编	内置	0.435	270	0.0058	5.80E-05	1	0.7308	20.52238806	12.5	45	20	67.89764722
	DM-J6248P-2EC	30	97	60	40	48	76*62.5	约628	24-48	15-65	11.3	38.7	125.7	14	24	CAN、CANFD	磁编，双编	内置	0.17	85	0.0033	5.40E-05	1	3.3264	01.044777	12.5	20	150	119.3352587
	DM-J8006-2EC (停产)	8	20	194.2@24V 392.8@48V	120	6	96*40	约550	24-48	15-52	9	21	100.5	21	36	CAN	磁编，双编	内置	0.4	215	0.0054	1.15E-04	1	1.0206	01.04477612	12.5	45	40	48.61806838
	DM-J8006-2EC V1.1	8	20	194.2@24V 392.8@48V	120	6	96*40	约559	24-48	15-52	9	21	100.5	21	36	CAN、CANFD	磁编，双编	内置	0.4	215	0.0054	1.15E-04	1	1.0206	01.04477612	12.5	45	40	48.61806838
	DM-J8009-2EC	20	40	168@24V	100@24V	9	98*61.7	约896	24-48	15-52	18.6	40	209.4	21	36	CAN、CANFD	磁编，双编	内置	0.145	80	0.00445	1.95E-04	1	1.261575	01.04477612	12.5	45	54	58.99720657
		20	40	335@48V	200@48V	9	98*61.7	约896	24-48	15-52	18.6	40	418.9	21	36	CAN、CANFD	磁编，双编	内置	0.145	80	0.00445	1.95E-04	1	1.261575	01.04477612	12.5	45	54	58.99720657
	DM-J8009P-2EC	20	40	168@24V	100@24V	9	98*61.7	约921	24-48	15-52	18.6	40	209.4	21	36	CAN、CANFD	磁编，双编	内置	0.145	80	0.00445	1.95E-04	1	1.261575	01.04477612	12.5	45	54	58.99720657
		20	40	335@48V	200@48V	9	98*61.7	约921	24-48	15-52	18.6	40	418.9	21	36	CAN、CANFD	磁编，双编	内置	0.145	80	0.00445	1.95E-04	1	1.261575	01.04477612	12.5	45	54	58.99720657
	DM-J10010-2EC	40	150	75@24V	50@24V	10	112*62 (最大外径120)	约1485	24-48	15-52	18.4	80.2	209.4	21	36	CAN、CANFD	磁编，双编	内置	0.125	100	0.00825	5.50E-04	1	2.59875	100	12.5	20	200	31.82273567
		40	150	150@48V	100@48V	10	112*62 (最大外径120)	约1485	24-48	15-52	18.4	80.2	418.9	21	36	CAN、CANFD	磁编，双编	内置	0.125	100	0.00825	5.50E-04	1	2.59875	100	12.5	20	200	31.82273567
	DM-J10010L-2EC	40	120	100@24V	70@24V	10	120*53 (高度不含定位销)	约1375	24-48	15-52	23.5	95	293.2	21	36	CAN、CANFD	磁编，双编	内置	0.11	85	0.00635	5.56E-04	1	2.00025	99.7	12.5	25	200	41.34449909
		40	120	200@48V	100@48V	10	120*53 (高度不含定位销)	约1375	24-48	15-52	23.5	95	418.9	21	36	CAN、CANFD	磁编，双编	内置	0.11	85	0.00635	5.56E-04	1	2.00025	99.7	12.5	25	200	41.34449909
分立电机	DM-J10422P-2EC	100	400	120	100	22	110*89.9	约2700	48	20-65	44.5	165	1047.2	16	36	CAN、CANFD	电感，双编	内置	0.081	38	0.00599	5.64E-04	1	3.16272	165	12.566	20	500	57.52596989
	DM-S3519-1EC	3.5	7.8	435	395	19.203	42*91.5	约396	24	15-32	9.2	20.5	144.8	7	12	CAN、CANFD	霍尔，增量式	分立	0.2	55	0.00225	1.80E-05	1	0.4536756	20.52238806	12.5	200	10	350.0500923
DM-S-定子直径+减速比+编码器数量+通信方式	DM-S2325-1EC	1.35	5	560	380	25	28*77.6	约172	24	15-60	5	13	53.7	7	12	CAN、CANFD	霍尔，增量式	分立	0.292	75	0.0014	3.80E-05	1	0.3675	20.523388	12.5	200	10	562.5805055
轮毂电机 DM-H-定子直径+高度	DM-H6215	1	2	320	120	1	68*42.5	约360	24	15-32	2.5	4.3	12.6	14	24	CAN、CANFD	霍尔，增量式	内置	2.5	2000	0.022	1.80E-04	1	0.462	10.261194	12.5	30	10	17.90028881
	DM-H3510	0.18	0.45	1800	500	1	42*31.5	约116	24	15-32	1.1	3.2	9.4	7	24	CAN、CANFD	磁编，绝对值	内置	2.08	1100	0.011	1.74E-05	1	0.1155	10.261194	12.5	280	1	71.60115525
	DM-H65	6	21.5	260@24V 395@36V 480@48V	120	1	171*66.3	约3150	24-48	20-65	9.4	33.6	250 (6nm 400rpm @48V S2工况)	15	27	CAN、CANFD	电感，绝对值	外置	0.42	750	0.024964	1.68E-03	1	0.56169	01.044777	12.566	100	40	14.72330544
	DM-H55	3.5	9	587rpm@24V 883rpm@36V 1185rpm@48V	350	1	141*66.9	约2100	24-48	20-65	13.05	33.55	128.3	10	18	CAN、CANFD	电感，绝对值	外置	0.281	336	0.018163	2.07E-03	1	0.272445	01.04477	12.566	100	40	30.35450616
中空云台 DM-G-定子直径+高度	DM-G6220	1.3	2.7	300	110	1	68*41.5	约493.5	24	15-32	2.3	4.6	15.0	14	24	CAN、CANFD	磁编，绝对值	内置	3	3000	0.028	1.25E-04	1	0.588	10.261194	12.5	45	10	14.06451264
谐波关节电机 DM-JH+系列+减速比+编码器数量+通信方式	DM-JH11-51-2EC	3.2	7.8	60	40	51	52*60	约345	24-48	20-54	2.23	4.26	13.4	7	12	CAN、CANFD	电感，双编	内置	1.1	538	0.0048	6.30E-06	0.6	2.5704	10.261194	12.5	10	12	164.0859808
	DM-JH11-101-2EC	4.8	10.5	30	20	101	52*60	约345	24-48	20-54	2.3	3.6	10.1	7	12	CAN、CANFD	电感，双编	内置	1.1	538	0.0048	6.30E-06	0.65	5.0904	10.261194	12.5	10	30	164.0859808
	DM-JH14-51-2EC	5.4	18	60	40	51	70*70	约775	24-48	20-54	4.89	13.7	22.6	10	18	CAN、CANFD	电感，双编	内置	0.243	170	0.0053518	6.00E-05	0.5	4.09414995	01.044777	12.566	10	50	103.0168924
	DM-JH14-101-2EC	7.8	28	30	20	101	70*70	约775	24-48	20-54	4.12	10.97	16.3	10	18	CAN、CANFD	电感，双编	内置	0.243	170	0.0053518	6.00E-05	0.45	8.10802245	01.044777	12.566	10	50	103.0168924
	DM-JH17-51-2EC	16	24	60	40	51	80*70	约985	24-48	20-54	4.62	12.94	67.0	10	18	CAN、CANFD	电感，双编	内置	0.161	107	0.00625	9.38E-05	0.5	4.78125	01.044777	12.566	20	80	88.21262327
	DM-JH17-101-2EC	24	54	30	20	101	80*70	约985	24-48	20-54	6.31	16.85	50.3	10	18	CAN、CANFD	电感，双编	内置	0.161	107	0.00625	9.38E-05	0.5	9.46875	01.044777	12.566	20	80	88.21262327
直驱电机 DM-D-定子直径+高度+编码器数量+E+通讯接口	DM-D5730 -1EE	0.65	1.9	1500	1100	1	57*95.2	约628	24-48	20-55	5.4	16.2	74.9	14	24	CAN、CANFD EtherCAT	电感，绝对值	内置	0.17	85	0.00617	6.00E-05	1	0.12957	20.522388	12.5	420	5	63.82598928
	DM-D5730 -1EC	0.65	1.9	1500	1100	1	57*95.2	约628	24-48	20-55	5.4	16.2	74.9	14	24	CAN、CANFD	电感，绝对值	内置	0.17	85	0.00617	6.00E-05	1	0.12957	20.522388	12.5	420	5	63.82598928