

Using Scikit Learn For Machine Learning

By..... Sakeeb Sheikh


Scikit Learn

- Let's talk about the basic structure of how to use Scikit Learn!
- First, a quick review of the machine learning process.

Scikit Learn

- Now let's go over an example of the process to use SciKit Learn.
- Don't worry about memorizing any of this, we'll get plenty of practice and review when we actually start coding in subsequent lectures!

Machine Learning Process



Scikit Learn

Every algorithm is exposed in scikit-learn via an "Estimator"
First you'll import the model, the general form is:

```
from sklearn.family import Model
```

For example:

```
from sklearn.linear_model import LinearRegression
```

Scikit Learn

Estimator parameters: All the parameters of an estimator can be set when it is instantiated, and have suitable default values.

You can use Shift+tab in jupyter to check the possible parameters.

Scikit Learn

For example:

```
model = LinearRegression(normalize=True)
print(model)
```

```
LinearRegression(copy_X=True, fit_intercept=True,  
normalize=True)
```


Scikit Learn

Once you have your model created with your parameters, it is time to fit your model on some data!

But remember, we should split this data into a training set and a test set.

Scikit Learn

```
>>> import numpy as np
>>> from sklearn.cross_validation import train_test_split
>>> X, y = np.arange(10).reshape((5, 2)), range(5)
>>> X
array([[0, 1],
       [2, 3],
       [4, 5],
       [6, 7],
       [8, 9]])
>>> list(y)
[0, 1, 2, 3, 4]
```

Scikit Learn

```
>>> X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.3)
```

```
>>> X_train
```

```
array([[4, 5],  
       [0, 1],  
       [6, 7]])
```

```
>>> y_train
```

```
[2, 0, 3]
```

```
>>> X_test
```

```
array([[2, 3],  
       [8, 9]])
```

```
>>> y_test
```

```
[1, 4]
```

Scikit Learn

Now that we have split the data, we can train/fit our model on the training data.

This is done through the `model.fit()` method:

```
model.fit(X_train,y_train)
```

Scikit Learn

- Now the model has been fit and trained on the training data.
- The model is ready to predict labels or values on the test set!

Scikit Learn

We get predicted values using the predict method:

```
predictions = model.predict(X_test)
```

Scikit Learn

We can then evaluate our model by comparing our predictions to the correct values.

The evaluation method depends on what sort of machine learning algorithm we are using (e.g. Regression, Classification, Clustering, etc.)

Scikit Learn

Scikit-learn strives to have a uniform interface across all methods, and we'll see examples of these below.

Given a scikit-learn *estimator* object named `model`, the following methods are available...

Scikit Learn

- Available in **all Estimators**
 - `model.fit()` : fit training data.
 - For supervised learning applications, this accepts two arguments: the data `X` and the labels `y` (e.g. `model.fit(X, y)`).
 - For unsupervised learning applications, this accepts only a single argument, the data `X` (e.g. `model.fit(X)`).

Scikit Learn

Available in **supervised estimators**

- `model.predict()` : given a trained model, predict the label of a new set of data. This method accepts one argument, the new data `X_new` (e.g. `model.predict(X_new)`), and returns the learned label for each object in the array.

Scikit Learn

Available in **supervised estimators**

- `model.predict_proba()` : For classification problems, some estimators also provide this method, which returns the probability that a new observation has each categorical label. In this case, the label with the highest probability is returned by `model.predict()`.

Scikit Learn

Available in **supervised estimators**

- `model.score()` : for classification or regression problems, most estimators implement a score method. Scores are between 0 and 1, with a larger score indicating a better fit.

Scikit Learn

Available in **unsupervised estimators**




- `model.transform()` : given an unsupervised model, transform new data into the new basis. This also accepts one argument `X_new`, and returns the new representation of the data based on the unsupervised model.

Scikit Learn

Available in **unsupervised estimators**

- `model.fit_transform()` : some estimators implement this method, which more efficiently performs a fit and a transform on the same input data.

classification



dimensionality
reduction



Now lets go for coding part to implement
a Machine Learning Model