



Create and manage volumes for Cloud Volumes Service for Google Cloud

Cloud Manager

Tom Onacki
October 07, 2020

This PDF was generated from https://docs.netapp.com/us-en/occm/task_manage_cvs_gcp.html on December 07, 2020. Always check docs.netapp.com for the latest.

Table of Contents

- Create and manage volumes for Cloud Volumes Service for Google Cloud 1
 - Create cloud volumes 1
 - Mount cloud volumes 4
 - Manage existing volumes..... 5
 - Remove Cloud Volumes Service from Cloud Manager 7
 - Manage Active Directory configuration 7

Create and manage volumes for Cloud Volumes Service for Google Cloud

Cloud Manager enables you to create cloud volumes based on your [Cloud Volumes Service for Google Cloud](#) subscription. You can also edit certain attributes of a volume, get the relevant mount commands, create snapshot copies, and delete cloud volumes.

Create cloud volumes

You can create NFS or SMB volumes in a new or existing Cloud Volumes Service for Google Cloud account. Cloud volumes currently support NFSv3 and NFSv4.1 for Linux and UNIX clients, and SMB 3.x for Windows clients.

Before you begin

- If you want to use SMB in GCP, you must have set up DNS and Active Directory.
- When planning to create an SMB volume, you must have a Windows Active Directory server available to which you can connect. You will enter this information when creating the volume. Also, make sure that the Admin user is able to create a machine account in the Organizational unit (OU) path specified.

Steps

1. Select the working environment and click **Add New Volume**.
2. In the Details & Location page, enter details about the volume:
 - a. Enter a name for the volume.
 - b. Specify a size within the range of 1 TiB (1024 GiB) to 100 TiB.

[Learn more about allocated capacity.](#)

- c. Specify a service level: Standard, Premium, or Extreme.

[Learn more about service levels.](#)

- d. Select the Google Cloud region.
- e. Select the VPC Network from which the volume will be accessible. Note that the VPC cannot be changed or edited after the volume is created.
- f. Click **Continue**.

3. In the Protocol page, select NFS or SMB and then define the details. Required entries for NFS and

SMB are shown in separate sections below.

4. For NFS:

- a. In the Volume Path field, specify the name of the volume export you will see when you mount the volume.
- b. Select NFSv3, NFSv4.1, or both depending on your requirements.
- c. Optionally, you can create an export policy to identify the clients that can access the volume. Specify the:
 - Allowed clients by using an IP address or Classless Inter-Domain Routing (CIDR).
 - Access rights as Read & Write or Read Only.
 - Access protocol (or protocols if the volume allows both NFSv3 and NFSv4.1 access) used for users.
 - Click + **Add Export Policy Rule** if you want to define additional export policy rules.

The following image shows the Volume page filled out for the NFS protocol:


The screenshot shows a configuration page titled "Protocol". At the top, there is a section "Select the volume's protocol:" with two radio buttons: "NFS Protocol" (selected) and "SMB Protocol". Below this, the page is divided into two columns. The left column is labeled "Protocol" and contains a "Volume Path" field with the value "vol1" and a "Select NFS Version:" section with checkboxes for "NFSv3" (checked) and "NFSv4.1" (unchecked). The right column is labeled "Export Policy" and contains an "Allowed Client & Access" section with a text field containing "0.0.0.0/24", radio buttons for "Read & Write" (selected) and "Read Only" (unchecked), and a "Select NFS Version:" section with checkboxes for "NFSv3" (checked) and "NFSv4.1" (unchecked). At the bottom of the right column, there is a button with a plus sign and the text "Add Export Policy Rule (Up to 5)".

5. For SMB:

- a. In the Volume Path field, specify the name of the volume export you will see when you mount the volume and click **Continue**.
- b. If Active Directory has been set up, you see the configuration. If it is the first volume being set up and no Active Directory has been set up, you can enable SMB session encryption in the SMB Connectivity Setup page:

Field	Description
DNS Primary IP Address	The IP addresses of the DNS servers that provide name resolution for the SMB server. Use a comma to separate the IP addresses when referencing multiple servers, for example, 172.31.25.223, 172.31.2.74..
Active Directory Domain to join	The FQDN of the Active Directory (AD) domain that you want the SMB server to join.
SMB Server NetBIOS name	A NetBIOS name for the SMB server that will be created.
Credentials authorized to join the domain	The name and password of a Windows account with sufficient privileges to add computers to the specified Organizational Unit (OU) within the AD domain.
Organizational Unit	The organizational unit within the AD domain to associate with the SMB server. The default is CN=Computers for connections to your own Windows Active Directory server.

The following image shows the Volume page filled out for the SMB protocol:



The screenshot shows the 'SMB Connectivity Setup' window. It contains six input fields arranged in two columns. The left column fields are: 'DNS Primary IP Address' (filled with '127.0.0.1'), 'Active Directory Domain to Join' (filled with 'yourdomain.com up to 107 characters'), and 'SMB Server NetBIOS Name' (filled with 'WEName'). The right column fields are: 'User Name' (filled with 'administrator'), 'Password' (empty), and 'Organizational Unit' (filled with 'CN=Computers').

6. Click **Continue**.
7. If you want to create the volume based on a snapshot of an existing volume, select the snapshot from the Snapshot Name drop-down list. Otherwise just click **Continue**.
8. In the Snapshot Policy page, you can enable Cloud Volumes Service to create snapshot copies of your volumes based on a schedule. You can do this now by moving the selector to the right, or you can edit the volume later to define the snapshot policy.

See [Creating a snapshot policy](#) for more information about snapshot functionality.

9. Click **Add Volume**.

The new volume is added to the working environment.

Continue with [Mounting the cloud volume](#).

Mount cloud volumes

Access mounting instructions from within Cloud Manager so you can mount the volume to a host.

Note: Please use the highlighted protocol/dialect supported by your client.

Steps

1. Open the working environment.
2. Hover over the volume and click **Mount the volume**.

NFS and SMB volumes display mount instructions for that protocol.

3. Hover over the commands and copy them to your clipboard to make this process easier. Just add the destination directory/mount point at the end of the command.


NFS example:

Mount the volume - testk


Setting up your instance

1. Open an SSH client and connect to your instance.
2. Install the nfs client on your instance.
On Red Hat Enterprise Linux or SuSE Linux instance:

```
$ sudo yum install -y nfs-utils
```


On an Ubuntu or Debian instance:


```
$ sudo apt-get install nfs-common
```




Mounting your volume

1. Create a new directory on your instance:


```
$ sudo mkdir /dir
```


2. Mount your NFSv3 volume using the command below:

```
sudo mount -t nfs -o rw,hard,rsize=65536,wsiz=65536,vers=3,tc...
```


3. Mount your NFSv4.1 volume using the command below:


```
sudo mount -t nfs -o rw,hard,rsize=65536,wsiz=65536,vers=4.1,t...
```



The maximum I/O size defined by the **rsize** and **wsiz** options is 1048576, however 65536 is the recommended default for most use cases.

Note that Linux clients will default to NFSv4.1 unless the version is specified with the `vers=<nfs_version>` option.

SMB example:



4. Map your network drive by following the mount instructions for your instance.


After completing the steps in the mount instructions, you have successfully mounted the cloud volume to your GCP instance.

Manage existing volumes

You can manage existing volumes as your storage needs change. You can view, edit, restore, and delete volumes.

Steps

1. Open the working environment.
2. Hover over the volume.




3. Manage your volumes:

Task	Action
View information about a volume	Click Info .
Edit a volume (including snapshot policy)	<ol style="list-style-type: none"> Click Edit. Modify the volume's properties and then click Update.
Get the NFS or SMB mount command	<ol style="list-style-type: none"> Click Mount the volume. Click Copy to copy the command(s).
Create a Snapshot copy on demand	<ol style="list-style-type: none"> Click Create a Snapshot copy. Change the name, if needed, and then click Create.
Replace the volume with the contents of a Snapshot copy	<ol style="list-style-type: none"> Click Revert volume to snapshot. Select a Snapshot copy and click Restore.
Delete a Snapshot copy	<ol style="list-style-type: none"> Click Delete a Snapshot copy. Select the snapshot and click Delete. Click Delete again when prompted to confirm.
Delete a volume	<ol style="list-style-type: none"> Unmount the volume from all clients: <ul style="list-style-type: none"> On Linux clients, use the umount command. On Windows clients, click Disconnect network drive. Select a volume, and then click Delete. Click Delete again to confirm.

Remove Cloud Volumes Service from Cloud Manager

You can remove a Cloud Volumes Service for Google Cloud subscription and all existing volumes from Cloud Manager. The volumes are not deleted, they are just removed from the Cloud Manager interface.



Steps

1. Open the working environment.
2. Click the  button at the top of the page and click **Remove Cloud Volumes Service**.
3. In the confirmation dialog box, click **Remove**.

Manage Active Directory configuration

If you change your DNS servers or Active Directory domain, you need to modify the SMB server in Cloud Volumes Services so that it can continue to serve storage to clients.

Steps

1. Open the working environment.
2. Click the  button at the top of the page and click **Manage Active Directory**.
If no Active Directory is configured, you can add one now. If one is configured, you can modify or delete the settings using the  button.
3. Specify the settings for the SMB server:

Field	Description
DNS Primary IP Address	The IP addresses of the DNS servers that provide name resolution for the SMB server. Use a comma to separate the IP addresses when referencing multiple servers, for example, 172.31.25.223, 172.31.2.74.
Active Directory Domain to join	The FQDN of the Active Directory (AD) domain that you want the SMB server to join.
SMB Server NetBIOS name	A NetBIOS name for the SMB server that will be created.
Credentials authorized to join the domain	The name and password of a Windows account with sufficient privileges to add computers to the specified Organizational Unit (OU) within the AD domain.
Organizational Unit	The organizational unit within the AD domain to associate with the SMB server. The default is CN=Computers for connections to your own Windows Active Directory server.

4. Click **Save** to save your settings.

Copyright Information

Copyright © 2020 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.