

runZero API

runZero API. API use is rate limited, you can make as many calls per day as you have licensed assets.
More information: <https://www.runzero.com/>
Contact Info: support@runzero.com
Version: 4.0.241219.0
BasePath:/api/v1.0
Commercial
<https://www.runzero.com/legal/terms>

Access

1. HTTP Bearer Token authentication
2. OAuth AuthorizationUrl:TokenUrl:<https://console.runzero.com/api/v1.0/account/api/token>

Methods

[Jump to [Models](#)]

Table of Contents

[Account](#)

- [POST /account/assets/ownership-types](#)
- [PUT /account/credentials](#)
- [POST /account/custom-integrations](#)
- [PUT /account/custom-integrations/{customIntegrationId}](#)
- [POST /account/groups](#)
- [POST /account/sso/groups](#)
- [PUT /account/keys](#)
- [PUT /account/orgs](#)
- [POST /account/orgs/{org_id}/exportTokens](#)
- [POST /account/tasks/templates](#)
- [PUT /account/users](#)
- [PUT /account/users/invite](#)
- [DELETE /account/assets/ownership-types/{ownership_type_id}](#)
- [DELETE /account/assets/ownership-types](#)
- [DELETE /account/custom-integrations/{customIntegrationId}](#)
- [DELETE /account/orgs/{org_id}/exportTokens/{key_id}](#)
- [DELETE /account/orgs/{org_id}/exportToken](#)
- [GET /account/events.json](#)
- [GET /account/events.jsonl](#)
- [POST /account/api/token](#)
- [GET /account/agents](#)
- [GET /account/assets/ownership-types](#)
- [GET /account/credentials/{credential_id}](#)
- [GET /account/credentials](#)
- [GET /account/custom-integrations/{customIntegrationId}](#)
- [GET /account/custom-integrations](#)
- [GET /account/groups/{group_id}](#)
- [GET /account/sso/groups/{group_mapping_id}](#)
- [GET /account/sso/groups](#)
- [GET /account/groups](#)
- [GET /account/keys/{key_id}](#)
- [GET /account/keys](#)
- [GET /account/license](#)
- [GET /account/orgs/{org_id}](#)
- [GET /account/orgs/{org_id}/exportTokens/{key_id}](#)
- [GET /account/orgs/{org_id}/exportTokens](#)
- [GET /account/orgs](#)
- [GET /account/tasks/templates/{scan_template_id}](#)
- [GET /account/tasks/templates](#)
- [GET /account/sites](#)
- [GET /account/tasks](#)
- [GET /account/users/{user_id}](#)
- [GET /account/users](#)
- [DELETE /account/credentials/{credential_id}](#)
- [DELETE /account/groups/{group_id}](#)

- [DELETE /account/sso/groups/{group_mapping_id}](#)
- [DELETE /account/keys/{key_id}](#)
- [DELETE /account/orgs/{org_id}](#)
- [DELETE /account/tasks/templates/{scan_template_id}](#)
- [DELETE /account/users/{user_id}](#)
- [PATCH /account/users/{user_id}/resetLockout](#)
- [PATCH /account/users/{user_id}/resetMFA](#)
- [PATCH /account/users/{user_id}/resetPassword](#)
- [POST /account/api/rotate](#)
- [PATCH /account/keys/{key_id}/rotate](#)
- [PATCH /account/orgs/{org_id}/exportTokens/{key_id}/rotate](#)
- [PATCH /account/orgs/{org_id}/exportToken/rotate](#)
- [PATCH /account/assets/ownership-types/{ownership_type_id}](#)
- [PUT /account/assets/ownership-types](#)
- [PATCH /account/custom-integrations/{customIntegrationId}](#)
- [PUT /account/groups](#)
- [PUT /account/sso/groups](#)
- [PATCH /account/orgs/{org_id}](#)
- [PUT /account/tasks/templates](#)
- [PATCH /account/users/{user_id}](#).

[CiscoSNTC](#)

- [GET /export/org/assets.cisco.csv](#)

[Export](#)

- [GET /org/assets/hw.csv](#)
- [GET /org/assets/os.csv](#)
- [GET /org/assets/tags.csv](#)
- [GET /org/assets/type.csv](#)
- [GET /export/org/assets.csv](#)
- [GET /export/org/assets.json](#)
- [GET /export/org/assets.jsonl](#)
- [GET /export/org/assets.nmap.xml](#)
- [GET /export/org/groups.csv](#)
- [GET /export/org/groups.json](#)
- [GET /export/org/groups.jsonl](#)
- [GET /export/org/users.csv](#)
- [GET /export/org/users.json](#)
- [GET /export/org/users.jsonl](#)
- [GET /export/org/snmp.arpcache.csv](#)
- [GET /export/org/services.csv](#)
- [GET /export/org/services.json](#)
- [GET /export/org/services.jsonl](#)
- [GET /org/services/products.csv](#)
- [GET /org/services/protocols.csv](#)
- [GET /org/services/tcp.csv](#)
- [GET /org/services/udp.csv](#)
- [GET /export/org/sites.csv](#)
- [GET /export/org/sites.json](#)
- [GET /export/org/sites.jsonl](#)
- [GET /export/org/software.csv](#)
- [GET /export/org/software.json](#)
- [GET /export/org/software.jsonl](#)
- [GET /export/org/subnet.stats.csv](#)
- [GET /export/org/tasks.json](#)
- [GET /export/org/tasks.jsonl](#)
- [GET /export/org/vulnerabilities.csv](#)
- [GET /export/org/vulnerabilities.json](#)
- [GET /export/org/vulnerabilities.jsonl](#)
- [GET /export/org/wireless.csv](#)
- [GET /export/org/wireless.json](#)
- [GET /export/org/wireless.jsonl](#)

[Import](#)

- [POST /import/org/{orgId}/assets](#)

Org

- [GET /org/custom-integrations/{customIntegrationId}](#).
- [GET /org/custom-integrations](#)

Organization

- [POST /org/custom-integrations/{custom_integration_id}/bulk/remove](#)
- [POST /org/assets/bulk/clearOwners](#)
- [POST /org/assets/bulk/clearTags](#)
- [PUT /org/sites/{site_id}/sample](#)
- [PUT /org/sites/{site_id}/scan](#)
- [PUT /org/sites](#)
- [GET /org/agents/{agent_id}](#).
- [GET /org/agents](#)
- [GET /org/assets/{asset_id}](#).
- [GET /org/assets](#)
- [GET /org/explorers/{explorer_id}](#).
- [GET /org/explorers](#)
- [GET /org/hosted-zones/{hosted_zone_id}](#).
- [GET /org/hosted-zones](#)
- [GET /org/key](#)
- [GET /org](#)
- [GET /org/services/{service_id}](#).
- [GET /org/services](#)
- [GET /org/sites/{site_id}](#).
- [GET /org/sites](#)
- [GET /org/tasks/{task_id}](#).
- [GET /org/tasks/{task_id}/changes](#)
- [GET /org/tasks/{task_id}/log](#)
- [GET /org/tasks/{task_id}/data](#)
- [GET /org/tasks](#)
- [GET /org/wireless/{wireless_id}](#).
- [GET /org/wireless](#)
- [POST /org/tasks/{task_id}/hide](#)
- [POST /import/org/{orgId}/assets](#)
- [PUT /org/sites/{site_id}/import/nessus](#)
- [PUT /org/sites/{site_id}/import/packet](#)
- [PUT /org/sites/{site_id}/import](#)
- [PATCH /org/assets/merge](#)
- [DELETE /org/agents/{agent_id}](#)
- [DELETE /org/assets/{asset_id}](#)
- [DELETE /org/assets/{asset_id}/sources/{source_id}/remove](#)
- [DELETE /org/assets/bulk/delete](#)
- [DELETE /org/assets/{asset_id}/custom-integrations/{custom_integration_id}/remove](#)
- [DELETE /org/explorers/{explorer_id}](#).
- [DELETE /org/key](#)
- [DELETE /org/services/{service_id}](#).
- [DELETE /org/sites/{site_id}](#).
- [DELETE /org/wireless/{wireless_id}](#).
- [PATCH /org/key/rotate](#)
- [POST /org/tasks/{task_id}/stop](#)
- [PATCH /org/agents/{agent_id}](#).
- [PATCH /org/assets/{asset_id}/comments](#)
- [PATCH /org/assets/{asset_id}/criticality](#)
- [PATCH /org/assets/{asset_id}/owners](#)
- [PATCH /org/assets/{asset_id}/tags](#)
- [PATCH /org/assets/bulk/criticality](#)
- [PATCH /org/assets/bulk/owners](#)
- [PATCH /org/assets/bulk/tags](#)
- [PATCH /org/explorers/{explorer_id}](#).
- [PATCH /org](#)
- [PATCH /org/sites/{site_id}](#).
- [PATCH /org/tasks/{task_id}](#).
- [POST /org/agents/{agent_id}/update](#)
- [POST /org/explorers/{explorer_id}/update](#)

Public

- [GET /health](#)
- [GET /releases/agent/version](#)
- [GET /releases/platform/version](#)
- [GET /releases/scanner/version](#)

[ServiceNow](#)

- [GET /export/org/assets.servicenow.csv](#)
- [GET /export/org/assets.servicenow.json](#)
- [GET /export/org/services.servicenow.csv](#)
- [GET /export/org/assets.servicegraph.json](#)

[Splunk](#)

- [GET /export/org/assets-sync/created/assets.json](#)
- [GET /export/org/assets-sync/updated/assets.json](#)

Account

POST /account/assets/ownership-types[Up](#)Create new asset ownership types ([createAccountAssetOwnershipTypes](#))**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

AssetOwnershipTypePost [AssetOwnershipTypePost](#) (required)
Body Parameter —

Return typearray[[AssetOwnershipType](#)]**Example data**

Content-Type: application/json

```
[ {
  "reference" : 1,
  "hidden" : true,
  "name" : "Asset Owner",
  "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
  "order" : 1
}, {
  "reference" : 1,
  "hidden" : true,
  "name" : "Asset Owner",
  "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
  "order" : 1
} ]
```

Example data

Content-Type: application/json

```
{ "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{ "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

array of asset ownership types

400

Invalid request body [Problem](#)

401

Access token is missing or invalid [Problem](#)

403

Action not allowed for this license type [Problem](#)

404

Resource not found [Problem](#)

422

Invalid request body [Problem](#)

500

Unexpected error occurred on the server [Problem](#)

PUT /account/credentials

[Up](#)

Create a new credential ([createAccountCredential](#))

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

CredentialOptions [CredentialOptions](#) (required)

Body Parameter —

Return type[Credential](#)**Example data**

Content-Type: application/json

```
{
  "last_used_at" : 1576300370,
  "name" : "credentials_name",
  "created_at" : 1576300370,
  "global" : false,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "created_by_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "acl" : {
    "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8" : "user"
  },
  "cidrs" : [ "10.0.0.47/32", "192.168.1.0/24" ],
  "last_used_by_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "type" : "miradore_api_key_v1",
  "created_by_email" : "user@example.com",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**credential details [Credential](#)**401**Access token is missing or invalid [Problem](#)**404**Resource not found [Problem](#)**POST /account/custom-integrations**[Up](#)Create a new custom integration ([createAccountCustomIntegration](#))**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request bodyNewCustomIntegration [NewCustomIntegration](#) (required)

Body Parameter —

Return type[CustomIntegration](#)**Example data**

runZero API documentation

Content-Type: application/json

```
{  
    "createdAt" : "2023-03-06T18:14:50.52Z",  
    "destroyedAt" : "2023-03-06T18:14:50.52Z",  
    "clientId" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "name" : "my-custom-integration",  
    "icon" : "aVZCT1j3METHZ29BQUFBTlNVaEVVZ0FBQUNBQUFBQWdDQVlBQUFCEmVucjBBQUFBQkdkQlRVRUFBTEdQQy94aEJRQUFBQ0Jq",  
    "description" : "My custom integration description.",  
    "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",  
    "createdById" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",  
    "updatedAt" : "2023-03-06T18:14:50.52Z"  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**The custom integration created [CustomIntegration](#)**400**Invalid request body [Problem](#)**401**Access token is missing or invalid [Problem](#)**403**Action not allowed for this license type [Problem](#)**404**Resource not found [Problem](#)**422**Invalid request body [Problem](#)**500**Unexpected error occurred on the server [Problem](#)**PUT /account/custom-integrations/{customIntegrationId}**[Up](#)Replace custom integration at provided ID ([createAccountCustomIntegrationAndID](#))**Path parameters****customIntegrationId (required)***Path Parameter* — UUID of the custom integration default: null format: uuid**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body**NewCustomIntegration [NewCustomIntegration](#) (required)***Body Parameter* —**Return type**[CustomIntegration](#)**Example data**

Content-Type: application/json

```
{
  "createdAt" : "2023-03-06T18:14:50.52Z",
  "destroyedAt" : "2023-03-06T18:14:50.52Z",
  "clientId" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "my-custom-integration",
  "icon" : "aVZCT13METH29BQUBTlNVaEVVZ0FBQUNBQUBQWdDQVlBQUFCemVucjBBQUFBQkdkQlRVRUFBTEdQQy94aEJRQUFBQ0Jq",
  "description" : "My custom integration description.",
  "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
  "createdById" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
  "updatedAt" : "2023-03-06T18:14:50.52Z"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**The updated custom integration [CustomIntegration](#)**400**Invalid request body [Problem](#)**401**Access token is missing or invalid [Problem](#)**403**Action not allowed for this license type [Problem](#)**404**Resource not found [Problem](#)**422**Invalid request body [Problem](#)**500**Unexpected error occurred on the server [Problem](#)**POST /account/groups**[Up](#)Create a new group ([createAccountGroup](#))**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body**GroupPost** [GroupPost \(required\)](#)

Body Parameter —

Return type

[Group](#)**Example data**

Content-Type: application/json

```
{
  "org_default_role" : "admin",
  "expires_at" : 1576300370,
  "user_count" : 2,
  "updated_at" : 1576300370,
  "name" : "Viewers",
  "org_roles" : {
    "key" : ""
  },
  "description" : "Viewers Group",
  "created_at" : 1576300370,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "role_summary" : "all:viewer",
  "created_by_email" : "jsmith@example.com"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**group information [Group](#)**401**Access token is missing or invalid [Problem](#)**POST /account/sso/groups**[Up](#)Create a new SSO group mapping ([createAccountGroupMapping](#))**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body**GroupMapping** [GroupMapping](#) (required)*Body Parameter* —**Return type**[GroupMapping](#)**Example data**

Content-Type: application/json

```
{
  "sso_value" : "basic-attribute-value",
  "updated_at" : 1576300370,
  "group_id" : "2b096711-4d28-4417-8635-64af4f62c1ae",
  "group_name" : "Viewers Group",
  "sso_attribute" : "basic-attribute",
  "description" : "Maps basic-attribute to Viewers Group",
  "created_at" : 1576300370,
  "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
  "created_by_email" : "jsmith@example.com"
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

group information [GroupMapping](#)

401

Access token is missing or invalid [Problem](#)

PUT /account/keys

[Up](#)

Create a new key ([createAccountKey](#))

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

APIKeyOptions [APIKeyOptions](#) (required)

Body Parameter —

Return type

[APIKey](#)

Example data

Content-Type: application/json

```
{  
    "usage_limit" : 10000,  
    "created_at" : 1576300370,  
    "counter" : 1,  
    "type" : "org",  
    "created_by" : "user@example.com",  
    "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "token" : "CTXXXXXXXXXXXXXX",  
    "usage_today" : 100,  
    "last_used_at" : 0,  
    "inactive" : true,  
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "last_used_ua" : "curl/7.44.1",  
    "comment" : "API key used for Splunk integration",  
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "last_used_ip" : "127.0.0.1"  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

key details [APIKey](#)

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)
PUT /account/orgs
[Up](#)

Create a new organization ([createAccountOrganization](#))

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

OrgOptions [OrgOptions](#) (required)

Body Parameter —

Return type

[Organization](#)

Example data

Content-Type: application/json

```
{
  "export_token_last_used_at" : 0,
  "deactivated_at" : 0,
  "download_token_created_at" : 1576300370,
  "export_token_created_at" : 1576300370,
  "created_at" : 1576300370,
  "description" : "All subdivisions of my company",
  "service_count_udp" : 1,
  "project" : false,
  "export_token" : "ET11226D9EEEA2B035D42569585900",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "export_token_counter" : 0,
  "asset_count" : 100,
  "inactive" : false,
  "updated_at" : 1576300370,
  "export_token_last_used_by" : "127.0.0.1",
  "expiration_assets_stale" : 365,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "download_token" : "DT11226D9EEEA2B035D42569585900",
  "service_count" : 10,
  "service_count_tcp" : 7,
  "service_count_arp" : 1,
  "expiration_scans" : 365,
  "service_count_icmp" : 1,
  "expiration_assets_offline" : 365,
  "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "My Company"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**organization details [Organization](#)**401**Access token is missing or invalid [Problem](#)**404**Resource not found [Problem](#)**POST /account/orgs/{org_id}/exportTokens**[Up](#)Create a new export token for an organization ([createAccountOrganizationExportToken](#))**Path parameters****org_id (required)***Path Parameter* — UUID of the organization to create an export token for default: null format: uuid**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body**ExportTokenOptions [ExportTokenOptions](#) (required)***Body Parameter* —**Return type**[ExportToken](#)**Example data**

Content-Type: application/json

```
{
  "last_used_at" : 0,
  "created_at" : 1576300370,
  "comment" : "Export token used for Splunk integration",
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "counter" : 0,
  "last_used_by" : "127.0.0.1",
  "token" : "ET11226D9EEEA2B035D42569585900"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

export token details [ExportToken](#)

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)**POST /account/tasks/templates**[Up](#)Create a new scan template (`createAccountScanTemplate`)**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body**ScanTemplateOptions** [ScanTemplateOptions](#) (required)

Body Parameter —

Return type[ScanTemplate](#)**Example data**

Content-Type: application/json

```
{
  "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hidden" : false,
  "description" : "My Scan Template",
  "created_at" : 1576300370,
  "global" : false,
  "acl" : {
    "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8" : "user"
  },
  "type" : "scan",
  "error" : "agent unavailable",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "updated_at" : 1576300370,
  "stats" : {
    "key" : ""
  },
  "recur" : false,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "size_site" : 0,
  "recur_last" : 1576300370,
  "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "params" : {
    "key" : "params"
  },
  "created_by" : "user@example.com",
  "created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "modified_by" : "user@example.com",
  "modified_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "last_modified" : 1576300370
}
```

```

    "size_results" : 0,
    "grace_period" : "4",
    "start_time" : 1576300370,
    "linked_task_count" : 1,
    "recur_frequency" : "hourly",
    "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "name" : "My Scan Template",
    "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "source_id" : "1",
    "size_data" : 0,
    "recur_next" : 1576300370,
    "status" : "processed"
}

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**scan template [ScanTemplate](#)**401**Access token is missing or invalid [Problem](#)**422**Invalid request body [Problem](#)**400**Invalid request body [Problem](#)**PUT /account/users**[Up](#)Create a new user account ([createAccountUser](#))**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body**UserOptions** [UserOptions](#) (required)

Body Parameter —

Return type[User](#)**Example data**

Content-Type: application/json

```
{
  "org_default_role" : "admin",
  "last_login_at" : 1576300370,
  "org_roles" : {
    "key" : ""
  },
  "created_at" : 1576300370,
  "last_name" : "Smith",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "invite_token_expiration" : 1576300370,
  "sso_only" : false,
  "updated_at" : 1576300370,
  "last_login_ip" : "192.168.0.1",
  "login_failures" : 0,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "reset_token_expiration" : 1576300370,
  "last_login_ua" : "curl/1.0",
  "first_name" : "James",
  "email" : "jsmith@example.com",
  "client_admin" : true
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

Key details [User](#)

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)**PUT /account/users/invite**[Up](#)Create a new user account and send an email invite ([createAccountUserInvite](#))**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request bodyUserInviteOptions [UserInviteOptions](#) (required)

Body Parameter —

Return type[User](#)**Example data**

Content-Type: application/json

```
{
  "org_default_role" : "admin",
  "last_login_at" : 1576300370,
  "org_roles" : {
    "key" : ""
  },
  "created_at" : 1576300370,
  "last_name" : "Smith",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "invite_token_expiration" : 1576300370,
  "sso_only" : false,
  "updated_at" : 1576300370,
  "last_login_ip" : "192.168.0.1",
  "login_failures" : 0,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "reset_token_expiration" : 1576300370,
  "last_login_ua" : "curl/1.0",
  "first_name" : "James",
  "email" : "jsmith@example.com",
  "client_admin" : true
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**Key details [User](#)**401**Access token is missing or invalid [Problem](#)**404**Resource not found [Problem](#)**DELETE /account/assets/ownership-types/{ownership_type_id}**[Up](#)Delete a single asset ownership type ([deleteAccountAssetOwnershipType](#))**Path parameters****ownership_type_id (required)**

Path Parameter — UUID of the asset ownership type default: null format: uuid

Return typearray[[AssetOwnershipType](#)]**Example data**

runZero API documentation

Content-Type: application/json

```
[ {  
    "reference" : 1,  
    "hidden" : true,  
    "name" : "Asset Owner",  
    "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",  
    "order" : 1  
}, {  
    "reference" : 1,  
    "hidden" : true,  
    "name" : "Asset Owner",  
    "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",  
    "order" : 1  
} ]
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

array of remaining asset ownership types

401

Access token is missing or invalid [Problem](#)

403

Action not allowed for this license type [Problem](#)

404Resource not found [Problem](#)**422**Invalid request body [Problem](#)**500**Unexpected error occurred on the server [Problem](#)**DELETE /account/assets/ownership-types**[Up](#)Delete asset ownership types ([deleteAccountAssetOwnershipTypes](#))**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body**string** **string** (required)*Body Parameter* —**Return type**array[[AssetOwnershipType](#)]**Example data**

Content-Type: application/json

```
[ {
    "reference" : 1,
    "hidden" : true,
    "name" : "Asset Owner",
    "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
    "order" : 1
}, {
    "reference" : 1,
    "hidden" : true,
    "name" : "Asset Owner",
    "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
    "order" : 1
} ]
```

Example data

Content-Type: application/json

```
{ "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{ "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{ "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**

array of remaining asset ownership types

400Invalid request body [Problem](#)**401**Access token is missing or invalid [Problem](#)**403**Action not allowed for this license type [Problem](#)**404**Resource not found [Problem](#)**500**Unexpected error occurred on the server [Problem](#)**DELETE /account/custom-integrations/{customIntegrationId}**[Up](#)Delete an custom integration ([deleteAccountCustomIntegration](#))**Path parameters****customIntegrationId (required)**

Path Parameter — UUID of the custom integration default: null format: uuid

Return type[CustomIntegration](#)**Example data**

Content-Type: application/json

```
{
  "createdAt" : "2023-03-06T18:14:50.52Z",
  "destroyedAt" : "2023-03-06T18:14:50.52Z",
  "clientId" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "my-custom-integration",
  "icon" : "aVZCT1J3MEtHZ29BQUFBTlNVaEVVZ0FBQUNBQUFBQWdDQVlBQUFCemVucjBBQUFBQkdQlRVRUFBTEdQQy94aEJRQUFBQ0Jq",
  "description" : "My custom integration description.",
  "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
  "createdById" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
  "updatedAt" : "2023-03-06T18:14:50.52Z"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**The deleted custom integration [CustomIntegration](#)**401**Access token is missing or invalid [Problem](#)**403**Action not allowed for this license type [Problem](#)**404**Resource not found [Problem](#)**500**Unexpected error occurred on the server [Problem](#)**DELETE /account/orgs/{org_id}/exportTokens/{key_id}**[Up](#)Removes the export token from the specified organization ([deleteAccountOrganizationExportToken](#))**Path parameters****org_id (required)***Path Parameter* — UUID of the organization to retrieve default: null format: uuid**key_id (required)***Path Parameter* — UUID of the export token ID to remove default: null format: uuid**Example data**

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

204
empty response
401
Access token is missing or invalid [Problem](#)

DELETE /account/orgs/{org_id}/exportToken[Up](#)

Removes the export token from the specified organization ([deleteAccountOrganizationExportTokenDeprecated](#))

This API has been deprecated. Please use `DELETE /account/orgs/{org_id}/exportTokens/{key_id}` instead. This API will fail if more than one export tokens exist for the given organization.

Path parameters**org_id (required)**

Path Parameter — UUID of the organization to retrieve default: null format: uuid

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**204**

empty response

401

Access token is missing or invalid [Problem](#)

GET /account/events.json[Up](#)

System event log as JSON ([exportEventsJSON](#))

Query parameters**search (optional)**

Query Parameter — an optional search string for filtering results default: null

fields (optional)

Query Parameter — an optional list of fields to export, comma-separated default: null

Return type

array[[Event](#)]

Example data

Content-Type: application/json

```
[
  {
    "target_name" : "SiteName",
    "target_type" : "api",
    "created_at" : 1576300370,
    "source_type" : "api",
    "target_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "success" : true,
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "action" : "login",
    "processor_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "processed_at" : 0,
    "details" : {
      "key" : ""
    }
  },
  ...
]
```

```

"id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"source_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"state" : "SiteName",
"source_name" : "SiteName"
}, {
  "target_name" : "SiteName",
  "target_type" : "api",
  "created_at" : 1576300370,
  "source_type" : "api",
  "target_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "success" : true,
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "action" : "login",
  "processor_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "processed_at" : 0,
  "details" : {
    "key" : ""
  },
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "source_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "state" : "SiteName",
  "source_name" : "SiteName"
} ]

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

filtered event results

401

Access token is missing or invalid [Problem](#)**GET /account/events.jsonl**[Up](#)System event log as JSON line-delimited ([exportEventsJSONL](#))**Query parameters****search (optional)**

Query Parameter — an optional search string for filtering results default: null

fields (optional)

Query Parameter — an optional list of fields to export, comma-separated default: null

Return typearray[[Event](#)]**Example data**

Content-Type: application/json

```
[
  {
    "target_name" : "SiteName",
    "target_type" : "api",
    "created_at" : 1576300370,
    "source_type" : "api",
    "target_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "success" : true,

```

```

"organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"action" : "login",
"processor_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"processed_at" : 0,
"details" : {
  "key" : ""
},
"id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"source_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"state" : "SiteName",
"source_name" : "SiteName"
}, {
  "target_name" : "SiteName",
  "target_type" : "api",
  "created_at" : 1576300370,
  "source_type" : "api",
  "target_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "success" : true,
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "action" : "login",
  "processor_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "processed_at" : 0,
  "details" : {
    "key" : ""
  },
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "source_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "state" : "SiteName",
  "source_name" : "SiteName"
}
]

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

filtered event results

401

Access token is missing or invalid [Problem](#)**POST /account/api/token**[Up](#)Generate an access token using an API client ([getAPIToken](#))**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/x-www-form-urlencoded

Form parameters**grant_type (required)**

Form Parameter — default: null

client_id (required)

Form Parameter — default: null

client_secret (required)

Form Parameter — default: null

Return type[AccessToken](#)**Example data**

Content-Type: application/json

```
{
  "access_token" : "access_token",
  "token_type" : "token_type",
  "expires_in" : 0
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**An access token [AccessToken](#)**400**Invalid request body [Problem](#)**401**Access token is missing or invalid [Problem](#)**GET /account/agents**[Up](#)Get all agents across all organizations ([getAccountAgents](#))**Query parameters****search (optional)**

Query Parameter — an optional search string for filtering results default: null

Return typearray[[Agent](#)]**Example data**

Content-Type: application/json

```
[
  {
    "os" : "Windows",
    "system_info" : {
      "key" : ""
    },
    "deactivated_at" : 0,
    "created_at" : 1576300370,
    "last_checkin" : 1576300370,
    "version" : "1.2.3 (build 20191219224016) [fc50c5eefdc3ff5c60533c3c345d14d336396272]",
    "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "host_id" : "6f9e6fe52271da70962e007183c5c9c9",
    "internal_ip" : "192.168.0.1",
    "connected" : true,
  }
]
```

```

"hub_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"inactive" : false,
"updated_at" : 1576300370,
"organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"name" : "RUNZERO-AGENT",
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"arch" : "amd64",
"external_ip" : "1.1.1.1"
}, {
  "os" : "Windows",
  "system_info" : {
    "key" : ""
  },
  "deactivated_at" : 0,
  "created_at" : 1576300370,
  "last_checkin" : 1576300370,
  "version" : "1.2.3 (build 20191219224016) [fc50c5eefdc3ff5c60533c3c345d14d336396272]",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "host_id" : "6f9e6fe52271da70962e007183c5c9c9",
  "internal_ip" : "192.168.0.1",
  "connected" : true,
  "hub_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "inactive" : false,
  "updated_at" : 1576300370,
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "RUNZERO-AGENT",
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "arch" : "amd64",
  "external_ip" : "1.1.1.1"
}
]

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**

array of tasks

401Access token is missing or invalid [Problem](#)**GET /account/assets/ownership-types**[Up](#)Get all asset ownership types ([getAccountAssetOwnershipTypes](#))**Return type**array[[AssetOwnershipType](#)]**Example data**

Content-Type: application/json

```
[
  {
    "reference" : 1,
    "hidden" : true,
    "name" : "Asset Owner",
    "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
    "order" : 1
  },
  {
    "reference" : 1,
    "hidden" : true,
    "name" : "Asset Manager",
    "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
    "order" : 2
  }
]
```

```
{
  "name" : "Asset Owner",
  "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
  "order" : 1
} ]
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**

array of asset ownership types

401Access token is missing or invalid [Problem](#)**403**Action not allowed for this license type [Problem](#)**500**Unexpected error occurred on the server [Problem](#)

GET /account/credentials/{credential_id}

Up

Get credential details ([getAccountCredential](#))**Path parameters****credential_id (required)**

Path Parameter — UUID of the credential to retrieve default: null format: uuid

Return type[Credential](#)**Example data**

Content-Type: application/json

```
{
  "last_used_at" : 1576300370,
  "name" : "credentials_name",
  "created_at" : 1576300370,
  "global" : false,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "created_by_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "acl" : {
    "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8" : "user"
}
```

```
},
"cidrs" : [ "10.0.0.47/32", "192.168.1.0/24" ],
"last_used_by_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"type" : "miradore_api_key_v1",
"created_by_email" : "user@example.com",
"client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**credential details [Credential](#)**401**Access token is missing or invalid [Problem](#)**404**Resource not found [Problem](#)**GET /account/credentials**[Up](#)Get all account credentials ([getAccountCredentials](#))**Query parameters****search (optional)**

Query Parameter — an optional search string for filtering results default: null

Return typearray[[Credential](#)]**Example data**

Content-Type: application/json

```
[
  {
    "last_used_at" : 1576300370,
    "name" : "credentials_name",
    "created_at" : 1576300370,
    "global" : false,
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "created_by_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "acl" : {
      "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8" : "user"
    },
    "cidrs" : [ "10.0.0.47/32", "192.168.1.0/24" ],
    "last_used_by_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "type" : "miradore_api_key_v1",
    "created_by_email" : "user@example.com",
    "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8"
  },
  {
    "last_used_at" : 1576300370,
    "name" : "credentials_name",
  }
]
```

```

"created_at" : 1576300370,
"global" : false,
"id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"created_by_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"acl" : [
    "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8" : "user"
],
"cidrs" : [ "10.0.0.47/32", "192.168.1.0/24" ],
"last_used_by_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"type" : "miradore_api_key_v1",
"created_by_email" : "user@example.com",
"client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8"
]
}

```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

array of credentials

401

Access token is missing or invalid [Problem](#)**GET /account/custom-integrations/{customIntegrationId}**[Up](#)Get single custom integration ([getAccountCustomIntegration](#))**Path parameters****customIntegrationId (required)**

Path Parameter — UUID of the custom integration default: null format: uuid

Return type[CustomIntegration](#)**Example data**

Content-Type: application/json

```
{
    "createdAt" : "2023-03-06T18:14:50.52Z",
    "destroyedAt" : "2023-03-06T18:14:50.52Z",
    "clientId" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "name" : "my-custom-integration",
    "icon" : "aVZCT1J3METHZ29BQUFBTlNVaEVVZ0FBQUNBQUFBQWdDQVlBQUFBCemVucjBBQUFBQkdQlRVRUFBTEdQQy94aEJRQUFBQ0Jq",
    "description" : "My custom integration description.",
    "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
    "createdById" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
    "updatedAt" : "2023-03-06T18:14:50.52Z"
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

The custom integration with given ID [CustomIntegration](#)

401

Access token is missing or invalid [Problem](#)

403

Action not allowed for this license type [Problem](#)

404

Resource not found [Problem](#)

500

Unexpected error occurred on the server [Problem](#)**GET /account/custom-integrations**[Up](#)Get all custom integrations ([getAccountCustomIntegrations](#))**Return type**[CustomIntegration](#)**Example data**

Content-Type: application/json

```
{
  "createdAt" : "2023-03-06T18:14:50.52Z",
  "destroyedAt" : "2023-03-06T18:14:50.52Z",
  "clientId" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "my-custom-integration",
  "icon" : "aVZCT1J3METHZ29BQUBTlNVaEVVZ0FBQUNBQUBQWdDQVlBQUFCemVucjBBQUBQkdkQlRVRUFBTEdQQy94aEJRQUBQ0Jq",
  "description" : "My custom integration description.",
  "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
  "createdById" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
  "updatedAt" : "2023-03-06T18:14:50.52Z"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**An array of all custom integrations [CustomIntegration](#)**401**Access token is missing or invalid [Problem](#)**403**Action not allowed for this license type [Problem](#)**404**Resource not found [Problem](#)**500**Unexpected error occurred on the server [Problem](#)
GET /account/groups/{group_id}
[Up](#)
Get group details ([getAccountGroup](#))**Path parameters****group_id (required)***Path Parameter* — UUID of the group default: null format: uuid**Return type**[Group](#)**Example data**

Content-Type: application/json

```
{
  "org_default_role" : "admin",
  "expires_at" : 1576300370,
  "user_count" : 2,
  "updated_at" : 1576300370,
  "name" : "Viewers",
  "org_roles" : {
    "key" : ""
  },
  "description" : "Viewers Group",
  "created_at" : 1576300370,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
```

```

    "role_summary" : "all:viewer",
    "created_by_email" : "jsmith@example.com"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**group information [Group](#)**401**Access token is missing or invalid [Problem](#)**404**Resource not found [Problem](#)
GET /account/sso/groups/{group_mapping_id}
Up
Get SSO group mapping details ([getAccountGroupMapping](#))**Path parameters****group_mapping_id (required)***Path Parameter* — UUID of the SSO group mapping default: null format: uuid**Return type**[GroupMapping](#)**Example data**

Content-Type: application/json

```
{
  "sso_value" : "basic-attribute-value",
  "updated_at" : 1576300370,
  "group_id" : "2b096711-4d28-4417-8635-64af4f62c1ae",
  "group_name" : "Viewers Group",
  "sso_attribute" : "basic-attribute",
  "description" : "Maps basic-attribute to Viewers Group",
  "created_at" : 1576300370,
  "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
  "created_by_email" : "jsmith@example.com"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

group information [GroupMapping](#)

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)**GET /account/sso/groups**[Up](#)Get all SSO group mappings ([getAccountGroupMappings](#))**Return type**[GroupMapping](#)**Example data**

Content-Type: application/json

```
{
  "sso_value" : "basic-attribute-value",
  "updated_at" : 1576300370,
  "group_id" : "2b096711-4d28-4417-8635-64af4f62c1ae",
  "group_name" : "Viewers Group",
  "sso_attribute" : "basic-attribute",
  "description" : "Maps basic-attribute to Viewers Group",
  "created_at" : 1576300370,
  "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
  "created_by_email" : "jsmith@example.com"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

group mapping information [GroupMapping](#)

401

Access token is missing or invalid [Problem](#)**GET /account/groups**[Up](#)Get all groups ([getAccountGroups](#))**Return type**[Group](#)

Example data

Content-Type: application/json

```
{
  "org_default_role" : "admin",
  "expires_at" : 1576300370,
  "user_count" : 2,
  "updated_at" : 1576300370,
  "name" : "Viewers",
  "org_roles" : {
    "key" : ""
  },
  "description" : "Viewers Group",
  "created_at" : 1576300370,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "role_summary" : "all:viewer",
  "created_by_email" : "jsmith@example.com"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

group information [Group](#)

401

Access token is missing or invalid [Problem](#)**GET /account/keys/{key_id}**[Up](#)Get key details ([getAccountKey](#))**Path parameters****key_id (required)**

Path Parameter — UUID of the key to retrieve default: null format: uuid

Return type[APIKey](#)**Example data**

Content-Type: application/json

```
{
  "usage_limit" : 10000,
  "created_at" : 1576300370,
  "counter" : 1,
  "type" : "org",
  "created_by" : "user@example.com",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "token" : "CTXXXXXXXXXXXXXX",
  "usage_today" : 100,
  "last_used_at" : 0,
  "inactive" : true,
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "last_used_ua" : "curl/7.44.1",
  "comment" : "API key used for Splunk integration",
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "last_used_ip" : "127.0.0.1"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

api key information [APIKey](#)

401

Access token is missing or invalid [Problem](#)**GET /account/keys**[Up](#)Get all active API keys ([getAccountKeys](#))**Return type**array[[APIKey](#)]**Example data**

Content-Type: application/json

```
[
  {
    "usage_limit" : 10000,
    "created_at" : 1576300370,
    "counter" : 1,
    "type" : "org",
    "created_by" : "user@example.com",
    "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "token" : "CTXXXXXXXXXXXXXX",
    "usage_today" : 100,
    "last_used_at" : 0,
    "inactive" : true,
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "last_used_ua" : "curl/7.44.1",
    "comment" : "API key used for Splunk integration",
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "last_used_ip" : "127.0.0.1"
  },
  {
    "usage_limit" : 10000,
    "created_at" : 1576300370,
    "counter" : 1,
    "type" : "org",
    "created_by" : "user@example.com",
    "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "token" : "CTXXXXXXXXXXXXXX",
    "usage_today" : 100,
    "last_used_at" : 0,
    "inactive" : true,
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "last_used_ua" : "curl/7.44.1",
    "comment" : "API key used for Splunk integration",
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "last_used_ip" : "127.0.0.1"
  }
]
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

array of keys

401

Access token is missing or invalid [Problem](#)

GET /account/license
[Up](#)

Get license details ([getAccountLicense](#))

Return type

[License](#)

Example data

Content-Type: application/json

```
{
  "via_reseller" : false,
  "sso_type" : "saml20",
  "sso_login_issuer_url" : "https://accounts.google.com/o/saml2?idpid=issuer",
  "address_postal" : "78700",
  "license_live_asset_count" : 1000,
  "created_at" : 1576300370,
  "subscription_canceled_at" : 1576300370,
  "license_expiration" : 1576300370,
  "updated_at" : 1576300370,
  "address_region" : "Texas",
  "sso_login_message" : "Hello",
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "settings" : {
    "key" : ""
  },
  "license_type" : "platform",
  "address_country" : "US",
  "sso_login_login_url" : "https://accounts.google.com/o/saml2?idpid=login",
  "subscription_period_end" : 1576300370,
  "sso_login_logout_url" : "https://accounts.google.com/o/saml2?idpid=logout",
  "address_city" : "Austin",
  "activated_at" : 1576300370,
  "license_max_assets" : 1000000,
  "partner" : "runZero",
  "phone" : "512-555-5555",
  "subscription_period_start" : 1576300370,
  "sso_domain" : "runzero.com",
  "address_street" : "1111 Main St",
  "license_project_asset_count" : 5000,
  "name" : "My Company",
  "sso_mode" : "required",
  "subscription_cancel_at" : 1576300370,
  "sso_default_role" : "viewer"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**license information [License](#)**401**Access token is missing or invalid [Problem](#)**GET /account/orgs/{org_id}**[Up](#)Get organization details ([getAccountOrganization](#))**Path parameters****org_id (required)***Path Parameter* — UUID of the organization to retrieve default: null format: uuid**Return type**[Organization](#)**Example data**

Content-Type: application/json

```
{
  "export_token_last_used_at" : 0,
  "deactivated_at" : 0,
  "download_token_created_at" : 1576300370,
  "export_token_created_at" : 1576300370,
  "created_at" : 1576300370,
  "description" : "All subdivisions of my company",
  "service_count_udp" : 1,
  "project" : false,
  "export_token" : "ET11226D9EEEA2B035D42569585900",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "export_token_counter" : 0,
  "asset_count" : 100,
  "inactive" : false,
  "updated_at" : 1576300370,
  "export_token_last_used_by" : "127.0.0.1",
  "expiration_assets_stale" : 365,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "download_token" : "DT11226D9EEEA2B035D42569585900",
  "service_count" : 10,
  "service_count_tcp" : 7,
  "service_count_arp" : 1,
  "expiration_scans" : 365,
  "service_count_icmp" : 1,
  "expiration_assets_offline" : 365,
  "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "My Company"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**organization information [Organization](#)**401**Access token is missing or invalid [Problem](#)[Up](#)

GET /account/orgs/{org_id}/exportTokens/{key_id}

Get export token details ([getAccountOrganizationExportToken](#))

Path parameters

org_id (required)

Path Parameter — UUID of the organization to retrieve default: null format: uuid

key_id (required)

Path Parameter — UUID of the export token ID to retrieve default: null format: uuid

Return type

[ExportToken](#)

Example data

Content-Type: application/json

```
{
  "last_used_at" : 0,
  "created_at" : 1576300370,
  "comment" : "Export token used for Splunk integration",
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "counter" : 0,
  "last_used_by" : "127.0.0.1",
  "token" : "ET11226D9EEEA2B035D42569585900"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

export token details [ExportToken](#)

401

Access token is missing or invalid [Problem](#)

GET /account/orgs/{org_id}/exportTokens

[Up](#)

Get all active export tokens for an organization ([getAccountOrganizationExportTokens](#))

Path parameters

org_id (required)

Path Parameter — UUID of the organization to retrieve export tokens for default: null format: uuid

Return type

array[[ExportToken](#)]

Example data

Content-Type: application/json

```
[
  {
    "last_used_at" : 0,
    "created_at" : 1576300370,
    "comment" : "Export token used for Splunk integration",
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "counter" : 0,
    "last_used_by" : "127.0.0.1",
    "token" : "ET11226D9EEEA2B035D42569585900"
}
```

```
}, [
  {
    "last_used_at" : 0,
    "created_at" : 1576300370,
    "comment" : "Export token used for Splunk integration",
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "counter" : 0,
    "last_used_by" : "127.0.0.1",
    "token" : "ET11226D9EEEA2B035D42569585900"
  }
]
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**

array of export tokens

401Access token is missing or invalid [Problem](#)**GET /account/orgs**[Up](#)Get all organization details ([getAccountOrganizations](#))**Query parameters****search (optional)**

Query Parameter — an optional search string for filtering results default: null

Return typearray[[Organization](#)]**Example data**

Content-Type: application/json

```
[
  {
    "export_token_last_used_at" : 0,
    "deactivated_at" : 0,
    "download_token_created_at" : 1576300370,
    "export_token_created_at" : 1576300370,
    "created_at" : 1576300370,
    "description" : "All subdivisions of my company",
    "service_count_udp" : 1,
    "project" : false,
    "export_token" : "ET11226D9EEEA2B035D42569585900",
    "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "export_token_counter" : 0,
    "asset_count" : 100,
    "inactive" : false,
    "updated_at" : 1576300370,
    "export_token_last_used_by" : "127.0.0.1",
    "expiration_assets_stale" : 365,
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "download_token" : "DT11226D9EEEA2B035D42569585900",
    "service_count" : 10,
    "service_count_tcp" : 7,
    "service_count_arp" : 1,
    "expiration_scans" : 365,
    "service_count_icmp" : 1,
    "expiration_assets_offline" : 365,
    "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "name" : "My Company"
  }
]
```

```
}, [
  "export_token_last_used_at" : 0,
  "deactivated_at" : 0,
  "download_token_created_at" : 1576300370,
  "export_token_created_at" : 1576300370,
  "created_at" : 1576300370,
  "description" : "All subdivisions of my company",
  "service_count_udp" : 1,
  "project" : false,
  "export_token" : "ET11226D9EEEA2B035D42569585900",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "export_token_counter" : 0,
  "asset_count" : 100,
  "inactive" : false,
  "updated_at" : 1576300370,
  "export_token_last_used_by" : "127.0.0.1",
  "expiration_assets_stale" : 365,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "download_token" : "DT11226D9EEEA2B035D42569585900",
  "service_count" : 10,
  "service_count_tcp" : 7,
  "service_count_arp" : 1,
  "expiration_scans" : 365,
  "service_count_icmp" : 1,
  "expiration_assets_offline" : 365,
  "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "My Company"
} ]
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**

array of organizations

401Access token is missing or invalid [Problem](#)**GET /account/tasks/templates/{scan_template_id}**[Up](#)Get scan template details ([getAccountScanTemplate](#))**Path parameters****scan_template_id (required)**

Path Parameter — UUID of the scan template to retrieve default: null format: uuid

Return type[ScanTemplate](#)**Example data**

Content-Type: application/json

```
{
  "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hidden" : false,
  "description" : "My Scan Template",
  "created_at" : 1576300370,
  "global" : false,
  "acl" : {
    "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8" : "user"
}
```

```
{
  "type" : "scan",
  "error" : "agent unavailable",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "updated_at" : 1576300370,
  "stats" : {
    "key" : ""
  },
  "recur" : false,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "size_site" : 0,
  "recur_last" : 1576300370,
  "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "params" : {
    "key" : "params"
  },
  "created_by" : "user@example.com",
  "created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "size_results" : 0,
  "grace_period" : "4",
  "start_time" : 1576300370,
  "linked_task_count" : 1,
  "recur_frequency" : "hourly",
  "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "My Scan Template",
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "source_id" : "1",
  "size_data" : 0,
  "recur_next" : 1576300370,
  "status" : "processed"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

scan template [ScanTemplate](#)

401

Access token is missing or invalid [Problem](#)

422

invalid scan template id

404

scan template not found

GET /account/tasks/templates[Up](#)Get all scan templates across all organizations (up to 1000) ([getAccountScanTemplates](#))**Query parameters****search (optional)**

Query Parameter — an optional search string for filtering results default: null

Return typearray[[ScanTemplate](#)]

Example data

Content-Type: application/json

```
[ {
  "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hidden" : false,
  "description" : "My Scan Template",
  "created_at" : 1576300370,
  "global" : false,
  "acl" : {
    "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8" : "user"
  },
  "type" : "scan",
  "error" : "agent unavailable",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "updated_at" : 1576300370,
  "stats" : {
    "key" : ""
  },
  "recur" : false,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "size_site" : 0,
  "recur_last" : 1576300370,
  "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "params" : {
    "key" : "params"
  },
  "created_by" : "user@example.com",
  "created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "size_results" : 0,
  "grace_period" : "4",
  "start_time" : 1576300370,
  "linked_task_count" : 1,
  "recur_frequency" : "hourly",
  "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "My Scan Template",
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "source_id" : "1",
  "size_data" : 0,
  "recur_next" : 1576300370,
  "status" : "processed"
}, {
  "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hidden" : false,
  "description" : "My Scan Template",
  "created_at" : 1576300370,
  "global" : false,
  "acl" : {
    "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8" : "user"
  },
  "type" : "scan",
  "error" : "agent unavailable",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "updated_at" : 1576300370,
  "stats" : {
    "key" : ""
  },
  "recur" : false,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "size_site" : 0,
  "recur_last" : 1576300370,
  "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "params" : {
    "key" : "params"
  },
  "created_by" : "user@example.com",
  "created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
}
```

```

"size_results" : 0,
"grace_period" : "4",
"start_time" : 1576300370,
"linked_task_count" : 1,
"recur_frequency" : "hourly",
"parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"name" : "My Scan Template",
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"source_id" : "1",
"size_data" : 0,
"recur_next" : 1576300370,
"status" : "processed"
} ]

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

array of scan templates

422

failed to parse search string

401

Access token is missing or invalid [Problem](#)**GET /account/sites**[Up](#)Get all sites details across all organizations ([getAccountSites](#))**Query parameters****search (optional)**

Query Parameter — an optional search string for filtering results default: null

Return typearray[[Site](#)]**Example data**

Content-Type: application/json

```
[
  {
    "data" : {
      "excludes" : "192.168.0.5",
      "updated_at" : 1576300370,
      "scope" : "192.168.0.0/24",
      "name" : "Primary",
      "created_at" : 1576300370,
      "description" : "Headquarters",
      "subnets" : [
        "key" : ""
      ],
      "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8"
    }
  },
  {
    "data" : {
      "excludes" : "192.168.0.5",
      "updated_at" : 1576300370,
      "scope" : "192.168.0.0/24",
      "name" : "Primary",
    }
  }
]
```

```

    "created_at" : 1576300370,
    "description" : "Headquarters",
    "subnets" : {
      "key" : ""
    },
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8"
  }
]
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

array of sites

401

Access token is missing or invalid [Problem](#)**GET /account/tasks**[Up](#)Get all task details across all organizations (up to 1000) ([getAccountTasks](#))**Query parameters****search (optional)**

Query Parameter — an optional search string for filtering results default: null

Return typearray[[TaskBase](#)]**Example data**

Content-Type: application/json

```
[
  {
    "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "hidden" : false,
    "description" : "Scan the headquarters hourly",
    "created_at" : 1576300370,
    "type" : "scan",
    "error" : "agent unavailable",
    "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "updated_at" : 1576300370,
    "stats" : {
      "key" : ""
    },
    "recur" : false,
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "recur_last" : 1576300370,
    "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "params" : {
      "key" : "params"
    },
    "created_by" : "user@example.com",
    "created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "start_time" : 1576300370,
    "recur_frequency" : "hourly",
    "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  }
]
```

```

"name" : "Hourly Scan",
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"source_id" : 1,
"recur_next" : 1576300370,
"status" : "processed"
}, {
"agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"hidden" : false,
"description" : "Scan the headquarters hourly",
"created_at" : 1576300370,
"type" : "scan",
"error" : "agent unavailable",
"client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"updated_at" : 1576300370,
"stats" : {
"key" : ""
},
"recur" : false,
"id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"recur_last" : 1576300370,
"custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"params" : {
"key" : "params"
},
"created_by" : "user@example.com",
"created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"start_time" : 1576300370,
"recur_frequency" : "hourly",
"parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"name" : "Hourly Scan",
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"source_id" : 1,
"recur_next" : 1576300370,
"status" : "processed"
} ]

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

array of tasks

401

Access token is missing or invalid [Problem](#)**GET /account/users/{user_id}**[Up](#)Get user details ([getAccountUser](#))**Path parameters****user_id (required)**

Path Parameter — UUID of the user to retrieve default: null format: uuid

Return type

[User](#)**Example data**

Content-Type: application/json

```
{
  "org_default_role" : "admin",
  "last_login_at" : 1576300370,
  "org_roles" : {
    "key" : ""
  },
  "created_at" : 1576300370,
  "last_name" : "Smith",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "invite_token_expiration" : 1576300370,
  "sso_only" : false,
  "updated_at" : 1576300370,
  "last_login_ip" : "192.168.0.1",
  "login_failures" : 0,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "reset_token_expiration" : 1576300370,
  "last_login_ua" : "curl/1.0",
  "first_name" : "James",
  "email" : "jsmith@example.com",
  "client_admin" : true
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**user information [User](#)**401**Access token is missing or invalid [Problem](#)**GET /account/users**[Up](#)Get all users ([getAccountUsers](#))**Return type**array [[User](#)]**Example data**

Content-Type: application/json

```
[
  {
    "org_default_role" : "admin",
    "last_login_at" : 1576300370,
    "org_roles" : {
      "key" : ""
    },
    "created_at" : 1576300370,
    "last_name" : "Smith",
    "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "invite_token_expiration" : 1576300370,
    "sso_only" : false,
    "updated_at" : 1576300370,
    "last_login_ip" : "192.168.0.1",
    "login_failures" : 0,
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "reset_token_expiration" : 1576300370,
    "last_login_ua" : "curl/1.0",
    "first_name" : "James",
    "email" : "jsmith@example.com",
    "client_admin" : true
  }
]
```

```

"reset_token_expiration" : 1576300370,
"last_login_ua" : "curl/1.0",
"first_name" : "James",
"email" : "jsmith@example.com",
"client_admin" : true
}, {
  "org_default_role" : "admin",
  "last_login_at" : 1576300370,
  "org_roles" : {
    "key" : ""
  },
  "created_at" : 1576300370,
  "last_name" : "Smith",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "invite_token_expiration" : 1576300370,
  "sso_only" : false,
  "updated_at" : 1576300370,
  "last_login_ip" : "192.168.0.1",
  "login_failures" : 0,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "reset_token_expiration" : 1576300370,
  "last_login_ua" : "curl/1.0",
  "first_name" : "James",
  "email" : "jsmith@example.com",
  "client_admin" : true
} ]

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

array of users

401

Access token is missing or invalid [Problem](#)**DELETE /account/credentials/{credential_id}**[Up](#)Remove this credential ([removeAccountCredential](#))**Path parameters****credential_id (required)**

Path Parameter — UUID of the credential to delete default: null format: uuid

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
```

```
{
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**204**

empty response

401Access token is missing or invalid [Problem](#)**404**Resource not found [Problem](#)**DELETE /account/groups/{group_id}**[Up](#)

Remove this group ([removeAccountGroup](#))

Path parameters**group_id (required)**

Path Parameter — UUID of the group default: null format: uuid

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**204**

empty response

401Access token is missing or invalid [Problem](#)**DELETE /account/sso/groups/{group_mapping_id}**[Up](#)

Remove this SSO group mapping ([removeAccountGroupMapping](#))

Path parameters**group_mapping_id (required)**

Path Parameter — UUID of the SSO group mapping default: null format: uuid

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**204**

empty response

401Access token is missing or invalid [Problem](#)**DELETE /account/keys/{key_id}**[Up](#)Remove this key ([removeAccountKey](#))**Path parameters****key_id (required)***Path Parameter* — UUID of the key to retrieve default: null format: uuid**Example data**

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces**204**

empty response

401Access token is missing or invalid [Problem](#)**DELETE /account/orgs/{org_id}**[Up](#)Remove this organization ([removeAccountOrganization](#))**Path parameters****org_id (required)***Path Parameter* — UUID of the organization to retrieve default: null format: uuid**Example data**

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces**204**

empty response

401Access token is missing or invalid [Problem](#)**DELETE /account/tasks/templates/{scan_template_id}**[Up](#)Remove scan template ([removeAccountScanTemplate](#))

Path parameters**scan_template_id (required)***Path Parameter* — UUID of the scan template to remove default: null format: uuid**Return type**[ScanTemplate](#)**Example data**

Content-Type: application/json

```
{
  "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hidden" : false,
  "description" : "My Scan Template",
  "created_at" : 1576300370,
  "global" : false,
  "acl" : {
    "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8" : "user"
  },
  "type" : "scan",
  "error" : "agent unavailable",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "updated_at" : 1576300370,
  "stats" : {
    "key" : ""
  },
  "recur" : false,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "size_site" : 0,
  "recur_last" : 1576300370,
  "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "params" : {
    "key" : "params"
  },
  "created_by" : "user@example.com",
  "created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "size_results" : 0,
  "grace_period" : "4",
  "start_time" : 1576300370,
  "linked_task_count" : 1,
  "recur_frequency" : "hourly",
  "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "My Scan Template",
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "source_id" : "1",
  "size_data" : 0,
  "recur_next" : 1576300370,
  "status" : "processed"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**scan template [ScanTemplate](#)**401**

Access token is missing or invalid [Problem](#)

422

invalid request

404

scan template not found

DELETE /account/users/{user_id}

[Up](#)

Remove this user ([removeAccountUser](#))

Path parameters

user_id (required)

Path Parameter — UUID of the user to delete default: null format: uuid

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

204

empty response

401

Access token is missing or invalid [Problem](#)

PATCH /account/users/{user_id}/resetLockout

[Up](#)

Resets the user's lockout status ([resetAccountUserLockout](#))

Path parameters

user_id (required)

Path Parameter — UUID of the user to retrieve default: null format: uuid

Return type

[User](#)

Example data

Content-Type: application/json

```
{
  "org_default_role" : "admin",
  "last_login_at" : 1576300370,
  "org_roles" : {
    "key" : ""
  },
  "created_at" : 1576300370,
  "last_name" : "Smith",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "invite_token_expiration" : 1576300370,
  "sso_only" : false,
  "updated_at" : 1576300370,
  "last_login_ip" : "192.168.0.1",
  "login_failures" : 0,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "reset_token_expiration" : 1576300370,
  "last_login_ua" : "curl/1.0",
  "first_name" : "James",
  "email" : "jsmith@example.com",
```

```

        "client_admin" : true
    }
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

user information [User](#)

401

Access token is missing or invalid [Problem](#)**PATCH /account/users/{user_id}/resetMFA**[Up](#)Resets the user's MFA tokens ([resetAccountUserMFA](#))**Path parameters****user_id (required)**

Path Parameter — UUID of the user to retrieve default: null format: uuid

Return type[User](#)**Example data**

Content-Type: application/json

```
{
    "org_default_role" : "admin",
    "last_login_at" : 1576300370,
    "org_roles" : {
        "key" : ""
    },
    "created_at" : 1576300370,
    "last_name" : "Smith",
    "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "invite_token_expiration" : 1576300370,
    "sso_only" : false,
    "updated_at" : 1576300370,
    "last_login_ip" : "192.168.0.1",
    "login_failures" : 0,
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "reset_token_expiration" : 1576300370,
    "last_login_ua" : "curl/1.0",
    "first_name" : "James",
    "email" : "jsmith@example.com",
    "client_admin" : true
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**user information [User](#)**401**Access token is missing or invalid [Problem](#)**PATCH /account/users/{user_id}/resetPassword**[Up](#)Sends the user a password reset email ([resetAccountUserPassword](#))**Path parameters****user_id (required)***Path Parameter* — UUID of the user to retrieve default: null format: uuid**Return type**[User](#)**Example data**

Content-Type: application/json

```
{
  "org_default_role" : "admin",
  "last_login_at" : 1576300370,
  "org_roles" : {
    "key" : ""
  },
  "created_at" : 1576300370,
  "last_name" : "Smith",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "invite_token_expiration" : 1576300370,
  "sso_only" : false,
  "updated_at" : 1576300370,
  "last_login_ip" : "192.168.0.1",
  "login_failures" : 0,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "reset_token_expiration" : 1576300370,
  "last_login_ua" : "curl/1.0",
  "first_name" : "James",
  "email" : "jsmith@example.com",
  "client_admin" : true
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**user information [User](#)**401**Access token is missing or invalid [Problem](#)**POST /account/api/rotate**[Up](#)Rotate the API client secret ([rotateAPIToken](#))**Consumes**

runZero API documentation

This API call consumes the following media types via the Content-Type request header:

- application/x-www-form-urlencoded

Form parameters

grant_type (required)

Form Parameter — default: null

client_id (required)

Form Parameter — default: null

client_secret (required)

Form Parameter — default: null

Return type

[APIClient](#)

Example data

Content-Type: application/json

```
{  
  "api_client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
  "api_client_secret" : "api_client_secret"  
}
```

Example data

Content-Type: application/json

```
{  
  "detail" : "A human readable explanation specific to this occurrence of the problem.",  
  "title" : "A short summary of the problem type.",  
  "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
  "detail" : "A human readable explanation specific to this occurrence of the problem.",  
  "title" : "A short summary of the problem type.",  
  "status" : 140  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

Client details with an updated api_client_secret value [APIClient](#)

400

Invalid request body [Problem](#)

401

Access token is missing or invalid [Problem](#)

PATCH /account/keys/{key_id}/rotate

[Up](#)

Rotates the key secret ([rotateAccountKey](#))

Path parameters

key_id (required)

Path Parameter — UUID of the key to retrieve default: null format: uuid

Return type

[APIKey](#)

Example data

Content-Type: application/json

```
{
  "usage_limit" : 10000,
  "created_at" : 1576300370,
  "counter" : 1,
  "type" : "org",
  "created_by" : "user@example.com",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "token" : "CTXXXXXXXXXXXXX",
  "usage_today" : 100,
  "last_used_at" : 0,
  "inactive" : true,
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "last_used_ua" : "curl/7.44.1",
  "comment" : "API key used for Splunk integration",
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "last_used_ip" : "127.0.0.1"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

key details [APIKey](#)

401

Access token is missing or invalid [Problem](#)**PATCH /account/orgs/{org_id}/exportTokens/{key_id}/rotate**[Up](#)

Rotates an organization export token and returns the updated token (`rotateAccountOrganizationExportToken`)

Path parameters**org_id (required)**

Path Parameter — UUID of the organization to retrieve default: null format: uuid

key_id (required)

Path Parameter — UUID of the export token ID to rotate default: null format: uuid

Return type[ExportToken](#)**Example data**

Content-Type: application/json

```
{
  "last_used_at" : 0,
  "created_at" : 1576300370,
  "comment" : "Export token used for Splunk integration",
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "counter" : 0,
  "last_used_by" : "127.0.0.1",
  "token" : "ET11226D9EEEA2B035D42569585900"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
```

```
{
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

export token details [ExportToken](#)

401

Access token is missing or invalid [Problem](#)

PATCH /account/orgs/{org_id}/exportToken/rotate Up

Rotates an organization export token and returns the updated token ([rotateAccountOrganizationExportTokenDeprecated](#))

This API has been deprecated. Please use PATCH /account/orgs/{org_id}/exportTokens/{key_id}/rotate instead. This API will fail if more than one export tokens exist for the given organization.

Path parameters**org_id (required)**

Path Parameter — UUID of the organization to retrieve default: null format: uuid

Return type

[ExportToken](#)

Example data

Content-Type: application/json

```
{
  "last_used_at" : 0,
  "created_at" : 1576300370,
  "comment" : "Export token used for Splunk integration",
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "counter" : 0,
  "last_used_by" : "127.0.0.1",
  "token" : "ET11226D9EEEA2B035D42569585900"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

export token details [ExportToken](#)

401

Access token is missing or invalid [Problem](#)

PATCH /account/assets/ownership-types/{ownership_type_id} Up

Update a single asset ownership type ([updateAccountAssetOwnershipType](#))

Path parameters**ownership_type_id (required)**

runZero API documentation

Path Parameter — UUID of the asset ownership type default: null format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

AssetOwnershipTypePost [AssetOwnershipTypePost](#) (required)

Body Parameter —

Return type

[AssetOwnershipType](#)

Example data

Content-Type: application/json

```
{  
  "reference" : 1,  
  "hidden" : true,  
  "name" : "Asset Owner",  
  "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",  
  "order" : 1  
}
```

Example data

Content-Type: application/json

```
{  
  "detail" : "A human readable explanation specific to this occurrence of the problem.",  
  "title" : "A short summary of the problem type.",  
  "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
  "detail" : "A human readable explanation specific to this occurrence of the problem.",  
  "title" : "A short summary of the problem type.",  
  "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
  "detail" : "A human readable explanation specific to this occurrence of the problem.",  
  "title" : "A short summary of the problem type.",  
  "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
  "detail" : "A human readable explanation specific to this occurrence of the problem.",  
  "title" : "A short summary of the problem type.",  
  "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
  "detail" : "A human readable explanation specific to this occurrence of the problem.",  
  "title" : "A short summary of the problem type.",  
  "status" : 140  
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

updated asset ownership type [AssetOwnershipType](#)

400

Invalid request body [Problem](#)

401

Access token is missing or invalid [Problem](#)

403

Action not allowed for this license type [Problem](#)

404

Resource not found [Problem](#)

422

Invalid request body [Problem](#)

500

Unexpected error occurred on the server [Problem](#)

PUT /account/assets/ownership-types

[Up](#)

Update asset ownership types ([updateAccountAssetOwnershipTypes](#))

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

AssetOwnershipType [AssetOwnershipType](#) (required)
Body Parameter —

Return type

array[[AssetOwnershipType](#)]

Example data

Content-Type: application/json

```
[
  {
    "reference" : 1,
    "hidden" : true,
    "name" : "Asset Owner",
    "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
    "order" : 1
  },
  {
    "reference" : 1,
    "hidden" : true,
    "name" : "Asset Owner",
    "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
    "order" : 1
  }
]
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**

array of asset ownership types

400Invalid request body [Problem](#)**401**Access token is missing or invalid [Problem](#)**403**Action not allowed for this license type [Problem](#)**404**Resource not found [Problem](#)**422**Invalid request body [Problem](#)**500**Unexpected error occurred on the server [Problem](#)

PATCH /account/custom-integrations/{customIntegrationId}

[Up](#)
Update a single custom integration ([updateAccountCustomIntegration](#))**Path parameters****customIntegrationId (required)**

Path Parameter — UUID of the custom integration default: null format: uuid

runZero API documentation

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

BaseCustomIntegration [BaseCustomIntegration](#) (required)

Body Parameter —

Return type

[CustomIntegration](#)

Example data

Content-Type: application/json

```
{  
    "createdAt" : "2023-03-06T18:14:50.52Z",  
    "destroyedAt" : "2023-03-06T18:14:50.52Z",  
    "clientId" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "name" : "my-custom-integration",  
    "icon" : "aVZCT13METHZ29BQFBTlNVaEVVZ0FBQUNBQUFQWdDQVlBQUFCEmVucjBBQUBQkdkQlRVRUFBTEdQQy94aEJRQUBQ0Jq",  
    "description" : "My custom integration description.",  
    "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",  
    "createdById" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",  
    "updatedAt" : "2023-03-06T18:14:50.52Z"  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

The updated custom integration [CustomIntegration](#)

400

Invalid request body [Problem](#)

401

Access token is missing or invalid [Problem](#)

403

Action not allowed for this license type [Problem](#)

404

Resource not found [Problem](#)

422

Invalid request body [Problem](#)

500

Unexpected error occurred on the server [Problem](#)**PUT /account/groups**[Up](#)Update an existing group ([updateAccountGroup](#))**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body[GroupPut](#) [GroupPut](#) (required)

Body Parameter —

Return type[Group](#)**Example data**

Content-Type: application/json

```
{
  "org_default_role" : "admin",
  "expires_at" : 1576300370,
  "user_count" : 2,
  "updated_at" : 1576300370,
  "name" : "Viewers",
  "org_roles" : {
    "key" : ""
  },
  "description" : "Viewers Group",
  "created_at" : 1576300370,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "role_summary" : "all:viewer",
  "created_by_email" : "jsmith@example.com"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
```

```

        "status" : 140
    }
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

group information [Group](#)

401

Access token is missing or invalid [Problem](#)

PUT /account/sso/groups
[Up](#)

Update an existing SSO group mapping ([updateAccountGroupMapping](#))

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

GroupMapping [GroupMapping](#) (required)

Body Parameter —

Return type

[GroupMapping](#)

Example data

Content-Type: application/json

```
{
    "sso_value" : "basic-attribute-value",
    "updated_at" : 1576300370,
    "group_id" : "2b096711-4d28-4417-8635-64af4f62c1ae",
    "group_name" : "Viewers Group",
    "sso_attribute" : "basic-attribute",
    "description" : "Maps basic-attribute to Viewers Group",
    "created_at" : 1576300370,
    "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
    "created_by_email" : "jsmith@example.com"
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

group information [GroupMapping](#)

401

Access token is missing or invalid [Problem](#)

PATCH /account/orgs/{org_id}
[Up](#)

Update organization details ([updateAccountOrganization](#))

Path parameters**org_id (required)***Path Parameter* — UUID of the organization to retrieve default: null format: uuid**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body**OrgOptions [OrgOptions](#) (required)***Body Parameter* —**Return type**[Organization](#)**Example data**

Content-Type: application/json

```
{
  "export_token_last_used_at" : 0,
  "deactivated_at" : 0,
  "download_token_created_at" : 1576300370,
  "export_token_created_at" : 1576300370,
  "created_at" : 1576300370,
  "description" : "All subdivisions of my company",
  "service_count_udp" : 1,
  "project" : false,
  "export_token" : "ET11226D9EEEA2B035D42569585900",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "export_token_counter" : 0,
  "asset_count" : 100,
  "inactive" : false,
  "updated_at" : 1576300370,
  "export_token_last_used_by" : "127.0.0.1",
  "expiration_assets_stale" : 365,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "download_token" : "DT11226D9EEEA2B035D42569585900",
  "service_count" : 10,
  "service_count_tcp" : 7,
  "service_count_arp" : 1,
  "expiration_scans" : 365,
  "service_count_icmp" : 1,
  "expiration_assets_offline" : 365,
  "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "My Company"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**organization details [Organization](#)**401**Access token is missing or invalid [Problem](#)**PUT /account/tasks/templates****Up**

runZero API documentation

Update scan template ([updateAccountScanTemplate](#))

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

[ScanTemplate](#) [ScanTemplate](#) (required)

Body Parameter —

Return type

[ScanTemplate](#)

Example data

Content-Type: application/json

```
{  
    "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "hidden" : false,  
    "description" : "My Scan Template",  
    "created_at" : 1576300370,  
    "global" : false,  
    "acl" : {  
        "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8" : "user"  
    },  
    "type" : "scan",  
    "error" : "agent unavailable",  
    "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "updated_at" : 1576300370,  
    "stats" : {  
        "key" : ""  
    },  
    "recur" : false,  
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "size_site" : 0,  
    "recur_last" : 1576300370,  
    "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "params" : {  
        "key" : "params"  
    },  
    "created_by" : "user@example.com",  
    "created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "size_results" : 0,  
    "grace_period" : "4",  
    "start_time" : 1576300370,  
    "linked_task_count" : 1,  
    "recur_frequency" : "hourly",  
    "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "name" : "My Scan Template",  
    "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "source_id" : "1",  
    "size_data" : 0,  
    "recur_next" : 1576300370,  
    "status" : "processed"  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

scan template [ScanTemplate](#)

401

Access token is missing or invalid [Problem](#)

422

Invalid request body [Problem](#)

400

Invalid request body [Problem](#)

404

scan template or permissions not found

PATCH /account/users/{user_id}[Up](#)Update a user's details ([updateAccountUser](#))**Path parameters****user_id (required)**

Path Parameter — UUID of the user to retrieve default: null format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body**UserOptions UserOptions (required)**

Body Parameter —

Return type[User](#)**Example data**

Content-Type: application/json

```
{
  "org_default_role" : "admin",
  "last_login_at" : 1576300370,
  "org_roles" : {
    "key" : ""
  },
  "created_at" : 1576300370,
  "last_name" : "Smith",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "invite_token_expiration" : 1576300370,
  "sso_only" : false,
  "updated_at" : 1576300370,
  "last_login_ip" : "192.168.0.1",
  "login_failures" : 0,
}
```

```

"id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"reset_token_expiration" : 1576300370,
"last_login_ua" : "curl/1.0",
"first_name" : "James",
"email" : "jsmith@example.com",
"client_admin" : true
}

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

user information [User](#)

401

Access token is missing or invalid [Problem](#)

CiscoSNTC

[GET /export/org/assets.cisco.csv](#)
Up

Cisco serial number and model name export for Cisco Smart Net Total Care Service. ([exportAssetsCiscoCSV](#))

Query parameters**_oid (optional)**

Query Parameter — The current Organization default: null

search (optional)

Query Parameter — an optional search string for filtering results default: null

Return type

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses

200

filtered asset results [File](#)

401

Access token is missing or invalid [Problem](#)

Export

[Up](#)

GET /org/assets/hw.csvTop asset hardware products as CSV ([exportAssetTopHWCSV](#))**Query parameters***Query Parameter* — The current Organization default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses

200

top asset hardware platforms and counts as csv [File](#)

401

Access token is missing or invalid [Problem](#)**GET /org/assets/os.csv**[Up](#)Top asset operating systems as CSV ([exportAssetTopOSCSV](#))**Query parameters**oid (optional)*Query Parameter* — The current Organization default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses

200

top operating systems and counts as csv [File](#)

401

Access token is missing or invalid [Problem](#)**GET /org/assets/tags.csv**[Up](#)

Top asset tags as CSV ([exportAssetTopTagsCSV](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses

200

top asset tags and counts as csv [File](#)

401

Access token is missing or invalid [Problem](#)**GET /org/assets/type.csv**[Up](#)Top asset types as CSV ([exportAssetTopTypesCSV](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses

200

top asset types and counts as csv [File](#)

401

Access token is missing or invalid [Problem](#)**GET /export/org/assets.csv**[Up](#)Asset inventory as CSV ([exportAssetsCSV](#))**Query parameters**

_oid (optional)*Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses

200

filtered asset results [File](#)

401

Access token is missing or invalid [Problem](#)**GET /export/org/assets.json**[Up](#)Exports the asset inventory ([exportAssetsJSON](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**fields (optional)***Query Parameter* — an optional list of fields to export, comma-separated default: null**Return type**array[[Asset](#)]**Example data**

Content-Type: application/json

```
[
  {
    "addresses" : [ "192.168.0.1", "192.168.0.1" ],
    "first_seen" : 1576300370,
    "alive" : true,
    "last_seen" : 1576300370,
    "agent_name" : "LAPTOP-F4P1R6",
    "credentials" : [
      "key" : {
        "key" : true
      }
    ],
    "created_at" : 1576300370,
    "service_count_udp" : 1,
    "mac_vendors" : [ "Dell", "Dell" ],
    "type" : "Server",
    "last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "service_ports_udp" : [ "53", "53" ],
    "hw" : "Dell PowerEdge 2500",
    "lowest_rtt" : 1,
    "service_ports_products" : [ "bind", "bind" ],
    "updated_at" : 1576300370,
  }
]
```

```

"detected_by" : "icmp",
"id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"service_ports_protocols" : [ "ssh", "ssh" ],
"org_name" : "Test Labs",
"addresses_extra" : [ "192.168.100.1", "192.168.100.1" ],
"comments" : "File Server",
"os" : "Ubuntu Linux",
"last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"os_version" : "18.04",
"service_count" : 10,
"domains" : [ "www", "www" ],
"service_count_tcp" : 7,
"newest_mac_vendor" : "Intel Corporate",
"lowest_ttl" : 0,
"newest_mac" : "11:22:33:44:55:66",
"service_count_arp" : 1,
"services" : {
  "key" : {
    "key" : "services"
  }
},
"service_ports_tcp" : [ "22", "22" ],
"tags" : {
  "key" : "tags"
},
"site_name" : "Primary",
"names" : [ "www", "www" ],
"service_count_icmp" : 1,
"rtts" : {
  "key" : ""
},
"organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"macs" : [ "11:22:33:44:55:66", "11:22:33:44:55:66" ],
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"attributes" : {
  "key" : "attributes"
},
"newest_mac_age" : 13040352000000000000
}, {
"addresses" : [ "192.168.0.1", "192.168.0.1" ],
"first_seen" : 1576300370,
"alive" : true,
"last_seen" : 1576300370,
"agent_name" : "LAPTOP-F4P1R6",
"credentials" : {
  "key" : {
    "key" : true
  }
},
"created_at" : 1576300370,
"service_count_udp" : 1,
"mac_vendors" : [ "Dell", "Dell" ],
"type" : "Server",
"last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"service_ports_udp" : [ "53", "53" ],
"hw" : "Dell PowerEdge 2500",
"lowest_rtt" : 1,
"service_ports_products" : [ "bind", "bind" ],
"updated_at" : 1576300370,
"detected_by" : "icmp",
"id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"service_ports_protocols" : [ "ssh", "ssh" ],
"org_name" : "Test Labs",
"addresses_extra" : [ "192.168.100.1", "192.168.100.1" ],
"comments" : "File Server",
"os" : "Ubuntu Linux",
"last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"os_version" : "18.04",
"service_count" : 10,
"domains" : [ "www", "www" ],
"service_count_tcp" : 7,
"newest_mac_vendor" : "Intel Corporate",
"lowest_ttl" : 0,
"newest_mac" : "11:22:33:44:55:66",
"service_count_arp" : 1,
"services" : {

```

```

    "key" : {
      "key" : "services"
    }
  },
  "service_ports_tcp" : [ "22", "22" ],
  "tags" : {
    "key" : "tags"
  },
  "site_name" : "Primary",
  "names" : [ "www", "www" ],
  "service_count_icmp" : 1,
  "rtts" : {
    "key" : ""
  },
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "macs" : [ "11:22:33:44:55:66", "11:22:33:44:55:66" ],
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "attributes" : {
    "key" : "attributes"
  },
  "newest_mac_age" : 13040352000000000000
} ]

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

filtered asset results

401

Access token is missing or invalid [Problem](#)**GET /export/org/assets.jsonl**[Up](#)Asset inventory as JSON line-delimited ([exportAssetsJSONL](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**fields (optional)***Query Parameter* — an optional list of fields to export, comma-separated default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**filtered asset results [File](#)**401**Access token is missing or invalid [Problem](#)**GET /export/org/assets.nmap.xml**[Up](#)Asset inventory as Nmap-style XML ([exportAssetsNmapXML](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/xml
- application/json

Responses**200**filtered asset results [File](#)**401**Access token is missing or invalid [Problem](#)**GET /export/org/groups.csv**[Up](#)Group inventory as CSV ([exportDirectoryGroupsCSV](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses**200**filtered group results [File](#)**401**Access token is missing or invalid [Problem](#)**GET /export/org/groups.json**[Up](#)Exports the group inventory ([exportDirectoryGroupsJSON](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**fields (optional)***Query Parameter* — an optional list of fields to export, comma-separated default: null**Return type**array[[DirectoryGroup](#)]**Example data**

Content-Type: application/json

```
[ {
  "directory_group_site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "directory_group_name" : "CN=Remote Desktop Users,CN=Builtin,DC=example,DC=com",
  "directory_group_created_at" : 1576300370,
  "directory_group_description" : "Members in this group are granted the right to logon remotely",
  "directory_group_email_normalized" : "user@example.com",
  "directory_group_display_name" : "Remote Desktop Users",
  "directory_group_group_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "directory_group_user_count" : 1,
  "directory_group_organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "directory_group_source_id" : 1,
  "directory_group_email" : "user@example.com",
  "directory_group_attributes" : {
    "key" : "directory_group_attributes"
  },
  "directory_group_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "directory_group_updated_at" : 1576300370
}, {
  "directory_group_site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "directory_group_name" : "CN=Remote Desktop Users,CN=Builtin,DC=example,DC=com",
  "directory_group_created_at" : 1576300370,
  "directory_group_description" : "Members in this group are granted the right to logon remotely",
  "directory_group_email_normalized" : "user@example.com",
  "directory_group_display_name" : "Remote Desktop Users",
  "directory_group_group_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "directory_group_user_count" : 1,
  "directory_group_organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "directory_group_source_id" : 1,
  "directory_group_email" : "user@example.com",
  "directory_group_attributes" : {
    "key" : "directory_group_attributes"
  },
  "directory_group_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "directory_group_updated_at" : 1576300370
} ]
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
```

```

        "status" : 140
    }
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

filtered group results

401

Access token is missing or invalid [Problem](#)

GET /export/org/groups.jsonl
[Up](#)

Group inventory as JSON line-delimited ([exportDirectoryGroupsJSONL](#))

Query parameters**_oid (optional)**

Query Parameter — The current Organization default: null

search (optional)

Query Parameter — an optional search string for filtering results default: null

fields (optional)

Query Parameter — an optional list of fields to export, comma-separated default: null

Return type

File

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

filtered group results [File](#)

401

Access token is missing or invalid [Problem](#)

GET /export/org/users.csv
[Up](#)

User inventory as CSV ([exportDirectoryUsersCSV](#))

Query parameters**_oid (optional)**

Query Parameter — The current Organization default: null

search (optional)

Query Parameter — an optional search string for filtering results default: null

Return type

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses

200

filtered user results [File](#)

401

Access token is missing or invalid [Problem](#)

GET /export/org/users.json

[Up](#)

Exports the user inventory ([exportDirectoryUsersJSON](#))

Query parameters**_oid (optional)**

Query Parameter — The current Organization default: null

search (optional)

Query Parameter — an optional search string for filtering results default: null

fields (optional)

Query Parameter — an optional list of fields to export, comma-separated default: null

Return type

array[[DirectoryUser](#)]

Example data

Content-Type: application/json

```
[
  {
    "directory_user_name" : "CN=Jane Doe,OU=Employees,DC=example,DC=com",
    "directory_user_attributes" : {
      "key" : "directory_user_attributes"
    },
    "directory_user_group_ids" : [ "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8", "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8" ],
    "directory_user_description" : "Example user",
    "directory_user_last_logon_at" : 1576300370,
    "directory_user_updated_at" : 1576300370,
    "directory_user_source_id" : 1,
    "directory_user_first_name" : "Jane",
    "directory_user_title" : "Software Engineer",
    "directory_user_phone" : "555-555-5555",
    "directory_user_display_name" : "Jane Doe",
    "directory_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "directory_user_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "directory_user_email_normalized" : "user@example.com",
    "directory_user_email" : "user@example.com",
    "directory_user_location" : "Remote",
    "directory_user_site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "directory_user_organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "directory_user_created_at" : 1576300370,
    "directory_user_last_name" : "Doe"
  },
  {
    "directory_user_name" : "CN=Jane Doe,OU=Employees,DC=example,DC=com",
    "directory_user_attributes" : {
      "key" : "directory_user_attributes"
    },
    "directory_user_group_ids" : [ "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8", "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8" ],
    "directory_user_description" : "Example user",
    "directory_user_last_logon_at" : 1576300370,
    "directory_user_updated_at" : 1576300370,
    "directory_user_source_id" : 1
  }
]
```

```

"directory_user_first_name" : "Jane",
"directory_user_title" : "Software Engineer",
"directory_user_phone" : "555-555-5555",
"directory_user_display_name" : "Jane Doe",
"directory_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"directory_user_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"directory_user_email_normalized" : "user@example.com",
"directory_user_email" : "user@example.com",
"directory_user_location" : "Remote",
"directory_user_site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"directory_user_organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"directory_user_created_at" : 1576300370,
"directory_user_last_name" : "Doe"
} ]

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**

filtered user results

401Access token is missing or invalid [Problem](#)**GET /export/org/users.jsonl**[Up](#)User inventory as JSON line-delimited ([exportDirectoryUsersJSONL](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**fields (optional)***Query Parameter* — an optional list of fields to export, comma-separated default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**filtered user results [File](#)**401**Access token is missing or invalid [Problem](#)

GET /export/org/snmp.arpcache.csv[Up](#)SNMP ARP cache data as CSV ([exportSNMPARPCacheCSV](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses**200**SNMP ARP cache data as csv [File](#)**401**Access token is missing or invalid [Problem](#)**GET /export/org/services.csv**[Up](#)Service inventory as CSV ([exportServicesCSV](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses**200**filtered service results [File](#)**401**Access token is missing or invalid [Problem](#)

GET /export/org/services.json[Up](#)Service inventory as JSON (`exportServicesJSON`)**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**fields (optional)***Query Parameter* — an optional list of fields to export, comma-separated default: null**Return type**array[[Service](#)]**Example data**

Content-Type: application/json

```
[
  {
    "addresses" : [ "192.168.0.1", "192.168.0.1" ],
    "last_seen" : 1576300370,
    "agent_name" : "LAPTOP-F4P1R6",
    "service_screenshot_link" : "service_screenshot_link",
    "type" : "Server",
    "last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "hw" : "Dell PowerEdge 2500",
    "lowest_rtt" : 1,
    "service_ports_products" : [ "bind", "bind" ],
    "service_protocol" : "http tls",
    "service_data" : {
      "key" : "service_data"
    },
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "service_ports_protocols" : [ "ssh", "ssh" ],
    "addresses_extra" : [ "192.168.100.1", "192.168.100.1" ],
    "service_updated_at" : 1576300370,
    "domains" : [ "CORPNET", "CORPNET" ],
    "newest_mac_vendor" : "Intel Corporate",
    "lowest_ttl" : 0,
    "newest_mac" : "11:22:33:44:55:66",
    "tags" : {
      "key" : "tags"
    },
    "site_name" : "Primary",
    "service_count_icmp" : 1,
    "service_link" : "http://192.168.0.1:80/",
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "macs" : [ "11:22:33:44:55:66", "11:22:33:44:55:66" ],
    "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "service_asset_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "service_port" : "80",
    "newest_mac_age" : 13040352000000000000,
    "first_seen" : 1576300370,
    "alive" : true,
    "credentials" : {
      "key" : {
        "key" : true
      }
    },
    "created_at" : 1576300370,
    "service_count_udp" : 1,
    "service_summary" : "Login Page",
    "mac_vendors" : [ "Dell", "Dell" ],
    "service_address" : "192.168.0.1",
    "service_ports_udp" : [ "53", "53" ],
    "service_created_at" : 1576300370,
    "updated_at" : 1576300370,
    "detected_by" : "icmp",
    "service_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "org_name" : "Test Labs",
    "comments" : "File Server",
    "os" : "Ubuntu Linux",
  }
]
```

```

"last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"service_transport" : "tcp",
"os_version" : "18.04",
"service_count" : 10,
"service_count_tcp" : 7,
"service_count_arp" : 1,
"services" : {
    "key" : {
        "key" : "services"
    }
},
"service_ports_tcp" : [ "22", "22" ],
"names" : [ "www", "www" ],
"rtts" : {
    "key" : ""
},
"attributes" : {
    "key" : "attributes"
},
"service_vhost" : "www"
}, {
    "addresses" : [ "192.168.0.1", "192.168.0.1" ],
    "last_seen" : 1576300370,
    "agent_name" : "LAPTOP-F4P1R6",
    "service_screenshot_link" : "service_screenshot_link",
    "type" : "Server",
    "last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "hw" : "Dell PowerEdge 2500",
    "lowest_rtt" : 1,
    "service_ports_products" : [ "bind", "bind" ],
    "service_protocol" : "http tls",
    "service_data" : {
        "key" : "service_data"
    },
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "service_ports_protocols" : [ "ssh", "ssh" ],
    "addresses_extra" : [ "192.168.100.1", "192.168.100.1" ],
    "service_updated_at" : 1576300370,
    "domains" : [ "CORPNET", "CORPNET" ],
    "newest_mac_vendor" : "Intel Corporate",
    "lowest_ttl" : 0,
    "newest_mac" : "11:22:33:44:55:66",
    "tags" : {
        "key" : "tags"
    },
    "site_name" : "Primary",
    "service_count_icmp" : 1,
    "service_link" : "http://192.168.0.1:80/",
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "macs" : [ "11:22:33:44:55:66", "11:22:33:44:55:66" ],
    "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "service_asset_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "service_port" : "80",
    "newest_mac_age" : 13040352000000000000,
    "first_seen" : 1576300370,
    "alive" : true,
    "credentials" : {
        "key" : {
            "key" : true
        }
    },
    "created_at" : 1576300370,
    "service_count_udp" : 1,
    "service_summary" : "Login Page",
    "mac_vendors" : [ "Dell", "Dell" ],
    "service_address" : "192.168.0.1",
    "service_ports_udp" : [ "53", "53" ],
    "service_created_at" : 1576300370,
    "updated_at" : 1576300370,
    "detected_by" : "icmp",
    "service_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "org_name" : "Test Labs",
    "comments" : "File Server",
    "os" : "Ubuntu Linux",
    "last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "service_transport" : "tcp",
}

```

```

"os_version" : "18.04",
"service_count" : 10,
"service_count_tcp" : 7,
"service_count_arp" : 1,
"services" : [
    "key" : {
        "key" : "services"
    }
],
"service_ports_tcp" : [ "22", "22" ],
"names" : [ "www", "www" ],
"rtts" : {
    "key" : ""
},
"attributes" : {
    "key" : "attributes"
},
"service_vhost" : "www"
} ]

```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

filtered service results

401

Access token is missing or invalid [Problem](#)**GET /export/org/services.jsonl**[Up](#)Service inventory as JSON line-delimited ([exportServicesJSONL](#))**Query parameters****_oid (optional)**

Query Parameter — The current Organization default: null

search (optional)

Query Parameter — an optional search string for filtering results default: null

fields (optional)

Query Parameter — an optional list of fields to export, comma-separated default: null

Return type

File

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**filtered service results [File](#)**401**Access token is missing or invalid [Problem](#)**GET /org/services/products.csv**[Up](#)Top service products as CSV ([exportServicesTopProductsCSV](#))**Query parameters**[_oid \(optional\)](#)*Query Parameter* — The current Organization default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses**200**top service products and counts as csv [File](#)**401**Access token is missing or invalid [Problem](#)**GET /org/services/protocols.csv**[Up](#)Top service protocols as CSV ([exportServicesTopProtocolsCSV](#))**Query parameters**[_oid \(optional\)](#)*Query Parameter* — The current Organization default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses**200**top service protocols and counts as csv [File](#)

401Access token is missing or invalid [Problem](#)**GET /org/services/tcp.csv**[Up](#)Top TCP services as CSV ([exportServicesTopTCPCSV](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses**200**top TCP services and counts as csv [File](#)**401**Access token is missing or invalid [Problem](#)**GET /org/services/udp.csv**[Up](#)Top UDP services as CSV ([exportServicesTopUDPCSV](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses**200**top UDP services and counts as csv [File](#)**401**Access token is missing or invalid [Problem](#)

GET /export/org/sites.csv[Up](#)Site list as CSV ([exportSitesCSV](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses

200

all sites [File](#)

401

Access token is missing or invalid [Problem](#)**GET /export/org/sites.json**[Up](#)Export all sites ([exportSitesJSON](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**fields (optional)***Query Parameter* — an optional list of fields to export, comma-separated default: null**Return type**array[[Site](#)]**Example data**

Content-Type: application/json

```
[
  {
    "data" : {
      "excludes" : "192.168.0.5",
      "updated_at" : 1576300370,
      "scope" : "192.168.0.0/24",
      "name" : "Primary",
      "created_at" : 1576300370,
      "description" : "Headquarters",
      "subnets" : [
        {
          "key" : ""
        }
      ],
      "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8"
    }
  },
  {
    "data" : {
      "excludes" : "192.168.0.5",
      "updated_at" : 1576300370,
    }
  }
]
```

```

    "scope" : "192.168.0.0/24",
    "name" : "Primary",
    "created_at" : 1576300370,
    "description" : "Headquarters",
    "subnets" : [
        {
            "key" : ""
        },
        {
            "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8"
        }
    ]
}

```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

all sites

401

Access token is missing or invalid [Problem](#)**GET /export/org/sites.jsonl**[Up](#)Site list as JSON line-delimited ([exportSitesJSONL](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**fields (optional)***Query Parameter* — an optional list of fields to export, comma-separated default: null**Return type**

File

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

all sites [File](#)

401

Access token is missing or invalid [Problem](#)**GET /export/org/software.csv**[Up](#)

Software inventory as CSV ([exportSoftwareCSV](#))

Query parameters

_oid (optional)

Query Parameter — The current Organization default: null

search (optional)

Query Parameter — an optional search string for filtering results default: null

Return type

File

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses

200

filtered software results [File](#)

401

Access token is missing or invalid [Problem](#)

GET /export/org/software.json

[Up](#)

Exports the software inventory ([exportSoftwareJSON](#))

Query parameters

_oid (optional)

Query Parameter — The current Organization default: null

search (optional)

Query Parameter — an optional search string for filtering results default: null

fields (optional)

Query Parameter — an optional list of fields to export, comma-separated default: null

Return type

array[[Software](#)]

Example data

Content-Type: application/json

```
[ {  
    "software_updated_at" : 1576300370,  
    "software_service_port" : 80,  
    "software_sw_edition" : "software_sw_edition",  
    "software_created_at" : 1576300370,  
    "software_service_address" : "192.168.0.1",  
    "software_target_sw" : "software_target_sw",  
    "software_language" : "software_language",  
    "software_cpe23" : "cpe:/a:openbsd:openssh:8.2",  
    "software_asset_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "software_organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "software_installed_from" : "software_installed_from",  
    "software_other" : "software_other",  
    "software_installed_size" : 0,  
    "software_vendor" : "OpenBSD",  
    "software_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "software_target_hw" : "software_target_hw",  
    "software_version" : "8.3p1",  
}
```

```

"software_product" : "OpenSSH",
"software_app_id" : "software_app_id",
"software_update" : "software_update",
"software_part" : "a",
"software_source_id" : 1,
"software_service_transport" : "tcp",
"software_edition" : "software_edition",
"software_attributes" : {
    "key" : "software_attributes"
},
"software_installed_at" : 1576300370
}, {
    "software_updated_at" : 1576300370,
    "software_service_port" : 80,
    "software_sw_edition" : "software_sw_edition",
    "software_created_at" : 1576300370,
    "software_service_address" : "192.168.0.1",
    "software_target_sw" : "software_target_sw",
    "software_language" : "software_language",
    "software_cpe23" : "cpe:/a:openbsd:openssh:8.2",
    "software_asset_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "software_organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "software_installed_from" : "software_installed_from",
    "software_other" : "software_other",
    "software_installed_size" : 0,
    "software_vendor" : "OpenBSD",
    "software_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "software_target_hw" : "software_target_hw",
    "software_version" : "8.3p1",
    "software_product" : "OpenSSH",
    "software_app_id" : "software_app_id",
    "software_update" : "software_update",
    "software_part" : "a",
    "software_source_id" : 1,
    "software_service_transport" : "tcp",
    "software_edition" : "software_edition",
    "software_attributes" : {
        "key" : "software_attributes"
    },
    "software_installed_at" : 1576300370
}
]

```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**

filtered software results

401Access token is missing or invalid [Problem](#)**GET /export/org/software.jsonl****Up**Software inventory as JSON line-delimited ([exportSoftwareJSONL](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null

fields (optional)

Query Parameter — an optional list of fields to export, comma-separated default: null

Return type

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

filtered software results [File](#)

401

Access token is missing or invalid [Problem](#)

GET /export/org/subnet.stats.csv[Up](#)

Subnet utilization statistics as CSV ([exportSubnetUtilizationStatsCSV](#))

Query parameters**_oid (optional)**

Query Parameter — The current Organization default: null

mask (optional)

Query Parameter — an optional subnet mask size (ex:24) default: null

Return type

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses

200

subnet utilization stats as csv [File](#)

401

Access token is missing or invalid [Problem](#)

GET /export/org/tasks.json[Up](#)

Exports organization tasks ([exportTasksJSON](#))

Query parameters**_oid (optional)**

runZero API documentation

Query Parameter — The current Organization default: null

search (optional)

Query Parameter — an optional search string for filtering results default: null

fields (optional)

Query Parameter — an optional list of fields to export, comma-separated default: null

Return type

array[[TaskBase](#)]

Example data

Content-Type: application/json

```
[ {  
    "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "hidden" : false,  
    "description" : "Scan the headquarters hourly",  
    "created_at" : 1576300370,  
    "type" : "scan",  
    "error" : "agent unavailable",  
    "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "updated_at" : 1576300370,  
    "stats" : {  
        "key" : ""  
    },  
    "recur" : false,  
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "recur_last" : 1576300370,  
    "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "params" : {  
        "key" : "params"  
    },  
    "created_by" : "user@example.com",  
    "created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "start_time" : 1576300370,  
    "recur_frequency" : "hourly",  
    "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "name" : "Hourly Scan",  
    "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "source_id" : 1,  
    "recur_next" : 1576300370,  
    "status" : "processed"  
}, {  
    "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "hidden" : false,  
    "description" : "Scan the headquarters hourly",  
    "created_at" : 1576300370,  
    "type" : "scan",  
    "error" : "agent unavailable",  
    "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "updated_at" : 1576300370,  
    "stats" : {  
        "key" : ""  
    },  
    "recur" : false,  
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "recur_last" : 1576300370,  
    "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "params" : {  
        "key" : "params"  
    },  
    "created_by" : "user@example.com",  
    "created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "start_time" : 1576300370,  
    "recur_frequency" : "hourly",  
    "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
}
```

```

"organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"name" : "Hourly Scan",
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"source_id" : 1,
"recur_next" : 1576300370,
"status" : "processed"
} ]

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

filtered task results

401

Access token is missing or invalid [Problem](#)**GET /export/org/tasks.jsonl**[Up](#)Organization tasks as JSON line-delimited ([exportTasksJSONL](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**fields (optional)***Query Parameter* — an optional list of fields to export, comma-separated default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

filtered task results [File](#)

401

Access token is missing or invalid [Problem](#)**GET /export/org/vulnerabilities.csv**[Up](#)Vulnerability inventory as CSV ([exportVulnerabilitiesCSV](#))

Query parameters**_oid (optional)***Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses**200**filtered vulnerability results [File](#)**401**Access token is missing or invalid [Problem](#)**GET /export/org/vulnerabilities.json**[Up](#)Exports the vulnerability inventory ([exportVulnerabilitiesJSON](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**fields (optional)***Query Parameter* — an optional list of fields to export, comma-separated default: null**Return type**array[[Vulnerability](#)]**Example data**

Content-Type: application/json

```
[
  {
    "addresses" : [ "192.168.0.1", "192.168.0.1" ],
    "last_seen" : 1576300370,
    "agent_name" : "LAPTOP-F4P1R6",
    "vulnerability_published_at" : 1576300370,
    "type" : "Server",
    "last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "hw" : "Dell PowerEdge 2500",
    "lowest_rtt" : 1,
    "vulnerability_severity_score" : 10,
    "vulnerability_name" : "Cisco IOS Software DHCP Remote Code Execution Vulnerability",
    "service_ports_products" : [ "bind", "bind" ],
    "vulnerability_severity" : "Critical",
    "vulnerability_first_detected_at" : 1576300370,
    "vulnerability_cvss2_temporal_score" : 8.7,
    "vulnerability_service_address" : "192.168.0.1",
    "vulnerability_solution" : "Upgrade to the relevant fixed version referenced in Cisco bug ID(s) CSCsm45390",
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "service_ports_protocols" : [ "ssh", "ssh" ],
    "addresses_extra" : [ "192.168.100.1", "192.168.100.1" ],
  }
]
```

```

"vulnerability_cve" : "CVE-2017-12240",
"vulnerability_risk_score" : 7.4,
"vulnerability_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"domains" : [ "www", "www" ],
"newest_mac_vendor" : "Intel Corporate",
"lowest_ttl" : 0,
"newest_mac" : "11:22:33:44:55:66",
"vulnerability_last_detected_at" : 1576300370,
"tags" : {
  "key" : "tags"
},
"site_name" : "Primary",
"service_count_icmp" : 1,
"vulnerability_asset_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"vulnerability_attributes" : {
  "key" : "vulnerability_attributes"
},
"organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"macs" : [ "11:22:33:44:55:66", "11:22:33:44:55:66" ],
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"vulnerability_category" : "Remote",
"newest_mac_age" : 13040352000000000000,
"vulnerability_service_transport" : "tcp",
"first_seen" : 1576300370,
"alive" : true,
"credentials" : {
  "key" : {
    "key" : true
  }
},
"created_at" : 1576300370,
"service_count_udp" : 1,
"vulnerability_description" : "The remote device is missing a vendor-supplied security patch.",
"mac_vendors" : [ "Dell", "Dell" ],
"vulnerability_organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"vulnerability_risk" : "High",
"service_ports_udp" : [ "53", "53" ],
"vulnerability_created_at" : 1576300370,
"updated_at" : 1576300370,
"detected_by" : "icmp",
"vulnerability_cpe23" : "cpe:/o:cisco:ios",
"vulnerability_updated_at" : 1576300370,
"org_name" : "Test Labs",
"vulnerability_cvss2_base_score" : 10,
"comments" : "File Server",
"vulnerability_service_port" : 80,
"os" : "Ubuntu Linux",
"last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"vulnerability_source_id" : 1,
"os_version" : "18.04",
"service_count" : 10,
"vulnerability_cvss3_temporal_score" : 9.4,
"service_count_tcp" : 7,
"service_count_arp" : 1,
"services" : {
  "key" : {
    "key" : "services"
  }
},
"service_ports_tcp" : [ "22", "22" ],
"vulnerability_vuln_id" : "103565",
"names" : [ "www", "www" ],
"rtts" : {
  "key" : ""
},
"attributes" : {
  "key" : "attributes"
},
"vulnerability_cvss3_base_score" : 9.8
}, {
"addresses" : [ "192.168.0.1", "192.168.0.1" ],
"last_seen" : 1576300370,
"agent_name" : "LAPTOP-F4P1R6",
"vulnerability_published_at" : 1576300370,
"type" : "Server",
"last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",

```

```

"hw" : "Dell PowerEdge 2500",
"lowest_rtt" : 1,
"vulnerability_severity_score" : 10,
"vulnerability_name" : "Cisco IOS Software DHCP Remote Code Execution Vulnerability",
"service_ports_products" : [ "bind", "bind" ],
"vulnerability_severity" : "Critical",
"vulnerability_first_detected_at" : 1576300370,
"vulnerability_cvss2_temporal_score" : 8.7,
"vulnerability_service_address" : "192.168.0.1",
"vulnerability_solution" : "Upgrade to the relevant fixed version referenced in Cisco bug ID(s) CSCsm45390
"id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"service_ports_protocols" : [ "ssh", "ssh" ],
"addresses_extra" : [ "192.168.100.1", "192.168.100.1" ],
"vulnerability_cve" : "CVE-2017-12240",
"vulnerability_risk_score" : 7.4,
"vulnerability_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"domains" : [ "www", "www" ],
"newest_mac_vendor" : "Intel Corporate",
"lowest_ttl" : 0,
"newest_mac" : "11:22:33:44:55:66",
"vulnerability_last_detected_at" : 1576300370,
"tags" : {
    "key" : "tags"
},
"site_name" : "Primary",
"service_count_icmp" : 1,
"vulnerability_asset_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"vulnerability_attributes" : {
    "key" : "vulnerability_attributes"
},
"organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"macs" : [ "11:22:33:44:55:66", "11:22:33:44:55:66" ],
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"vulnerability_category" : "Remote",
"newest_mac_age" : 13040352000000000000,
"vulnerability_service_transport" : "tcp",
"first_seen" : 1576300370,
"alive" : true,
"credentials" : {
    "key" : {
        "key" : true
    }
},
"created_at" : 1576300370,
"service_count_udp" : 1,
"vulnerability_description" : "The remote device is missing a vendor-supplied security patch.",
"mac_vendors" : [ "Dell", "Dell" ],
"vulnerability_organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"vulnerability_risk" : "High",
"service_ports_udp" : [ "53", "53" ],
"vulnerability_created_at" : 1576300370,
"updated_at" : 1576300370,
"detected_by" : "icmp",
"vulnerability_cpe23" : "cpe:/o:cisco:ios",
"vulnerability_updated_at" : 1576300370,
"org_name" : "Test Labs",
"vulnerability_cvss2_base_score" : 10,
"comments" : "File Server",
"vulnerability_service_port" : 80,
"os" : "Ubuntu Linux",
"last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"vulnerability_source_id" : 1,
"os_version" : "18.04",
"service_count" : 10,
"vulnerability_cvss3_temporal_score" : 9.4,
"service_count_tcp" : 7,
"service_count_arp" : 1,
"services" : {
    "key" : {
        "key" : "services"
    }
},
"service_ports_tcp" : [ "22", "22" ],
"vulnerability_vuln_id" : "103565",
"names" : [ "www", "www" ],
"rtts" : {
}

```

```

    "key" : "",
},
"attributes" : {
    "key" : "attributes"
},
"vulnerability_cvss3_base_score" : 9.8
} ]

```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**

filtered vulnerability results

401Access token is missing or invalid [Problem](#)**GET /export/org/vulnerabilities.jsonl**[Up](#)Vulnerability inventory as JSON line-delimited ([exportVulnerabilitiesJSONL](#))**Query parameters****_oid (optional)**

Query Parameter — The current Organization default: null

search (optional)

Query Parameter — an optional search string for filtering results default: null

fields (optional)

Query Parameter — an optional list of fields to export, comma-separated default: null

Return type

File

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**filtered vulnerability results [File](#)**401**Access token is missing or invalid [Problem](#)**GET /export/org/wireless.csv**[Up](#)Wireless inventory as CSV ([exportWirelessCSV](#))

Query parameters**_oid (optional)***Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses**200**filtered wireless results [File](#)**401**Access token is missing or invalid [Problem](#)**GET /export/org/wireless.json**[Up](#)Wireless inventory as JSON ([exportWirelessJSON](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**fields (optional)***Query Parameter* — an optional list of fields to export, comma-separated default: null**Return type**array[[Wireless](#)]**Example data**

Content-Type: application/json

```
[
  {
    "last_seen" : 1576300370,
    "last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "data" : {
      "key" : "data"
    },
    "agent_name" : "LAPTOP-F4P1R6",
    "essid" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "bssid" : "11:22:33:44:55:66",
    "created_at" : 1576300370,
    "type" : "infrastructure",
    "interface" : "wlan0",
    "last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "site_name" : "Primary",
    "encryption" : "aes",
    "channels" : "11, 158+1",
    "vendor" : "Ubiquiti Networks",
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  }
]
```

```

"family" : "223344",
"org_name" : "Test Labs",
"signal" : 99,
"authentication" : "wpa2-psk"
}, {
"last_seen" : 1576300370,
"last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"data" : {
  "key" : "data"
},
"agent_name" : "LAPTOP-F4P1R6",
"essid" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
"bssid" : "11:22:33:44:55:66",
"created_at" : 1576300370,
"type" : "infrastructure",
"interface" : "wlan0",
"last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"site_name" : "Primary",
"encryption" : "aes",
"channels" : "11, 158+1",
"vendor" : "Ubiquiti Networks",
"organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"family" : "223344",
"org_name" : "Test Labs",
"signal" : 99,
"authentication" : "wpa2-psk"
} ]

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

filtered wireless results

401

Access token is missing or invalid [Problem](#)**GET /export/org/wireless.jsonl**[Up](#)Wireless inventory as JSON line-delimited ([exportWirelessJSONL](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**fields (optional)***Query Parameter* — an optional list of fields to export, comma-separated default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
```

```

    "title" : "A short summary of the problem type.",
    "status" : 140
}

```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

filtered wireless results [File](#)

401

Access token is missing or invalid [Problem](#)

Import

POST /import/org/{orgId}/assets

[Up](#)

Import assets described by a registered custom integration ([importCustomIntegrationAssets](#))

Assets can be discovered, imported, and merged by runZero scan tasks, first-party integrations, and third-party defined custom integrations. See [/account/custom-integrations](#). Currently only assets for custom integrations are importable here.

Path parameters**orgId (required)**

Path Parameter — The unique ID of the organization that the assets will be imported into. default: null
format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- multipart/form-data

Form parameters**sitId (required)**

Form Parameter — The ID of the site assets are to be imported into. default: null format: uuid

customIntegrationId (required)

Form Parameter — The unique ID of the registered custom integration which produced the asset data.
Uniqueness is not checked/enforced. See [/account/custom-integrations](#) api. default: null format: uuid

importTask (required)

Form Parameter — default: null

assetData (required)

Form Parameter — A gzip (not .tar.gz) compressed file containing ImportAsset objects. The file data may be a JSON array of ImportAsset objects, e.g. [{}], or JSONL format, with a single JSON representation of an ImportAsset object on each new line, e.g. {}
default: null format: binary

Return type

[TaskBase](#)

Example data

Content-Type: application/json

```
{
  "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hidden" : false,
  "description" : "Scan the headquarters hourly",
  "created_at" : 1576300370,
  "type" : "scan",
  "error" : "agent unavailable",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "updated_at" : 1576300370,
  "stats" : {
    "key" : ""
  },
  "recur" : false,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
}
```

```
"recur_last" : 1576300370,
"custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"params" : {
    "key" : "params"
},
"created_by" : "user@example.com",
"created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"start_time" : 1576300370,
"recur_frequency" : "hourly",
"parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"name" : "Hourly Scan",
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"source_id" : 1,
"recur_next" : 1576300370,
"status" : "processed"
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**

import task created. The task ID should be checked for its status. [Task](#)

400

Invalid request body [Problem](#)

401

Access token is missing or invalid [Problem](#)

403

Action not allowed for this license type [Problem](#)

404

Resource not found [Problem](#)

422

Invalid request body [Problem](#)

500

Unexpected error occurred on the server [Problem](#)

Org

GET /org/custom-integrations/{customIntegrationId}

[Up](#)

Get single custom integration ([getOrgCustomIntegration](#))

Path parameters**customIntegrationId (required)**

Path Parameter — UUID of the custom integration default: null format: uuid

Return type[CustomIntegration](#)**Example data**

Content-Type: application/json

```
{
  "createdAt" : "2023-03-06T18:14:50.52Z",
  "destroyedAt" : "2023-03-06T18:14:50.52Z",
  "clientId" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "my-custom-integration",
  "icon" : "aVZCT1J3MEtHZ29BQUFBTlNVaEVVZ0FBQUNBQUFBQWdDQVlBQUFCemVucjBBQUFBQkdkQlRVRUFBTEdQQy94aEJRQUFBQ0Jq",
  "description" : "My custom integration description.",
  "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
  "createdById" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
  "updatedAt" : "2023-03-06T18:14:50.52Z"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**The custom integration with given ID [CustomIntegration](#)**401**Access token is missing or invalid [Problem](#)**403**Action not allowed for this license type [Problem](#)**404**Resource not found [Problem](#)**500**Unexpected error occurred on the server [Problem](#)**GET /org/custom-integrations**[Up](#)Get all custom integrations ([getOrgCustomIntegrations](#))**Return type**[CustomIntegration](#)**Example data**

Content-Type: application/json

```
{
  "createdAt" : "2023-03-06T18:14:50.52Z",
  "destroyedAt" : "2023-03-06T18:14:50.52Z",
  "clientId" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "my-custom-integration",
  "icon" : "aVZCT1J3METHZ29BQUFBTlNVaEVVZ0FBQUNBQUFBQWdDQVlBQUFCEmVucjBBQUFBQdkQlRVRUFBTEdQQy94aEJRQUFBQ0Jq",
  "description" : "My custom integration description.",
  "id" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
  "createdById" : "f6cfb91a-52ea-4a86-bf9a-5a891a26f52b",
  "updatedAt" : "2023-03-06T18:14:50.52Z"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

An array of all custom integrations [CustomIntegration](#)

401

Access token is missing or invalid [Problem](#)

403

Action not allowed for this license type [Problem](#)

404

Resource not found [Problem](#)

500

Unexpected error occurred on the server [Problem](#)

Organization

POST /org/custom-integrations/{custom_integration_id}/bulk/remove [Up](#)

Remove custom integration from a list of assets ([bulkRemoveCustomIntegration](#))

Path parameters**custom_integration_id (required)**

Path Parameter — UUID of the custom integration default: null format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body**AssetIDs AssetIDs (required)**

Body Parameter —

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
```

```
{
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**204**

empty response

400**401**Access token is missing or invalid [Problem](#)**403**Action not allowed for this license type [Problem](#)**404**Resource not found [Problem](#)**500**Unexpected error occurred on the server [Problem](#)**POST /org/assets/bulk/clearOwners****Up**

Clear all owners across multiple assets based on a search query ([clearBulkAssetOwners](#))

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request bodySearch [Search](#) (required)

Body Parameter —

Query parameters_oid (optional)

Query Parameter — The current Organization default: null

Return type[updateBulkAssetOwners_200_response](#)**Example data**

Content-Type: application/json

```
{
  "updated_asset_count" : 10
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

updated asset count [updateBulkAssetOwners_200_response](#)

400

Invalid request body [Problem](#)

403

Unexpected error occurred on the server [Problem](#)**POST /org/assets/bulk/clearTags**[Up](#)Clear all tags across multiple assets based on a search query ([clearBulkAssetTags](#))**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

Search [Search](#) (required)
Body Parameter —

Query parameters

[_oid](#) (optional)
Query Parameter — The current Organization default: null

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**

Summary of operation results

401Access token is missing or invalid [Problem](#)**404**Resource not found [Problem](#)**PUT /org/sites/{site_id}/sample**[Up](#)Create a traffic sampling task for a given site ([createSample](#))**Path parameters****site_id (required)***Path Parameter* — UUID or name of the site to scan default: null format: uuid**Consumes**

This API call consumes the following media types via the Content-Type request header:

- text/json

Request body**SampleOptions SampleOptions (optional)***Body Parameter* —**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**Return type**[TaskBase](#)**Example data**

Content-Type: application/json

```
{
  "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hidden" : false,
  "description" : "Scan the headquarters hourly",
  "created_at" : 1576300370,
  "type" : "scan",
  "error" : "agent unavailable",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "updated_at" : 1576300370,
  "stats" : {
    "key" : ""
  },
  "recur" : false,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last" : 1576300370,
  "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "params" : {
    "key" : "params"
  },
  "created_by" : "user@example.com",
  "created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "start_time" : 1576300370,
  "recur_frequency" : "hourly",
  "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "Hourly Scan",
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "source_id" : 1,
  "recur_next" : 1576300370,
}
```

```

        "status" : "processed"
    }
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**a created scan task [Task](#)**401**Access token is missing or invalid [Problem](#)**403**License has expired [Problem](#)**404**Resource not found [Problem](#)**500**Request could not be processed [Problem](#)

PUT /org/sites/{site_id}/scan

[Up](#)

Create a scan task for a given site ([createScan](#))

Path parameters**site_id (required)**

Path Parameter — UUID or name of the site to scan default: null format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- text/json

Request body

runZero API documentation

ScanOptions [ScanOptions](#) (optional)

Body Parameter —

Query parameters

[_oid](#) (optional)

Query Parameter — The current Organization default: null

Return type

[TaskBase](#)

Example data

Content-Type: application/json

```
{  
    "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "hidden" : false,  
    "description" : "Scan the headquarters hourly",  
    "created_at" : 1576300370,  
    "type" : "scan",  
    "error" : "agent unavailable",  
    "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "updated_at" : 1576300370,  
    "stats" : {  
        "key" : ""  
    },  
    "recur" : false,  
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "recur_last" : 1576300370,  
    "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "params" : {  
        "key" : "params"  
    },  
    "created_by" : "user@example.com",  
    "created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "start_time" : 1576300370,  
    "recur_frequency" : "hourly",  
    "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "name" : "Hourly Scan",  
    "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "source_id" : 1,  
    "recur_next" : 1576300370,  
    "status" : "processed"  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
```

```
{
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

a created scan task [Task](#)

401

Access token is missing or invalid [Problem](#)

403

License has expired [Problem](#)

404

Resource not found [Problem](#)

500

Request could not be processed [Problem](#)**PUT /org/sites**[Up](#)Create a new site ([createSite](#))**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body**SiteOptions** [SiteOptions](#) (required)

Body Parameter —

Query parameters**_oid** (optional)

Query Parameter — The current Organization default: null

Return type[Site](#)**Example data**

Content-Type: application/json

```
{
  "data" : {
    "excludes" : "192.168.0.5",
    "updated_at" : 1576300370,
    "scope" : "192.168.0.0/24",
    "name" : "Primary",
    "created_at" : 1576300370,
    "description" : "Headquarters",
    "subnets" : {
      "key" : ""
    },
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8"
  }
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

site details [Site](#)

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)**GET /org/agents/{agent_id}**[Up](#)Get details for a single agent. Legacy path for /org/explorers/{explorer_id} ([getAgent](#))**Path parameters**[agent_id \(required\)](#)

Path Parameter — UUID of the agent default: null format: uuid

Query parameters[_oid \(optional\)](#)

Query Parameter — The current Organization default: null

Return type[Agent](#)**Example data**

Content-Type: application/json

```
{
  "os" : "Windows",
  "system_info" : {
    "key" : ""
  },
  "deactivated_at" : 0,
  "created_at" : 1576300370,
  "last_checkin" : 1576300370,
  "version" : "1.2.3 (build 20191219224016) [fc50c5eefdc3ff5c60533c3c345d14d336396272]",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "host_id" : "6f9e6fe52271da70962e007183c5c9c9",
  "internal_ip" : "192.168.0.1",
  "connected" : true,
  "hub_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "inactive" : false,
  "updated_at" : 1576300370,
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "RUNZERO-AGENT",
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "arch" : "amd64",
  "external_ip" : "1.1.1.1"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

agent details [Agent](#)

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)**GET /org/agents**[Up](#)Get all agents. Legacy path for /org/explorers ([getAgents](#))**Query parameters**_oid (optional)

Query Parameter — The current Organization default: null

Return typearray[[Agent](#)]**Example data**

Content-Type: application/json

```
[
  {
    "os" : "Windows",
    "system_info" : {
      "key" : ""
    },
    "deactivated_at" : 0,
    "created_at" : 1576300370,
    "last_checkin" : 1576300370,
    "version" : "1.2.3 (build 20191219224016) [fc50c5eefdc3ff5c60533c3c345d14d336396272]",
    "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "host_id" : "6f9e6fe52271da70962e007183c5c9c9",
    "internal_ip" : "192.168.0.1",
    "connected" : true,
    "hub_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "inactive" : false,
    "updated_at" : 1576300370,
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "name" : "RUNZERO-AGENT",
    "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "arch" : "amd64",
    "external_ip" : "1.1.1.1"
  },
  {
    "os" : "Windows",
    "system_info" : {
```

```

        "key" : "",
    },
    "deactivated_at" : 0,
    "created_at" : 1576300370,
    "last_checkin" : 1576300370,
    "version" : "1.2.3 (build 20191219224016) [fc50c5eefdc3ff5c60533c3c345d14d336396272]",
    "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "host_id" : "6f9e6fe52271da70962e007183c5c9c9",
    "internal_ip" : "192.168.0.1",
    "connected" : true,
    "hub_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "inactive" : false,
    "updated_at" : 1576300370,
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "name" : "RUNZERO-AGENT",
    "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "arch" : "amd64",
    "external_ip" : "1.1.1.1"
}
]

```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

array of agents

401

Access token is missing or invalid [Problem](#)**GET /org/assets/{asset_id}**[Up](#)Get asset details ([getAsset](#))**Path parameters****asset_id (required)**

Path Parameter — UUID of the asset to retrieve default: null format: uuid

Query parameters**_oid (optional)**

Query Parameter — The current Organization default: null

Return type[Asset](#)**Example data**

Content-Type: application/json

```
{
    "addresses" : [ "192.168.0.1", "192.168.0.1" ],
    "first_seen" : 1576300370,
    "alive" : true,
    "last_seen" : 1576300370,
    "agent_name" : "LAPTOP-F4P1R6",
    "credentials" : {
        "key" : {
            "key" : true
        }
    },
}
```

```

"created_at" : 1576300370,
"service_count_udp" : 1,
"mac_vendors" : [ "Dell", "Dell" ],
"type" : "Server",
"last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"service_ports_udp" : [ "53", "53" ],
"hw" : "Dell PowerEdge 2500",
"lowest_rtt" : 1,
"service_ports_products" : [ "bind", "bind" ],
"updated_at" : 1576300370,
"detected_by" : "icmp",
"id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"service_ports_protocols" : [ "ssh", "ssh" ],
"org_name" : "Test Labs",
"addresses_extra" : [ "192.168.100.1", "192.168.100.1" ],
"comments" : "File Server",
"os" : "Ubuntu Linux",
"last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"os_version" : "18.04",
"service_count" : 10,
"domains" : [ "www", "www" ],
"service_count_tcp" : 7,
"newest_mac_vendor" : "Intel Corporate",
"lowest_ttl" : 0,
"newest_mac" : "11:22:33:44:55:66",
"service_count_arp" : 1,
"services" : {
    "key" : {
        "key" : "services"
    }
},
"service_ports_tcp" : [ "22", "22" ],
"tags" : {
    "key" : "tags"
},
"site_name" : "Primary",
"names" : [ "www", "www" ],
"service_count_icmp" : 1,
"rtts" : {
    "key" : ""
},
"organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"macs" : [ "11:22:33:44:55:66", "11:22:33:44:55:66" ],
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"attributes" : {
    "key" : "attributes"
},
"newest_mac_age" : 13040352000000000000
}

```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200
asset details [Asset](#)
401
Access token is missing or invalid [Problem](#)
404
Resource not found [Problem](#)

GET /org/assets

[Up](#)

Get all assets ([getAssets](#))

Query parameters

`_oid` (optional)

Query Parameter — The current Organization default: null

`search` (optional)

Query Parameter — an optional search string for filtering results default: null

`fields` (optional)

Query Parameter — an optional list of fields to export, comma-separated default: null

Return type

array[[Asset](#)]

Example data

Content-Type: application/json

```
[ {
  "addresses" : [ "192.168.0.1", "192.168.0.1" ],
  "first_seen" : 1576300370,
  "alive" : true,
  "last_seen" : 1576300370,
  "agent_name" : "LAPTOP-F4P1R6",
  "credentials" : {
    "key" : {
      "key" : true
    }
  },
  "created_at" : 1576300370,
  "service_count_udp" : 1,
  "mac_vendors" : [ "Dell", "Dell" ],
  "type" : "Server",
  "last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "service_ports_udp" : [ "53", "53" ],
  "hw" : "Dell PowerEdge 2500",
  "lowest_rtt" : 1,
  "service_ports_products" : [ "bind", "bind" ],
  "updated_at" : 1576300370,
  "detected_by" : "icmp",
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "service_ports_protocols" : [ "ssh", "ssh" ],
  "org_name" : "Test Labs",
  "addresses_extra" : [ "192.168.100.1", "192.168.100.1" ],
  "comments" : "File Server",
  "os" : "Ubuntu Linux",
  "last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "os_version" : "18.04",
  "service_count" : 10,
  "domains" : [ "www", "www" ],
  "service_count_tcp" : 7,
  "newest_mac_vendor" : "Intel Corporate",
  "lowest_ttl" : 0,
  "newest_mac" : "11:22:33:44:55:66",
  "service_count_arp" : 1,
  "services" : {
    "key" : {
      "key" : "services"
    }
  },
  "service_ports_tcp" : [ "22", "22" ],
  "tags" : {
    "key" : "tags"
  },
}
```

```

"site_name" : "Primary",
"names" : [ "www", "www" ],
"service_count_icmp" : 1,
"rtts" : {
  "key" : ""
},
"organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"macs" : [ "11:22:33:44:55:66", "11:22:33:44:55:66" ],
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"attributes" : {
  "key" : "attributes"
},
"newest_mac_age" : 13040352000000000000
}, {
  "addresses" : [ "192.168.0.1", "192.168.0.1" ],
  "first_seen" : 1576300370,
  "alive" : true,
  "last_seen" : 1576300370,
  "agent_name" : "LAPTOP-F4P1R6",
  "credentials" : {
    "key" : {
      "key" : true
    }
  },
  "created_at" : 1576300370,
  "service_count_udp" : 1,
  "mac_vendors" : [ "Dell", "Dell" ],
  "type" : "Server",
  "last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "service_ports_udp" : [ "53", "53" ],
  "hw" : "Dell PowerEdge 2500",
  "lowest_rtt" : 1,
  "service_ports_products" : [ "bind", "bind" ],
  "updated_at" : 1576300370,
  "detected_by" : "icmp",
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "service_ports_protocols" : [ "ssh", "ssh" ],
  "org_name" : "Test Labs",
  "addresses_extra" : [ "192.168.100.1", "192.168.100.1" ],
  "comments" : "File Server",
  "os" : "Ubuntu Linux",
  "last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "os_version" : "18.04",
  "service_count" : 10,
  "domains" : [ "www", "www" ],
  "service_count_tcp" : 7,
  "newest_mac_vendor" : "Intel Corporate",
  "lowest_ttl" : 0,
  "newest_mac" : "11:22:33:44:55:66",
  "service_count_arp" : 1,
  "services" : {
    "key" : {
      "key" : "services"
    }
  },
  "service_ports_tcp" : [ "22", "22" ],
  "tags" : {
    "key" : "tags"
  },
  "site_name" : "Primary",
  "names" : [ "www", "www" ],
  "service_count_icmp" : 1,
  "rtts" : {
    "key" : ""
  },
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "macs" : [ "11:22:33:44:55:66", "11:22:33:44:55:66" ],
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "attributes" : {
    "key" : "attributes"
  },
  "newest_mac_age" : 13040352000000000000
} ]

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

array of assets

401

Access token is missing or invalid [Problem](#)

GET /org/explorers/{explorer_id}

[Up](#)

Get details for a single explorer. ([getExplorer](#))

Get details for a single explorer. This is the same call as legacy path /org/agents/{agent_id}

Path parameters**explorer_id (required)**

Path Parameter — UUID of the explorer default: null format: uuid

Query parameters**_oid (optional)**

Query Parameter — The current Organization default: null

Return type

[Agent](#)

Example data

Content-Type: application/json

```
{
  "os" : "Windows",
  "system_info" : {
    "key" : ""
  },
  "deactivated_at" : 0,
  "created_at" : 1576300370,
  "last_checkin" : 1576300370,
  "version" : "1.2.3 (build 20191219224016) [fc50c5eefdc3ff5c60533c3c345d14d336396272]",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "host_id" : "6f9e6fe52271da70962e007183c5c9c9",
  "internal_ip" : "192.168.0.1",
  "connected" : true,
  "hub_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "inactive" : false,
  "updated_at" : 1576300370,
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "RUNZERO-AGENT",
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "arch" : "amd64",
  "external_ip" : "1.1.1.1"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

explorer details [Agent](#)

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)

GET /org/explorers

[Up](#)

Get all explorers ([getExplorers](#))

Get all explorers. This is the same call as legacy path /org/agents

Query parameters

_oid (optional)

Query Parameter — The current Organization default: null

Return type

array[[Agent](#)]

Example data

Content-Type: application/json

```
[ null, null ]
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

array of agents

401

Access token is missing or invalid [Problem](#)

GET /org/hosted-zones/{hosted_zone_id}

[Up](#)

Get details for a single hosted zone. ([getHostedZone](#))

Get details for a single Hosted Zone. Hosted Zones are only available to Enterprise licensed customers.

Path parameters

hosted_zone_id (required)

runZero API documentation

Path Parameter — UUID of the hosted zone default: null format: uuid

Query parameters

_oid (optional)

Query Parameter — The current Organization default: null

Return type

[HostedZone](#)

Example data

Content-Type: application/json

```
{  
    "tasks_active" : 0,  
    "updated_at" : "2023-03-06T18:14:50.52Z",  
    "explorers_total" : 0,  
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "name" : "zone1",  
    "tasks_waiting" : 0,  
    "processor_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "explorers_concurrency" : 0,  
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "enabled" : true  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

hosted zone details [HostedZone](#)

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)

GET /org/hosted-zones

[Up](#)

Get all hosted zones ([getHostedZones](#))

Get all hosted zones. Hosted Zones are only available to Enterprise licensed customers.

Query parameters

_oid (optional)

Query Parameter — The current Organization default: null

Return type

array[[HostedZone](#)]

Example data

Content-Type: application/json

```
[ {
  "tasks_active" : 0,
  "updated_at" : "2023-03-06T18:14:50.52Z",
  "explorers_total" : 0,
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "zone1",
  "tasks_waiting" : 0,
  "processor_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "explorers_concurrency" : 0,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "enabled" : true
}, {
  "tasks_active" : 0,
  "updated_at" : "2023-03-06T18:14:50.52Z",
  "explorers_total" : 0,
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "zone1",
  "tasks_waiting" : 0,
  "processor_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "explorers_concurrency" : 0,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "enabled" : true
} ]
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**

array of hosted zones

401Access token is missing or invalid [Problem](#)**GET /org/key**[Up](#)Get API key details ([getKey](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**Return type**[APIKey](#)**Example data**

Content-Type: application/json

```
{
  "usage_limit" : 10000,
  "created_at" : 1576300370,
  "counter" : 1,
  "type" : "org",
  "created_by" : "user@example.com",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "token" : "CTXXXXXXXXXXXXXX",
  "usage_today" : 100,
```

```

    "last_used_at" : 0,
    "inactive" : true,
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "last_used_ua" : "curl/7.44.1",
    "comment" : "API key used for Splunk integration",
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "last_used_ip" : "127.0.0.1"
}

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

api key details [APIKey](#)

401

Access token is missing or invalid [Problem](#)**GET /org**[Up](#)Get organization details ([getOrganization](#))**Query parameters**_oid (optional)

Query Parameter — The current Organization default: null

Return type[Organization](#)**Example data**

Content-Type: application/json

```
{
  "export_token_last_used_at" : 0,
  "deactivated_at" : 0,
  "download_token_created_at" : 1576300370,
  "export_token_created_at" : 1576300370,
  "created_at" : 1576300370,
  "description" : "All subdivisions of my company",
  "service_count_udp" : 1,
  "project" : false,
  "export_token" : "ET11226D9EEEA2B035D42569585900",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "export_token_counter" : 0,
  "asset_count" : 100,
  "inactive" : false,
  "updated_at" : 1576300370,
  "export_token_last_used_by" : "127.0.0.1",
  "expiration_assets_stale" : 365,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "download_token" : "DT11226D9EEEA2B035D42569585900",
  "service_count" : 10,
  "service_count_tcp" : 7,
  "service_count_arp" : 1,
  "expiration_scans" : 365,
  "service_count_icmp" : 1,
  "expiration_assets_offline" : 365,
  "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "My Company"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**organization details [Organization](#)**401**Access token is missing or invalid [Problem](#)**GET /org/services/{service_id}**[Up](#)Get service details ([getService](#))**Path parameters****service_id (required)***Path Parameter* — UUID of the service to retrieve default: null format: uuid**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**Return type**[Service](#)**Example data**

Content-Type: application/json

```
{
  "addresses" : [ "192.168.0.1", "192.168.0.1" ],
  "last_seen" : 1576300370,
  "agent_name" : "LAPTOP-F4P1R6",
  "service_screenshot_link" : "service_screenshot_link",
  "type" : "Server",
  "last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hw" : "Dell PowerEdge 2500",
  "lowest_rtt" : 1,
  "service_ports_products" : [ "bind", "bind" ],
  "service_protocol" : "http tls",
  "service_data" : {
    "key" : "service_data"
  },
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "service_ports_protocols" : [ "ssh", "ssh" ],
  "addresses_extra" : [ "192.168.100.1", "192.168.100.1" ],
  "service_updated_at" : 1576300370,
  "domains" : [ "CORPNET", "CORPNET" ],
  "newest_mac_vendor" : "Intel Corporate",
  "lowest_ttl" : 0,
  "newest_mac" : "11:22:33:44:55:66",
  "tags" : {
    "key" : "tags"
  },
  "site_name" : "Primary",
  "service_count_icmp" : 1,
  "service_link" : "http://192.168.0.1:80/",
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "macs" : [ "11:22:33:44:55:66", "11:22:33:44:55:66" ],
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
}
```

runZero API documentation

```
"service_asset_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"service_port" : "80",
"newest_mac_age" : 13040352000000000000,
"first_seen" : 1576300370,
"alive" : true,
"credentials" : {
    "key" : {
        "key" : true
    }
},
"created_at" : 1576300370,
"service_count_udp" : 1,
"service_summary" : "Login Page",
"mac_vendors" : [ "Dell", "Dell" ],
"service_address" : "192.168.0.1",
"service_ports_udp" : [ "53", "53" ],
"service_created_at" : 1576300370,
"updated_at" : 1576300370,
"detected_by" : "icmp",
"service_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"org_name" : "Test Labs",
"comments" : "File Server",
"os" : "Ubuntu Linux",
"last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"service_transport" : "tcp",
"os_version" : "18.04",
"service_count" : 10,
"service_count_tcp" : 7,
"service_count_arp" : 1,
"services" : {
    "key" : {
        "key" : "services"
    }
},
"service_ports_tcp" : [ "22", "22" ],
"names" : [ "www", "www" ],
"rtts" : {
    "key" : ""
},
"attributes" : {
    "key" : "attributes"
},
"service_vhost" : "www"
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

service details [Service](#)

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)**GET /org/services**[Up](#)Get all services ([getServices](#))**Query parameters****_oid (optional)**

Query Parameter — The current Organization default: null

search (optional)

Query Parameter — an optional search string for filtering results default: null

Return typearray[[Service](#)]**Example data**

Content-Type: application/json

```
[ {
  "addresses" : [ "192.168.0.1", "192.168.0.1" ],
  "last_seen" : 1576300370,
  "agent_name" : "LAPTOP-F4P1R6",
  "service_screenshot_link" : "service_screenshot_link",
  "type" : "Server",
  "last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hw" : "Dell PowerEdge 2500",
  "lowest_rtt" : 1,
  "service_ports_products" : [ "bind", "bind" ],
  "service_protocol" : "http tls",
  "service_data" : {
    "key" : "service_data"
  },
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "service_ports_protocols" : [ "ssh", "ssh" ],
  "addresses_extra" : [ "192.168.100.1", "192.168.100.1" ],
  "service_updated_at" : 1576300370,
  "domains" : [ "CORPNET", "CORPNET" ],
  "newest_mac_vendor" : "Intel Corporate",
  "lowest_ttl" : 0,
  "newest_mac" : "11:22:33:44:55:66",
  "tags" : {
    "key" : "tags"
  },
  "site_name" : "Primary",
  "service_count_icmp" : 1,
  "service_link" : "http://192.168.0.1:80/",
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "macs" : [ "11:22:33:44:55:66", "11:22:33:44:55:66" ],
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "service_asset_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "service_port" : "80",
  "newest_mac_age" : 13040352000000000000,
  "first_seen" : 1576300370,
  "alive" : true,
  "credentials" : {
    "key" : {
      "key" : true
    }
  },
  "created_at" : 1576300370,
  "service_count_udp" : 1,
  "service_summary" : "Login Page",
  "mac_vendors" : [ "Dell", "Dell" ],
  "service_address" : "192.168.0.1",
  "service_ports_udp" : [ "53", "53" ],
  "service_created_at" : 1576300370,
  "updated_at" : 1576300370,
  "detected_by" : "icmp",
  "service_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "org_name" : "Test Labs",
  "comments" : "File Server",
  "os" : "Ubuntu Linux",
}
```

```

"last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"service_transport" : "tcp",
"os_version" : "18.04",
"service_count" : 10,
"service_count_tcp" : 7,
"service_count_arp" : 1,
"services" : {
    "key" : {
        "key" : "services"
    }
},
"service_ports_tcp" : [ "22", "22" ],
"names" : [ "www", "www" ],
"rtts" : {
    "key" : ""
},
"attributes" : {
    "key" : "attributes"
},
"service_vhost" : "www"
}, {
    "addresses" : [ "192.168.0.1", "192.168.0.1" ],
    "last_seen" : 1576300370,
    "agent_name" : "LAPTOP-F4P1R6",
    "service_screenshot_link" : "service_screenshot_link",
    "type" : "Server",
    "last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "hw" : "Dell PowerEdge 2500",
    "lowest_rtt" : 1,
    "service_ports_products" : [ "bind", "bind" ],
    "service_protocol" : "http tls",
    "service_data" : {
        "key" : "service_data"
    },
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "service_ports_protocols" : [ "ssh", "ssh" ],
    "addresses_extra" : [ "192.168.100.1", "192.168.100.1" ],
    "service_updated_at" : 1576300370,
    "domains" : [ "CORPNET", "CORPNET" ],
    "newest_mac_vendor" : "Intel Corporate",
    "lowest_ttl" : 0,
    "newest_mac" : "11:22:33:44:55:66",
    "tags" : {
        "key" : "tags"
    },
    "site_name" : "Primary",
    "service_count_icmp" : 1,
    "service_link" : "http://192.168.0.1:80/",
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "macs" : [ "11:22:33:44:55:66", "11:22:33:44:55:66" ],
    "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "service_asset_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "service_port" : "80",
    "newest_mac_age" : 13040352000000000000,
    "first_seen" : 1576300370,
    "alive" : true,
    "credentials" : {
        "key" : {
            "key" : true
        }
    },
    "created_at" : 1576300370,
    "service_count_udp" : 1,
    "service_summary" : "Login Page",
    "mac_vendors" : [ "Dell", "Dell" ],
    "service_address" : "192.168.0.1",
    "service_ports_udp" : [ "53", "53" ],
    "service_created_at" : 1576300370,
    "updated_at" : 1576300370,
    "detected_by" : "icmp",
    "service_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "org_name" : "Test Labs",
    "comments" : "File Server",
    "os" : "Ubuntu Linux",
    "last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "service_transport" : "tcp",
}

```

```

"os_version" : "18.04",
"service_count" : 10,
"service_count_tcp" : 7,
"service_count_arp" : 1,
"services" : [
    "key" : {
        "key" : "services"
    }
},
"service_ports_tcp" : [ "22", "22" ],
"names" : [ "www", "www" ],
"rtts" : [
    "key" : ""
],
"attributes" : [
    "key" : "attributes"
],
"service_vhost" : "www"
} ]

```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

array of services

401

Access token is missing or invalid [Problem](#)**GET /org/sites/{site_id}**[Up](#)Get site details ([getSite](#))**Path parameters****site_id (required)***Path Parameter* — UUID or name of the site default: null format: uuid**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**Return type**[Site](#)**Example data**

Content-Type: application/json

```
{
    "data" : {
        "excludes" : "192.168.0.5",
        "updated_at" : 1576300370,
        "scope" : "192.168.0.0/24",
        "name" : "Primary",
        "created_at" : 1576300370,
        "description" : "Headquarters",
        "subnets" : [
            "key" : ""
        ],
        "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8"
    }
}
```

```
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

site details [Site](#)

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)**GET /org/sites**[Up](#)Get all sites ([getSites](#))**Query parameters**_oid (optional)

Query Parameter — The current Organization default: null

Return typearray[[Site](#)]**Example data**

Content-Type: application/json

```
[
  {
    "data" : {
      "excludes" : "192.168.0.5",
      "updated_at" : 1576300370,
      "scope" : "192.168.0.0/24",
      "name" : "Primary",
      "created_at" : 1576300370,
      "description" : "Headquarters",
      "subnets" : [
        {
          "key" : ""
        }
      ],
      "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8"
    }
  },
  {
    "data" : {
      "excludes" : "192.168.0.5",
      "updated_at" : 1576300370,
      "scope" : "192.168.0.0/24",
      "name" : "Primary",
      "created_at" : 1576300370,
      "description" : "Headquarters",
      "subnets" : [
        {
          "key" : ""
        }
      ]
    }
  }
]
```

```

    },
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8"
}
]

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

array of sites

401

Access token is missing or invalid [Problem](#)**GET /org/tasks/{task_id}**[Up](#)Get task details ([getTask](#))**Path parameters****task_id (required)**

Path Parameter — UUID of the task to retrieve default: null format: uuid

Query parameters**_oid (optional)**

Query Parameter — The current Organization default: null

Return type[TaskBase](#)**Example data**

Content-Type: application/json

```
{
  "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hidden" : false,
  "description" : "Scan the headquarters hourly",
  "created_at" : 1576300370,
  "type" : "scan",
  "error" : "agent unavailable",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "updated_at" : 1576300370,
  "stats" : {
    "key" : ""
  },
  "recur" : false,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last" : 1576300370,
  "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "params" : {
    "key" : "params"
  },
  "created_by" : "user@example.com",
  "created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "start_time" : 1576300370,
  "recur_frequency" : "hourly",
  "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
}
```

```

"organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"name" : "Hourly Scan",
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"source_id" : 1,
"recur_next" : 1576300370,
"status" : "processed"
}

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

task details [Task](#)

401

Access token is missing or invalid [Problem](#)**GET /org/tasks/{task_id}/changes**[Up](#)Returns a temporary task change report data url ([getTaskChangeReport](#))**Path parameters****task_id (required)***Path Parameter* — UUID of the task default: null format: uuid**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**Return type**[URL](#)**Example data**

Content-Type: application/json

```
{
  "id" : "https://www.runzero.com/docs/"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

URL [URL](#)

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)**GET /org/tasks/{task_id}/log**[Up](#)Returns a temporary task log data url ([getTaskLog](#))**Path parameters****task_id (required)**

Path Parameter — UUID of the task default: null format: uuid

Query parameters**_oid (optional)**

Query Parameter — The current Organization default: null

Return type[URL](#)**Example data**

Content-Type: application/json

```
{
  "id" : "https://www.runzero.com/docs/"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

URL [URL](#)

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)[Up](#)

GET /org/tasks/{task_id}/dataReturns a temporary task scan data url ([getTaskScanData](#))**Path parameters****task_id (required)***Path Parameter* — UUID of the task default: null format: uuid**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**Return type**[URL](#)**Example data**

Content-Type: application/json

```
{
  "id" : "https://www.runzero.com/docs/"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**URL [URL](#)**401**Access token is missing or invalid [Problem](#)**404**Resource not found [Problem](#)**GET /org/tasks**[Up](#)Get all tasks (last 1000) ([getTasks](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**status (optional)***Query Parameter* — an optional status string for filtering results default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**Return type**

array[[TaskBase](#)]**Example data**

Content-Type: application/json

```
[ {
  "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hidden" : false,
  "description" : "Scan the headquarters hourly",
  "created_at" : 1576300370,
  "type" : "scan",
  "error" : "agent unavailable",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "updated_at" : 1576300370,
  "stats" : {
    "key" : ""
  },
  "recur" : false,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last" : 1576300370,
  "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "params" : {
    "key" : "params"
  },
  "created_by" : "user@example.com",
  "created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "start_time" : 1576300370,
  "recur_frequency" : "hourly",
  "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "Hourly Scan",
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "source_id" : 1,
  "recur_next" : 1576300370,
  "status" : "processed"
}, {
  "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hidden" : false,
  "description" : "Scan the headquarters hourly",
  "created_at" : 1576300370,
  "type" : "scan",
  "error" : "agent unavailable",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "updated_at" : 1576300370,
  "stats" : {
    "key" : ""
  },
  "recur" : false,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last" : 1576300370,
  "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "params" : {
    "key" : "params"
  },
  "created_by" : "user@example.com",
  "created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "start_time" : 1576300370,
  "recur_frequency" : "hourly",
  "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "Hourly Scan",
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "source_id" : 1,
  "recur_next" : 1576300370,
  "status" : "processed"
} ]
```

Example data

runZero API documentation

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

array of tasks

401

Access token is missing or invalid [Problem](#)

GET /org/wireless/{wireless_id}

[Up](#)

Get wireless LAN details ([getWirelessLAN](#))

Path parameters

wireless_id (required)

Path Parameter — UUID of the wireless LAN to retrieve default: null format: uuid

Query parameters

_oid (optional)

Query Parameter — The current Organization default: null

Return type

[Wireless](#)

Example data

Content-Type: application/json

```
{  
    "last_seen" : 1576300370,  
    "last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "data" : {  
        "key" : "data"  
    },  
    "agent_name" : "LAPTOP-F4P1R6",  
    "essid" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",  
    "bssid" : "11:22:33:44:55:66",  
    "created_at" : 1576300370,  
    "type" : "infrastructure",  
    "interface" : "wlan0",  
    "last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "site_name" : "Primary",  
    "encryption" : "aes",  
    "channels" : "11, 158+1",  
    "vendor" : "Ubiquiti Networks",  
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "family" : "223344",  
    "org_name" : "Test Labs",  
    "signal" : 99,  
    "authentication" : "wpa2-psk"  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",
```

```

        "status" : 140
    }
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**wireless details [Wireless](#)**401**Access token is missing or invalid [Problem](#)
GET /org/wireless
[Up](#)Get all wireless LANs ([getWirelessLANs](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**Return type**array[[Wireless](#)]**Example data**

Content-Type: application/json

```
[
  {
    "last_seen" : 1576300370,
    "last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "data" : {
      "key" : "data"
    },
    "agent_name" : "LAPTOP-F4P1R6",
    "essid" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "bssid" : "11:22:33:44:55:66",
    "created_at" : 1576300370,
    "type" : "infrastructure",
    "interface" : "wlan0",
    "last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "site_name" : "Primary",
    "encryption" : "aes",
    "channels" : "11, 158+1",
    "vendor" : "Ubiquiti Networks",
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "family" : "223344",
    "org_name" : "Test Labs",
    "signal" : 99,
    "authentication" : "wpa2-psk"
  },
  {
    "last_seen" : 1576300370,
    "last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "data" : {
      "key" : "data"
    },
    "agent_name" : "LAPTOP-F4P1R6",
    "essid" : "046b6c7f-0b8a-43b9-b35d-6489e6daee91",
    "bssid" : "11:22:33:44:55:66",
    "created_at" : 1576300370,
    "type" : "infrastructure",
    "interface" : "wlan0",
    "last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "site_name" : "Primary",
    "encryption" : "aes",
    "channels" : "11, 158+1",
    "vendor" : "Ubiquiti Networks",
  }
]
```

```

"organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"family" : "223344",
"org_name" : "Test Labs",
"signal" : 99,
"authentication" : "wpa2-psk"
} ]

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

array of wireless LANs

401

Access token is missing or invalid [Problem](#)**POST /org/tasks/{task_id}/hide**[Up](#)Signal that a completed task should be hidden ([hideTask](#))**Path parameters****task_id (required)**

Path Parameter — UUID of the task to hide default: null format: uuid

Query parameters**_oid (optional)**

Query Parameter — The current Organization default: null

Return type[TaskBase](#)**Example data**

Content-Type: application/json

```
{
  "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hidden" : false,
  "description" : "Scan the headquarters hourly",
  "created_at" : 1576300370,
  "type" : "scan",
  "error" : "agent unavailable",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "updated_at" : 1576300370,
  "stats" : {
    "key" : ""
  },
  "recur" : false,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last" : 1576300370,
  "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "params" : {
    "key" : "params"
  },
  "created_by" : "user@example.com",
}
```

```

"created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"start_time" : 1576300370,
"recur_frequency" : "hourly",
"parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"name" : "Hourly Scan",
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"source_id" : 1,
"recur_next" : 1576300370,
"status" : "processed"
}

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

task information [Task](#)

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)**POST /import/org/{orgId}/assets**[Up](#)

Import assets described by a registered custom integration ([importCustomIntegrationAssets](#))

Assets can be discovered, imported, and merged by runZero scan tasks, first-party integrations, and third-party defined custom integrations. See [/account/custom-integrations](#). Currently only assets for custom integrations are importable here.

Path parameters**orgId (required)**

Path Parameter — The unique ID of the organization that the assets will be imported into. default: null
format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- multipart/form-data

Form parameters**siteld (required)**

Form Parameter — The ID of the site assets are to be imported into. default: null format: uuid

customIntegrationId (required)

Form Parameter — The unique ID of the registered custom integration which produced the asset data.
Uniqueness is not checked/enforced. See [/account/custom-integrations](#) api. default: null format: uuid

importTask (required)

Form Parameter — default: null

runZero API documentation

assetData (required)

Form Parameter — A gzip (not .tar.gz) compressed file containing ImportAsset objects. The file data may be a JSON array of ImportAsset objects, e.g. [{}], or JSONL format, with a single JSON representation of an ImportAsset object on each new line, e.g. {}
default: null format: binary

Return type

[TaskBase](#)

Example data

Content-Type: application/json

```
{  
    "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "hidden" : false,  
    "description" : "Scan the headquarters hourly",  
    "created_at" : 1576300370,  
    "type" : "scan",  
    "error" : "agent unavailable",  
    "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "updated_at" : 1576300370,  
    "stats" : {  
        "key" : ""  
    },  
    "recur" : false,  
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "recur_last" : 1576300370,  
    "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "params" : {  
        "key" : "params"  
    },  
    "created_by" : "user@example.com",  
    "created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "start_time" : 1576300370,  
    "recur_frequency" : "hourly",  
    "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "name" : "Hourly Scan",  
    "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "source_id" : 1,  
    "recur_next" : 1576300370,  
    "status" : "processed"  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**import task created. The task ID should be checked for its status. [Task](#)**400**Invalid request body [Problem](#)**401**Access token is missing or invalid [Problem](#)**403**Action not allowed for this license type [Problem](#)**404**Resource not found [Problem](#)**422**Invalid request body [Problem](#)**500**Unexpected error occurred on the server [Problem](#)**PUT /org/sites/{site_id}/import/nessus**[Up](#)Import a Nessus scan data file into a site ([importNessusScanData](#))**Path parameters****site_id (required)***Path Parameter* — UUID or name of the site to import Nessus scan data into default: null format: uuid**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/octet-stream

Request body**body [file](#) (optional)***Body Parameter* —**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null

Return type[TaskBase](#)**Example data**

Content-Type: application/json

```
{
  "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hidden" : false,
  "description" : "Scan the headquarters hourly",
  "created_at" : 1576300370,
  "type" : "scan",
  "error" : "agent unavailable",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "updated_at" : 1576300370,
  "stats" : {
    "key" : ""
  },
  "recur" : false,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last" : 1576300370,
  "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "params" : {
    "key" : "params"
  },
  "created_by" : "user@example.com",
  "created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "start_time" : 1576300370,
  "recur_frequency" : "hourly",
  "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "Hourly Scan",
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "source_id" : 1,
  "recur_next" : 1576300370,
  "status" : "processed"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

import task [Task](#)

401

Access token is missing or invalid [Problem](#)

403

License has expired [Problem](#)

404

Resource not found [Problem](#)

500

Request could not be processed [Problem](#)

PUT /org/sites/{site_id}/import/packet Up

Import a packet capture file into a site ([importPacketData](#))

Path parameters**site_id (required)***Path Parameter* — UUID or name of the site to import packet capture into default: null format: uuid**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/octet-stream

Request body**body [file](#) (optional)***Body Parameter* —**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**Return type**[TaskBase](#)**Example data**

Content-Type: application/json

```
{
  "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hidden" : false,
  "description" : "Scan the headquarters hourly",
  "created_at" : 1576300370,
  "type" : "scan",
  "error" : "agent unavailable",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "updated_at" : 1576300370,
  "stats" : {
    "key" : ""
  },
  "recur" : false,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last" : 1576300370,
  "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
}
```

```

"hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"params" : {
    "key" : "params"
},
"created_by" : "user@example.com",
"created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"start_time" : 1576300370,
"recur_frequency" : "hourly",
"parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"name" : "Hourly Scan",
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"source_id" : 1,
"recur_next" : 1576300370,
"status" : "processed"
}

```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

import task [Task](#)

401

Access token is missing or invalid [Problem](#)

403

License has expired [Problem](#)

404

Resource not found [Problem](#)

500

Request could not be processed [Problem](#)

PUT /org/sites/{site_id}/import

[Up](#)

Import a scan data file into a site ([importScanData](#))

Path parameters

`site_id` (required)

Path Parameter — UUID or name of the site to import scan data into default: null format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/octet-stream

Request body

`body_file` (optional)

Body Parameter —

Query parameters

`_oid` (optional)

Query Parameter — The current Organization default: null

Return type

[TaskBase](#)

Example data

Content-Type: application/json

```
{
  "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hidden" : false,
  "description" : "Scan the headquarters hourly",
  "created_at" : 1576300370,
  "type" : "scan",
  "error" : "agent unavailable",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "updated_at" : 1576300370,
  "stats" : {
    "key" : ""
  },
  "recur" : false,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last" : 1576300370,
  "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "params" : {
    "key" : "params"
  },
  "created_by" : "user@example.com",
  "created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "start_time" : 1576300370,
  "recur_frequency" : "hourly",
  "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "Hourly Scan",
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "source_id" : 1,
  "recur_next" : 1576300370,
  "status" : "processed"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

import task [Task](#)

401

Access token is missing or invalid [Problem](#)

403

License has expired [Problem](#)

404

Resource not found [Problem](#)

500

Request could not be processed [Problem](#)**PATCH /org/assets/merge**[Up](#)Merge multiple assets ([mergeAssets](#))**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request bodyAssetIDs [AssetIDs](#) (required)*Body Parameter* —**Query parameters**[_oid](#) (optional)*Query Parameter* — The current Organization default: null**Example data**

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
```

```
{
    "status" : 140
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**

Summary of operation results

401Access token is missing or invalid [Problem](#)**404**Resource not found [Problem](#)**DELETE /org/agents/{agent_id}**[Up](#)Remove and uninstall an agent. Legacy path for /org/explorers/{explorer_id} ([removeAgent](#))**Path parameters****agent_id (required)***Path Parameter* — UUID of the agent to remove default: null format: uuid**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**Example data**

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**204**

empty response

401Access token is missing or invalid [Problem](#)**404**Resource not found [Problem](#)

DELETE /org/assets/{asset_id}[Up](#)Remove an asset ([removeAsset](#))**Path parameters****asset_id (required)***Path Parameter* — UUID of the asset to remove default: null format: uuid**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**Example data**

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**204**

empty response

401Access token is missing or invalid ([Problem](#))**404**Resource not found ([Problem](#))**DELETE /org/assets/{asset_id}/sources/{source_id}/remove**[Up](#)Remove single source from asset ([removeAssetSource](#))**Path parameters****asset_id (required)***Path Parameter* — UUID of the asset to update default: null format: uuid**source_id (required)***Path Parameter* — UUID of the source default: null format: uuid**Example data**

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**204**

empty response

400**401**Access token is missing or invalid [Problem](#)**403**Action not allowed for this license type [Problem](#)**500**Unexpected error occurred on the server [Problem](#)**DELETE /org/assets/bulk/delete**[Up](#)Removes multiple assets by ID ([removeBulkAssets](#))**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body**AssetIDs AssetIDs (required)**

Body Parameter —

Query parameters**_oid (optional)**

Query Parameter — The current Organization default: null

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

204

empty response

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)

500

Unexpected error occurred on the server [Problem](#)

DELETE /org/assets/{asset_id}/custom-integrations/{custom_integration_id}

Remove single custom integration from asset ([removeCustomIntegration](#))

Path parameters**asset_id (required)**

Path Parameter — UUID of the asset to update default: null format: uuid

custom_integration_id (required)

Path Parameter — UUID of the custom integration default: null format: uuid

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

204

empty response

400

401

Access token is missing or invalid [Problem](#)

403

Action not allowed for this license type [Problem](#)

500

Unexpected error occurred on the server [Problem](#)

DELETE /org/explorers/{explorer_id}

[Up](#)

Remove and uninstall an explorer ([removeExplorer](#))

Remove and uninstall an explorer. This is the same call as legacy path /org/agents/{agent_id}

Path parameters

`explorer_id` (required)

Path Parameter — UUID of the explorer to remove default: null format: uuid

Query parameters

`_oid` (optional)

Query Parameter — The current Organization default: null

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

204

empty response

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)

DELETE /org/key

[Up](#)

Remove the current API key ([removeKey](#))

Query parameters

`_oid` (optional)

Query Parameter — The current Organization default: null

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
```

```

        "status" : 140
    }
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**204**

empty response

401Access token is missing or invalid [Problem](#)**DELETE /org/services/{service_id}**[Up](#)

Remove a service ([removeService](#))

Path parameters**service_id (required)**

Path Parameter — UUID of the service to remove default: null format: uuid

Query parameters**_oid (optional)**

Query Parameter — The current Organization default: null

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**204**

empty response

401Access token is missing or invalid [Problem](#)**404**Resource not found [Problem](#)**DELETE /org/sites/{site_id}**[Up](#)

Remove a site and associated assets ([removeSite](#))

Path parameters**site_id (required)**

Path Parameter — UUID or name of the site to remove default: null format: uuid

Query parameters

_oid (optional)

Query Parameter — The current Organization default: null

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

204

empty response

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)

DELETE /org/wireless/{wireless_id}

[Up](#)

Remove a wireless LAN ([removeWirelessLAN](#))

Path parameters

wireless_id (required)

Path Parameter — UUID of the wireless LAN to remove default: null format: uuid

Query parameters

_oid (optional)

Query Parameter — The current Organization default: null

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Produces

runZero API documentation

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

204

empty response

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)

PATCH /org/key/rotate

Up

Rotate the API key secret and return the updated key (**rotateKey**)

Query parameters

_oid (optional)

Query Parameter — The current Organization default: null

Return type

[APIKey](#)

Example data

Content-Type: application/json

```
{  
    "usage_limit" : 10000,  
    "created_at" : 1576300370,  
    "counter" : 1,  
    "type" : "org",  
    "created_by" : "user@example.com",  
    "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "token" : "CTXXXXXXXXXXXXXX",  
    "usage_today" : 100,  
    "last_used_at" : 0,  
    "inactive" : true,  
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "last_used_ua" : "curl/7.44.1",  
    "comment" : "API key used for Splunk integration",  
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "last_used_ip" : "127.0.0.1"  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

api key details [APIKey](#)

401

Access token is missing or invalid [Problem](#)

POST /org/tasks/{task_id}/stop

Up

Signal that a task should be stopped or canceled. This will also remove recurring and scheduled tasks (**stopTask**)

runZero API documentation

Path parameters

task_id (required)

Path Parameter — UUID of the task to stop default: null format: uuid

Query parameters

_oid (optional)

Query Parameter — The current Organization default: null

Return type

[TaskBase](#)

Example data

Content-Type: application/json

```
{  
    "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "hidden" : false,  
    "description" : "Scan the headquarters hourly",  
    "created_at" : 1576300370,  
    "type" : "scan",  
    "error" : "agent unavailable",  
    "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "updated_at" : 1576300370,  
    "stats" : {  
        "key" : ""  
    },  
    "recur" : false,  
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "recur_last" : 1576300370,  
    "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "params" : {  
        "key" : "params"  
    },  
    "created_by" : "user@example.com",  
    "created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "start_time" : 1576300370,  
    "recur_frequency" : "hourly",  
    "parent_id" : "e77602e0-4734-aef9-fbc6fdcb0fa8",  
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "name" : "Hourly Scan",  
    "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
    "source_id" : 1,  
    "recur_next" : 1576300370,  
    "status" : "processed"  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**task information [Task](#)**401**Access token is missing or invalid [Problem](#)**404**Resource not found [Problem](#)**PATCH /org/agents/{agent_id}**[Up](#)Update the site associated with agent. Legacy path for /org/explorers/{explorer_id} ([updateAgentSite](#))**Path parameters****agent_id (required)***Path Parameter* — UUID of the agent to update default: null format: uuid**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body**AgentSiteID [AgentSiteID](#) (required)***Body Parameter* —**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**Return type**[Agent](#)**Example data**

Content-Type: application/json

```
{
  "os" : "Windows",
  "system_info" : {
    "key" : ""
  },
  "deactivated_at" : 0,
  "created_at" : 1576300370,
  "last_checkin" : 1576300370,
  "version" : "1.2.3 (build 20191219224016) [fc50c5eefdc3ff5c60533c3c345d14d336396272]",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "host_id" : "6f9e6fe52271da70962e007183c5c9c9",
  "internal_ip" : "192.168.0.1",
  "connected" : true,
  "hub_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "inactive" : false,
  "updated_at" : 1576300370,
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "RUNZERO-AGENT",
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "arch" : "amd64",
  "external_ip" : "1.1.1.1"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**agent details [Agent](#)**401**Access token is missing or invalid [Problem](#)**404**Resource not found [Problem](#)**PATCH /org/assets/{asset_id}/comments**[Up](#)Update asset comments ([updateAssetComments](#))**Path parameters****asset_id (required)**

Path Parameter — UUUID of the asset to update default: null format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body**AssetComments AssetComments (required)**

Body Parameter —

Query parameters**_oid (optional)**

Query Parameter — The current Organization default: null

Return type[Asset](#)**Example data**

Content-Type: application/json

```
{
  "addresses" : [ "192.168.0.1", "192.168.0.1" ],
  "first_seen" : 1576300370,
  "alive" : true,
  "last_seen" : 1576300370,
  "agent_name" : "LAPTOP-F4P1R6",
  "credentials" : {
    "key" : {
      "key" : true
    }
  },
  "created_at" : 1576300370,
  "service_count_udp" : 1,
  "mac_vendors" : [ "Dell", "Dell" ],
  "type" : "Server",
  "last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "service_ports_udp" : [ "53", "53" ],
  "hw" : "Dell PowerEdge 2500",
  "lowest_rtt" : 1,
```

```

"service_ports_products" : [ "bind", "bind" ],
"updated_at" : 1576300370,
"detected_by" : "icmp",
"id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"service_ports_protocols" : [ "ssh", "ssh" ],
"org_name" : "Test Labs",
"addresses_extra" : [ "192.168.100.1", "192.168.100.1" ],
"comments" : "File Server",
"os" : "Ubuntu Linux",
"last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"os_version" : "18.04",
"service_count" : 10,
"domains" : [ "www", "www" ],
"service_count_tcp" : 7,
"newest_mac_vendor" : "Intel Corporate",
"lowest_ttl" : 0,
"newest_mac" : "11:22:33:44:55:66",
"service_count_arp" : 1,
"services" : {
  "key" : {
    "key" : "services"
  }
},
"service_ports_tcp" : [ "22", "22" ],
"tags" : {
  "key" : "tags"
},
"site_name" : "Primary",
"names" : [ "www", "www" ],
"service_count_icmp" : 1,
"rtts" : {
  "key" : ""
},
"organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"macs" : [ "11:22:33:44:55:66", "11:22:33:44:55:66" ],
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"attributes" : {
  "key" : "attributes"
},
"newest_mac_age" : 13040352000000000000
}
}

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**asset details [Asset](#)**401**Access token is missing or invalid [Problem](#)**404**Resource not found [Problem](#)

PATCH /org/assets/{asset_id}/criticality

[Up](#)

Update asset criticality ([updateAssetCriticality](#))

Path parameters

asset_id (required)

Path Parameter — UUID of the asset to update default: null format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

AssetCriticality [AssetCriticality](#) (required)

Body Parameter —

Query parameters

_oid (optional)

Query Parameter — The current Organization default: null

Return type

[Asset](#)

Example data

Content-Type: application/json

```
{
  "addresses" : [ "192.168.0.1", "192.168.0.1" ],
  "first_seen" : 1576300370,
  "alive" : true,
  "last_seen" : 1576300370,
  "agent_name" : "LAPTOP-F4P1R6",
  "credentials" : {
    "key" : {
      "key" : true
    }
  },
  "created_at" : 1576300370,
  "service_count_udp" : 1,
  "mac_vendors" : [ "Dell", "Dell" ],
  "type" : "Server",
  "last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "service_ports_udp" : [ "53", "53" ],
  "hw" : "Dell PowerEdge 2500",
  "lowest_rtt" : 1,
  "service_ports_products" : [ "bind", "bind" ],
  "updated_at" : 1576300370,
  "detected_by" : "icmp",
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "service_ports_protocols" : [ "ssh", "ssh" ],
  "org_name" : "Test Labs",
  "addresses_extra" : [ "192.168.100.1", "192.168.100.1" ],
  "comments" : "File Server",
  "os" : "Ubuntu Linux",
  "last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "os_version" : "18.04",
  "service_count" : 10,
  "domains" : [ "www", "www" ],
  "service_count_tcp" : 7,
  "newest_mac_vendor" : "Intel Corporate",
  "lowest_ttl" : 0,
  "newest_mac" : "11:22:33:44:55:66",
  "service_count_arp" : 1,
  "services" : {
    "key" : {
      "key" : "services"
    }
  },
  "service_ports_tcp" : [ "22", "22" ],
}
```

```

"tags" : {
    "key" : "tags"
},
"site_name" : "Primary",
"names" : [ "www", "www" ],
"service_count_icmp" : 1,
"rtts" : {
    "key" : ""
},
"organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"macs" : [ "11:22:33:44:55:66", "11:22:33:44:55:66" ],
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"attributes" : {
    "key" : "attributes"
},
"newest_mac_age" : 13040352000000000000
}

```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

asset details [Asset](#)

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)**PATCH /org/assets/{asset_id}/owners**[Up](#)Update asset owners ([updateAssetOwners](#))**Path parameters****asset_id (required)**

Path Parameter — UUID of the asset to update default: null format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body**AssetOwnerships [AssetOwnerships](#) (required)**

Body Parameter —

Query parameters**_oid (optional)**

Query Parameter — The current Organization default: null

Return type[Asset](#)**Example data**

Content-Type: application/json

```
{
  "addresses" : [ "192.168.0.1", "192.168.0.1" ],
  "first_seen" : 1576300370,
  "alive" : true,
  "last_seen" : 1576300370,
  "agent_name" : "LAPTOP-F4P1R6",
  "credentials" : {
    "key" : {
      "key" : true
    }
  },
  "created_at" : 1576300370,
  "service_count_udp" : 1,
  "mac_vendors" : [ "Dell", "Dell" ],
  "type" : "Server",
  "last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "service_ports_udp" : [ "53", "53" ],
  "hw" : "Dell PowerEdge 2500",
  "lowest_rtt" : 1,
  "service_ports_products" : [ "bind", "bind" ],
  "updated_at" : 1576300370,
  "detected_by" : "icmp",
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "service_ports_protocols" : [ "ssh", "ssh" ],
  "org_name" : "Test Labs",
  "addresses_extra" : [ "192.168.100.1", "192.168.100.1" ],
  "comments" : "File Server",
  "os" : "Ubuntu Linux",
  "last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "os_version" : "18.04",
  "service_count" : 10,
  "domains" : [ "www", "www" ],
  "service_count_tcp" : 7,
  "newest_mac_vendor" : "Intel Corporate",
  "lowest_ttl" : 0,
  "newest_mac" : "11:22:33:44:55:66",
  "service_count_arp" : 1,
  "services" : {
    "key" : {
      "key" : "services"
    }
  },
  "service_ports_tcp" : [ "22", "22" ],
  "tags" : {
    "key" : "tags"
  },
  "site_name" : "Primary",
  "names" : [ "www", "www" ],
  "service_count_icmp" : 1,
  "rtts" : {
    "key" : ""
  },
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "macs" : [ "11:22:33:44:55:66", "11:22:33:44:55:66" ],
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "attributes" : {
    "key" : "attributes"
  },
  "newest_mac_age" : 13040352000000000000
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
```

```

        "status" : 140
    }
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Example data

Content-Type: application/json

```
{
    "detail" : "A human readable explanation specific to this occurrence of the problem.",
    "title" : "A short summary of the problem type.",
    "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

asset details [Asset](#)

400

Invalid request body [Problem](#)

403

Action not allowed for this license type [Problem](#)

404

Resource not found [Problem](#)

500

Unexpected error occurred on the server [Problem](#)**PATCH /org/assets/{asset_id}/tags**[Up](#)Update asset tags ([updateAssetTags](#))**Path parameters****asset_id (required)***Path Parameter* — UUID of the asset to update default: null format: uuid**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body**AssetTags AssetTags (required)***Body Parameter* —**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null

Return type[Asset](#)**Example data**

Content-Type: application/json

```
{
  "addresses" : [ "192.168.0.1", "192.168.0.1" ],
  "first_seen" : 1576300370,
  "alive" : true,
  "last_seen" : 1576300370,
  "agent_name" : "LAPTOP-F4P1R6",
  "credentials" : {
    "key" : {
      "key" : true
    }
  },
  "created_at" : 1576300370,
  "service_count_udp" : 1,
  "mac_vendors" : [ "Dell", "Dell" ],
  "type" : "Server",
  "last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "service_ports_udp" : [ "53", "53" ],
  "hw" : "Dell PowerEdge 2500",
  "lowest_rtt" : 1,
  "service_ports_products" : [ "bind", "bind" ],
  "updated_at" : 1576300370,
  "detected_by" : "icmp",
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "service_ports_protocols" : [ "ssh", "ssh" ],
  "org_name" : "Test Labs",
  "addresses_extra" : [ "192.168.100.1", "192.168.100.1" ],
  "comments" : "File Server",
  "os" : "Ubuntu Linux",
  "last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "os_version" : "18.04",
  "service_count" : 10,
  "domains" : [ "www", "www" ],
  "service_count_tcp" : 7,
  "newest_mac_vendor" : "Intel Corporate",
  "lowest_ttl" : 0,
  "newest_mac" : "11:22:33:44:55:66",
  "service_count_arp" : 1,
  "services" : {
    "key" : {
      "key" : "services"
    }
  },
  "service_ports_tcp" : [ "22", "22" ],
  "tags" : {
    "key" : "tags"
  },
  "site_name" : "Primary",
  "names" : [ "www", "www" ],
  "service_count_icmp" : 1,
  "rtts" : {
    "key" : ""
  },
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "macs" : [ "11:22:33:44:55:66", "11:22:33:44:55:66" ],
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "attributes" : {
    "key" : "attributes"
  },
  "newest_mac_age" : 13040352000000000000
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

asset details [Asset](#)

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)**PATCH /org/assets/bulk/criticality**[Up](#)Update criticality across multiple assets based on a search query ([updateBulkAssetCriticality](#))**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body[AssetCriticalityWithSearch](#) [AssetCriticalityWithSearch](#) (required)

Body Parameter —

Query parameters[_oid \(optional\)](#)

Query Parameter — The current Organization default: null

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

Summary of operation results

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)

PATCH /org/assets/bulk/owners

[Up](#)

Update asset owners across multiple assets based on a search query ([updateBulkAssetOwners](#))

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

[AssetOwnershipsWithSearch](#) [AssetOwnershipsWithSearch](#) (required)
Body Parameter —

Query parameters

_oid (optional)

Query Parameter — The current Organization default: null

Return type

[updateBulkAssetOwners_200_response](#)

Example data

Content-Type: application/json

```
{
  "updated_asset_count" : 10
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

- 200**
updated asset count [updateBulkAssetOwners_200_response](#)
- 400**
Invalid request body [Problem](#)
- 403**
Action not allowed for this license type [Problem](#)
- 404**
Resource not found [Problem](#)
- 500**
Unexpected error occurred on the server [Problem](#)

PATCH /org/assets/bulk/tags[Up](#)Update tags across multiple assets based on a search query ([updateBulkAssetTags](#))**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

AssetTagsWithSearch [AssetTagsWithSearch](#) (required)
Body Parameter —

Query parameters

_oid (optional)
Query Parameter — The current Organization default: null

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

- 200**
Summary of operation results
- 401**
Access token is missing or invalid [Problem](#)
- 404**
Resource not found [Problem](#)

PATCH /org/explorers/{explorer_id}[Up](#)Update the site associated with the explorer ([updateExplorerSite](#))

Update the site associated with the explorer. This is the same call as legacy path /org/agents/{agent_id}

Path parameters

runZero API documentation

explorer_id (required)

Path Parameter — UUID of the explorer to update default: null format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

body [AgentSiteID](#) (required)

Body Parameter —

Query parameters

_oid (optional)

Query Parameter — The current Organization default: null

Return type

[Agent](#)

Example data

Content-Type: application/json

```
{  
  "os" : "Windows",  
  "system_info" : {  
    "key" : ""  
  },  
  "deactivated_at" : 0,  
  "created_at" : 1576300370,  
  "last_checkin" : 1576300370,  
  "version" : "1.2.3 (build 20191219224016) [fc50c5eefdc3ff5c60533c3c345d14d336396272]",  
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
  "host_id" : "6f9e6fe52271da70962e007183c5c9c9",  
  "internal_ip" : "192.168.0.1",  
  "connected" : true,  
  "hub_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
  "inactive" : false,  
  "updated_at" : 1576300370,  
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
  "name" : "RUNZERO-AGENT",  
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",  
  "arch" : "amd64",  
  "external_ip" : "1.1.1.1"  
}
```

Example data

Content-Type: application/json

```
{  
  "detail" : "A human readable explanation specific to this occurrence of the problem.",  
  "title" : "A short summary of the problem type.",  
  "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
  "detail" : "A human readable explanation specific to this occurrence of the problem.",  
  "title" : "A short summary of the problem type.",  
  "status" : 140  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200
 explorer details [Agent](#)
401
 Access token is missing or invalid [Problem](#)
404
 Resource not found [Problem](#)

PATCH /org

[Up](#)

Update organization details (updateOrganization)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

OrgOptions [OrgOptions](#) (required)

Body Parameter —

Query parameters

_oid (optional)

Query Parameter — The current Organization default: null

Return type

[Organization](#)

Example data

Content-Type: application/json

```
{
  "export_token_last_used_at" : 0,
  "deactivated_at" : 0,
  "download_token_created_at" : 1576300370,
  "export_token_created_at" : 1576300370,
  "created_at" : 1576300370,
  "description" : "All subdivisions of my company",
  "service_count_udp" : 1,
  "project" : false,
  "export_token" : "ET11226D9EEEA2B035D42569585900",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "export_token_counter" : 0,
  "asset_count" : 100,
  "inactive" : false,
  "updated_at" : 1576300370,
  "export_token_last_used_by" : "127.0.0.1",
  "expiration_assets_stale" : 365,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "download_token" : "DT11226D9EEEA2B035D42569585900",
  "service_count" : 10,
  "service_count_tcp" : 7,
  "service_count_arp" : 1,
  "expiration_scans" : 365,
  "service_count_icmp" : 1,
  "expiration_assets_offline" : 365,
  "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "My Company"
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**organization details [Organization](#)**401**Access token is missing or invalid [Problem](#)**PATCH /org/sites/{site_id}**[Up](#)Update a site definition ([updateSite](#))**Path parameters****site_id (required)***Path Parameter* — UUID or name of the site to update default: null format: uuid**Consumes**

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body**SiteOptions SiteOptions (required)***Body Parameter* —**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**Return type**[Site](#)**Example data**

Content-Type: application/json

```
{
  "data" : {
    "excludes" : "192.168.0.5",
    "updated_at" : 1576300370,
    "scope" : "192.168.0.0/24",
    "name" : "Primary",
    "created_at" : 1576300370,
    "description" : "Headquarters",
    "subnets" : {
      "key" : ""
    },
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8"
  }
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

site details [Site](#)

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)

PATCH /org/tasks/{task_id}

Up

Update task parameters ([updateTask](#))

Path parameters

task_id (required)

Path Parameter — UUID of the task to update default: null format: uuid

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

TaskOptions TaskOptions (required)

Body Parameter —

Query parameters

_oid (optional)

Query Parameter — The current Organization default: null

Return type

[TaskBase](#)

Example data

Content-Type: application/json

```
{
  "agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hidden" : false,
  "description" : "Scan the headquarters hourly",
  "created_at" : 1576300370,
  "type" : "scan",
  "error" : "agent unavailable",
  "client_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "cruncher_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "updated_at" : 1576300370,
  "stats" : {
    "key" : ""
  },
  "recur" : false,
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last" : 1576300370,
  "custom_integration_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "recur_last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "hosted_zone_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "params" : {
    "key" : "params"
  },
  "created_by" : "user@example.com",
  "created_by_user_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "start_time" : 1576300370,
  "recur_frequency" : "hourly",
  "parent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "name" : "Hourly Scan",
}
```

```

    "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "template_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "source_id" : 1,
    "recur_next" : 1576300370,
    "status" : "processed"
}

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

task details [Task](#)

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)**POST /org/agents/{agent_id}/update**[Up](#)

Force an agent to update and restart. Legacy path for /org/explorers/{explorer_id}/update ([upgradeAgent](#))

Path parameters**agent_id (required)**

Path Parameter — UUID of the agent to update default: null format: uuid

Query parameters**_oid (optional)**

Query Parameter — The current Organization default: null

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

runZero API documentation

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

204

empty response

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)

POST /org/explorers/{explorer_id}/update

Up

Force an explorer to update and restart ([upgradeExplorer](#))

Force an explorer to update and restart. This is the same call as legacy path /org/agents/{agent_id}/update

Path parameters

explorer_id (required)

Path Parameter — UUID of the explorer to update default: null format: uuid

Query parameters

_oid (optional)

Query Parameter — The current Organization default: null

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Example data

Content-Type: application/json

```
{  
    "detail" : "A human readable explanation specific to this occurrence of the problem.",  
    "title" : "A short summary of the problem type.",  
    "status" : 140  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

204

empty response

401

Access token is missing or invalid [Problem](#)

404

Resource not found [Problem](#)

Public

GET /health

Up

Returns a health check status (cloud and self-hosted) ([getHealthCheck](#))

Return type

[HealthCheckResponse](#)

Example data

Content-Type: application/json

```
{  
    "version" : "3.0.0",  
    "status" : "ok"  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

health status and current version [HealthCheckResponse](#)

GET /releases/agent/version

Up

Returns latest agent version ([getLatestAgentVersion](#))

Return type

[ComponentVersion](#)

Example data

Content-Type: application/json

```
{  
    "id" : "agent",  
    "version" : "1.0.0"  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

component version [ComponentVersion](#)

GET /releases/platform/version

Up

Returns latest platform version ([getLatestPlatformVersion](#))

Return type

[ComponentVersion](#)

Example data

Content-Type: application/json

```
{  
    "id" : "agent",  
    "version" : "1.0.0"  
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

component version [ComponentVersion](#)

GET /releases/scanner/version

Up

Returns latest scanner version ([getLatestScannerVersion](#))

Return type[ComponentVersion](#)**Example data**

Content-Type: application/json

```
{
  "id" : "agent",
  "version" : "1.0.0"
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**component version [ComponentVersion](#)

ServiceNow

GET /export/org/assets.servicenow.csv[Up](#)Export an asset inventory as CSV for ServiceNow integration ([snowExportAssetsCSV](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses**200**asset export [File](#)**401**Access token is missing or invalid [Problem](#)**GET /export/org/assets.servicenow.json**[Up](#)Exports the asset inventory as JSON ([snowExportAssetsJSON](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**Return type**array[[AssetServiceNow](#)]**Example data**

Content-Type: application/json

```
[ {
  "mac_manufacturer" : "Dell",
  "hw_version" : "2.0",
  "alive" : true,
  "service_count_udp" : 1,
  "asset_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "mac_vendors" : "Dell",
  "type" : "Server",
  "last_discovered" : "2006-01-02 15:04:05",
  "sys_class_name" : "cmdb_ci_iot",
  "lowest_rtt" : 1,
  "first_discovered" : "2006-01-02 15:04:05",
  "detected_by" : "icmp",
  "mac_address" : "11:22:33:44:55:66",
  "addresses_scope" : "192.168.100.1;192.168.100.2",
  "addresses_extra" : "192.168.0.5;192.168.0.3",
  "os_vendor" : "Microsoft",
  "last_updated" : "2006-01-02 15:04:05",
  "comments" : "File Server",
  "os_product" : "Windows 10",
  "os_version" : "1903",
  "service_count" : 10,
  "domains" : "runzero.com;runzero.local.lan",
  "service_count_tcp" : 7,
  "lowest_ttl" : 0,
  "ip_address" : "192.168.0.1",
  "service_count_arp" : 1,
  "tags" : "owner=IT;location=Austin",
  "site" : "Primary",
  "service_count_icmp" : 1,
  "organization" : "Headquarters",
  "macs" : "11:22:33:44:55:66",
  "name" : "www;server",
  "hw_product" : "PowerEdge",
  "hw_vendor" : "Dell",
  "newest_mac_age" : "2020-01-01"
}, {
  "mac_manufacturer" : "Dell",
  "hw_version" : "2.0",
  "alive" : true,
  "service_count_udp" : 1,
  "asset_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "mac_vendors" : "Dell",
  "type" : "Server",
  "last_discovered" : "2006-01-02 15:04:05",
  "sys_class_name" : "cmdb_ci_iot",
  "lowest_rtt" : 1,
  "first_discovered" : "2006-01-02 15:04:05",
  "detected_by" : "icmp",
  "mac_address" : "11:22:33:44:55:66",
  "addresses_scope" : "192.168.100.1;192.168.100.2",
  "addresses_extra" : "192.168.0.5;192.168.0.3",
  "os_vendor" : "Microsoft",
  "last_updated" : "2006-01-02 15:04:05",
  "comments" : "File Server",
  "os_product" : "Windows 10",
  "os_version" : "1903",
  "service_count" : 10,
  "domains" : "runzero.com;runzero.local.lan",
  "service_count_tcp" : 7,
  "lowest_ttl" : 0,
  "ip_address" : "192.168.0.1",
  "service_count_arp" : 1,
  "tags" : "owner=IT;location=Austin",
  "site" : "Primary",
  "service_count_icmp" : 1,
  "organization" : "Headquarters",
  "macs" : "11:22:33:44:55:66",
  "name" : "www;server",
  "hw_product" : "PowerEdge",
  "hw_vendor" : "Dell",
  "newest_mac_age" : "2020-01-01"
} ]
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**

filtered asset results

401Access token is missing or invalid [Problem](#)**GET /export/org/services.servicenow.csv**[Up](#)Export a service inventory as CSV for ServiceNow integration ([snowExportServicesCSV](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**Return type**

File

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- text/csv
- application/json

Responses**200**services export [File](#)**401**Access token is missing or invalid [Problem](#)**GET /export/org/assets.servicegraph.json**[Up](#)Exports the asset inventory as JSON ([snowServiceGraphExportAssetsJSON](#))**Query parameters****_oid (optional)***Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**Return type**array[AssetServiceNow](#)**Example data**

Content-Type: application/json

```
[ {
  "mac_manufacturer" : "Dell",
  "hw_version" : "2.0",
  "alive" : true,
  "service_count_udp" : 1,
  "asset_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "mac_vendors" : "Dell",
  "type" : "Server",
  "last_discovered" : "2006-01-02 15:04:05",
  "sys_class_name" : "cmdb_ci_iot",
  "lowest_rtt" : 1,
  "first_discovered" : "2006-01-02 15:04:05",
  "detected_by" : "icmp",
  "mac_address" : "11:22:33:44:55:66",
  "addresses_scope" : "192.168.100.1;192.168.100.2",
  "addresses_extra" : "192.168.0.5;192.168.0.3",
  "os_vendor" : "Microsoft",
  "last_updated" : "2006-01-02 15:04:05",
  "comments" : "File Server",
  "os_product" : "Windows 10",
  "os_version" : "1903",
  "service_count" : 10,
  "domains" : "runzero.com;runzero.local.lan",
  "service_count_tcp" : 7,
  "lowest_ttl" : 0,
  "ip_address" : "192.168.0.1",
  "service_count_arp" : 1,
  "tags" : "owner=IT;location=Austin",
  "site" : "Primary",
  "service_count_icmp" : 1,
  "organization" : "Headquarters",
  "macs" : "11:22:33:44:55:66",
  "name" : "www;server",
  "hw_product" : "PowerEdge",
  "hw_vendor" : "Dell",
  "newest_mac_age" : "2020-01-01"
}, {
  "mac_manufacturer" : "Dell",
  "hw_version" : "2.0",
  "alive" : true,
  "service_count_udp" : 1,
  "asset_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "mac_vendors" : "Dell",
  "type" : "Server",
  "last_discovered" : "2006-01-02 15:04:05",
  "sys_class_name" : "cmdb_ci_iot",
  "lowest_rtt" : 1,
  "first_discovered" : "2006-01-02 15:04:05",
  "detected_by" : "icmp",
  "mac_address" : "11:22:33:44:55:66",
  "addresses_scope" : "192.168.100.1;192.168.100.2",
  "addresses_extra" : "192.168.0.5;192.168.0.3",
  "os_vendor" : "Microsoft",
  "last_updated" : "2006-01-02 15:04:05",
  "comments" : "File Server",
  "os_product" : "Windows 10",
  "os_version" : "1903",
  "service_count" : 10,
  "domains" : "runzero.com;runzero.local.lan",
  "service_count_tcp" : 7,
  "lowest_ttl" : 0,
  "ip_address" : "192.168.0.1",
  "service_count_arp" : 1,
  "tags" : "owner=IT;location=Austin",
  "site" : "Primary",
  "service_count_icmp" : 1,
  "organization" : "Headquarters",
  "macs" : "11:22:33:44:55:66",
  "name" : "www;server",
  "hw_product" : "PowerEdge",
  "hw_vendor" : "Dell",
  "newest_mac_age" : "2020-01-01"
} ]
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**

filtered asset results

400Invalid request body [Problem](#)**401**Access token is missing or invalid [Problem](#)**403**Action not allowed for this license type [Problem](#)

Splunk

GET /export/org/assets-sync/created/assets.json Up

Exports the asset inventory in a sync-friendly manner using created_at as a checkpoint. Requires the Splunk entitlement.
[\(splunkAssetSyncCreatedJSON\)](#)

Query parameters**_oid (optional)***Query Parameter* — The current Organization default: null**search (optional)***Query Parameter* — an optional search string for filtering results default: null**fields (optional)***Query Parameter* — an optional list of fields to export, comma-separated default: null**since (optional)***Query Parameter* — an optional unix timestamp to use as a checkpoint default: null format: int64**Return type**[AssetsWithCheckpoint](#)**Example data**

Content-Type: application/json

```
{
  "assets" : [ {
    "addresses" : [ "192.168.0.1", "192.168.0.1" ],
    "first_seen" : 1576300370,
    "last_seen" : 1576300370
  } ]
}
```

```

"alive" : true,
"last_seen" : 1576300370,
"agent_name" : "LAPTOP-F4P1R6",
"credentials" : {
    "key" : {
        "key" : true
    }
},
"created_at" : 1576300370,
"service_count_udp" : 1,
"mac_vendors" : [ "Dell", "Dell" ],
"type" : "Server",
"last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"service_ports_udp" : [ "53", "53" ],
"hw" : "Dell PowerEdge 2500",
"lowest_rtt" : 1,
"service_ports_products" : [ "bind", "bind" ],
"updated_at" : 1576300370,
"detected_by" : "icmp",
"id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"service_ports_protocols" : [ "ssh", "ssh" ],
"org_name" : "Test Labs",
"addresses_extra" : [ "192.168.100.1", "192.168.100.1" ],
"comments" : "File Server",
"os" : "Ubuntu Linux",
"last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"os_version" : "18.04",
"service_count" : 10,
"domains" : [ "www", "www" ],
"service_count_tcp" : 7,
"newest_mac_vendor" : "Intel Corporate",
"lowest_ttl" : 0,
"newest_mac" : "11:22:33:44:55:66",
"service_count_arp" : 1,
"services" : {
    "key" : {
        "key" : "services"
    }
},
"service_ports_tcp" : [ "22", "22" ],
"tags" : {
    "key" : "tags"
},
"site_name" : "Primary",
"names" : [ "www", "www" ],
"service_count_icmp" : 1,
"rtts" : {
    "key" : ""
},
"organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"macs" : [ "11:22:33:44:55:66", "11:22:33:44:55:66" ],
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"attributes" : {
    "key" : "attributes"
},
"newest_mac_age" : 13040352000000000000
}, {
    "addresses" : [ "192.168.0.1", "192.168.0.1" ],
    "first_seen" : 1576300370,
    "alive" : true,
    "last_seen" : 1576300370,
    "agent_name" : "LAPTOP-F4P1R6",
    "credentials" : {
        "key" : {
            "key" : true
        }
    },
    "created_at" : 1576300370,
    "service_count_udp" : 1,
    "mac_vendors" : [ "Dell", "Dell" ],
    "type" : "Server",
    "last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "service_ports_udp" : [ "53", "53" ],
    "hw" : "Dell PowerEdge 2500",
    "lowest_rtt" : 1,
    "service_ports_products" : [ "bind", "bind" ],
}

```

```

"updated_at" : 1576300370,
"detected_by" : "icmp",
"id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"service_ports_protocols" : [ "ssh", "ssh" ],
"org_name" : "Test Labs",
"addresses_extra" : [ "192.168.100.1", "192.168.100.1" ],
"comments" : "File Server",
"os" : "Ubuntu Linux",
"last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"os_version" : "18.04",
"service_count" : 10,
"domains" : [ "www", "www" ],
"service_count_tcp" : 7,
"newest_mac_vendor" : "Intel Corporate",
"lowest_ttl" : 0,
"newest_mac" : "11:22:33:44:55:66",
"service_count_arp" : 1,
"services" : {
  "key" : {
    "key" : "services"
  }
},
"service_ports_tcp" : [ "22", "22" ],
"tags" : {
  "key" : "tags"
},
"site_name" : "Primary",
"names" : [ "www", "www" ],
"service_count_icmp" : 1,
"rtts" : {
  "key" : ""
},
"organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"macs" : [ "11:22:33:44:55:66", "11:22:33:44:55:66" ],
"site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
"attributes" : {
  "key" : "attributes"
},
"newest_mac_age" : 13040352000000000000
} ],
"since" : 1576300370
}

```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses**200**filtered asset results with a checkpoint wrapper [AssetsWithCheckpoint](#)**401**Access token is missing or invalid [Problem](#)
GET /export/org/assets-sync/updated/assets.json
Up

Exports the asset inventory in a sync-friendly manner using updated_at as a checkpoint. Requires the Splunk entitlement.
[\(splunkAssetSyncUpdatedJSON\)](#)

Query parameters**_oid (optional)***Query Parameter* — The current Organization default: null

search (optional)*Query Parameter* — an optional search string for filtering results default: null**fields (optional)***Query Parameter* — an optional list of fields to export, comma-separated default: null**since (optional)***Query Parameter* — an optional unix timestamp to use as a checkpoint default: null format: int64**Return type**[AssetsWithCheckpoint](#)**Example data**

Content-Type: application/json

```
{
  "assets" : [ {
    "addresses" : [ "192.168.0.1", "192.168.0.1" ],
    "first_seen" : 1576300370,
    "alive" : true,
    "last_seen" : 1576300370,
    "agent_name" : "LAPTOP-F4P1R6",
    "credentials" : {
      "key" : {
        "key" : true
      }
    },
    "created_at" : 1576300370,
    "service_count_udp" : 1,
    "mac_vendors" : [ "Dell", "Dell" ],
    "type" : "Server",
    "last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "service_ports_udp" : [ "53", "53" ],
    "hw" : "Dell PowerEdge 2500",
    "lowest_rtt" : 1,
    "service_ports_products" : [ "bind", "bind" ],
    "updated_at" : 1576300370,
    "detected_by" : "icmp",
    "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "service_ports_protocols" : [ "ssh", "ssh" ],
    "org_name" : "Test Labs",
    "addresses_extra" : [ "192.168.100.1", "192.168.100.1" ],
    "comments" : "File Server",
    "os" : "Ubuntu Linux",
    "last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "os_version" : "18.04",
    "service_count" : 10,
    "domains" : [ "www", "www" ],
    "service_count_tcp" : 7,
    "newest_mac_vendor" : "Intel Corporate",
    "lowest_ttl" : 0,
    "newest_mac" : "11:22:33:44:55:66",
    "service_count_arp" : 1,
    "services" : {
      "key" : {
        "key" : "services"
      }
    },
    "service_ports_tcp" : [ "22", "22" ],
    "tags" : {
      "key" : "tags"
    },
    "site_name" : "Primary",
    "names" : [ "www", "www" ],
    "service_count_icmp" : 1,
    "rtts" : {
      "key" : ""
    },
    "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "macs" : [ "11:22:33:44:55:66", "11:22:33:44:55:66" ],
    "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
    "attributes" : {
      "key" : "attributes"
    },
    "newest_mac_age" : 13040352000000000000
  } ]
}
```

```
{
  "addresses" : [ "192.168.0.1", "192.168.0.1" ],
  "first_seen" : 1576300370,
  "alive" : true,
  "last_seen" : 1576300370,
  "agent_name" : "LAPTOP-F4P1R6",
  "credentials" : {
    "key" : {
      "key" : true
    }
  },
  "created_at" : 1576300370,
  "service_count_udp" : 1,
  "mac_vendors" : [ "Dell", "Dell" ],
  "type" : "Server",
  "last_agent_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "service_ports_udp" : [ "53", "53" ],
  "hw" : "Dell PowerEdge 2500",
  "lowest_rtt" : 1,
  "service_ports_products" : [ "bind", "bind" ],
  "updated_at" : 1576300370,
  "detected_by" : "icmp",
  "id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "service_ports_protocols" : [ "ssh", "ssh" ],
  "org_name" : "Test Labs",
  "addresses_extra" : [ "192.168.100.1", "192.168.100.1" ],
  "comments" : "File Server",
  "os" : "Ubuntu Linux",
  "last_task_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "os_version" : "18.04",
  "service_count" : 10,
  "domains" : [ "www", "www" ],
  "service_count_tcp" : 7,
  "newest_mac_vendor" : "Intel Corporate",
  "lowest_ttl" : 0,
  "newest_mac" : "11:22:33:44:55:66",
  "service_count_arp" : 1,
  "services" : {
    "key" : {
      "key" : "services"
    }
  },
  "service_ports_tcp" : [ "22", "22" ],
  "tags" : {
    "key" : "tags"
  },
  "site_name" : "Primary",
  "names" : [ "www", "www" ],
  "service_count_icmp" : 1,
  "rtts" : {
    "key" : ""
  },
  "organization_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "macs" : [ "11:22:33:44:55:66", "11:22:33:44:55:66" ],
  "site_id" : "e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8",
  "attributes" : {
    "key" : "attributes"
  },
  "newest_mac_age" : 13040352000000000000
} ],
  "since" : 1576300370
}
```

Example data

Content-Type: application/json

```
{
  "detail" : "A human readable explanation specific to this occurrence of the problem.",
  "title" : "A short summary of the problem type.",
  "status" : 140
}
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

filtered asset results with a checkpoint wrapper [AssetsWithCheckpoint](#)

401

Access token is missing or invalid [Problem](#)

Models

[Jump to [Methods](#)]

Table of Contents

1. [APIClient](#) -
2. [APIKey](#) -
3. [APIKeyOptions](#) -
4. [AWSCredentialFields](#) -
5. [AccessToken](#) -
6. [Agent](#) -
7. [AgentSiteID](#) -
8. [Asset](#) -
9. [AssetComments](#) -
10. [AssetCriticality](#) -
11. [AssetCriticalitywithSearch](#) -
12. [AssetIDs](#) :
13. [AssetOwnershipType](#) -
14. [AssetOwnershipTypePost](#) -
15. [AssetOwnerships](#) -
16. [AssetOwnershipsWithSearch](#) -
17. [AssetOwnerships_ownerships_inner](#) -
18. [AssetServiceNow](#) -
19. [AssetTags](#) -
20. [AssetTagsWithSearch](#) -
21. [AssetsWithCheckpoint](#) -
22. [AzureClientSecretCredentialFields](#) -
23. [AzureUsernamePasswordCredentialFields](#) -
24. [BaseCustomIntegration](#) -
25. [BaseResponse](#) -
26. [CensysCredentialFields](#) -
27. [ComponentVersion](#) -
28. [Credential](#) -
29. [CredentialFields](#) -
30. [CredentialOptions](#) -
31. [CrowdstrikeCredentialFields](#) -
32. [CustomAttributes_value](#) -
33. [CustomIntegration](#) -
34. [DirectoryGroup](#) -
35. [DirectoryUser](#) -
36. [Event](#) -
37. [ExportToken](#) -
38. [ExportTokenOptions](#) -
39. [Group](#) -
40. [GroupMapping](#) -
41. [GroupPost](#) -
42. [GroupPut](#) -
43. [HealthCheckResponse](#) -
44. [HostedZone](#) -
45. [ImportAsset](#) -
46. [ImportTask](#) - ImportTask
47. [License](#) -
48. [MiradoreCredentialFields](#) -
49. [NetworkInterfaces_inner](#) -
50. [NewCustomIntegration](#) -
51. [OrgOptions](#) -
52. [Organization](#) -
53. [Problem](#) -
54. [SNMPv2CommunitiesCredentialFields](#) -

55. [SNMPv3CredentialFields](#) -
56. [SampleOptions](#) -
57. [ScanOptions](#) -
58. [ScanTemplate](#) -
59. [ScanTemplateOptions](#) -
60. [Search](#) -
61. [Service](#) -
62. [Site](#) -
63. [SiteOptions](#) -
64. [Site_data](#) -
65. [Software](#) -
66. [Task](#) -
67. [TaskBase](#) -
68. [TaskOptions](#) -
69. [URL](#) -
70. [User](#) -
71. [UserInviteOptions](#) -
72. [UserOptions](#) -
73. [VMwareCredentialFields](#) -
74. [Vulnerability](#) -
75. [Wireless](#) -
76. [updateBulkAssetOwners 200 response](#) -

[APIClient](#) -

[Up](#)

api_client_id (optional)
[UUID](#) format: uuid
api_client_secret (optional)
[String](#).

[APIKey](#) -

[Up](#)

id
[UUID](#) format: uuid
client_id (optional)
[UUID](#) format: uuid
organization_id (optional)
[UUID](#) format: uuid
created_at (optional)
[Long](#) format: int64
created_by (optional)
[String](#) format: email
comment (optional)
[String](#).
last_used_at (optional)
[Long](#) format: int64
last_used_ip (optional)
[String](#).
last_used_ua (optional)
[String](#).
counter (optional)
[Long](#) format: int64
usage_today (optional)
[Long](#) format: int64
usage_limit (optional)
[Long](#) format: int64
token (optional)
[String](#).
inactive (optional)
[Boolean](#)
type (optional)
[String](#).

APIKeyOptions - [Up](#)

comment (optional)
String.

organization_id (optional)
UUID format: uuid

AWSCredentialFields - [Up](#)

access_key
String format: string

secret_access_key
String format: string

regions (optional)
String format: string

use_cross_account_org (optional)
String format: string

role (optional)
String format: string

AccessToken - [Up](#)

access_token (optional)
String.

token_type (optional)
String.

expires_in (optional)
Integer

Agent - [Up](#)

A deployed service which performs scan tasks. Explorers may be referred to by their legacy name, Agents.

id
UUID format: uuid

client_id (optional)
UUID format: uuid

organization_id (optional)
UUID format: uuid

created_at (optional)
Long format: int64

updated_at (optional)
Long format: int64

host_id (optional)
String.

hub_id (optional)
UUID format: uuid

name (optional)
String.

site_id (optional)
UUID format: uuid

last_checkin (optional)
Long format: int64

os (optional)
String.

arch (optional)
String.

version (optional)
String.

external_ip (optional)
String.
internal_ip (optional)
String.
system_info (optional)
map[String, oas_any_type_not_mapped].
connected (optional)
Boolean.
inactive (optional)
Boolean.
deactivated_at (optional)
Long format: int64

AgentSiteID -

[Up](#)

site_id
UUID format: uuid

Asset -

[Up](#)

id
UUID format: uuid.
created_at (optional)
Long format: int64.
updated_at (optional)
Long format: int64.
organization_id (optional)
UUID format: uuid.
site_id (optional)
UUID format: uuid.
alive (optional)
Boolean.
first_seen (optional)
Long format: int64.
last_seen (optional)
Long format: int64.
detected_by (optional)
String.
type (optional)
String.
os (optional)
String.
os_version (optional)
String.
hw (optional)
String.
addresses (optional)
array[String].
addresses_extra (optional)
array[String].
macs (optional)
array[String]. format: mac.
mac_vendors (optional)
array[String].
names (optional)
array[String].
domains (optional)
array[String].

service_count (optional)
Long format: int64

service_count_tcp (optional)
Long format: int64

service_count_udp (optional)
Long format: int64

service_count_arp (optional)
Long format: int64

service_count_icmp (optional)
Long format: int64

lowest_ttl (optional)
Long format: int64

lowest_rtt (optional)
Long format: int64

last_agent_id (optional)
UUID format: uuid

last_task_id (optional)
UUID format: uuid

newest_mac (optional)
String format: mac

newest_mac_vendor (optional)
String

newest_mac_age (optional)
Long format: int64

comments (optional)
String

service_ports_tcp (optional)
array[String] format: port

service_ports_udp (optional)
array[String] format: port

service_ports_protocols (optional)
array[String]

service_ports_products (optional)
array[String]

org_name (optional)
String

site_name (optional)
String

agent_name (optional)
String

tags (optional)
map[String, String]

services (optional)
map[String, map[String, String]]

rtts (optional)
map[String, oas-any-type-not-mapped]

credentials (optional)
map[String, map[String, Boolean]]

attributes (optional)
map[String, String]

AssetComments -

[Up](#)

comments
String

AssetCriticality -

[Up](#)

comments (optional)
String.

AssetCriticalityWithSearch -

[Up](#)

criticality
String.

search
String.

AssetIDs -

[Up](#)

asset_ids
array[String].

AssetOwnershipType -

[Up](#)

id
UUID format: uuid

name
String.

reference (optional)
Long format: int64

order (optional)
Long format: int64

hidden (optional)
Boolean

AssetOwnershipTypePost -

[Up](#)

name
String.

reference (optional)
Long format: int64

order (optional)
Long format: int64

hidden (optional)
Boolean

AssetOwnerships -

[Up](#)

ownerships (optional)
array[AssetOwnerships_ownerships_inner].

AssetOwnershipsWithSearch -

[Up](#)

search
String.

ownerships
array[AssetOwnerships_ownerships_inner].

AssetOwnerships_ownerships_inner -

[Up](#)

ownership_type_id (optional)
String.

owner (optional)
String.

AssetServiceNow -[Up](#)

asset_id
[UUID](#) format: uuid

organization (optional)
[String](#).

site (optional)
[String](#).

detected_by (optional)
[String](#).

type (optional)
[String](#).

sys_class_name (optional)
[String](#).

os_vendor (optional)
[String](#).

os_product (optional)
[String](#).

os_version (optional)
[String](#).

hw_vendor (optional)
[String](#).

hw_product (optional)
[String](#).

hw_version (optional)
[String](#).

ip_address (optional)
[String](#).

addresses_scope (optional)
[String](#).

addresses_extra (optional)
[String](#).

mac_address (optional)
[String](#) format: mac

mac_manufacturer (optional)
[String](#).

newest_mac_age (optional)
[String](#).

macs (optional)
[String](#) format: mac

mac_vendors (optional)
[String](#).

name (optional)
[String](#).

tags (optional)
[String](#).

domains (optional)
[String](#).

service_count (optional)
[Long](#) format: int64

service_count_tcp (optional)
[Long](#) format: int64

service_count_udp (optional)
[Long](#) format: int64

service_count_arp (optional)
[Long](#) format: int64

service_count_icmp (optional)
[Long](#) format: int64

lowest_ttl (optional)

Long format: int64
lowest_rtt (optional)
Long format: int64
alive (optional)
Boolean
first_discovered (optional)
String
last_discovered (optional)
String
last_updated (optional)
String
comments (optional)
String

AssetTags -

[Up](#)

tags
String

AssetTagsWithSearch -

[Up](#)

tags
String.
search
String.

AssetsWithCheckpoint -

[Up](#)

since
Long format: int64
assets
array[Asset]

AzureClientSecretCredentialFields -

[Up](#)

client_id
String format: string
client_secret
String format: string
tenant_id
String format: string
multi_subscription (optional)
String format: string
subscription_id (optional)
String format: string

AzureUsernamePasswordCredentialFields -

[Up](#)

client_id
String format: string
tenant_id
String format: string
username
String format: string
password
String format: string

BaseCustomIntegration -

[Up](#)

name (optional)

String. The unique name of the custom integration, without spaces.

icon (optional)

byte[]. Base64 encoded png with maximum size 256x256 pixels format: byte

description (optional)

String. A text description of the custom integration

BaseResponse -

[Up](#)

Minimal identifying information with lifecycle metadata

id

UUID. The unique ID of the object format: uuid

clientId

UUID. The unique ID of the runZero client/customer account that owns the object format: uuid

createdById

UUID. The unique ID of the entity that created the object format: uuid

createdAt

Date. A timestamp indicating creation time of the object format: date-time

updatedAt

Date. A timestamp indicating last modified time of the object format: date-time

destroyedAt (optional)

Date. A timestamp indicating deletion time of the object format: date-time

CensysCredentialFields -

[Up](#)

client_id

String. format: string

client_secret

String. format: string

api_url (optional)

String. format: string

ComponentVersion -

[Up](#)

A component ID and version

id

String. format: string

version

String. format: string

Credential -

[Up](#)

id

UUID. format: uuid

client_id (optional)

UUID. format: uuid

name (optional)

String.

type (optional)

String. The service the credentials are for.

Enum:

miradore_api_key_v1
aws_access_secret
crowdstrike_api_key
azure_client_secret
azure_username_password
censys_search_api_key
snmpv2_community
snmpv3_credential
vmware_username_password

created_at (optional)

Long format: int64
created_by_id (optional)
UUID format: uuid
created_by_email (optional)
String format: email
acl (optional)
`map[String,oas-any-type-not-mapped]`
global (optional)
Boolean
cidrs (optional)
`array[String]`
last_used_at (optional)
Long format: int64
last_used_by_id (optional)
UUID format: uuid

CredentialFields -[Up](#)

hostname
String format: string
api_key
String format: string
access_key
String format: string
secret_access_key
String format: string
regions (optional)
String format: string
use_cross_account_org (optional)
String format: string
role (optional)
String format: string
client_id
String format: string
client_secret
String format: string
tenant_id
String format: string
multi_subscription (optional)
String format: string
subscription_id (optional)
String format: string
username
String format: string
password
String format: string
api_url
String format: string
community
String format: string
context (optional)
String format: string
auth-protocol (optional)
String format: string
auth-passphrase (optional)
String format: string
privacy-protocol (optional)
String format: string

privacy-passphrase (optional)*String*, format: string**insecure (optional)***String*, format: string**thumbprints (optional)***String*, format: string**CredentialOptions -**[Up](#)**name (optional)***String***type (optional)***String*

Enum:

*miradore_api_key_v1**aws_access_secret***acl (optional)***map[String,oas any type not mapped]***global (optional)***Boolean***cidrs (optional)***String***secret (optional)***CredentialFields***CrowdStrikeCredentialFields -**[Up](#)**client_id***String*, format: string**client_secret***String*, format: string**api_url***String*, format: string**CustomAttributes_value -**[Up](#)**CustomIntegration -**[Up](#)**name***String*. The unique name of the custom integration, without spaces.**icon (optional)***byte[]*. Base64 encoded png with maximum size 256x256 pixels format: byte**description (optional)***String*. A text description of the custom integration**id***UUID*. The unique ID of the object format: uuid**clientId***UUID*. The unique ID of the runZero client/customer account that owns the object format: uuid**createdById***UUID*. The unique ID of the entity that created the object format: uuid**createdAt***Date*. A timestamp indicating creation time of the object format: date-time**updatedAt***Date*. A timestamp indicating last modified time of the object format: date-time**destroyedAt (optional)***Date*. A timestamp indicating deletion time of the object format: date-time**DirectoryGroup -**[Up](#)

directory_group_id (optional)
[UUID](#) format: uuid

directory_group_organization_id (optional)
[UUID](#) format: uuid

directory_group_site_id (optional)
[UUID](#) format: uuid

directory_group_source_id (optional)
[Integer](#)

directory_group_created_at (optional)
[Long](#) format: int64

directory_group_updated_at (optional)
[Long](#) format: int64

directory_group_group_id (optional)
[String](#)

directory_group_user_count (optional)
[Long](#) format: int64

directory_group_name (optional)
[String](#)

directory_group_display_name (optional)
[String](#)

directory_group_description (optional)
[String](#)

directory_group_email (optional)
[String](#) format: email

directory_group_email_normalized (optional)
[String](#) format: email

directory_group_attributes (optional)
[map\[String, String\]](#).

DirectoryUser -

[Up](#)

directory_user_id (optional)
[UUID](#) format: uuid

directory_user_organization_id (optional)
[UUID](#) format: uuid

directory_user_site_id (optional)
[UUID](#) format: uuid

directory_user_source_id (optional)
[Integer](#)

directory_user_created_at (optional)
[Long](#) format: int64

directory_user_updated_at (optional)
[Long](#) format: int64

directory_user_user_id (optional)
[String](#)

directory_user_group_ids (optional)
[array\[String\]](#)

directory_user_display_name (optional)
[String](#)

directory_user_name (optional)
[String](#)

directory_user_first_name (optional)
[String](#)

directory_user_last_name (optional)
[String](#)

directory_user_description (optional)
[String](#)

directory_user_email (optional)

`String` format: email
`directory_user_email_normalized` (optional)
`String` format: email
`directory_user_phone` (optional)
`String`
`directory_user_title` (optional)
`String`
`directory_user_location` (optional)
`String`
`directory_user_last_logon_at` (optional)
`Long` format: int64
`directory_user_attributes` (optional)
`map[String, String]`.

Event -[Up](#)

`id` (optional)
`UUID` format: uuid
`created_at` (optional)
`Long` format: int64
`client_id` (optional)
`UUID` format: uuid
`organization_id` (optional)
`UUID` format: uuid
`site_id` (optional)
`UUID` format: uuid
`action` (optional)
`String`
`source_id` (optional)
`UUID` format: uuid
`source_name` (optional)
`String`
`source_type` (optional)
`String`
`target_id` (optional)
`UUID` format: uuid
`target_name` (optional)
`String`
`target_type` (optional)
`String`
`success` (optional)
`Boolean`
`details` (optional)
`map[String, oas-any-type-not-mapped]`.
`state` (optional)
`String`
`processor_id` (optional)
`UUID` format: uuid
`processed_at` (optional)
`Long` format: int64

ExportToken -[Up](#)

`id`
`oas-any-type-not-mapped` format: uuid
`token` (optional)
`String`
`comment` (optional)
`String`

created_at (optional)
Long format: int64
last_used_at (optional)
Long format: int64
last_used_by (optional)
String.
counter (optional)
Long format: int64

ExportTokenOptions -

[Up](#)

comment (optional)
String.

Group -

[Up](#)

id
UUID format: uuid
description (optional)
String.
name (optional)
String.
role_summary (optional)
String.
user_count (optional)
Long format: int64
created_by_email (optional)
String.
created_at (optional)
Long format: int64
updated_at (optional)
Long format: int64
expires_at (optional)
Long format: int64
org_default_role (optional)
String.
org_roles (optional)
map[String, oas-any-type-not-mapped].

GroupMapping -

[Up](#)

id
UUID format: uuid
group_id
UUID format: uuid
group_name (optional)
String.
sso_attribute
String.
sso_value
String.
description (optional)
String.
created_by_email (optional)
String.
created_at (optional)
Long format: int64
updated_at (optional)

[Long](#), format: int64

GroupPost -

[Up](#)

description (optional)
[String](#).

name (optional)
[String](#).

expires_at (optional)
[Long](#), format: int64

org_default_role (optional)
[String](#).

org_roles (optional)
[map\[String,oas any type not mapped\]](#).

GroupPut -

[Up](#)

id (optional)
[UUID](#) format: uuid

description (optional)
[String](#).

name (optional)
[String](#).

expires_at (optional)
[Long](#), format: int64

org_default_role (optional)
[String](#).

org_roles (optional)
[map\[String,oas any type not mapped\]](#).

HealthCheckResponse -

[Up](#)

A health check response and version

status
[String](#), format: string

version
[String](#), format: string

HostedZone -

[Up](#)

A hosted service which performs scan tasks. Hosted zones are only available to Enterprise customers.

id
[UUID](#) The ID of the hosted zone format: uuid

name (optional)
[String](#).

enabled (optional)
[Boolean](#) Whether the hosted zone is enabled

updated_at (optional)
[Date](#) The last modification time of the hosted zone format: date-time

processor_id (optional)
[UUID](#) The processor ID assigned to the hosted zone format: uuid

explorers_concurrency (optional)
[Long](#) The number of concurrent explorer tasks that can be executed format: int64

explorers_total (optional)
[Long](#) The number of explorers available in the zone format: int64

tasks_active (optional)
[Long](#) The number of tasks executing in the zone format: int64

tasks_waiting (optional)
[Long](#) The number of tasks waiting to execute in the zone format: int64

organization_id (optional)

UUID The ID of the organization the hosted zone is assigned to format: uuid

ImportAsset -

[Up](#)

Represents a custom asset to be created or merged after import.

id

String. Any value which can uniquely identify the asset within the custom integration.

runZeroID (optional)

UUID The unique identifier of the runZero asset to merge into. format: uuid

networkInterfaces (optional)

array[NetworkInterfaces_inner] The asset's networking configuration.

hostnames (optional)

array[String]. Represents hostnames the asset is assigned or reachable at. These can be fully-qualified hostnames with the domain name, or a short hostname.

domain (optional)

String. Represents a single domain name which could be applied to all non-fqdns in the hostnames field.

firstSeenTS (optional)

Date Represents the earliest time the asset was seen by the custom integration reporting it, using a date string as defined by RFC 3339, section 5.6. format: date-time

os (optional)

String. The name of the asset's operating system. It is advisable to keep the data clean by normalizing to existing values when possible.

osVersion (optional)

String. The version of the asset's operating system. It is advisable to keep the data clean by normalizing to existing values when possible.

manufacturer (optional)

String. The manufacturer of the operating system of the asset. It is advisable to keep the data clean by normalizing to existing values when possible.

model (optional)

String. The hardware model of the asset. It is advisable to keep the data clean by normalizing to existing values when possible.

tags (optional)

array[String]. Arbitrary string tags applied to the asset.

deviceType (optional)

String.

customAttributes (optional)

map[String,CustomAttributes_value]. Flat map of arbitrary string key/value pairs representing custom attribute data not described in properties above. Note the maximum number of keys and length of values. Additionally, property names may only be 256 characters long.

ImportTask - ImportTask

[Up](#)

Information which describes the task created when asset data is imported.

name

String.

description (optional)

String.

excludeUnknown (optional)

Boolean Instructs the data ingestion process whether to skip assets which do not merge into an existing asset in the asset inventory

tags (optional)

array[String]. Arbitrary string tag values which are applied to the asset data import task created.

License -

[Up](#)

id (optional)

UUID format: uuid

created_at (optional)

Long format: int64

updated_at (optional)

`Long` format: int64
name (optional)
`String`.
activated_at (optional)
`Long` format: int64
license_type (optional)
`String`.
license_expiration (optional)
`Long` format: int64
license_max_assets (optional)
`Long` format: int64
license_live_asset_count (optional)
`Long` format: int64
license_project_asset_count (optional)
`Long` format: int64
via_reseller (optional)
`Boolean`.
phone (optional)
`String`.
address_street (optional)
`String`.
address_country (optional)
`String`.
address_city (optional)
`String`.
address_region (optional)
`String`.
address_postal (optional)
`String`.
subscription_period_start (optional)
`Long` format: int64
subscription_period_end (optional)
`Long` format: int64
subscription_cancel_at (optional)
`Long` format: int64
subscription_canceled_at (optional)
`Long` format: int64
settings (optional)
`map[String,oas-any-type-not-mapped]`.
sso_type (optional)
`String`.
sso_domain (optional)
`String`.
sso_mode (optional)
`String`.
sso_login_message (optional)
`String`.
sso_login_issuer_url (optional)
`String`.
sso_login_login_url (optional)
`String`.
sso_login_logout_url (optional)
`String`.
sso_default_role (optional)
`String`.
partner (optional)
`String`.

MiradoreCredentialFields -[Up](#)

hostname
`String` format: string

api_key
`String` format: string

NetworkInterfaces_inner -[Up](#)

ipv4Addresses (optional)
`array[String]`. Represents IPv4 addresses. Addresses are ordered from most to least likely to uniquely identify the asset. format: ipv4

ipv6Addresses (optional)
`array[String]`. Represents the IPv6 addresses. Addresses are ordered from most to least likely to uniquely identify the asset. format: ipv6

macAddress (optional)
`String`. Represents a MAC address in IEEE 802 MAC/EUI-48, or EUI-64 form in one of the following formats: 01:23:45:67:89:AB 01:23:45:67:89:ab:cdef 01-23-45-67-89-ab 01-23-45-67-89-ab-cd-ef 0123.4567.89ab 0123.4567.89ab.cdef 0123 4567 89ab cdEF

NewCustomIntegration -[Up](#)

name
`String`. The unique name of the custom integration, without spaces.

icon (optional)
`byte[]`. Base64 encoded png with maximum size 256x256 pixels format: byte

description (optional)
`String`. A text description of the custom integration

OrgOptions -[Up](#)

name (optional)
`String`.

description (optional)
`String`.

parent_id (optional)
`UUID` format: uuid

expiration_assets_stale (optional)
`BigDecimal` format: number

expiration_assets_offline (optional)
`BigDecimal` format: number

expiration_scans (optional)
`BigDecimal` format: number

Organization -[Up](#)

id
`UUID` format: uuid

created_at (optional)
`Long` format: int64

updated_at (optional)
`Long` format: int64

client_id (optional)
`UUID` format: uuid

download_token (optional)
`String`.

download_token_created_at (optional)
`Long` format: int64

name
`String`.

description (optional)
[String](#).

inactive (optional)
[Boolean](#).

deactivated_at (optional)
[Long](#) format: int64

service_count (optional)
[Long](#) format: int64

service_count_tcp (optional)
[Long](#) format: int64

service_count_udp (optional)
[Long](#) format: int64

service_count_arp (optional)
[Long](#) format: int64

service_count_icmp (optional)
[Long](#) format: int64

asset_count (optional)
[Long](#) format: int64

project (optional)
[Boolean](#).

parent_id (optional)
[UUID](#) format: uuid

expiration_assets_stale (optional)
[Long](#) format: int64

expiration_assets_offline (optional)
[Long](#) format: int64

expiration_scans (optional)
[Long](#) format: int64

export_token (optional)
[String](#).

export_token_created_at (optional)
[Long](#) format: int64

export_token_last_used_at (optional)
[Long](#) format: int64

export_token_last_used_by (optional)
[String](#).

export_token_counter (optional)
[Long](#) format: int64

Problem -[Up](#)

RFC7807 Problem JSON object from <https://opensource.zalando.com/restful-api-guidelines/models/problem-1.0.1.yaml> without the standard 'type' and 'instance' fields.

title (optional)

[String](#). A short summary of the problem type. Written in English and readable for engineers, usually not suited for non technical stakeholders and not localized.

status (optional)

[Integer](#). The HTTP status code generated by the origin server for this occurrence of the problem. format: int32

detail (optional)

[String](#). A human readable explanation specific to this occurrence of the problem that is helpful to locate the problem and give advice on how to proceed. Written in English and readable for engineers, usually not suited for non technical stakeholders and not localized.

SNMPv2CommunitiesCredentialFields -[Up](#)**community**

[String](#) format: string

SNMPv3CredentialFields -[Up](#)

username
`String` format: string

context (optional)
`String` format: string

auth-protocol (optional)
`String` format: string

auth-passphrase (optional)
`String` format: string

privacy-protocol (optional)
`String` format: string

privacy-passphrase (optional)
`String` format: string

SampleOptions -[Up](#)

Options which can be set to create or modify traffic sampling.

explorer (optional)
`UUID` format: uuid

agent (optional)
`UUID` format: uuid

targets (optional)
`String`

excludes (optional)
`String`

tags (optional)
`String`

interfaces
`String`

ScanOptions -[Up](#)

Options which can be set to create or modify a scan.

targets
`String`

excludes (optional)
`String`

scan-name (optional)
`String`

scan-description (optional)
`String`. A description of the scan.

scan-template (optional)
`UUID` format: uuid

scan-frequency (optional)
`String`. A string time duration value representing execution frequency, if scheduled to repeat.
 Enum:
`once`
`hourly`
`daily`
`weekly`
`monthly`
`continuous`

scan-start (optional)
`String`. Unix timestamp value indicating when the template was created.

scan-tags (optional)
`String`

scan-grace-period (optional)
`String`

agent (optional)
`UUID` format: uuid

explorer (optional)

UUID format: uuid

hosted-zone-id (optional)

String. The string 'auto' will use any available hosted zone. Otherwise, provide the string name (hostedzone1) or UUID (e77602e0-3fb8-4734-aef9-fbc6fdcb0fa8) of a hosted zone.

hosted-zone-name (optional)

String. The string 'auto' will use any available hosted zone. Otherwise, provide the string name (hostedzone1) of the hosted zone.

rate (optional)

String.

max-host-rate (optional)

String.

passes (optional)

String.

max-attempts (optional)

String.

max-sockets (optional)

String.

max-group-size (optional)

String.

max-ttl (optional)

String.

tos (optional)

String.

tcp-ports (optional)

String.

tcp-excludes (optional)

String.

screenshots (optional)

String.

nameservers (optional)

String.

subnet-ping (optional)

String.

subnet-ping-net-size (optional)

String.

subnet-ping-probes (optional)

String. Optional subnet ping probe list as comma separated strings. The example shows possibilities.

subnet-ping-sample-rate (optional)

String.

host-ping (optional)

String.

host-ping-probes (optional)

String. Optional host ping probe list as comma separated strings. The example shows possibilities.

probes (optional)

String. Optional probe list, otherwise all probes are used

ScanTemplate -

[Up](#)

A scan task template

id

UUID ID of the template. format: uuid

name (optional)

String. The name of the template.

description (optional)

String. The description of the template.

client_id (optional)

UUID ID of the account which owns the template. format: uuid

organization_id

runZero API documentation

UUID ID of the organization the template is available in. format: uuid

agent_id (optional)
UUID ID of the explorer which may execute the template. format: uuid

site_id (optional)
UUID ID of the site the template is being used in. format: uuid

cruncher_id (optional)
UUID ID of the runZero cruncher the task is executing on. format: uuid

created_at (optional)
Long Unix timestamp value indicating when the template was created. format: int64

created_by (optional)
String The username of the account which created the template.

created_by_user_id (optional)
UUID The ID of the account which created the template. format: uuid

updated_at (optional)
Long Unix timestamp value indicating when the template was last modified. format: int64

type (optional)
String The type of task the template creates.

status (optional)
String The status of the last task using the template.

error (optional)
String The error message, if any, of the last task using the template.

params (optional)
map[String, String] A number of task parameter values. Currently there is no authoritative list of in-use values. See existing templates for examples.

stats (optional)
map[String, oas-any-type-not-mapped] A map of statistics about the last task executed with the template. Currently there is no authoritative list of in-use values. See existing templates for examples.

hidden (optional)
Boolean A flag indicating whether the item is hidden from common view.

parent_id (optional)
UUID The ID of the parent entity of the task scheduled. format: uuid

recur (optional)
Boolean A flag representing whether derived tasks are scheduled to repeat.

recur_frequency (optional)
String A string time duration value representing execution frequency, if scheduled to repeat. You may use values including as once, hourly, daily, weekly, monthly, continuous

start_time (optional)
Long Unix timestamp representing the next execution time. format: int64

recur_last (optional)
Long Unix timestamp representing the last execution if scheduled to repeat. format: int64

recur_next (optional)
Long Unix timestamp representing the next execution if scheduled to repeat. format: int64

recur_last_task_id (optional)
UUID The ID of the task that last executed if scheduled to repeat. format: uuid

grace_period (optional)
String Additional time beyond hard expiration deadline by which the task may still be allowed to execute.

custom_integration_id (optional)
UUID The ID of the custom integration source, if the last task executed with this template was an import of Asset Data. format: uuid

source_id (optional)
String The numeric ID of the data source, if the task executed with this template is a runZero scan or third party data connection import.

template_id (optional)
UUID The ID of the template. format: uuid

size_site (optional)
Long The size in assets of the site the last task the template was executed against. format: int64

size_data (optional)
Long The total size of result data of the last task the template was used with. format: int64

size_results (optional)
Long The number of results in the last task the template was used with. format: int64

hosted_zone_id (optional)

UUID The ID of the hosted zone that ran the last task the template was used with. format: uuid

linked_task_count (optional)

Integer The number of tasks derived from the template. format: int32

global

Boolean Whether the template is globally available to all organizations.

acl

map[String, oas any type not mapped] A map of IDs to strings which describe how the template may be accessed. Currently there is no authoritative list of in-use values. See existing templates for examples.

ScanTemplateOptions -

[Up](#)

Options which can be set to create a scan template.

name

String Name of the template.

description (optional)

String Description of the template.

organization_id

UUID The ID of the organization the template will be created in format: uuid

params (optional)

map[String, String] A number of scan parameter values. Currently there is no authoritative list of acceptable values. See existing templates for examples.

global

Boolean Whether the template is globally available to all organizations.

acl

map[String, oas any type not mapped] A map of IDs to strings which describe how the template may be accessed. Currently there is no authoritative list of acceptable values. See existing templates for examples.

Search -

[Up](#)

search

String

Service -

[Up](#)

service_id

UUID format: uuid

service_asset_id (optional)

UUID format: uuid

service_created_at (optional)

Long format: int64

service_updated_at (optional)

Long format: int64

service_address (optional)

String

service_transport (optional)

String

service_vhost (optional)

String

service_port (optional)

String format: port

service_data (optional)

map[String, String]

service_protocol (optional)

String

service_summary (optional)

String

service_screenshot_link (optional)

`String.`
service_link (optional)
`String.`
id
`UUID` format: uuid
created_at (optional)
`Long` format: int64
updated_at (optional)
`Long` format: int64
organization_id (optional)
`UUID` format: uuid
site_id (optional)
`UUID` format: uuid
alive (optional)
`Boolean`
first_seen (optional)
`Long` format: int64
last_seen (optional)
`Long` format: int64
detected_by (optional)
`String.`
type (optional)
`String.`
os (optional)
`String.`
os_version (optional)
`String.`
hw (optional)
`String.`
addresses (optional)
`array[String].`
addresses_extra (optional)
`array[String].`
macs (optional)
`array[String].` format: mac
mac_vendors (optional)
`array[String].`
names (optional)
`array[String].`
domains (optional)
`array[String].`
service_count (optional)
`Long` format: int64
service_count_tcp (optional)
`Long` format: int64
service_count_udp (optional)
`Long` format: int64
service_count_arp (optional)
`Long` format: int64
service_count_icmp (optional)
`Long` format: int64
lowest_ttl (optional)
`Long` format: int64
lowest_rtt (optional)
`Long` format: int64
last_agent_id (optional)
`UUID` format: uuid
last_task_id (optional)
`UUID` format: uuid

newest_mac (optional)
String. format: mac

newest_mac_vendor (optional)
String.

newest_mac_age (optional)
Long. format: int64

comments (optional)
String.

service_ports_tcp (optional)
array[String]. format: port

service_ports_udp (optional)
array[String]. format: port

service_ports_protocols (optional)
array[String].

service_ports_products (optional)
array[String].

org_name (optional)
String.

site_name (optional)
String.

agent_name (optional)
String.

tags (optional)
map[String, String].

services (optional)
map[String, map[String, String]].

rtts (optional)
map[String, oas any type not mapped].

credentials (optional)
map[String, map[String, Boolean]].

attributes (optional)
map[String, String].

[Site](#) - [Up](#)

data (optional)
[Site data](#)

[SiteOptions](#) - [Up](#)

name
String.

description (optional)
String.

scope (optional)
String.

excludes (optional)
String.

subnets (optional)
map[String, oas any type not mapped].

[Site_data](#) - [Up](#)

id (optional)
UUID format: uuid

created_at (optional)
Long format: int64

updated_at (optional)

Long, format: int64
name (optional)
String
description (optional)
String
scope (optional)
String
excludes (optional)
String
subnets (optional)
map[String, oas any type not mapped].

Software -

[Up](#)

software_id (optional)
UUID, format: uuid
software_asset_id (optional)
UUID, format: uuid
software_organization_id (optional)
UUID, format: uuid
software_source_id (optional)
Integer
software_created_at (optional)
Long, format: int64
software_updated_at (optional)
Long, format: int64
software_service_address (optional)
String
software_service_transport (optional)
String
software_service_port (optional)
Long, format: int64
software_installed_at (optional)
Long, format: int64
software_installed_size (optional)
Long, format: int64
software_installed_from (optional)
String
software_app_id (optional)
String
software_part (optional)
String
software_vendor (optional)
String
software_product (optional)
String
software_version (optional)
String
software_update (optional)
String
software_edition (optional)
String
software_language (optional)
String
software_sw_edition (optional)
String
software_target_sw (optional)
String

software_target_hw (optional)
`String`

software_other (optional)
`String`

software_cpe23 (optional)
`String`

software_attributes (optional)
`map[String, String]`

Task -[Up](#)

A task object

id
`UUID` format: uuid

name (optional)
`String`

description (optional)
`String`

template_id (optional)
`UUID` format: uuid

client_id (optional)
`UUID` format: uuid

organization_id (optional)
`UUID` format: uuid

agent_id (optional)
`UUID` format: uuid

hosted_zone_id (optional)
`UUID` The ID of the Hosted Zone which executes the task. If the format: uuid

site_id (optional)
`UUID` format: uuid

cruncher_id (optional)
`UUID` format: uuid

created_at (optional)
`Long` format: int64

created_by (optional)
`String`

created_by_user_id (optional)
`UUID` format: uuid

custom_integration_id (optional)
`UUID` The ID of the custom integration source, if the last task executed with this template was an import of Asset Data. format: uuid

source_id (optional)
`Integer` The numeric ID of the data source, if the task executed with this template is a runZero scan or third party data connection import.

updated_at (optional)
`Long` format: int64

type (optional)
`String`

status (optional)
`String`

error (optional)
`String`

params (optional)
`map[String, String]`

stats (optional)
`map[String, oas-any-type-not-mapped]`

hidden (optional)
`Boolean`

parent_id (optional)

[UUID](#) format: uuid
recur (optional)
[Boolean](#)
recur_frequency (optional)
[String](#)
start_time (optional)
[Long](#) format: int64
recur_last (optional)
[Long](#) format: int64
recur_next (optional)
[Long](#) format: int64
recur_last_task_id (optional)
[UUID](#) format: uuid

TaskBase -[Up](#)

All fields of a Task with none required

id (optional)
[UUID](#) format: uuid
name (optional)
[String](#)
description (optional)
[String](#)
template_id (optional)
[UUID](#) format: uuid
client_id (optional)
[UUID](#) format: uuid
organization_id (optional)
[UUID](#) format: uuid
agent_id (optional)
[UUID](#) format: uuid
hosted_zone_id (optional)
[UUID](#) The ID of the Hosted Zone which executes the task. If the format: uuid
site_id (optional)
[UUID](#) format: uuid
cruncher_id (optional)
[UUID](#) format: uuid
created_at (optional)
[Long](#) format: int64
created_by (optional)
[String](#)
created_by_user_id (optional)
[UUID](#) format: uuid
custom_integration_id (optional)
[UUID](#) The ID of the custom integration source, if the last task executed with this template was an import of Asset Data. format: uuid
source_id (optional)
[Integer](#) The numeric ID of the data source, if the task executed with this template is a runZero scan or third party data connection import.
updated_at (optional)
[Long](#) format: int64
type (optional)
[String](#)
status (optional)
[String](#)
error (optional)
[String](#)
params (optional)
[map\[String, String\]](#)

stats (optional)
`map[String,oas any type not mapped]`.

hidden (optional)
`Boolean`

parent_id (optional)
`UUID` format: uuid

recur (optional)
`Boolean`

recur_frequency (optional)
`String`.

start_time (optional)
`Long` format: int64

recur_last (optional)
`Long` format: int64

recur_next (optional)
`Long` format: int64

recur_last_task_id (optional)
`UUID` format: uuid

TaskOptions -[Up](#)

Options which can be set to create or modify a task.

hosted_zone_name (optional)
`String` The string 'auto' will use any available hosted zone. Otherwise, provide the string name (hostedzone1) of the hosted zone.

id (optional)
`UUID` format: uuid

name (optional)
`String`.

description (optional)
`String`.

template_id (optional)
`UUID` format: uuid

client_id (optional)
`UUID` format: uuid

organization_id (optional)
`UUID` format: uuid

agent_id (optional)
`UUID` format: uuid

hosted_zone_id (optional)
`UUID` The ID of the Hosted Zone which executes the task. If the format: uuid

site_id (optional)
`UUID` format: uuid

cruncher_id (optional)
`UUID` format: uuid

created_at (optional)
`Long` format: int64

created_by (optional)
`String`.

created_by_user_id (optional)
`UUID` format: uuid

custom_integration_id (optional)
`UUID` The ID of the custom integration source, if the last task executed with this template was an import of Asset Data. format: uuid

source_id (optional)
`Integer` The numeric ID of the data source, if the task executed with this template is a runZero scan or third party data connection import.

updated_at (optional)
`Long` format: int64

type (optional)
`String`.

status (optional)
`String`.

error (optional)
`String`.

params (optional)
`map[String, String]`.

stats (optional)
`map[String, oas-any-type-not-mapped]`.

hidden (optional)
`Boolean`

parent_id (optional)
`UUID` format: uuid

recur (optional)
`Boolean`

recur_frequency (optional)
`String`.

start_time (optional)
`Long` format: int64

recur_last (optional)
`Long` format: int64

recur_next (optional)
`Long` format: int64

recur_last_task_id (optional)
`UUID` format: uuid

URL -[Up](#)

A URL to a resource

id (optional)
`String` format: url

User -[Up](#)

id
`UUID` format: uuid

client_id (optional)
`UUID` format: uuid

created_at (optional)
`Long` format: int64

updated_at (optional)
`Long` format: int64

first_name (optional)
`String`.

last_name (optional)
`String`.

email (optional)
`String`.

client_admin (optional)
`Boolean`

org_default_role (optional)
`String`.

org_roles (optional)
`map[String, oas-any-type-not-mapped]`.

reset_token_expiration (optional)
`Long` format: int64

invite_token_expiration (optional)
`Long` format: int64

last_login_ip (optional)
String.

last_login_at (optional)
Long format: int64

last_login_ua (optional)
String.

sso_only (optional)
Boolean

login_failures (optional)
Long format: int64

UserInviteOptions -

[Up](#)

first_name (optional)
String.

last_name (optional)
String.

email (optional)
String.

client_admin (optional)
Boolean

org_default_role (optional)
String.

org_roles (optional)
map[String,oas any type not mapped].

subject (optional)
String.

message (optional)
String.

UserOptions -

[Up](#)

first_name (optional)
String.

last_name (optional)
String.

email (optional)
String.

client_admin (optional)
Boolean

org_default_role (optional)
String.

org_roles (optional)
map[String,oas any type not mapped].

VMwareCredentialFields -

[Up](#)

username
String format: string

password
String format: string

insecure (optional)
String format: string

thumbprints (optional)
String format: string

Vulnerability -

[Up](#)

vulnerability_id (optional)
[UUID](#) format: uuid

vulnerability_asset_id (optional)
[UUID](#) format: uuid

vulnerability_organization_id (optional)
[UUID](#) format: uuid

vulnerability_source_id (optional)
[Integer](#)

vulnerability_created_at (optional)
[Long](#) format: int64

vulnerability_updated_at (optional)
[Long](#) format: int64

vulnerability_service_address (optional)
[String](#)

vulnerability_service_transport (optional)
[String](#)

vulnerability_service_port (optional)
[Long](#) format: int64

vulnerability_cpe23 (optional)
[String](#)

vulnerability_vuln_id (optional)
[String](#)

vulnerability_category (optional)
[String](#)

vulnerability_name (optional)
[String](#)

vulnerability_description (optional)
[String](#)

vulnerability_solution (optional)
[String](#)

vulnerability_cve (optional)
[String](#)

vulnerability_cvss2_base_score (optional)
[Double](#) format: double

vulnerability_cvss2_temporal_score (optional)
[Double](#) format: double

vulnerability_cvss3_base_score (optional)
[Double](#) format: double

vulnerability_cvss3_temporal_score (optional)
[Double](#) format: double

vulnerability_severity (optional)
[String](#)

vulnerability_severity_score (optional)
[Double](#) format: double

vulnerability_risk (optional)
[String](#)

vulnerability_risk_score (optional)
[Double](#) format: double

vulnerability_published_at (optional)
[Long](#) format: int64

vulnerability_first_detected_at (optional)
[Long](#) format: int64

vulnerability_last_detected_at (optional)
[Long](#) format: int64

vulnerability_attributes (optional)
[map\[String, String\]](#)

id
[UUID](#) format: uuid

created_at (optional)
[Long](#) format: int64

updated_at (optional)
[Long](#) format: int64

organization_id (optional)
[UUID](#) format: uuid

site_id (optional)
[UUID](#) format: uuid

alive (optional)
[Boolean](#)

first_seen (optional)
[Long](#) format: int64

last_seen (optional)
[Long](#) format: int64

detected_by (optional)
[String](#).

type (optional)
[String](#).

os (optional)
[String](#).

os_version (optional)
[String](#).

hw (optional)
[String](#).

addresses (optional)
[array\[String\]](#).

addresses_extra (optional)
[array\[String\]](#).

macs (optional)
[array\[String\]](#) format: mac

mac_vendors (optional)
[array\[String\]](#).

names (optional)
[array\[String\]](#).

domains (optional)
[array\[String\]](#).

service_count (optional)
[Long](#) format: int64

service_count_tcp (optional)
[Long](#) format: int64

service_count_udp (optional)
[Long](#) format: int64

service_count_arp (optional)
[Long](#) format: int64

service_count_icmp (optional)
[Long](#) format: int64

lowest_ttl (optional)
[Long](#) format: int64

lowest_rtt (optional)
[Long](#) format: int64

last_agent_id (optional)
[UUID](#) format: uuid

last_task_id (optional)
[UUID](#) format: uuid

newest_mac (optional)
[String](#) format: mac

newest_mac_vendor (optional)
[String](#).

newest_mac_age (optional)
`Long` format: int64

comments (optional)
`String`.

service_ports_tcp (optional)
`array[String]`. format: port

service_ports_udp (optional)
`array[String]`. format: port

service_ports_protocols (optional)
`array[String]`.

service_ports_products (optional)
`array[String]`.

org_name (optional)
`String`.

site_name (optional)
`String`.

agent_name (optional)
`String`.

tags (optional)
`map[String, String]`.

services (optional)
`map[String, map[String, String]]`.

rtt (optional)
`map[String, oas any type not mapped]`.

credentials (optional)
`map[String, map[String, Boolean]]`.

attributes (optional)
`map[String, String]`.

Wireless -

[Up](#)

id
`UUID` format: uuid

created_at (optional)
`Long` format: int64

last_seen (optional)
`Long` format: int64

organization_id (optional)
`UUID` format: uuid

site_id (optional)
`UUID` format: uuid

last_agent_id (optional)
`UUID` format: uuid

last_task_id (optional)
`UUID` format: uuid

essid (optional)
`String` format: mac

type (optional)
`String`.

authentication (optional)
`String`.

encryption (optional)
`String`.

signal (optional)
`Integer`

channels (optional)

String.
interface (optional)
String.
vendor (optional)
String.
family (optional)
String.
data (optional)
map[String, String].
org_name (optional)
String.
site_name (optional)
String.
agent_name (optional)
String.

updateBulkAssetOwners_200_response -

[Up](#)

updated_asset_count (optional)
Integer