

Chapter 8

Maximum Likelihood for Log-Location-Scale Distributions

W. Q. Meeker, L. A. Escobar, and F. G. Pascual

Iowa State University, Louisiana State University, and Washington State University.

Copyright 2021 W. Q. Meeker, L. A. Escobar, and F. G. Pascual.

Based on [Meeker, Escobar, and Pascual \(2021\)](#): *Statistical Methods for Reliability Data, Second Edition*, John Wiley & Sons Inc.

May 24, 2021
10h 54min

Chapter 8

Maximum Likelihood for Log-Location-Scale Distributions

Topics discussed in this chapter are:


- How to express the likelihood for location-distributions like the normal distribution and log-location-scale distributions like the Lognormal and Weibull distributions.
- How to construct and interpret likelihood confidence intervals for parameters and for **functions** of parameters of log-location-scale distributions.
- The construction of Wald (normal-approximation) confidence intervals for parameters and functions of parameters of log-location-scale distributions.
- Inference for log-location-scale distribution parameters and functions of parameters with a given shape parameter.

Chapter 8

Segment 1

Likelihood for Log-Location-Scale Distributions

Weibull Probability Plot of the Shock Absorber Data



Weibull Distribution Likelihood for Right-Censored Data

- The Weibull distribution model is

$$\Pr(T \leq t) = F(t; \mu, \sigma) = \Phi_{\text{sev}}\{[\log(t) - \mu]/\sigma\}.$$

- The likelihood has the form

$$\begin{aligned} L(\mu, \sigma) &= \prod_{i=1}^n L_i(\mu, \sigma; \text{data}_i) \\ &= \prod_{i=1}^n [f(t_i; \mu, \sigma)]^{\delta_i} [1 - F(t_i; \mu, \sigma)]^{1-\delta_i} \\ &= \prod_{i=1}^n \left[\frac{1}{\sigma t_i} \phi_{\text{sev}}\left(\frac{\log(t_i) - \mu}{\sigma}\right) \right]^{\delta_i} \times \left[1 - \Phi_{\text{sev}}\left(\frac{\log(t_i) - \mu}{\sigma}\right) \right]^{1-\delta_i} \end{aligned}$$

$$\delta_i = \begin{cases} 1 & \text{if } t_i \text{ is an exact observation} \\ 0 & \text{if } t_i \text{ is a right-censored observation} \end{cases}$$

$\phi_{\text{sev}}(z)$ and $\Phi_{\text{sev}}(z)$ are the standardized smallest extreme value density and distribution functions, respectively.

Lognormal Distribution Likelihood for Right-Censored Data

- The lognormal distribution model is

$$\Pr(T \leq t) = F(t; \mu, \sigma) = \Phi_{\text{norm}}\{[\log(t) - \mu]/\sigma\}.$$

- The likelihood has the form


$$\begin{aligned} L(\mu, \sigma) &= \prod_{i=1}^n L_i(\mu, \sigma; \text{data}_i) \\ &= \prod_{i=1}^n [f(t_i; \mu, \sigma)]^{\delta_i} [1 - F(t_i; \mu, \sigma)]^{1-\delta_i} \\ &= \prod_{i=1}^n \left[\frac{1}{\sigma t_i} \phi_{\text{norm}}\left(\frac{\log(t_i) - \mu}{\sigma}\right) \right]^{\delta_i} \times \left[1 - \Phi_{\text{norm}}\left(\frac{\log(t_i) - \mu}{\sigma}\right) \right]^{1-\delta_i} \end{aligned}$$

$$\delta_i = \begin{cases} 1 & \text{if } t_i \text{ is an exact observation} \\ 0 & \text{if } t_i \text{ is a right-censored observation} \end{cases}$$


$\phi_{\text{norm}}(z)$ and $\Phi_{\text{norm}}(z)$ are the standardized normal density and distribution functions, respectively.

Weibull Relative Likelihood for the Shock Absorber Data


ML Estimates: $\hat{\mu} = 10.23$ and $\hat{\sigma} = 0.3164$

$$R(\mu, \log(\sigma)) = L(\mu, \log(\sigma)) / L(\hat{\mu}, \log(\hat{\sigma}))$$



**Weibull Relative Likelihood
for the Shock Absorber Data**
ML Estimates: $\hat{\mu} = 10.23$ and $\hat{\sigma} = 0.3164$
 $R(\mu, \sigma) = L(\mu, \sigma) / L(\hat{\mu}, \hat{\sigma})$



Weibull Probability Plot of Shock Absorber Failure Times (Both Failure Modes) with Maximum Likelihood Estimates and Wald 95% Pointwise Confidence Intervals for $F(t)$



**Lognormal Probability Plots of Shock Absorber Data
with ML Estimates and Wald 95% Pointwise
Confidence Intervals for $F(t)$. The Curved Line Is the
Weibull ML Estimate**



Chapter 8

Segment 2

Likelihood-Based Confidence Intervals for Log-Location-Scale Distribution Parameters μ and σ

Large-Sample Approximate Theory for Likelihood Ratios for Parameter Vector

- Relative likelihood for (μ, σ) is


$$R(\mu, \sigma) = \frac{L(\mu, \sigma)}{L(\hat{\mu}, \hat{\sigma})}.$$

- If evaluated at the true (μ, σ) , then, asymptotically, $-2 \log[R(\mu, \sigma)]$ has a chi-square distribution with 2 degrees of freedom.
- General theory in the Appendix.

**Weibull Relative Likelihood
for the Shock Absorber Data**

ML Estimates: $\hat{\mu} = 10.23$ and $\hat{\sigma} = 0.3164$


$$R(\mu, \sigma) = L(\mu, \sigma) / L(\hat{\mu}, \hat{\sigma})$$



Weibull Likelihood-Based Joint Confidence Regions for μ and σ for the Shock Absorber Data


ML Estimates: $\hat{\mu} = 10.23$ and $\hat{\sigma} = 0.3164$

100(1 - α)% Region: $R(\mu, \sigma) > \exp[-\chi^2_{(1-\alpha;2)}/2] = \alpha$




**Weibull Profile Likelihood $R(\mu)$ ($\exp(\mu) = \eta \approx t_{0.63}$)
for the Shock Absorber Data**

$$R(\mu) = \max_{\sigma} \left[\frac{L(\mu, \sigma)}{L(\hat{\mu}, \hat{\sigma})} \right]$$



Weibull Profile Likelihood $R(\sigma)$ ($\sigma = 1/\beta$) for the Shock Absorber Data

$$R(\sigma) = \max_{\mu} \left[\frac{L(\mu, \sigma)}{L(\hat{\mu}, \hat{\sigma})} \right]$$



Large-Sample Approximate Theory for Likelihood Ratios for a Parameter Vector Subset

Need: Inferences on subset θ_1 , from the partition $\theta = (\theta_1, \theta_2)'$.

- The parameter(s) in θ_2 are known as “nuisance parameters.”
- $k_1 = \text{length}(\theta_1)$.
- When $(\theta_1, \theta_2)' = (\mu, \sigma)'$, profile likelihood for $\theta_1 = \mu$ is

$$R(\mu) = \max_{\sigma} \left[\frac{L(\mu, \sigma)}{L(\hat{\mu}, \hat{\sigma})} \right].$$

- If evaluated at the true $\theta_1 = \mu$, then, asymptotically, $-2 \log[R(\mu)]$ follows, a chi-square distribution with $k_1 = 1$ degrees of freedom.
- General theory in the Appendix.

Large-Sample Approximate Theory of Likelihood Ratios – Continued

- An approximate $100(1 - \alpha)\%$ likelihood-based confidence region for θ_1 is the set of all values of θ_1 such that

$$-2 \log[R(\theta_1)] < \chi^2_{(1-\alpha; k_1)}$$

or, equivalently, the set defined by

$$R(\theta_1) > \exp\left[-\chi^2_{(1-\alpha; k_1)}/2\right].$$

- Transformation of θ_1 will not affect the confidence statement.
- Can improve the asymptotic approximation with simulation (only small effect except in very small samples).

Chapter 8

Segment 3

Likelihood-Based Confidence Intervals for Functions of μ and σ

Confidence Regions and Intervals for Functions of μ and σ


- The likelihood approach can be applied to functions of parameters. For monotone functions of a single parameter (e.g., $\beta = 1/\sigma$), the interval translates directly.
- Otherwise, define the function of interest as one of the parameters, replacing one of the original parameters giving one-to-one reparameterization $\mathbf{g}(\mu, \sigma) = [g_1(\mu, \sigma), g_2(\mu, \sigma)]$.
- Then use a profile likelihood, as with the original parameters.
- Simple to implement if the function and its inverse are easy to compute.

Reparameterization to Make t_p a Parameter

- We want to re-express the likelihood so that $t_p = \exp[\mu + \sigma\Phi^{-1}(p)]$ replaces μ in the likelihood.
- This can be done by substituting $\mu = \log(t_p) - \sigma\Phi^{-1}(p)$ for μ in the (log)-likelihood expression, giving an expression for $L(t_p, \sigma)$.
- A similar reparameterization is possible for writing the likelihood as a function of $F(t_e)$ and σ for a given t_e .


**Contour Plot of Weibull Relative Likelihood $R(t_{0.1}, \sigma)$
for the Shock Absorber Data
(Parameterized with $t_{0.1}$ and σ)**

$$R(t_{0.1}, \sigma) = L(t_{0.1}, \sigma) / L(\hat{t}_{0.1}, \hat{\sigma})$$




Weibull Profile Likelihood $R(t_{0.1})$ for the Shock Absorber Data

$$R(t_{0.1}) = \max_{\sigma} \left[\frac{L(t_{0.1}, \sigma)}{L(\hat{t}_{0.1}, \hat{\sigma})} \right]$$



Weibull Profile Likelihood $R[F(10000)]$ for the Shock Absorber Data

$$R[F(10000)] = \max_{\sigma} \left\{ \frac{L[F(10000), \sigma]}{L[\hat{F}(10000), \hat{\sigma}]} \right\}$$



Chapter 8

Segment 4

Wald Approximate Confidence Intervals for Log-Location-Scale Distribution Parameters μ and σ and Functions of μ and σ

Large-Sample Approximation Theory of ML Estimation

Let $\hat{\theta}$ denote the ML estimator of θ .

- If evaluated at the true value of θ , then asymptotically, (large samples) $\hat{\theta}$ has a $\text{MVN}(\theta, \Sigma_{\hat{\theta}})$ and thus the **Wald** statistic

$$(\hat{\theta} - \theta)' [\Sigma_{\hat{\theta}}]^{-1} (\hat{\theta} - \theta)$$

has a chi-square distribution with k degrees of freedom, where k is the length of θ .

- Here, $\Sigma_{\hat{\theta}} = I_{\theta}^{-1}$ is the large-sample approximate covariance matrix where the Fisher information matrix for θ is

$$I_{\theta} = \text{E} \left[- \frac{\partial^2 \mathcal{L}(\theta)}{\partial \theta \partial \theta'} \right].$$

- For (log)-location-scale distributions, $\theta = (\mu, \sigma)'$.

Large-Sample Approximation Theory for Wald's Statistic

- Alternative asymptotic theory is based on the large-sample distribution of quadratic forms (Wald's statistic).
- Let $\hat{\Sigma}_{\hat{\theta}}$ be a consistent estimator of $\Sigma_{\hat{\theta}}$, the asymptotic covariance matrix of $\hat{\theta}$. For example,

$$\hat{\Sigma}_{\hat{\theta}} = \left[-\frac{\partial^2 \mathcal{L}(\theta)}{\partial \theta \partial \theta'} \right]^{-1}$$

where the derivatives are evaluated at $\hat{\theta}$.

- Asymptotically, the Wald statistic

$$w(\theta) = (\hat{\theta} - \theta)' [\hat{\Sigma}_{\hat{\theta}}]^{-1} (\hat{\theta} - \theta)$$

when evaluated at the true θ , follows a chi-square distribution with k degrees of freedom, where k is the length of θ .

Large-Sample Approximation Theory for Wald's Statistic – Continued

- A Wald approximate $100(1 - \alpha)\%$ confidence region for θ is the set of all values of θ in the ellipsoid

$$(\hat{\theta} - \theta)' [\hat{\Sigma}_{\hat{\theta}}]^{-1} (\hat{\theta} - \theta) \leq \chi^2_{(1-\alpha; k)}.$$

- This is sometimes known as the normal-approximation confidence region.
- Can specialize to functions or subsets of θ .
- Wald confidence intervals are not transformation invariant. Thus there are multiple ways to compute a Wald interval.
- Can try to find a transformation that results in a log-likelihood with approximate quadratic shape.

Wald Confidence Intervals for μ and σ

- Estimated variance matrix for the shock absorber data

$$\hat{\Sigma}_{\hat{\mu}, \hat{\sigma}} = \begin{bmatrix} \widehat{\text{Var}}(\hat{\mu}) & \widehat{\text{Cov}}(\hat{\mu}, \hat{\sigma}) \\ \widehat{\text{Cov}}(\hat{\mu}, \hat{\sigma}) & \widehat{\text{Var}}(\hat{\sigma}) \end{bmatrix} = \begin{bmatrix} 0.01208 & 0.00399 \\ 0.00399 & 0.00535 \end{bmatrix}$$

- Assuming that $Z_{\hat{\mu}} = (\hat{\mu} - \mu) / \text{se}_{\hat{\mu}} \sim \text{NORM}(0, 1)$ distribution, an approximate $100(1 - \alpha)\%$ confidence interval for μ is

$$[\underline{\mu}, \quad \tilde{\mu}] = \hat{\mu} \mp z_{(1-\alpha/2)} \text{se}_{\hat{\mu}}$$

where $\text{se}_{\hat{\mu}} = \sqrt{\widehat{\text{Var}}(\hat{\mu})}$.

- Assuming that $Z_{\log(\hat{\sigma})} = [\log(\hat{\sigma}) - \log(\sigma)] / \text{se}_{\log(\hat{\sigma})} \sim \text{NORM}(0, 1)$ an approximate $100(1 - \alpha)\%$ confidence interval for σ is

$$[\underline{\sigma}, \quad \tilde{\sigma}] = [\hat{\sigma} / w, \quad \hat{\sigma} \times w]$$

where $w = \exp[z_{(1-\alpha/2)} \text{se}_{\hat{\sigma}} / \hat{\sigma}]$ and $\text{se}_{\hat{\sigma}} = \sqrt{\widehat{\text{Var}}(\hat{\sigma})}$.

Wald Confidence Intervals for a Function $g_1 = g_1(\mu, \sigma)$

- ML estimate $\hat{g}_1 = g_1(\hat{\mu}, \hat{\sigma})$.
- Assuming $Z_{\hat{g}_1} = (\hat{g}_1 - g_1)/\text{se}_{\hat{g}_1} \sim \text{NORM}(0, 1)$, an approximate $100(1 - \alpha)\%$ confidence interval for g_1 is

$$[\underline{g}_1, \quad \tilde{g}_1] = \hat{g}_1 \mp z_{(1-\alpha/2)} \text{se}_{\hat{g}_1},$$

where

$$\begin{aligned} \text{se}_{\hat{g}_1} &= \sqrt{\widehat{\text{Var}}(\hat{g}_1)} \\ &= \left[\left(\frac{\partial g_1}{\partial \mu} \right)^2 \widehat{\text{Var}}(\hat{\mu}) + \left(\frac{\partial g_1}{\partial \sigma} \right)^2 \widehat{\text{Var}}(\hat{\sigma}) + 2 \left(\frac{\partial g_1}{\partial \mu} \right) \left(\frac{\partial g_1}{\partial \sigma} \right) \widehat{\text{Cov}}(\hat{\mu}, \hat{\sigma}) \right]^{1/2} \end{aligned}$$

- Partial derivatives evaluated at $\hat{\mu}, \hat{\sigma}$.
- General theory in the Appendix.

Wald Confidence Interval for $F(t_e; \mu, \sigma)$

Objective: Obtain a point estimate and a confidence interval for $\Pr(T \leq t_e) = F(t_e; \mu, \sigma)$ at a given point t_e .

- The ML estimates $\hat{\theta} = (\hat{\mu}, \hat{\sigma})$ and $\hat{\Sigma}_{\hat{\theta}}$ are available.
- The ML estimate for $F(t_e; \mu, \sigma)$ is

$$\hat{F} = F(t_e; \hat{\mu}, \hat{\sigma}) = \Phi(\hat{z}_e)$$

where $\hat{z}_e = [\log(t_e) - \hat{\mu}]/\hat{\sigma}$.

- There are many ways to obtain a Wald confidence interval for $F(t_e; \mu, \sigma)$.

Wald Confidence Interval for $F(t_e; \mu, \sigma)$ —Continued

Note: Wald confidence intervals depend on the parameterization used to derive the intervals.

For example, an approximate $100(1-\alpha)\%$ confidence interval for $F(t_e; \mu, \sigma)$ can be obtained using:

- The asymptotic normality of $Z_{\hat{F}} = (\hat{F} - F)/\text{se}_{\hat{F}}$

$$[\underline{F}, \quad \tilde{F}] = \hat{F}(t_e) \mp z_{(1-\alpha/2)} \text{se}_{\hat{F}}.$$

- The asymptotic normality of $\hat{z}_e = [\log(t_e) - \hat{\mu}]/\hat{\sigma}$

$$[\underline{z}_e, \quad \tilde{z}_e] = \hat{z}_e \mp z_{(1-\alpha/2)} \text{se}_{\hat{z}_e}.$$

Then

$$[\underline{F}(t_e), \quad \tilde{F}(t_e)] = [\Phi(\underline{z}_e), \quad \Phi(\tilde{z}_e)].$$

- Expressions for $\text{se}_{\hat{F}}$ and $\text{se}_{\hat{z}_e}$ are obtained by using the delta method.

Wald Confidence Interval for $F(t_e; \mu, \sigma)$ —Continued


Comments:

- The confidence interval procedure based on the asymptotic normality of $Z_{\hat{F}}$ has poor statistical properties because $Z_{\hat{F}}$ converges slowly toward normality.
- The confidence interval procedure based on \hat{z}_e has better statistical properties because \hat{z}_e converges to normality faster than $Z_{\hat{F}}$.


Example: Bearing-A Life Test Results

- Continuous-run test for a newly-designed bearing.
- Sample of 12 units put on test; one early removal; 3 failures.
- Test terminated at 1100 thousand cycles.
- What is the failure-time distribution of the bearing?

Bearing-A Weibull Probability Plot and ML Estimate



Bearing-A Weibull Probability Plot and ML Estimate



Bearing-A Life Test Example Conclusions

- Sometimes the ML estimate does not go through the points on a Weibull (or other) probability plot.
- When the ML estimate does not go through the points, it is an indication that the Weibull distribution does not agree with the data.
- It is important to find the reason that the line does not fit.

Chapter 8

Segment 5

Weibull Distribution Inference with Few Failures

Weibull Inference with Few Failures

- Suppose that β is given. Knowledge of the failure mechanism will often provide information about β .
- Simplifies problem. Only one parameter with r failures and t_1, \dots, t_n failures and censor times

$$\hat{\eta} = \left(\frac{\sum_{i=1}^n t_i^\beta}{r} \right)^{1/\beta}, \quad \text{se}_{\hat{\eta}} = \frac{\hat{\eta}}{\beta} \sqrt{\frac{1}{r}}.$$


- Provides much more precision, especially with small r .
- Requires **sensitivity analysis** because β is unknown.

Bearing-Cage Fracture Field Data


- Data from the Weibull Handbook [Abernethy et al. \(1983\)](#).
- $n = 1703$ units had been introduced into service over time; oldest unit had 2220 hours of operation.
- 6 units had failed.
- Design life specification was $B10 = t_{0.1} = 8000$ hours.
- ML estimate is $\hat{t}_{0.1} = 3.903$ thousand hours. Does this indicate a problem?
- How many replacement parts will be needed?

Bearing-Cage Fracture Data Event Plot


Bearing Cage Failure Data




Weibull Probability Plots Bearing-Cage Fracture Data with Weibull ML Estimates and Sets of 95% Pointwise Confidence Intervals for $F(t)$ with β Estimated




Weibull Probability Plots Bearing-Cage Fracture Data with Weibull ML Estimates and Sets of 95% Pointwise Confidence Intervals for $F(t)$ with Given $\beta = 1.5$



Weibull Probability Plots Bearing-Cage Fracture Data with Weibull ML Estimates and Sets of 95% Pointwise Confidence Intervals for $F(t)$ with Given $\beta = 2$




Weibull Probability Plots Bearing-Cage Fracture Data with Weibull ML Estimates and Sets of 95% Pointwise Confidence Intervals for $F(t)$ with Given $\beta = 3$




Lognormal and Weibull Comparison

Bearing-Cage Fracture Field Data


Lognormal Probability Paper



Relative Weibull Likelihood with One Failure at 1 and One Survivor at 2



Relative Weibull Likelihood with One Failure at 1.9 and One Survivor at 2



Chapter 8

Segment 6

Weibull Distribution Inference with Zero Failures

Weibull Distribution with Given β and Zero Failures

- ML estimate for the Weibull scale parameter η cannot be computed unless the available data contains one or more failures.
- For a sample of n units with running times t_1, \dots, t_n and no failures, a conservative $100(1-\alpha)\%$ lower confidence bound for η is

$$\underline{\eta} = \left(\frac{2 \sum_{i=1}^n t_i^\beta}{\chi_{(1-\alpha; 2)}^2} \right)^{\frac{1}{\beta}}.$$

- The lower bound $\underline{\eta}$ can be translated into a lower confidence bound for functions like t_p for specified p or an upper confidence bound for $F(t_e)$ for a specified t_e .

Component A Safe Data


- A metal component in a ship's propulsion system fails from fatigue-caused fracture.
- Because of persistent reliability problems, the component was redesigned to have a longer service life.
- Previous experience suggests that the Weibull shape parameter is near $\beta = 2$, and almost certainly between 1.5 and 2.5.
- Many copies of a newly designed component were put into service during the past year and no failures have been reported.

Hours:	500	1000	1500	2000	2500	3000	3500	4000
Number of Units:	10	12	8	9	7	9	6	3

Staggered entry data, with no reported failures.

- Can the replacement time be safely increased from 2000 hours to 4000 hours?

Weibull Model 95% Upper Confidence Bounds on $F(t)$ for Component-A with Different Fixed Values for the Weibull Shape Parameter



Chapter 8

Segment 7

Regularity Conditions and Other Topics

Regularity Conditions

- Each technical result (e.g., the asymptotic distribution of an estimator) has its own set of conditions on the model (see Lehmann 1983, Rao 1973).
- Frequent reference to Regularity Conditions which give rise to simple results.
- For special cases the regularity conditions are easy to state and check. For example, for some location-scale distributions the needed conditions are:

$$\lim_{z \rightarrow -\infty} \frac{z^2 \phi^2(z)}{\Phi(z)} = 0$$
$$\lim_{z \rightarrow +\infty} \frac{z^2 \phi^2(z)}{1 - \Phi(z)} = 0.$$

- In **non-regular** models, asymptotic behavior is more complicated (e.g., behavior depends on θ), but there are still useful asymptotic results.

Regularity Conditions – Continued

Some **typical** regularity conditions include:

- Support does not depend on unknown parameters.
- Number of parameters does not grow too fast with n .
- Continuous derivatives of log likelihood (w.r.t. θ).
- Bounded derivatives of likelihood.
- Can exchange the order of differentiation of log likelihood w.r.t. θ and integration w.r.t. data.
- Identifiability.

Other Topics Related to Parametric Likelihood Covered in the Book

- Bayesian methods (Chapter 9).
- Truncated data (Chapter 11).
- Threshold parameters (Chapter 11).
- Other distributions (e.g., generalized gamma) (Chapters 4, 11).
- Comparison of failure-time distributions (Chapter 12).
- Prediction (Chapter 15).
- Multiple failure modes (Chapter 16).
- Regression analysis and accelerated testing (Chapters 17-19).

References

- Abernethy, R. B., J. E. Breneman, C. H. Medlin, and G. L. Reinman (1983). *Weibull Analysis Handbook*. Air Force Wright Aeronautical Laboratories Technical Report AFWAL-TR-83-2079. Available from: <http://apps.dtic.mil/dtic/tr/fulltext/u2/a143100.pdf>. []
- Meeker, W. Q., L. A. Escobar, and F. G. Pascual (2021). *Statistical Methods for Reliability Data* (Second Edition). Wiley. [1]