

NOTES: (UNLESS OTHERWISE SPECIFIED)

- 1.1. JP1 CLOSED, JP2 OPEN, JP3 OPEN
VBUS POWERS BY BUS UNTIL EXT PWR (VCC) APPLIED.
WHEN 5V BUS IS POWERED BY VCC.
(PREFERRED/DEFAULT OPTION)
- 1.2. JP1 OPEN, JP2 CLOSED, JP3 OPEN
5V BUS IS SOLELY POWERED BY RAW EXT PWR (VCC).
- 1.3. JP1 OPEN, JP2 OPEN, JP3 CLOSED
5V BUS IS SOLELY POWERED BY RAW USB VBUS.
CAUTION: FALSE INDICATION OF EXT PWR VIA VCC-SENS
WILL OCCUR IF EXT PWR CONNECTED.
- 1.4. JP1 OPEN, JP2 OPEN, JP3 OPEN
NO 5V POWER IS SUPPLIED TO THE UFC.
WARNING: UFC WILL NOT FUNCTION IN THIS STATE.
2. ORIENT COMM DISPLAYS (DS7/DS8) SO THE TAB IS TOWARDS
THE TOP OF THE PCB.
3. ADD PTH RESISTORS TO G0/GNO-G0 LED CABLES AS REQUIRED
TO REDUCE BRIGHTNESS.
4. POPULATE DISPLAYS (DS7/DS8) WITH
TEKCREATIONS TEK000104W PACKAGE.
(HTTPS://TEKCREATIONS.SPACE)

