


Thesis Title

Thesis Subtitle

A thesis presented for the degree of
Doctor of Physics



Department Name
University Name

Abstract

The increased necessity of experimental proof of physics beyond Standard Model (SM) and Dark Matter theories leads us to develop new detectors for high energy experiments, like ATLAS with his upgrade (New Small Wheel project in particular) for the luminosity increase at LHC and a new experiment on SPS facilities at CERN called NA64; to search for Dark Matter on invisible(visible) decays of dark photons.

For this two experiments, detectors from our institute have been made to be part on such enterprise. Characterizations and tests have been done with the use of particles beam (electrons, pions, muons and gamma rays) from the Experimental Area at CERN.

Dedication

Acknowledgments

Contents

1. Introduction	11
2. Characterization of sTGC	13
2.1. ATLAS Detector Upgrade	13
2.1.1. High Luminosity Large Hadron Collider - HL-LHC	13
2.1.2. ATLAS Detector	14
2.1.3. New Small Wheel	14
2.2. Small-strip Thing Gap Chamber	14
2.3. Construction process	15
2.4. Gain and uniformity	15
2.5. Working under high gamma rate	15
2.6. Spatial resolution strips	15
2.7. Charge sharing between pads	15
2.8. summary	15
3. Brillance380 under high gamma rate	17
3.1. Scintillators counters	17
3.2. high count rates	17
3.3. Internal radiation	17
3.4. Experimental setup	17
3.5. Spectrum and rates under different attenuation filters	17
3.6. Data Analysis	17
3.6.1. Wavelets	17
3.6.2. Peak identification	17
3.7. Results	17
4. LYSO crystals array as SRD	19
4.1. NA64 experiment	19
4.1.1. Physics Motivation	19
4.1.2. Dark Photon signal	19
4.1.3. Setup	19
4.2. Synchrotron Radiation Detector	19
4.2.1. BGO	19
4.2.2. Pb+Sc	19

4.2.3. LYSO	19
4.3. Cosmic ray calibration?	19
4.4. Calibration	19
4.5. Position and time resolution	19
4.6. Hadron rejection	19
4.7. Purity 100 GeV electron identification	19
4.8. Summary	19
5. Conclusion	21
A. Appendix	23
A.1. Mechanical Measurements sTGC Module 0	23
A.2. PMT RT7525 Data Sheet	23
A.3. Data Structure NA64 Experiment	23
A.4. DAQ system	23

1. Introduction

Let's see if this thing appear as a introductio

2. Characterization of sTGC

2.1. ATLAS Detector Upgrade

2.1.1. High Luminosity Large Hadron Collider - HL-LHC

The Large Hadron Collider (LHC), run by CERN at the Franco-Swiss border near Geneva, is a circular accelerator with 27 km of acceleration pipes, is the largest scientific instrument ever designed and built for scientific research. Successfully commissioned in March 2010 for proton-proton collision with a 7 GeV centre-of-mass energy.

The LHC is pushing the limits of human knowledge, enabling physicist to go beyond Standar Model (SM): the enigmatic Higgs boson, mysterious Dark Matter and the world of supersymetry are just three of the long-awaited mysterious that the LHC will unveil. The announcement given by CERN on 4 July 2012 about the discovery of new boson at 125-126 GeV, almost certainly the long awaited Higgs particle, is the first fundamental discovery, hopefully the first of a series, that the LHC can deliver.

Such discovery was thanks to the different multipurpose detectors located at the four interaction points; ALICE, LHCb, CMS and ATLAS. This last one is the detector where our university is taking part.

	Period	Energy \sqrt{s}	Upgrade on LS	L	Integrate L
Run I	2010-2012	7-8 TeV	-	$6 \times 10^{33} \text{cm}^{-2} \text{s}^{-1}$	25 fb $^{-1}$
LS1	2013-2014	Go to design energy, nominal luminosity, bunch spacing 25ns			
Phase 0	2015-2018	14 TeV	-	$1 \times 10^{34} \text{cm}^{-2} \text{s}^{-1}$	75-100 fb $^{-1}$
LS2	2019-2020	Upgrade muon spectrometer; NSW, LAr Calorimeter & FTK			
Phase I	2021-2023	14 TeV	-	$2 \times 10^{34} \text{cm}^{-2} \text{s}^{-1}$	$\sim 350 \text{ fb}^{-1}$
LS3	2024-2025	New Inner Tracker and trigger architecture			
Phase II	2026-2030	14 TeV	-	$5 \times 10^{34} \text{cm}^{-2} \text{s}^{-1}$	$\sim 3000 \text{ fb}^{-1}$

Figure 2.1: LCH Schedule

CONTINUE WITH LHC UPGRADE and GOALS

2.1.2. ATLAS Detector

The ATLAS detector it is a general-purpose detector, designed to explore proton-proton collisions at center of mass up to $\sqrt{s} = 14\text{GeV}$. Looking for....

Such energy has been achieved from 2015 and successfully working with a luminosity of $1 \times 10^{34} \text{cm}^{-2} \text{s}^{-1}$ from 2016.

Describe ATLAS detector and its part, together with the problem faced by now.
ENDING WITH THE FAKE TRIGGERS AND PROBLEMS FOR LOW PT.

2.1.3. New Small Wheel

In manner to fulfill the LHC program (in fig.2.1), and in order to benefit from the expected high luminosity performance that will be provided by the Phase-I upgraded LHC, the first station of ATLAS muon end-cap system (Small Wheel, SW) will need to be replaced. The New Small Wheel (NSW) will have to operate in a high background radiation region (upto 15kHz/cm^2) while reconstructing muon tracks with high precision as well as furnishing information for the Level-1 trigger. These performance criteria are demanding. In particular, the precision reconstruction of tracks for offline analysis requires a spatial resolution about $100 \mu\text{m}$, and the Level-1 trigger track segments have to be reconstructed online with an angular resolution of approximately 1mrad . The NSW will have to chamber technologies, one primarily devoted to the Level-1 trigger function (small-strip Thin Gap Chambers, sTGC) and one dedicated to precision tracking (Microegas detectors, MM). The sTGC are primarily deployed for triggering given their single bunch crossing identification capability. The MM detectors have exceptional precision tracking capabilities due to their small gap (5mm) and strip pitch (approximately 0.5mm). Such a precision is crucial to maintain the current ATLAS muon momentum resolution in the high background environment of the upgraded LHC. The MM chambers can, at the same time, confirm the existence of a track segments found by the muon end-cap middle station (Big Wheels) online. The sTGC also has the ability to measure offline muon tracks with good precision, so the sTGC-MM chamber technology combination forms a fully redundant detector system for triggering and tracking both for online and offline functions. This detector combination has been designed to be able to also provide excellent performance for the eventual High Luminosity LHC upgrade.

2.2. Small-strip Thin Gap Chamber

The sTGC detector it is a multiwire proportional chamber with a cathode-anode pitch smaller than the anode-anode pitch, mostly based on the design of the Thin Gap Chamber, [Mikenberg paper], with thinner strips as the main improvement. The TGC technology has been used since 1988 in OPAL and currently are part of the the muon spectrometer in ATLAS.

The new TGC chamber has the advantage of having a 3.2mm strip width compare to the $5\text{-}6 \text{mm}$ from TGC, that is why called small strip Thin Gap Chamber (sTGC from now

on).

This number has been chosen to cope up with the precision resolution require for the NSW (explained before), where the resolution for the detectors has to be better than $100\ \mu\text{m}$ with a few nanoseconds of response. For this purpose, chambers with different strips sizes has been build and test under pion beams, chosed the 3.2mm has the best option[1].

The sTGC is made of two cathods planes, one with copper strips and the other with pads, each plane is made of FR4 with 1.4mm of thickness, $100\ \mu\text{m}$ for strips or pads, $100\ \mu\text{m}$ of FR4 and finally sprayed with $100\ \mu\text{m}$ of graphite to achieve $100\text{--}200\ \text{k}\Omega/\square$. The anodes are made of tungsten wires with $50\ \mu\text{m}$ diameter, distributed in group of 5, with 1.8mm distances between wires. The gas gap (2.8mm) is fill with a mixture of CO_2 and n-pentane in proportion 55:45 respectively.




Figure 2.2: Single plane sTGC

2.3. Construction process

2.4. Gain and uniformity

2.5. Working under high gamma rate

2.6. Spatial resolution strips

2.7. Charge sharing between pads

2.8. summary

3. Brillance380 under high gamma rate

3.1. Scintilators counters

3.2. high count rates

3.3. Internal radiation

3.4. Experimental setup

3.5. Spectrum and rates under different attenuation filters

3.6. Data Analysys

3.6.1. Wavelets

3.6.2. Peak identification

3.7. Results

4. LYSO crystals array as SRD

4.1. NA64 experiment

4.1.1. Physics Motivation

4.1.2. Dark Photon signal

4.1.3. Setup

4.2. Synchrotron Radiation Detector

4.2.1. BGO

4.2.2. Pb+Sc

4.2.3. LYSO

4.3. Cosmic ray calibration?

4.4. Calibration

4.5. Position and time resolution

4.6. Hadron rejection

4.7. Purity 100 GeV electron identification

4.8. Summary

5. Conclusion

A. Appendix

A.1. Mechanical Measurements sTGC Module 0

A.2. PMT RT7525 Data Sheet

A.3. Data Structure NA64 Experiment

A.4. DAQ system

Bibliography

- [1] et al V.Smakhtin. Thin gap chamber upgrade for slhc: Position resolution in a test beam. *Nucl. Instr. and Meth. A*, 598:196–200, 2009.