

Beyond “Has a World Model?”:

A Layered Profile of Predictive Abstraction, Intervention, Decision Sufficiency, and Robustness under Shift

Guillaume Harbonnier
MMALS Research Program

Draft v0.3 – 9 September 2026

Abstract

The term *world model* is used for systems that differ substantially in what they represent, what they predict, how they are queried, and what kinds of decisions or shifts they support. This makes the binary question “does system X have a world model?” too coarse for technical comparison. We propose instead a declared, layered evaluation profile. L0 measures predictive closure at a stated abstraction frontier; $L1_{\text{int}}$ concerns interventional validity of the abstract dynamics; L2 separates class-level decision adequacy from operational model-search adequacy; and L3 records system-level robustness under a declared shift class. Acquisition-policy exposure is not treated as an independent layer: an elementary convexity argument bounds it by L0 aliasing, so we report it only as an attribution ratio inside L0. The profile is explicitly grounded in classical state abstraction and bisimulation, approximate information states, value equivalence, self-predictive representations, causal abstraction, and recent analyses of learned planning models. Two exact finite constructions establish only that L0 and L2 are non-identical coordinates: one representation is predictively closed at a coarse abstraction while incurring positive contingent-decision regret, while a second model is exactly value-equivalent on a declared value class despite failing full-state predictive closure. We additionally give manuscript-level diagnostics illustrating the geometry dependence of the acquisition-policy attribution ratio and a minimal operational-vs-global adequacy failure. We do not claim a unique definition of world models, a necessary-and-sufficient theory, or superiority over the eliminativist alternative of reporting the underlying technical tuple directly.

Scope and evidence. The profile proposed here is an evaluation framework, not a peer-reviewed theory or a claim to a unique definition of world models. Its two main finite separation results are exact and reproducible from explicit finite environments. Other coordinates combine literature-grounded criteria with evaluation contracts that remain only partly instantiated in this manuscript, and the additional diagnostics are illustrative rather than general empirical validation. Whether the profile improves practical comparison or failure localisation beyond direct reporting of its primitive objects remains open.

1 Introduction

Consider two systems that can both reasonably attract the label “world model” while supporting very different claims. A passive, non-action-conditioned video predictor may forecast future observations accurately and therefore be predictively strong at the observation level, yet provide no declared semantics for intervention or decision. MuZero sits almost at the opposite end: its learned dynamics need not be a faithful simulator across unseen policies, yet they can support strong planning on the query distribution induced by search [6, 17]. These systems are not simply better and worse points on one scale. They answer different technical questions.

That tension recurs across the literature. Ha and Schmidhuber used the term for a learned compressed spatiotemporal model supporting policies trained inside imagined rollouts [3]. PlaNet learned latent dynamics from pixels and planned in latent space [4]; Dreamer learned behaviour by latent imagination [5]. LeCun’s autonomous-machine proposal places a configurable predictive world model inside a larger agent and emphasises multiple abstraction levels and joint-embedding prediction [7]. Chen et al. explicitly note the lack of consensus and propose a resource-relative, compression-oriented account [8].

The motivating question for this paper came from a narrower problem in adaptive learning: *which distinctions in an agent’s history may be safely discarded, and which must be preserved because later actions, evidence or tasks may make them relevant?* The label “world model” turned that question into several questions at once:

1. What aspects of past observations are represented internally?
2. Can the representation be advanced through an internal transition operator without reconstructing the next observation?
3. Is the representation or model adequate for a particular planning or decision problem?
4. Does the whole system remain adequate when the intervention regime or environment changes?

A single yes/no predicate tends to collapse these questions. A representation can be predictively closed at one abstraction and inadequate for a decision that depends on information it discards. Conversely, a model can preserve every Bellman computation relevant to a restricted decision class while being predictively wrong about variables that the decision class ignores.

This paper therefore asks a narrower question than “what is the true definition of a world model?”:

Can a declared profile separate technically distinct claims that are often compressed into the phrase “has a world model”, while remaining explicit about its own limits and about existing state-abstraction theory?

Our answer is a profile

$$\text{WMPProfile}_{\mathcal{D}}(X) = \langle L0[\rho_{\text{pol}}], L1_{\text{int}}, L2.G, L2.O, L3 \rangle,$$

where each entry is reported as *pass with measured budget*, *fail*, *not declared*, or *not applicable*. The profile is not a hierarchy: the coordinates quantify different questions, and the finite evidence in this paper establishes only non-identity of L0 and L2 in two controlled constructions.

The main contributions are deliberately modest:

- We formulate L0 as a *predictive abstraction frontier*: the report names the finest tested abstraction level at which declared budgets hold and, when available, a natural richer level that fails.
- We separate class-level decision adequacy (L2.G) from operational model–search adequacy (L2.O), so that performance measured on a planner’s self-induced query distribution is not silently read as a global claim.
- We show exactly in finite constructions that $L0 \not\approx L2$ and $L2.G \not\approx L0$ under explicit declarations. Interventional validity remains a separate coordinate, while acquisition-policy exposure is retained only as an attribution diagnostic inside L0.

We keep a competing eliminativist position alive throughout: the term *world model* may ultimately add less than a direct report of $(\sigma, K, \text{sufficiency class}, \text{shift class}, \dots)$. The paper’s burden is therefore not to defend a label, but to show whether the profile improves localisation of what a system has and has not demonstrated.

2 Lineage and related work

2.1 Internal models, regulation, and anticipation

The intuition that intelligent regulation requires an internal surrogate of external dynamics predates modern machine learning. Craik argued that nervous systems can carry internal models that parallel external events and allow anticipation [1]. Conant and Ashby formalised a closely related regulator-model relation under explicit assumptions in the good-regulator theorem [2]. We cite these works as conceptual lineage only; the present profile is not a derivation of either theorem.

Modern world-model systems made the idea computational. Ha and Schmidhuber combined compressed visual representations with recurrent dynamics [3]. PlaNet explicitly learned a transition model, observation model, reward model, and approximate belief from history, then used the latent dynamics for planning [4]. Dreamer shifted behaviour learning into imagined latent trajectories [5]. MuZero demonstrated that a learned model need not reconstruct environment observations or rules to support high-performance planning; it can instead preserve reward, value and policy-relevant predictions [6]. These systems motivate the question of what a model must preserve, but they do not by themselves define a universal criterion.

2.2 Abstraction is not new

Any framework that compresses histories into latent states must be positioned against classical abstraction theory. Givan, Dean and Greig developed stochastic bisimulation and model minimisation [9]. Ferns, Panangaden and

Precup introduced bisimulation metrics and value-related bounds [10]. Li, Walsh and Littman organised state abstractions ranging from model-irrelevance to value-, action-, and policy-oriented notions [11]. The present L0 coordinate is therefore not proposed as a new theory of state abstraction. Its closest analogue is a reward-free/model-level abstraction claim, augmented here by an explicit query-defined frontier and embedded in a profile that separately records decision and robustness claims.

This distinction matters because the profile’s contribution, if any, cannot be “abstraction exists”. State abstraction, approximate information states and value-equivalent modelling already provide mature formalisms for different parts of the problem. They are often reported under different technical contracts, however, so evidence established in one register can be read as evidence in another. The proposed contribution is therefore a reporting and localisation discipline: declare which abstraction is being preserved, which decision class is being protected, and which robustness or intervention claim is actually being made.

2.3 Information states and decision-relative adequacy

In partially observed systems, the full observation-action history can be replaced by an information state when that statistic is sufficient for the relevant dynamic program. Approximate Information State (AIS) makes this operational by defining reward- and next-information-state approximation conditions under a declared integral probability metric and deriving value/policy-loss guarantees under the theorem assumptions [12]. This addresses a central weakness of vague phrases such as “sufficient representation”: it provides checkable conditions that imply decision guarantees.

Value Equivalence (VE) approaches adequacy from a different direction. Instead of asking whether a history statistic approximates an information state, it asks whether a learned model induces the Bellman computations that matter over declared policy and value-function classes [13]. Proper and approximate variants extend the programme [14, 15]. These literatures motivate our decision-relative L2 coordinate. They also prevent us from claiming as novel the generic fact that preserving one-step or restricted predictive quantities is weaker than preserving all longer-horizon decision structure.

2.4 Self-predictive representations and abstraction level

Self-predictive reinforcement-learning work analyses representations that can predict their own next latent state and relates such conditions to other state/history abstractions [16]. LeCun’s JEPA-oriented proposal similarly emphasises prediction in representation space and multiple abstraction levels rather than reconstruction of all observation details [7]. These ideas motivate two commitments in L0: the model must support internal predictive closure, and the abstraction level must be declared rather than left implicit.

This is also why a video generator is not excluded by definition. If the declared abstraction level is the observation itself, an accurate video generator may pass L0 there. That says nothing about whether the same system passes at a causal, object-centric, control-relevant, or decision-relevant abstraction.

2.5 Planning, query distributions, and extractable models

A planner and a learned model cannot always be separated cleanly by interface. He et al. show that MuZero’s learned model generalises poorly to evaluating unseen policies, while the policy prior in search steers computation towards regions in which the model is more accurate [17]. This motivates our separation between class-level adequacy and operational model-search adequacy.

Complementary capability theorems show that sufficiently general goal-directed agents contain enough predictive information for an environment model to be extracted from their policies [21]. Cifuentes extends this type of result to stochastic agents under partial observability [22]. These theorems defeat simple interface-based exclusion rules: a system need not expose a module called “world model” for predictive environment structure to be recoverable from its behaviour. They do not, however, establish that a planner component is identical to a world model.

2.6 Causal abstraction and robustness under shift

Intervention on a lossy quotient is not automatically well defined. Work on causal abstraction and exact transformations formalises when causal relationships survive abstraction [18, 19]. Richens and Everitt further show, under their stated robustness conditions involving local interventions on all environment variables, that robust agents must encode extractable approximate causal structure [20]. We therefore keep causal/interventional validity

Table 1: Interpretation of the profile coordinates. Acquisition-policy exposure ρ_{pol} is an L0 diagnostic, not an independent layer.

Coordinate	Question	Typical evidence
L0	What predictive abstraction is closed and retained?	Aliasing, fit, rollout, query-retention frontier
ρ_{pol}	How much of an existing L0 aliasing defect can the declared acquisition-policy class expose?	Mixture-diameter attribution ratio
$L1_{\text{int}}$	Are abstract transition claims interventionally valid?	Causal-abstraction guard, interventional calibration
L2.G	Is the model/representation adequate over the declared decision class?	AIS or VE-style criteria; direct regret
L2.O	Is the actual model–search pair adequate where it queries, and how fragile is that claim off-prior?	In-prior error + off-prior family/coverage
L3	Is the whole system robust under a declared shift class?	Uniform regret or task-specific robustness criteria

separate from ordinary predictive closure and make robustness claims relative to a declared shift class rather than treating causality as constitutive of every world model.

2.7 Definition by resources versus definition by task

Chen et al. propose a recent perspective in which world models are fundamentally compression-based models of world transition processes under finite computational resources [8]. That view is importantly different from task-relative definitions that make decision usefulness constitutive. Our profile separates these concerns: L0 is task-free but abstraction-relative; task-relative sufficiency enters only at L2. This does not make the profile compatible with every definition. It is better understood as an explication syntax for reporting what a system demonstrably preserves.

3 A declared world-model profile

Let the history at time t be

$$h_t = (o_{\leq t}, a_{< t}) \in \mathcal{H},$$

and let a representation map compress history to

$$z_t = \sigma(h_t) \in \mathcal{Z}.$$

Let $a_t \in \mathcal{A}$, and let $d_{\mathcal{F}}$ denote a declared integral probability metric (IPM).

Before reporting any layer, declare

$$\mathcal{D} = \left(\underbrace{\mathbb{A}, H_{\mathbb{A}}, \Omega_0, \mathcal{F}, \mathcal{B}}_{L0}; \underbrace{\mathcal{I}}_{L1_{\text{int}}}; \underbrace{\mathcal{T}, H, \Pi, \pi_{\text{ref}}, \mathcal{U}, \varepsilon, R, \mathcal{N}}_{L2}; \underbrace{\Delta, \pi_{\text{ref}}}_{L3} \right).$$

Here $\mathbb{A}$ is a family of measurable queries $q : S \rightarrow Y_q$ that defines the abstraction level; $H_{\mathbb{A}}$ is a rollout horizon; Ω_0 the support over which the claim is made; $\mathcal{B}$ a behaviour/acquisition-policy class; $\mathcal{I}$ a family of interventions; $(\mathcal{T}, H, \Pi, \pi_{\text{ref}}, \mathcal{U}, \varepsilon, R)$ a decision contract; $\mathcal{N}$ an off-prior evaluation family or equivalent coverage condition; and Δ a shift class.

An undeclared component has no default. A layer is reported as *pass with measured budget*, *fail*, *not declared*, or *not applicable*. The reporting discipline is structurally similar to engineering qualification: scope is fixed before measurement, budgets and admissible-case coverage are explicit, and an untested condition is not reported as a pass.

3.1 L0: predictive closure at an abstraction frontier

The operational question is not whether a latent model is “predictive” in the abstract, but whether histories that the representation treats as equivalent remain interchangeable under the projected dynamics and whether the declared properties of interest survive that quotient.

Define the true projected one-step law

$$P_\sigma(\cdot \mid h, a) = \text{Law}(\sigma(H_{t+1}) \mid H_t = h, A_t = a)$$

and a candidate latent transition kernel $K(\cdot \mid z, a)$.

Aliasing floor and kernel fit. Two failures are easy to conflate. The first belongs to the compression: if σ merges two histories, do their projected successor laws actually agree? The second belongs to the learned operator: given that compression, does K reproduce those projected laws?

For histories collapsed to the same latent,

$$\delta_{\text{alias}} = \sup_{\substack{h, h' \in \Omega_0 \\ \sigma(h) = \sigma(h')}} \sup_a d_{\mathcal{F}}(P_\sigma(\cdot \mid h, a), P_\sigma(\cdot \mid h', a)).$$

The associated worst-case fit is

$$\delta_{\text{fit}} = \sup_{h \in \Omega_0} \sup_a d_{\mathcal{F}}(K(\cdot \mid \sigma(h), a), P_\sigma(\cdot \mid h, a)).$$

For the sup/IPM form,

$$\delta_{\text{alias}} \leq 2\delta_{\text{fit}}, \quad \frac{\delta_{\text{alias}}}{2} \leq \inf_K \delta_{\text{fit}}(K) \leq \delta_{\text{alias}}.$$

We treat this as an elementary triangle-inequality consequence, not as a novelty claim. Under these worst-case definitions, the two quantities are linked: $\delta_{\text{fit}} = 0$ forces $\delta_{\text{alias}} = 0$. Their practical separation is clearest when model training reports an *averaged* fit loss. A kernel can fit the average next-latent law in a cell while the histories inside that cell disagree strongly. δ_{alias} then identifies disagreement caused by the quotient itself rather than by insufficient optimisation.

There is an equally important limitation. P_σ and K are compared after projection through σ on both sides. A distinction erased by σ is absent from both laws and can therefore be invisible to δ_{alias} , δ_{fit} and δ_{roll} . These quantities measure internal coherence of the projected dynamics, not the external adequacy of what was retained. The query-retention term below supplies that external reference.

Conditional rollout closure. For legal action sequence $a_{t:t+k-1}$,

$$\delta_{\text{roll}}(k) = \sup d_{\mathcal{F}}(K^k(\cdot \mid \sigma(h), a_{t:t+k-1}), P_\sigma^k(\cdot \mid h, a_{t:t+k-1})).$$

The word *conditional* is load-bearing. A model could ignore its starting state yet match an unconditional long-run marginal, while being useless for the planning question “where do I end up from here under these actions?” Hence the comparison is conditioned on the starting history and action sequence. Each horizon-indexed report also carries an admissible case count: termination can remove every relevant continuation at a later horizon, and an empty case set is N/A, not a zero-error success.

Query retention and external reference. For each declared query $q \in \mathbb{A}$,

$$\eta_q(k) = \inf_{g_q} \sup d_q(\text{Law}(g_q(\hat{Z}_{t+k})), \text{Law}(q(S_{t+k}) \mid h, a_{t:t+k-1})), \quad 0 \leq k \leq H_{\mathbb{A}}.$$

Unlike the projected-dynamics quantities, η_q is anchored to something the model did not generate: the declared external query $q(S)$. The price is labelled, oracle, or otherwise justified access to that reference. The $k = 0$ term is essential because reproducing a future distribution is weaker than decoding the property now. A representation may forecast the correct marginal of a query while having erased which value is currently true.

Toy A below exposes both issues. At the phase abstraction the projected process is exact. When the mode query is added, $\eta_{q_{\text{mode}}}(0) = \eta_{q_{\text{mode}}}(1) = 1$ under the L1-TV convention. At $k = 2$ the raw error becomes zero only because the mode-bearing revealed histories have terminated; the report therefore includes query-bearing case counts and marks that horizon as non-informative rather than as recovered decodability.

The abstraction frontier. An L0 statement is therefore not simply “the system passes L0”. It reports

$$\mathbb{A}^* = \text{finest tested abstraction level at which the declared budgets pass,}$$

paired, where possible, with a natural richer level that fails. For a frontier-style claim, a pass without a tested richer level or another non-vacuity certificate is incomplete: it shows that the chosen $\mathbb{A}$ was easy enough, but not where the representation stops being adequate. Toy A’s useful statement is thus “phase passes; phase+mode fails; the separating query is the one later required by the decision”, not merely “L0 passes”.

3.2 Policy exposure as an L0 attribution diagnostic

A change of acquisition policy can alter which full histories are mixed inside one latent cell. It cannot create a compression defect that the cell does not already contain.

For behaviour policy β , define

$$K_\beta^\sigma(\cdot \mid z, a) = \int P_\sigma(\cdot \mid h, a) dP_\beta(h \mid z, a).$$

The behaviour-induced discrepancy is evaluated only where both behaviour policies support the same latent–action pair:

$$\delta_{\text{inv}}^{\text{latent}} = \sup_{\beta, \beta' \in \mathcal{B}(z, a) \in \text{supp}_\beta(Z_t, A_t) \cap \text{supp}_{\beta'}(Z_t, A_t)} \sup_{\beta, \beta'} d_{\mathcal{F}}(K_\beta^\sigma(\cdot \mid z, a), K_{\beta'}^\sigma(\cdot \mid z, a)).$$

Without this common-support condition, one of the two conditional kernels may be undefined at the point being compared. Let w^β and $w^{\beta'}$ denote the corresponding mixture weights over the member histories of a fixed latent cell. An elementary mixture-diameter argument gives

$$d_{\mathcal{F}}(K_\beta^\sigma, K_{\beta'}^\sigma) \leq \frac{1}{2} \|w^\beta - w^{\beta'}\|_1 \delta_{\text{alias}} \leq \delta_{\text{alias}}.$$

Consequently

$$0 \leq \delta_{\text{inv}}^{\text{latent}} \leq \delta_{\text{alias}}.$$

We make no novelty claim for this mixture bound; a dedicated prior-statement search remains a manuscript obligation.

When $\delta_{\text{alias}} > 0$ and the behaviour class $\mathcal{B}$ is explicitly restricted, we report

$$\rho_{\text{pol}} = \frac{\delta_{\text{inv}}^{\text{latent}}}{\delta_{\text{alias}}} \in [0, 1].$$

The interpretation is attribution, not another world-model axis: how much of an existing quotient defect can the declared acquisition class expose? A behaviour change that cannot place weight on the histories carrying the defect leaves it unobserved, not absent. The simple two-history witness used during framework review reduces to behaviour-weight spread; Sec. 5.1 shows why cell geometry matters once three member laws are present.

3.3 $L1_{\text{int}}$: interventional validity

Action conditioning records what happened when an action was *chosen*; an interventional claim concerns what would happen if that action were *set*. If the mechanism choosing the action has access to information not represented in the conditioning variables, the two laws can differ because of confounding rather than transition-model error.

We therefore assert an abstract interventional quantity only when σ is compatible with a declared causal abstraction or exact-transformation relation for intervention family $\mathcal{I}$ [18, 19]. When well posed,

$$\delta_{\text{do}} = \sup_{z, a} d_{\mathcal{F}}(K(\cdot \mid z, a), \text{Law}(\sigma(H_{t+1}) \mid z_t = z, \text{do}(A_t = a))).$$

In an unconfounded online setting in which the agent action is the sole intervention point, the interventional law can coincide with ordinary action-conditioned transition fit. In that case the report should state that $L1_{\text{int}}$ adds no independent information in the declared setting; *not applicable* is reserved for cases in which the intervention question itself is outside scope. Additional empirical content arises with confounded offline data or interventions on variables beyond the agent action. This draft does not yet claim a dedicated empirical $L1_{\text{int}}$ separation.

3.4 L2: global and operational decision adequacy

L2 is explicitly task-relative. Two established routes are useful but answer different questions. AIS asks whether a compressed history statistic approximately preserves reward and next-information-state predictions well enough to support approximate dynamic programming [12]. VE instead asks whether the model preserves Bellman computations over declared policies and value functions [13, 14, 15]. We keep both because they quantify different objects.

We further separate:

- **L2.G**: adequacy over the declared class $(\mathcal{T}, H, \Pi, \pi_{\text{ref}}, \dots)$;
- **L2.O**: adequacy of the actual model–search pair under the planner-induced query distribution μ_{Π} .

The distinction matters because μ_{Π} need not be exogenous. A planner steered by the model’s own scores can avoid regions the model calls unpromising, including regions it calls unpromising because it is wrong there. Error measured only under μ_{Π} can therefore partly measure the system’s own avoidance behaviour: the model influences where it is examined, and it is examined where it appears accurate. This is the failure mode motivating the L2.G/L2.O split [17].

Operational evaluation must additionally report either

$$E_{\text{off}}^* = \sup_{\nu \in \mathcal{N}} E_{\nu}[\ell]$$

or a declared coverage/concentrability coefficient such as

$$C(\nu \parallel \mu_{\Pi}) = \sup_{z,a} \frac{\nu(z,a)}{\mu_{\Pi}(z,a)}.$$

A single convenient off-prior distribution is not enough, because it is selected by the same evaluator reporting the result. Regret always names its comparator:

$$\text{Regret}(\pi; \pi_{\text{ref}}) = V^{\pi_{\text{ref}}} - V^{\pi}.$$

3.5 L3: robustness under declared shift

L3 is system-level:

$$\sup_{\delta \in \Delta} \text{Regret}_{\delta}(\pi; \pi_{\text{ref}}) \leq \rho.$$

A low system-level regret does not license a claim that one latent transition kernel is robust. Online adaptation can compensate for it; memory can identify the regime; replanning can correct a poor prediction at query time; or another component can mask the internal failure. L3 therefore records a property of the system under Δ , not of any one module.

Causal-robustness results such as Richens and Everitt’s must also be imported with their explicit intervention scope and extractability interpretation [20]. Their result concerns robustness to specified local interventions on all environment variables under theorem assumptions and extractable causal structure; it is not a blanket claim that every robust system explicitly stores a causal model.

4 Exact finite evidence

4.1 Toy A: predictive closure at a coarse frontier, contingent decision failure

Let hidden mode $M \in \{0, 1\}$ be uniform. Before termination, the agent is in an unrevealed phase u or a revealed phase r . At u it may choose `commit0`, `commit1`, or `probe`. A probe costs c and reveals M perfectly; at r the agent then commits. A correct commit yields reward 1 and an incorrect commit reward 0.

Consider the coarse representation

$$\sigma_C(h) = \text{phase}(h),$$

which deliberately merges the revealed histories for $M = 0$ and $M = 1$. The mechanism is simple: the hidden mode enters the reward but does not enter the projected phase dynamics. L0 is reward-free, so the phase quotient can be exactly closed even though it has erased the distinction that later determines which commitment is correct.

At

$$\mathbb{A}_{\text{phase}} = \{q_{\text{phase}}\},$$




Figure 1: Toy A. Predictive closure at the phase abstraction is exact, while the information-gathering action makes the discarded mode decision-relevant. Positive L2 regret is certified directly by policy enumeration.

exact enumeration gives

$$\delta_{\text{alias}} = \delta_{\text{fit}} = \delta_{\text{roll}}(1) = \delta_{\text{roll}}(2) = 0,$$

and zero phase-query error on every informative horizon. Yet at the richer

$$\mathbb{A}' = \{q_{\text{phase}}, q_{\text{mode}}\},$$

mode-query error is 1 at $k = 0$ and $k = 1$ under the L1-TV convention. At $k = 2$ the raw mode-query error is zero only because the revealed, mode-bearing histories have terminated; the query-bearing case count is zero and the horizon is reported as non-informative rather than as recovered decodability.

The decision consequence is exact. Enumerating all 12 deterministic history-measurable policies and all 6 deterministic σ_C -measurable policies yields

$$V_{\text{hist}}^*(c) = \max(\tfrac{1}{2}, 1 - c), \quad V_C^*(c) = \tfrac{1}{2},$$

so

$$\text{Regret}(c) = \max(0, \tfrac{1}{2} - c).$$

At $c = 0.10$, the history-aware optimum is 0.90, the best coarse-policy value is 0.50, and regret is 0.40.

Without the probe, both immediate commitments are worth $1/2$ and the coarse representation is optimal: discarding an unknowable distinction costs nothing. The probe is load-bearing because it makes the mode acquirable. For $c < 1/2$, the regret can therefore be read as the value of the discarded information net of its acquisition cost,

$$\text{Regret}(c) = \tfrac{1}{2} - c.$$

This construction therefore establishes only

$$L0(\mathbb{A}_{\text{phase}}) \not\Rightarrow L2_{\text{contingent}}.$$

The certificate is direct positive regret, not failure of an AIS sufficient-condition bound. AIS AP1 error remains a diagnostic: because the hidden mode affects reward, the coarse statistic fails reward prediction at the revealed phase, but failure of a sufficient condition alone would not imply positive regret.

4.2 Toy B: exact decision equivalence despite predictive failure

Let state be $s = (x, n)$, where $x \in \{0, 1\}$ is decision-relevant and $n \in \{0, 1, 2, 3\}$ is nuisance noise. Actions **stay** and **flip** update x deterministically. In the true model, n' is uniform. An intentionally wrong model always predicts $n' = 0$ while predicting the x' dynamics exactly. Reward depends only on x .

With identity representation and full abstraction

$$\mathbb{A}_{\text{full}} = \{q_x, q_n\},$$

the full-state transition error is

$$\delta_{\text{fit}} = 1.5$$

under the L1-TV convention, so L0 fails for any smaller budget.

Now declare the value-function class

$$\mathcal{V}_x = \{V : V(x, n) = v(x)\}.$$

A Bellman update integrates the declared V over the next-state distribution. If V is constant in n , the n' marginal disappears from that integral. Because the true and approximate models have identical x' marginals and identical rewards, every Bellman update on $\mathcal{V}_x$ is therefore identical even though the approximate model is maximally wrong about the nuisance component. Exhaustive computation over all 256 deterministic stationary policies gives maximum Bellman gap zero.

Thus

$$L2.G\text{-VE} = \text{pass} \quad \text{while} \quad L0(\mathbb{A}_{\text{full}}) = \text{fail}.$$

The limitation follows from the same mechanism: value equivalence is a property of a model paired with a declared value class. Enlarge that class to include functions sensitive to n , and the equivalence need not survive. This is intentionally close to classical noisy-TV/state-abstraction examples; we claim no novelty for the phenomenon itself.

4.3 Why the two constructions form a pair

The two directions are possible because L0 and L2 quantify over different index sets. L0 asks what a declared query family $\mathbb{A}$ survives under the representation and its projected dynamics. L2 asks what a declared reward, policy or value-function class requires for decision. Neither declaration automatically dominates the other. The finite constructions therefore establish

$$L0 \not\Rightarrow L2, \quad L2.G \not\Rightarrow L0,$$

under explicit declarations, but they do *not* establish non-collinearity in a non-degenerate regime: Toy A uses a very coarse phase abstraction, and Toy B chooses a value class blind to nuisance by construction.

5 Manuscript-level diagnostics beyond the accepted spine

The following examples are additions for the manuscript. They do not modify the accepted profile.

5.1 A three-history witness for ρ_{pol}

With only two member laws in a latent cell, every behaviour-induced mixture lies on the line segment joining those laws. The distance between two mixtures is then forced to scale with the behaviour-weight displacement, so the ratio ρ_{pol} cannot demonstrate dependence on richer cell geometry.

Consider instead three histories and the same two behaviour mixtures

$$w = (0.5, 0.5, 0), \quad w' = (0, 0.5, 0.5).$$

Their half-L1 weight spread is $\frac{1}{2}\|w - w'\|_1 = 0.5$. The mixture bound from Sec. 3 implies

$$\rho_{\text{pol}} \leq \frac{1}{2}\|w - w'\|_1 = 0.5.$$

In geometry 1, let the projected laws be $(\delta_A, \delta_B, \delta_C)$. Then $\delta_{\text{alias}} = 2$, the two behaviour mixtures are at distance 1, and

$$\rho_{\text{pol}} = 0.5,$$




Figure 2: Same declared behaviour-weight spread, different ρ_{pol} because the latent-cell law geometry differs. This illustrates attribution; it is not a novelty claim.

so the bound is tight. In geometry 2, let the laws be

$$\delta_A, \quad \delta_B, \quad 0.8\delta_A + 0.2\delta_B.$$

The same $\delta_{alias} = 2$ and the same behaviour-weight spread now produce mixture distance 0.2 and

$$\rho_{pol} = 0.1.$$

The third law lies inside the convex hull of the first two, so a substantial weight displacement can move the induced mixture only slightly. The slack in the bound is therefore geometric: ρ_{pol} depends jointly on what behaviour weights are reachable and on how the member laws are arranged inside the aliased cell.

This example answers a narrow reviewer concern. It does not elevate ρ_{pol} into a separate coordinate; it only shows why the attribution diagnostic can contain more information than behaviour-class spread once the cell has at least three non-collinear member laws.

5.2 A minimal L2.O witness

L2.O exists because the model can influence the query distribution under which its own accuracy is measured. A deliberately minimal two-action example makes the loop explicit.

Suppose the true one-step returns are

$$Q_{true}(a_{safe}) = 1, \quad Q_{true}(a_{unseen}) = 2,$$

while the learned model predicts

$$\hat{Q}(a_{safe}) = 1, \quad \hat{Q}(a_{unseen}) = 0.$$

A greedy planner under the learned model therefore selects a_{safe} and induces

$$\mu_{\Pi}(a_{safe}) = 1.$$

The operational prediction error is zero precisely because the model’s own error on a_{unseen} makes the planner avoid querying it. Under a uniform off-prior evaluation distribution, however, the mean absolute error is 1, and the planner incurs regret 1 against the global optimum.

The construction is intentionally minimal; it is not a model of MuZero. It isolates the closed loop motivating L2.O: the model shapes the operating points on which it is evaluated. A representative empirical test would require a learned model and search procedure whose query distribution is genuinely endogenous, together with a declared off-prior family or non-vacuous coverage coefficient.

6 What does the profile add beyond a flat tuple?

The strongest criticism of the proposal is eliminativist. Every reported quantity is ultimately derived from more primitive objects such as the representation σ , the transition operator K , declared decision classes, resources and shift classes. Why not retire “world model” as a technical term and report

$$(\sigma, K, \text{sufficiency class, shift class, resources, } \dots)$$

directly? Naming a bundle of derived quantities does not create a natural kind, and the profile adds no raw information that could not in principle be represented elsewhere. This criticism remains live.

The current positive case has three parts, and they are not equally strong.

The abstraction frontier. This is the strongest profile-level object at present. A single-level tuple reports a point: one chosen $\mathbb{A}$ and its errors. The frontier reports where that claim stops. “Phase passes, phase+mode fails” requires testing and recording at least two levels and naming the separating query. The informational gain is therefore not a new primitive, but an enforced comparison across declared levels.

Bidirectional non-implication. The exact toys show that predictive abstraction and decision adequacy are not two names for the same condition. This is useful defensively, but the flat tuple can represent the same fact. The finite evidence therefore establishes non-identity, not superiority of the profile.

L2.G versus L2.O. This may be the most useful distinction operationally: a model-search pair can look accurate on the distribution it induces while being poor on the larger declared class. But that distinction would remain valuable even if the phrase “world model” disappeared tomorrow. It is a methodological argument for how to evaluate model-search systems, not evidence that a new natural kind has been discovered. He et al.’s analysis of MuZero provides a retrospective example rather than a prediction of this framework: evaluation confined to the search-induced region would miss the model’s poorer evaluation of unseen policies, whereas widening the query contract reveals the discrepancy [17].

The profile earns its name only if cross-layer localisation changes what experiments we run or which failures we predict. A stronger future test would show a case where the frontier or an L2.G/L2.O distinction identifies a failure that a single-level report would have missed, or changes an ablation, shift declaration or data-collection design. Absent such evidence, the eliminativist option remains the default competitor and the burden stays on the profile.

7 Implications for adaptive learning systems and MMALS

The motivating scientific question behind this work is more specific than the definitional dispute. An adaptive learner cannot retain every detail of every past interaction indefinitely. It must in some sense quotient its history. The difficult question is when two histories may safely be treated as equivalent.

The profile is useful here as an instrument rather than as a label. A history compression σ can be closed at one predictive abstraction and fail at another. It can be adequate for one decision class and fail as soon as a new information-gathering action becomes valuable. It can look accurate on the operational region induced by the current planner while being brittle outside that region. Under shift, the whole system may compensate through memory or adaptation even when one transition model is wrong.

For MMALS, the useful object is therefore not the assertion “MMALS is a world model”, but a record of which distinctions are currently preserved, which have been deliberately quotiented away, and under which actions, evidence channels, tasks and regimes that quotient remains defensible.

The present profile still assumes that the abstraction family $\mathbb{A}$ is declared externally. The stronger continual-learning problem is to let the abstraction itself change,

$$\mathbb{A}_t \rightarrow \mathbb{A}_{t+1}.$$

That is closer to MMALS’s REUSE $\rightarrow$ ADAPT $\rightarrow$ FORK $\rightarrow$ NEW REGIME logic: preserve a quotient while it remains adequate, then refine or split it when a previously discarded distinction becomes dynamically, decisionally or causally relevant.

This yields the research question that now motivates the next stage:

Which distinctions between histories should an adaptive learner preserve, and which may it safely quotient away as its actions, evidence channels, tasks and operating regimes change?

8 Research process and transparency

The framework evolved through an explicitly adversarial drafting process. Early versions treated “sufficiency” as the load-bearing constitutive word and separated model from planner too sharply. Review forced the proposal to import AIS and VE as existing decision-sufficiency frameworks, to treat interface-based boundaries cautiously, and to demote behaviour-policy invariance after it was shown to be bounded by L0 aliasing. A later executable audit found that a correct numerical result had initially been supported by a non-evidential script; the script was replaced by environment-derived enumeration and independently recomputed before the present manuscript was prepared.

This history is relevant because the final contribution is smaller than the initial proposal. We regard that reduction as evidence of process quality, not as a weakness to hide.

AI-assistance disclosure. The conceptual programme, problem selection, acceptance/rejection of claims, and final scientific responsibility belong to the author. AI systems were used extensively for literature navigation, drafting, mathematical challenge, code generation, and adversarial review. Independent review passes were themselves AI-assisted, but included checksum verification, clean reruns, independent code paths, and explicit reviewer disclosure. Any public submission should retain a concise disclosure appropriate to the venue and should not describe AI-assisted review as human peer review.

9 Limitations

The present evidence is intentionally narrow.

- The finite constructions establish non-identity of L0 and L2 only in toy regimes.
- Toy A’s passing abstraction is extremely coarse; it does not establish non-degenerate non-collinearity between predictive and decision adequacy.
- Toy B’s decision class is explicitly blind to the nuisance variable.
- $L1_{\text{int}}$ and L3 remain uninstantiated by dedicated finite witnesses in this draft.
- The L2.O witness is diagnostic rather than representative of learned model-search systems.
- The mixture-diameter inequality used to bound $\delta_{\text{inv}}^{\text{latent}}$ is treated as an elementary convexity property; we do not claim novelty and have not performed an exhaustive prior-statement search across probability-metric and aggregation literatures.
- The abstraction frontier is externally declared. Adaptive abstraction discovery and revision remain future work.
- The term “world model” may ultimately be less useful than direct reporting of representation, dynamics, adequacy, and shift contracts.

10 Conclusion

The binary question “does this system have a world model?” often compresses several technically different claims. We proposed a smaller alternative: report predictive abstraction, interventional validity, decision adequacy, operational model-search adequacy and shift robustness separately, under an explicit declaration tuple.

The framework does not settle what a world model *is*. It supplies a disciplined syntax for saying what a particular system has actually demonstrated and where that demonstration stops. Two exact finite constructions show that predictive closure and decision adequacy can come apart in both directions under declared abstractions and decision classes. A three-history diagnostic shows that policy exposure of an L0 compression defect can depend on latent-cell geometry rather than only behaviour-policy spread. A minimal L2.O example illustrates how adequacy measured only where a planner chooses to look can become self-confirming.

Whether this deserves the name “world-model profile” remains an open explanatory question. If the profile does not improve failure localisation, comparison or experimental design, the eliminativist option should win. The more durable scientific problem is the one that motivated the exercise in the first place:

Which distinctions between histories should an adaptive learner preserve, and which may it safely quotient away as its actions, evidence channels, tasks and operating regimes change?

A Finite results summary

Table 2: Exact finite evidence used in the manuscript. TV values use the L1 convention $\sum_x |p(x) - q(x)|$.

Construction	Quantity	Result
Toy A	$\delta_{\text{alias}}, \delta_{\text{fit}}$ at phase level	0, 0
Toy A	Regret at $c = 0.10$	0.40
Toy A	Regret law	$\max(0, \frac{1}{2} - c)$
Toy A	$\eta_{q_{\text{mode}}}(0), \eta_{q_{\text{mode}}}(1)$	1, 1
Toy B	full-state δ_{fit}	1.5
Toy B	max Bellman gap on $\mathcal{V}_x$	0
3-history diagnostic	same weight spread, geometry 1 ρ_{pol}	0.5
3-history diagnostic	same weight spread, geometry 2 ρ_{pol}	0.1
L2.O diagnostic	in-prior absolute error	0
L2.O diagnostic	uniform off-prior absolute error	1

B Reproducibility boundary

The finite evidence underlying the framework is reproduced by an executable package that derives transition laws from explicit environments and enumerates the relevant finite policy classes. The manuscript-only diagnostics in Sec. 5.1 are contained in a separate JSON artifact. The intended submission package should include source, scripts, machine-readable outputs, and checksums. No Monte Carlo estimate is needed for the main two finite separation claims.

References

- [1] K. J. W. Craik. *The Nature of Explanation*. Cambridge University Press, 1943.
- [2] R. C. Conant and W. R. Ashby. Every good regulator of a system must be a model of that system. *International Journal of Systems Science*, 1(2):89–97, 1970. doi:10.1080/00207727008920220.
- [3] D. Ha and J. Schmidhuber. World Models. arXiv:1803.10122, 2018.
- [4] D. Hafner, T. Lillicrap, I. Fischer, R. Villegas, D. Ha, H. Lee, and J. Davidson. Learning Latent Dynamics for Planning from Pixels. In *Proceedings of the 36th International Conference on Machine Learning*, PMLR 97:2555–2565, 2019.
- [5] D. Hafner, T. Lillicrap, J. Ba, and M. Norouzi. Dream to Control: Learning Behaviors by Latent Imagination. *International Conference on Learning Representations*, 2020.
- [6] J. Schrittwieser et al. Mastering Atari, Go, chess and shogi by planning with a learned model. *Nature*, 588:604–609, 2020. doi:10.1038/s41586-020-03051-4.
- [7] Y. LeCun. A Path Towards Autonomous Machine Intelligence. OpenReview position paper, version 0.9.2, 2022.
- [8] X. Chen et al. A Definition and Roadmap for World Models. arXiv:2607.06401, 2026.
- [9] R. Givan, T. Dean, and M. Greig. Equivalence notions and model minimization in Markov decision processes. *Artificial Intelligence*, 147(1–2):163–223, 2003.
- [10] N. Ferns, P. Panangaden, and D. Precup. Metrics for Finite Markov Decision Processes. In *UAI 2004*, pages 162–169, 2004.
- [11] L. Li, T. J. Walsh, and M. L. Littman. Towards a Unified Theory of State Abstraction for MDPs. *ISAIM*, 2006.

- [12] J. Subramanian, A. Sinha, R. Seraj, and A. Mahajan. Approximate Information State for Approximate Planning and Reinforcement Learning in Partially Observed Systems. *Journal of Machine Learning Research*, 23(12):1–83, 2022.
- [13] C. Grimm, A. Barreto, S. Singh, and D. Silver. The Value Equivalence Principle for Model-Based Reinforcement Learning. *NeurIPS*, 33, 2020.
- [14] C. Grimm, A. Barreto, G. Farquhar, D. Silver, and S. Singh. Proper Value Equivalence. *NeurIPS*, 34:7773–7786, 2021.
- [15] C. Grimm, A. Barreto, and S. Singh. Approximate Value Equivalence. *NeurIPS*, 35, 2022.
- [16] T. Ni, B. Eysenbach, E. Seyedsalehi, M. Ma, C. Gehring, A. Mahajan, and P.-L. Bacon. Bridging State and History Representations: Understanding Self-Predictive RL. *International Conference on Learning Representations*, 2024.
- [17] J. He, T. M. Moerland, J. A. de Vries, and F. A. Oliehoek. What Model Does MuZero Learn? *ECAI 2024*, FAIA 392:1599–1606, 2024. doi:10.3233/FAIA240666.
- [18] P. K. Rubenstein et al. Causal Consistency of Structural Equation Models. *UAI*, 2017.
- [19] S. Beckers and J. Y. Halpern. Abstracting Causal Models. *AAAI*, 33(01):2678–2685, 2019.
- [20] J. Richens and T. Everitt. Robust Agents Learn Causal World Models. *International Conference on Learning Representations*, 2024.
- [21] J. Richens, T. Everitt, and D. Abel. General agents need world models. In *Proceedings of the 42nd International Conference on Machine Learning*, PMLR 267:51659–51687, 2025.
- [22] S. Cifuentes. General Agents Contain World Models, even under Partial Observability and Stochasticity. arXiv:2602.03146, 2026.