



2023 송실대학교 SAP_홍석민 프로젝트 결과

2023-06-17



작성일 : 2023년 06월 17일
작성자 : 홍석민

목차

1. 구매처, 자재관리마스터
 1. 구매처 생성 흐름도
 2. 구매처, 자재관리마스터 테이블
 3. 구매처 생성 프로그램
 4. 구매처 생성 화면
2. PO
 1. PO 생성 흐름도
 2. PO 생성 테이블
 3. PO 생성 프로그램
 4. PO 생성 화면

1.1 구매처 생성 흐름도

흐름도	요구 기능
<pre> graph TD A["(Transaction) 실행"] --> B["구매처 생성 화면 실행"] A --> C["구매처 조회 화면 실행"] B --> D["구매처 항목 추가"] D --> E["구매처 항목 저장"] C --> F["구매처 항목 조회"] F --> G["사업자번호 수정"] G --> H["사업자번호 저장"] </pre> The flowchart illustrates the process for creating and managing purchase locations. It starts with a '(Transaction) 실행' (Execute Transaction) step, which branches into two main paths: '구매처 생성 화면 실행' (Execute Purchase Location Creation Screen) and '구매처 조회 화면 실행' (Execute Purchase Location Search Screen). The creation path involves '구매처 항목 추가' (Add Purchase Location Item) followed by '구매처 항목 저장' (Save Purchase Location Item). The search path involves '구매처 항목 조회' (Search Purchase Location Item), which leads to '사업자번호 수정' (Modify Business Number) and then '사업자번호 저장' (Save Business Number).	1. 구매처 저장, 조회가 가능해야 함 2. '구매처 생성 화면' 에서 추가버튼 클릭 시 사용자가 데이터 입력이 가능해야 함 3. '구매처 생성 화면' 에서 저장버튼 클릭 시 DB테이블에 반영 되어야 함 4. '구매처 생성 화면' 에서 계정그룹이 3000 일 때 개인번호 (LFA18-STCD1) 필드가 보여야하며, 2000 일 때 LFA18-STCD1, STCD2 필드가 보이면 안됨 5. '구매처 조회 화면' 에서 사업자번호는 사용자가 데이터 변경이 가능해야 함 6. '구매처 조회 화면' 에서 저장버튼 클릭 시 DB테이블에 반영 되어야 함

1.2 구매처, 자재관리마스터 테이블

다음과 같은 테이블을 생성한다.

Table Name	Description
ZEDT18_015	구매처
ZEDT18_016	자재관리마스터

* 고려사항

1) 회사코드, 구매조직은 1100으로 고정

구매처 테이블 (ZEDT18_015)

Field name	Key	Data Element	Description	Domain	Type	Length	Fixed Value
MANDT	X	MANDT	Client	MANDT	CLNT	3	
ZLFA_LIFNR	X	ZLFA18_LIFNR	구매처번호	ZLFA18_LIFNR	CHAR	10	
ZLFA_KTOKK		ZLFA18_KTOKK	구매처그룹	ZLFA18_KTOKK	CHAR	4	
ZLFA_NAME1		ZLFA18_NAME1	구매처이름	ZLFA18_NAME1	CHAR	30	
ZLFB_BUKRS		ZLFB18_BUKRS	회사코드	ZLFB18_BUKRS	CHAR	4	
ZLFM_EKORG		ZLFM18_EKORG	구매조직	ZLFM18_EKORG	CHAR	4	
ZLFM_WAERS		ZLFM18_WAERS	통화	ZLFM18_WAERS	CUKY	5	
ZLFM_MWSKZ		ZLFM18_MWSKZ	세금코드	ZLFM18_MWSKZ	CHAR	2	
ZLFA_STCD1		ZLFA18_STCD1	개인번호	ZLFA18_STCD1	CHAR	10	
ZLFA_STCD2		ZLFA18_STCD2	사업자번호	ZLFA18_STCD2	CHAR	10	
ZLFA_STCD3		ZLFA18_STCD3	통관번호	ZLFA18_STCD3	CHAR	10	
ZLFA_ORT01		ZLFA18_ORT01	주소	ZLFA18_ORT01	CHAR	50	

1.2 구매처, 자재관리마스터 테이블

자재관리마스터(ZEDT18_016)

Field name	Key	Data Element	Description	Domain	Type	Length	Fixed Value
MANDT	X	MANDT	Client	MANDT	CLNT	3	
ZMARA_MATNR	X	ZMARA18_MATNR	자재코드	ZMARA18_MATNR	CHAR	10	
ZMAKT_MAKTX		ZMAKT18_MAKTX	자재명	ZMAKT18_MAKTX	CHAR	50	
ZMARA_MEINS		ZMARA18_MEINS	단위	ZMARA18_MEINS	CHAR	10	
ZEINE_NETPR		ZEINE18_NETPR	단가	ZEINE18_NETPR	CURR	13	
ZEINE_WAERS		ZEINE18_WAERS	통화	ZEINE18_WAERS	CUKY	5	
ZEINE_APLFZ		ZEINE18_APLFZ	납품소요시간	ZEINE18_APLFZ	NUMC	5	

1.3 구매처 생성 프로그램

프로그램명 : ZPROJECT18_001

```
1  *-----*
2  * Report ZPROJECT18_001
3  *-----*
4  *
5  *-----*
6  REPORT ZPROJECT18_001 MESSAGE-ID ZEDM18.
7
8  INCLUDE ZPROJECT18_001_CLS.
9  INCLUDE ZPROJECT18_001_TOP.
10 INCLUDE ZPROJECT18_001_SCR.
11 INCLUDE ZPROJECT18_001_F01.
12 INCLUDE ZPROJECT18_001_PBO.
13 INCLUDE ZPROJECT18_001_PAI.
14
15 START-OF-SELECTION.
16 IF P_R1 = 'X'.
17     PERFORM SELECT_PURCHASE.
18     IF GT_ZEDT18_015[] IS INITIAL.
19         MESSAGE I001.
20     ELSE.
21         SET SCREEN 100.
22     ENDIF.
23 ELSE.
24     PERFORM SELECT_PURCHASE2.
25     IF GT_ZEDT18_015[] IS INITIAL.
26         MESSAGE I001.
27     ELSE.
28         SET SCREEN 200.
29     ENDIF.
30 ENDIF.
```

1.3 구매처 생성 프로그램

프로그램명 : ZPROJECT18_001 (ZPROJECT18_001_CLS)

```

*~-----*
*~ Include      ZPROJECT18_001_CLS
*~-----*
CLASS EVENT DEFINITION.
  PUBLIC SECTION.
    METHODS HANDLE_DATA_FINISHED FOR EVENT DATA_CHANGED_FINISHED
                                      OF CL_GUI_ALV_GRID
                                      IMPORTING E_MODIFIED ET_GOOD_CELLS.
ENDCLASS.

CLASS EVENT IMPLEMENTATION.
  METHOD HANDLE_DATA_FINISHED.
    PERFORM ALV_HANDLE_DATA_FINISHED USING E_MODIFIED ET_GOOD_CELLS.
  ENDMETHOD.
ENDCLASS.

```

1.3 구매처 생성 프로그램

프로그램명 : ZPROJECT18_001 (ZPROJECT18_001_TOP)

```
*&-----*
*&  Include          ZPROJECT18_001_TOP
*&-----*

TABLES: ZEDT18_015, ZEDT18_016.

* LIST용 변수
DATA : NAME TYPE vrm_id,
      LIST TYPE vrm_values,
      VALUE LIKE LINE OF list.

DATA : GS_ZEDT18_015 TYPE ZEDT18_015,
      GT_ZEDT18_015 LIKE TABLE OF GS_ZEDT18_015,
      GT_ZEDT18_015_TEMP LIKE TABLE OF GS_ZEDT18_015.

DATA : GS_ZEDT18_SH_007 TYPE ZEDT18_SH_007,
      GT_ZEDT18_SH_007 LIKE TABLE OF GS_ZEDT18_SH_007.

DATA : GC_DOCKING TYPE REF TO CL_GUI_DOCKING_CONTAINER.
DATA : GC_GRID TYPE REF TO CL_GUI_ALV_GRID.

DATA : GS_FIELDCAT TYPE LVC_S_FCAT,
      GT_FIELDCAT TYPE LVC_T_FCAT.

DATA : GS_SORT TYPE LVC_S_SORT,
      GT_SORT TYPE LVC_T_SORT.

DATA : GS_LAYOUT TYPE LVC_S_LAYO.

DATA : GS_VARIANT TYPE DISVARIANT.

DATA : OK_CODE TYPE SY-UCOMM.

DATA : GO_EVENT TYPE REF TO EVENT.

DATA : GV_CNT TYPE NUM.

DATA : GV_INDEX TYPE P.
```


1.3 구매처 생성 프로그램

프로그램명 : ZPROJECT18_001 (ZPROJECT18_001_SCR)

```
-----*
Include      ZPROJECT18_001_SCR
-----*

LECTION-SCREEN BEGIN OF BLOCK B1 WITH FRAME TITLE TEXT-002.
  RAMETERS : P_LIFNR LIKE ZEDT18_015-ZLFA_LIFNR AS LISTBOX VISIBLE LENGTH 25 MODIF ID M1.
  RAMETERS : P_BUKRS TYPE C LENGTH 40 VISIBLE LENGTH 15 DEFAULT '1100'.
  RAMETERS : P_KTOKK TYPE C LENGTH 40 AS LISTBOX VISIBLE LENGTH 15 DEFAULT '선택' OBLIGATORY MODIF ID M2.
LECTION-SCREEN END OF BLOCK B1.

LECTION-SCREEN BEGIN OF BLOCK B2 WITH FRAME.
LECTION-SCREEN BEGIN OF LINE.
  RAMETERS : P_R1 RADIOBUTTON GROUP R1 USER-COMMAND UCOM1 DEFAULT 'X'.
  LECTION-SCREEN POSITION 3.
  LECTION-SCREEN : COMMENT (8) FOR FIELD P_R1.
  RAMETERS : P_R2 RADIOBUTTON GROUP R1.
  LECTION-SCREEN POSITION 17.
  LECTION-SCREEN : COMMENT (11) FOR FIELD P_R2.
LECTION-SCREEN END OF LINE.
LECTION-SCREEN END OF BLOCK B2.

SELECTION-SCREEN OUTPUT.
IF P_R1 = 'X'.
  PERFORM SET_KTOKK.
ELSE.
  PERFORM SET_LIFNR.
ENDIF.
PERFORM SET_SCREEN.
```

1.3 구매처 생성 프로그램

프로그램명 : ZPROJECT18_001 (ZPROJECT18_001_F01)-1

```
*-----*
* Include      ZPROJECT18_001_F01
*-----*
* Form SET_KTOKK
*-----*
FORM SET_KTOKK .
  SELECT * INTO CORRESPONDING FIELDS OF TABLE GT_ZEDT18_SH_007 FROM ZEDT18_SH_007.
  CLEAR : VALUE, LIST, NAME.
  LOOP AT GT_ZEDT18_SH_007 INTO GS_ZEDT18_SH_007.
    IF SY-TABIX = 1.
      NAME = 'P_KTOKK'.
      VALUE-KEY = CONV string( SY-TABIX ).
      VALUE-TEXT = GS_ZEDT18_SH_007-ZLFA_KTOKK && ' / ' && GS_ZEDT18_SH_007-ZLFA_KTONM.
      APPEND VALUE TO LIST.
    ELSE.
      VALUE-KEY = CONV string( SY-TABIX ).
      VALUE-TEXT = GS_ZEDT18_SH_007-ZLFA_KTOKK && ' / ' && GS_ZEDT18_SH_007-ZLFA_KTONM.
      APPEND VALUE TO LIST.
    ENDIF.
  ENDOLOOP.
  CALL FUNCTION 'VRM_SET_VALUES'
  EXPORTING
    id      = NAME
    values = LIST.
ENDFORM.
```

```
*-----*
* Form SET_SCREEN
*-----*
FORM SET_SCREEN .
  IF P_R1 = 'X'.
    LOOP AT SCREEN.
      IF SCREEN-GROUP1 = 'M2'.
        SCREEN-ACTIVE = '1'.
      ELSEIF SCREEN-GROUP1 = 'M1'.
        SCREEN-ACTIVE = '0'.
      ENDIF.
    ENDLOOP.
    MODIFY SCREEN.
  ELSEIF P_R2 = 'X'.
    LOOP AT SCREEN.
      IF SCREEN-GROUP1 = 'M1'.
        SCREEN-ACTIVE = '1'.
      ELSEIF SCREEN-GROUP1 = 'M2'.
        SCREEN-ACTIVE = '0'.
      ENDIF.
    ENDLOOP.
    MODIFY SCREEN.
  ENDIF.
ENDFORM.
```

```
*-----*
* Form SET_LIFNR
*-----*
FORM SET_LIFNR .
  SELECT ZLFA_LIFNR ZLFA_NAME1 INTO CORRESPONDING FIELDS OF TABLE GT_ZEDT18_015 FROM ZEDT18_015.
  CLEAR : VALUE, LIST, NAME.
  LOOP AT GT_ZEDT18_015 INTO GS_ZEDT18_015.
    IF SY-TABIX = 1.
      NAME = 'P_LIFNR'.
      VALUE-KEY = CONV string( SY-TABIX ).
      VALUE-TEXT = GS_ZEDT18_015-ZLFA_LIFNR && ' / ' && GS_ZEDT18_015-ZLFA_NAME1.
      APPEND VALUE TO LIST.
    ELSE.
      VALUE-KEY = CONV string( SY-TABIX ).
      VALUE-TEXT = GS_ZEDT18_015-ZLFA_LIFNR && ' / ' && GS_ZEDT18_015-ZLFA_NAME1.
      APPEND VALUE TO LIST.
    ENDIF.
  ENDOLOOP.
  CALL FUNCTION 'VRM_SET_VALUES'
  EXPORTING
    id      = NAME
    values = LIST.
ENDFORM.
```

```
*-----*
* Form SELECT_PURCHASE
*-----*
FORM SELECT_PURCHASE .
  SELECT * INTO CORRESPONDING FIELDS OF TABLE GT_ZEDT18_015 FROM ZEDT18_015.
ENDFORM.
```

```
*-----*
* Form CREATE_OBJECT
*-----*
FORM CREATE_OBJECT .
  CREATE OBJECT GC_DOCKING
  EXPORTING
    REPID      = SY-REPID
    DYNNR      = SY-DYNNR
    EXTENSION  = 2000.
  IF SY-SUBRC <> 0.
    ENDIF.
  CREATE OBJECT GC_GRID
  EXPORTING
    I_PARENT   = GC_DOCKING.
  IF SY-SUBRC <> 0.
    ENDIF.
ENDFORM.
```

1.3 구매처 생성 프로그램

프로그램명 : ZPROJECT18_001 (ZPROJECT18_001_F01)-2

```

*-----*
* Form SET_FIELDCAT
*-----*
FORM SET_FIELDCAT .
  READ TABLE LIST INTO VALUE WITH KEY KEY = P_KTOKK.
  CLEAR : GS_FIELDCAT, GT_FIELDCAT.
  GS_FIELDCAT-COL_POS = 1.
  GS_FIELDCAT-FIELDNAME = 'ZLFA_LIFNR'.
  GS_FIELDCAT-COLTEXT = '구매처번호'.
  APPEND GS_FIELDCAT TO GT_FIELDCAT.

  CLEAR : GS_FIELDCAT.
  GS_FIELDCAT-COL_POS = 2.
  GS_FIELDCAT-FIELDNAME = 'ZLFA_KTOKK'.
  GS_FIELDCAT-COLTEXT = '구매처그룹'.
  APPEND GS_FIELDCAT TO GT_FIELDCAT.

  CLEAR : GS_FIELDCAT.
  GS_FIELDCAT-COL_POS = 3.
  GS_FIELDCAT-FIELDNAME = 'ZLFA_NAME1'.
  GS_FIELDCAT-COLTEXT = '구매처이름'.
  GS_FIELDCAT-EDIT = 'X'.
  APPEND GS_FIELDCAT TO GT_FIELDCAT.

  CLEAR : GS_FIELDCAT.
  GS_FIELDCAT-COL_POS = 4.
  GS_FIELDCAT-FIELDNAME = 'ZLFB_BUKRS'.
  GS_FIELDCAT-COLTEXT = '회사코드'.
  APPEND GS_FIELDCAT TO GT_FIELDCAT.

  CLEAR : GS_FIELDCAT.
  GS_FIELDCAT-COL_POS = 5.
  GS_FIELDCAT-FIELDNAME = 'ZLFM_EKORG'.
  GS_FIELDCAT-COLTEXT = '구매조직'.
  GS_FIELDCAT-EDIT = 'X'.
  APPEND GS_FIELDCAT TO GT_FIELDCAT.

  CLEAR : GS_FIELDCAT.
  GS_FIELDCAT-COL_POS = 6.
  GS_FIELDCAT-FIELDNAME = 'ZLFM_WAERS'.
  GS_FIELDCAT-COLTEXT = '통화'.
  GS_FIELDCAT-EDIT = 'X'.
  APPEND GS_FIELDCAT TO GT_FIELDCAT.

  CLEAR : GS_FIELDCAT.
  GS_FIELDCAT-COL_POS = 7.
  GS_FIELDCAT-FIELDNAME = 'ZLFM_MWSKZ'.
  GS_FIELDCAT-COLTEXT = '세금코드'.
  GS_FIELDCAT-EDIT = 'X'.
  APPEND GS_FIELDCAT TO GT_FIELDCAT.

```

```

IF VALUE-TEXT(4) = '1000'.
  CLEAR : GS_FIELDCAT.
  GS_FIELDCAT-COL_POS = 8.
  GS_FIELDCAT-FIELDNAME = 'ZLFA_STCD2'.
  GS_FIELDCAT-COLTEXT = '사업자번호'.
  GS_FIELDCAT-EDIT = 'X'.
  APPEND GS_FIELDCAT TO GT_FIELDCAT.

  CLEAR : GS_FIELDCAT.
  GS_FIELDCAT-COL_POS = 9.
  GS_FIELDCAT-FIELDNAME = 'ZLFA_ORT01'.
  GS_FIELDCAT-COLTEXT = '주소'.
  GS_FIELDCAT-EDIT = 'X'.
  APPEND GS_FIELDCAT TO GT_FIELDCAT.

ELSEIF VALUE-TEXT(4) = '2000'.
  CLEAR : GS_FIELDCAT.
  GS_FIELDCAT-COL_POS = 8.
  GS_FIELDCAT-FIELDNAME = 'ZLFA_STCD3'.
  GS_FIELDCAT-COLTEXT = '출판번호'.
  GS_FIELDCAT-EDIT = 'X'.
  APPEND GS_FIELDCAT TO GT_FIELDCAT.

  CLEAR : GS_FIELDCAT.
  GS_FIELDCAT-COL_POS = 9.
  GS_FIELDCAT-FIELDNAME = 'ZLFA_ORT01'.
  GS_FIELDCAT-COLTEXT = '주소'.
  GS_FIELDCAT-EDIT = 'X'.
  APPEND GS_FIELDCAT TO GT_FIELDCAT.
ELSE.
  CLEAR : GS_FIELDCAT.
  GS_FIELDCAT-COL_POS = 8.
  GS_FIELDCAT-FIELDNAME = 'ZLFA_STCD1'.
  GS_FIELDCAT-COLTEXT = '개인번호'.
  GS_FIELDCAT-EDIT = 'X'.
  APPEND GS_FIELDCAT TO GT_FIELDCAT.

  CLEAR : GS_FIELDCAT.
  GS_FIELDCAT-COL_POS = 9.
  GS_FIELDCAT-FIELDNAME = 'ZLFA_STCD2'.
  GS_FIELDCAT-COLTEXT = '사업자번호'.
  GS_FIELDCAT-EDIT = 'X'.
  APPEND GS_FIELDCAT TO GT_FIELDCAT.

  CLEAR : GS_FIELDCAT.
  GS_FIELDCAT-COL_POS = 10.
  GS_FIELDCAT-FIELDNAME = 'ZLFA_ORT01'.
  GS_FIELDCAT-COLTEXT = '주소'.
  GS_FIELDCAT-EDIT = 'X'.
  APPEND GS_FIELDCAT TO GT_FIELDCAT.
ENDIF.
ENDFORM.

```

1.3 구매처 생성 프로그램

프로그램명 : ZPROJECT18_001 (ZPROJECT18_001_F01)-3

```
*-----*  
* Form SET_SORT  
*-----*  
FORM SET_SORT .  
  CLEAR : GS_SORT, GT_SORT.  
  GS_SORT-SPQS = '1'.  
  GS_SORT-FIELDNAME = 'ZLFA_LIFNR'.  
  GS_SORT-UP = 'X'.  
  APPEND GS_SORT TO GT_SORT.  
ENDFORM.  
  
*-----*  
* Form SET_LAYOUT  
*-----*  
FORM SET_LAYOUT .  
  CLEAR : GS_LAYOUT.  
  GS_LAYOUT-ZEBRA = 'X'.  
  
  CLEAR GS_VARIANT.  
  GS_VARIANT-REPORT = SY-REPID.  
  GS_VARIANT-USERNAME = SY-UNAME.  
ENDFORM.  
  
*-----*  
* Form CALL_ALV  
*-----*  
FORM CALL_ALV .  
  CLEAR : GV_CNT.  
  
  IF P_R1 = 'X'.  
    CLEAR : GS_ZEDT18_015, GT_ZEDT18_015.  
  ENDIF.  
  CALL METHOD GC_GRID->SET_TABLE_FOR_FIRST_DISPLAY  
    EXPORTING  
      IS_VARIANT          = GS_VARIANT  
      I_SAVE              = 'X'  
      IS_LAYOUT           = GS_LAYOUT  
      CHANGING  
        IT_OUTTAB         = GT_ZEDT18_015  
        IT_FIELDCATALOG   = GT_FIELDCAT  
        IT_SORT            = GT_SORT.  
  IF SY-SUBRC <> 0.  
    * Implement suitable error handling here  
  ENDIF.  
ENDFORM.  
  
*-----*  
* Form REFRESH  
*-----*  
FORM REFRESH .  
  DATA : LS_STABLE TYPE LVC_S_STBL.  
  
  CALL METHOD GC_GRID->REFRESH_TABLE_DISPLAY  
    EXPORTING  
      IS_STABLE           = LS_STABLE .  
  IF SY-SUBRC <> 0.  
    * Implement suitable error handling here  
  ENDIF.  
ENDFORM.
```

```
*-----*  
* Form ADD_ROW  
*-----*  
FORM ADD_ROW .  
  CLEAR : VALUE.  
  GS_ZEDT18_015-ZLFB_BUKRS = P_BUKRS.  
  READ TABLE LIST INTO VALUE WITH KEY KEY = P_KTOKK.  
  SELECT COUNT(*) FROM ZEDT18_015 WHERE ZLFA_KTOKK = VALUE-TEXT(4).  
  GS_ZEDT18_015-ZLFA_KTOKK = VALUE-TEXT(4).  
  IF GV_CNT = 0.  
    GV_INDEX = VALUE-TEXT(4) && '0000000'.  
    GV_INDEX = GV_INDEX + SY-DBCNT.  
    GV_CNT = 1.  
  ELSE.  
    GV_INDEX = GV_INDEX + 1.  
  ENDIF.  
  GS_ZEDT18_015-ZLFA_LIFNR = GV_INDEX.  
  APPEND GS_ZEDT18_015 TO GT_ZEDT18_015.  
  PERFORM REFRESH.  
ENDFORM.  
  
*-----*  
* Form ALV_HANDLE_DATA_FINISHED  
*-----*  
FORM ALV_HANDLE_DATA_FINISHED USING P_MODIFIED  
  P_GOOD_CELLS TYPE LVC_T_MODI.  
ENDFORM.  
  
*-----*  
* Form CLASS_EVENT  
*-----*  
FORM CLASS_EVENT .  
  CALL METHOD GC_GRID->REGISTER_EDIT_EVENT  
    EXPORTING  
      I_EVENT_ID = CL_GUI_ALV_GRID->MC_EVT_MODIFIED.  
  IF SY-SUBRC <> 0.  
    * Implement suitable error handling here  
  ENDIF.  
  
  CREATE OBJECT GO_EVENT.  
  SET HANDLER GO_EVENT->HANDLE_DATA_FINISHED FOR GC_GRID.  
ENDFORM.  
  
*-----*  
* Form SAVE_ROWS  
*-----*  
FORM SAVE_ROWS .  
  LOOP AT GT_ZEDT18_015 INTO GS_ZEDT18_015.  
    IF GS_ZEDT18_015-ZLFA_NAME1 = '' OR GS_ZEDT18_015-ZLFB_ERORG = '',  
      IF GS_ZEDT18_015-ZLFA_KTOKK = '1000',  
        IF GS_ZEDT18_015-ZLFA_STCD2 = '',  
          MESSAGE '사입번호는 필수 항목입니다.' TYPE 'I'.  
          STOP.  
        ELSE.  
          MESSAGE '입력에 전언이 있는지 확인해주세요.' TYPE 'I'.  
          STOP.  
        ENDIF.  
      ELSEIF GS_ZEDT18_015-ZLFA_KTOKK = '2000',  
        IF GS_ZEDT18_015-ZLFA_STCD3 = '',  
          MESSAGE '사입번호는 필수 항목입니다.' TYPE 'I'.  
          STOP.  
        ELSE.  
          MESSAGE '입력에 전언이 있는지 확인해주세요.' TYPE 'I'.  
          STOP.  
        ENDIF.  
      ELSEIF GS_ZEDT18_015-ZLFA_KTOKK = '3000',  
        IF GS_ZEDT18_015-ZLFA_STCD2 = '',  
          MESSAGE '사입번호는 필수 항목입니다.' TYPE 'I'.  
          STOP.  
        ELSE.  
          MESSAGE '입력에 전언이 있는지 확인해주세요.' TYPE 'I'.  
          STOP.  
        ENDIF.  
      ENDIF.  
      INSERT ZEDT18_015 FROM GS_ZEDT18_015.  
    ENDLOOP.  
    MESSAGE '저장되었습니다.' TYPE 'I'.  
    LEAVE TO SCREEN 0.  
  ENDFORM.
```

1.3 구매처 생성 프로그램

프로그램명 : ZPROJECT18_001 (ZPROJECT18_001_F01)-4

```
*-----*  
* Form SELECT_PURCHASE2  
*-----*  
FORM SELECT_PURCHASE2 .  
  CLEAR : VALUE.  
  READ TABLE LIST INTO VALUE WITH KEY KEY = P_LIFNR.  
  SELECT * INTO CORRESPONDING FIELDS OF TABLE GT_ZEDT18_015 FROM ZEDT18_015  
    WHERE ZLFA_LIFNR = VALUE-TEXT(10).  
ENDFORM.  
*-----*  
* Form SET_FIELDCAT2  
*-----*  
FORM SET_FIELDCAT2 .  
  DATA : LV_LIFNR LIKE GS_ZEDT18_015-ZLFA_KTOKK.  
  LOOP AT GT_ZEDT18_015 INTO GS_ZEDT18_015.  
    LV_LIFNR = GS_ZEDT18_015-ZLFA_LIFNR.  
  ENDLOOP.  
  CLEAR : GS_FIELDCAT, GT_FIELDCAT.  
  GS_FIELDCAT-COL_POS = 1.  
  GS_FIELDCAT-FIELDNAME = 'ZLFA_LIFNR'.  
  GS_FIELDCAT-COLTEXT = '구매처명'.  
  APPEND GS_FIELDCAT TO GT_FIELDCAT.  
  
  CLEAR : GS_FIELDCAT.  
  GS_FIELDCAT-COL_POS = 2.  
  GS_FIELDCAT-FIELDNAME = 'ZLFA_KTOKK'.  
  GS_FIELDCAT-COLTEXT = '구매처코드'.  
  APPEND GS_FIELDCAT TO GT_FIELDCAT.  
  
  CLEAR : GS_FIELDCAT.  
  GS_FIELDCAT-COL_POS = 3.  
  GS_FIELDCAT-FIELDNAME = 'ZLFA_NAME1'.  
  GS_FIELDCAT-COLTEXT = '구매처이름'.  
  APPEND GS_FIELDCAT TO GT_FIELDCAT.  
  
  CLEAR : GS_FIELDCAT.  
  GS_FIELDCAT-COL_POS = 4.  
  GS_FIELDCAT-FIELDNAME = 'ZLFB_BUKRS'.  
  GS_FIELDCAT-COLTEXT = '회사코드'.  
  APPEND GS_FIELDCAT TO GT_FIELDCAT.  
  
  CLEAR : GS_FIELDCAT.  
  GS_FIELDCAT-COL_POS = 5.  
  GS_FIELDCAT-FIELDNAME = 'ZLFM_EKORG'.  
  GS_FIELDCAT-COLTEXT = '구매조직'.  
  APPEND GS_FIELDCAT TO GT_FIELDCAT.  
  
  CLEAR : GS_FIELDCAT.  
  GS_FIELDCAT-COL_POS = 6.  
  GS_FIELDCAT-FIELDNAME = 'ZLFM_WAERS'.  
  GS_FIELDCAT-COLTEXT = '통관'.  
  APPEND GS_FIELDCAT TO GT_FIELDCAT.  
  
  CLEAR : GS_FIELDCAT.  
  GS_FIELDCAT-COL_POS = 7.  
  GS_FIELDCAT-FIELDNAME = 'ZLFM_MMSKZ'.  
  GS_FIELDCAT-COLTEXT = '세출코드'.  
  APPEND GS_FIELDCAT TO GT_FIELDCAT.
```

```
IF LV_LIFNR = '1000'.  
  CLEAR : GS_FIELDCAT.  
  GS_FIELDCAT-COL_POS = 8.  
  GS_FIELDCAT-FIELDNAME = 'ZLFA_STCD2'.  
  GS_FIELDCAT-COLTEXT = '사출사출코드'.  
  GS_FIELDCAT-EDIT = 'X'.  
  APPEND GS_FIELDCAT TO GT_FIELDCAT.  
  
  CLEAR : GS_FIELDCAT.  
  GS_FIELDCAT-COL_POS = 9.  
  GS_FIELDCAT-FIELDNAME = 'ZLFA_ORT01'.  
  GS_FIELDCAT-COLTEXT = '주소'.  
  APPEND GS_FIELDCAT TO GT_FIELDCAT.  
  
ELSEIF LV_LIFNR = '2000'.  
  CLEAR : GS_FIELDCAT.  
  GS_FIELDCAT-COL_POS = 8.  
  GS_FIELDCAT-FIELDNAME = 'ZLFA_STCD3'.  
  GS_FIELDCAT-COLTEXT = '세출사출코드'.  
  APPEND GS_FIELDCAT TO GT_FIELDCAT.  
  
  CLEAR : GS_FIELDCAT.  
  GS_FIELDCAT-COL_POS = 9.  
  GS_FIELDCAT-FIELDNAME = 'ZLFA_ORT01'.  
  GS_FIELDCAT-COLTEXT = '주소'.  
  APPEND GS_FIELDCAT TO GT_FIELDCAT.  
ELSE.  
  CLEAR : GS_FIELDCAT.  
  GS_FIELDCAT-COL_POS = 8.  
  GS_FIELDCAT-FIELDNAME = 'ZLFA_STCD1'.  
  GS_FIELDCAT-COLTEXT = '세출사출코드'.  
  APPEND GS_FIELDCAT TO GT_FIELDCAT.  
  
  CLEAR : GS_FIELDCAT.  
  GS_FIELDCAT-COL_POS = 9.  
  GS_FIELDCAT-FIELDNAME = 'ZLFA_STCD2'.  
  GS_FIELDCAT-COLTEXT = '사출사출코드'.  
  APPEND GS_FIELDCAT TO GT_FIELDCAT.  
  
  CLEAR : GS_FIELDCAT.  
  GS_FIELDCAT-COL_POS = 10.  
  GS_FIELDCAT-FIELDNAME = 'ZLFA_ORT01'.  
  GS_FIELDCAT-COLTEXT = '주소'.  
  APPEND GS_FIELDCAT TO GT_FIELDCAT.  
ENDIF.  
ENDFORM.  
*-----*  
* Form UPDATE_ROWS  
*-----*  
FORM UPDATE_ROWS .  
  LOOP AT GT_ZEDT18_015 INTO GS_ZEDT18_015.  
    UPDATE ZEDT18_015 SET ZLFA_STCD2 = GS_ZEDT18_015-ZLFA_STCD2 WHERE ZLFA_LIFNR = GS_ZEDT18_015-ZLFA_LIFNR.  
  ENDLOOP.  
  MESSAGE '구매처생성완료.' TYPE 'I'.  
  LEAVE TO SCREEN 0.  
ENDFORM.
```

1.3 구매처 생성 프로그램

프로그램명 : ZPROJECT18_001 (ZPROJECT18_001_PBO)

```
1  *-----*
2  * Include      ZPROJECT18_001_PBO
3  *-----*
4  *-----*
5  *      Module  STATUS_0100  OUTPUT
6  *-----*
7  *      text
8  *-----*
9  MODULE STATUS_0100 OUTPUT.
10   SET PF-STATUS 'STATUS_0100'.
11   SET TITLEBAR '구매처 생성'.
12 ENDMODULE.
13 *-----*
14 *      Module  ALV_DISPLAY  OUTPUT
15 *-----*
16 MODULE ALV_DISPLAY OUTPUT.
17   IF P_R1 = 'X'.
18     IF GC_DOCKING IS INITIAL.
19       PERFORM CREATE_OBJECT.
20       PERFORM SET_FIELDCAT.
21       PERFORM SET_SORT.
22       PERFORM SET_LAYOUT.
23       PERFORM CLASS_EVENT.
24       PERFORM CALL_ALV.
25     ELSE.
26       PERFORM REFRESH.
27     ENDIF.
28   ELSE.
29     IF GC_DOCKING IS INITIAL.
30       PERFORM CREATE_OBJECT.
31       PERFORM SET_FIELDCAT2.
32       PERFORM SET_SORT.
33       PERFORM SET_LAYOUT.
34       PERFORM CLASS_EVENT.
35       PERFORM CALL_ALV.
36     ELSE.
37       PERFORM REFRESH.
38     ENDIF.
39   ENDIF.
40 ENDMODULE.
41 *-----*
42 *      Module  STATUS_0200  OUTPUT
43 *-----*
44 *      text
45 *-----*
46 MODULE STATUS_0200 OUTPUT.
47   SET PF-STATUS 'STATUS_0200'.
48   SET TITLEBAR '구매처 조회'.
49 ENDMODULE.
```

1.3 구매처 생성 프로그램

프로그램명 : ZPROJECT18_001 (ZPROJECT18_001_PAI)

```
1  *-----*
2  * Include      ZPROJECT18_001_PAI
3  *-----*
4  *
5  * Module  USER_COMMAND_0100  INPUT
6  *-----*
7  MODULE USER_COMMAND_0100 INPUT.
8  CASE OK_CODE.
9  WHEN 'ADD'.
10     PERFORM ADD_ROW.
11  WHEN 'SAVE'.
12     PERFORM SAVE_ROWS.
13  ENDCASE.
14 ENDMODULE.
15 *-----*
16 * Module  EXIT_COMMAND  INPUT
17 *-----*
18 MODULE EXIT_COMMAND INPUT.
19 CASE OK_CODE.
20 WHEN 'BACK' OR 'EXIT'.
21     LEAVE TO SCREEN 0.
22 WHEN 'CANC'.
23     LEAVE PROGRAM.
24 ENDCASE.
25 ENDMODULE.
26 *-----*
27 * Module  USER_COMMAND2  INPUT
28 *-----*
29 MODULE USER_COMMAND2 INPUT.
30 CASE OK_CODE.
31 WHEN 'SAVE'.
32     PERFORM UPDATE_ROWS.
33 ENDCASE.
34 ENDMODULE.
```

1.4 구매처 생성 화면

초기화면 (생성 / 조회)

✓ [] [] Cancel More ▾

회사코드 1100

계정그룹 선택

1000 / 국내
2000 / 해외
3000 / 개인
4000 / 부서
5000 / 법인카드
6000 / 금융기관
9000 / 1회성
선택

☒ 생성 ☐ 조회

✓ [] [] Cancel More ▾

구매처코드 []

회사코드 1000000000 / 석민유통

1000000001 / 연준야채
1000000002 / 원기축산
2000000000 / 심플로트
2000000001 / 소스매니아
3000000000 / 홍두표

☐ 생성 ☒ 조회

- 버튼에 따라 다른 화면 출력
- 계정그룹, 구매처코드는 LIST BOX로 구현

1.4 구매처 생성 화면

생성화면 추가

☐	구매처번호	구매처그룹	구매처이름	회사코드	구매조직	통화	세금코드	사업자번호	주소
☐	1000000003	1000		1100					
☐	1000000004	1000		1100					
☐	1000000005	1000		1100					
☐	1000000006	1000		1100					

- 추가버튼 클릭 시 한 행씩 화면에 추가되어 출력
- 구매번호 : DB테이블 데이터 중 마지막 구매처 번호 + 1로 자동 채움
- 구매처그룹 : 초기화면에서 설정한 값으로 자동 채움
- 회사코드 : 초기화면에서 설정한 값으로 자동 채움

2.1 PO 생성 흐름도

흐름도	요구 기능
<pre> graph TD A([(Transaction) 실행]) --> B([PO 생성 화면 실행]) B --> C([PO 헤더 생성]) B --> D([PO 아이템 항목 추가]) D --> E([PO 아이템 항목 삭제]) D --> F([PO 아이템 항목 저장]) </pre>	1. PO 아이템 생성 시 자동으로 PO 헤더가 DB테이블에 저장되어야 함 2. PO 아이템 생성 화면에서 항목추가, 항목삭제, PO저장 버튼이 필요함 3. 품목 필드는 10씩 증가하며 자동으로 채워짐 4. 구매처 필드는 Search Help 기능을 통해 어떤 것을 기입해야 하는지 알 수 있어야함 5. 자재명, 단위, 단가는 자재마스터 DB에서 참조해야 함 6. 통화, 세금코드는 구매처마스터 DB에서 참조해야 함 7. 'PO 생성 화면' 에서 PO 저장 버튼을 클릭 시 데이터가 DB에 반영되어야 함

2.2 PO 헤더, PO 아이템 테이블

다음과 같은 테이블을 생성한다.

Table Name	Description
ZEDT18_017	PO 헤더
ZEDT18_018	PO 아이템

* 고려사항

1) 오더번호 필드는 PO 헤더, PO 아이템 테이블에 똑같이 들어gå야 함

PO 헤더 테이블 (ZEDT18_017)

Field name	Key	Data Element	Description	Domain	Type	Length	Fixed Value
MANDT	X	MANDT	Client	MANDT	CLNT	3	
ZEKKO_EBELN	X	ZEKKO18_EBELN	오더번호	ZEKKO18_EBELN	CHAR	10	
ZEKKO_BUKRS		ZEKKO18_BUKRS	회사코드	ZEKKO18_BUKRS	CHAR	4	
ZEKKO_EKGRP		ZEKKO18_EKGRP	구매그룹	ZEKKO18_EKGRP	CHAR	4	
ZEKKO_EKORG		ZEKKO18_EKORG	구매조직	ZEKKO18_EKORG	CHAR	4	
ZEKKO_LIFNR		ZEKKO18_LIFNR	구매처번호	ZEKKO18_LIFNR	CHAR	10	
ZEKKO_BEDAT		ZEKKO18_BEDAT	증빙일	ZEKKO18_BEDAT	DATS	8	
ZEKKO_WAERS		ZEKKO18_WAERS	통화	ZEKKO18_WAERS	CUKY	5	

1.2 구매처, 자재관리마스터 테이블

PO 아이템 테이블(ZEDT18_018)

Field name	Key	Data Element	Description	Domain	Type	Length	Fixed Value
MANDT	X	MANDT	Client	MANDT	CLNT	3	
ZEKPO_EBELN	X	ZEKPO18_EBELN	오더번호	ZEKPO18_EBELN	CHAR	10	
ZEKPO_EBELP	X	ZEKPO18_EBELP	품목	ZEKPO18_EBELP	INT2	5	
ZEKPO_MATNR		ZEKPO18_MATNR	자재코드	ZEKPO18_MATNR	CHAR	10	
ZMAKT_MAKTX		ZMAKT18_MAKTX	자재명	ZMAKT18_MAKTX	CHAR	50	
ZEKPO_MENGE		ZEKPO18_MENGE	수량	ZEKPO18_MENGE	INT2	5	
ZEKPO_MEINS		ZEKPO18_MEINS	단위	ZEKPO18_MEINS	CHAR	10	
ZEKPO_BPRME		ZEKPO18_BPRME	단가	ZEKPO18_BPRME	CURR	13	
ZEKKO_WAERS		ZEKKO18_WAERS	통화	ZEKKO18_WAERS	CUKY	5	
ZEKPO_PRDAT		ZEKPO18_PRDAT	납품일	ZEKPO18_PRDAT	DATS	8	
ZEKPO_WERKS		ZEKPO18_WERKS	플랜트	ZEKPO18_WERKS	CHAR	4	
ZEKPO_LGORT		ZEKPO18_LGORT	저장위치	ZEKPO18_LGORT	CHAR	4	
ZEKPO_MWSKZ		ZEKPO18_MWSKZ	세금코드	ZEKPO18_MWSKZ	CHAR	2	

2.3 PO 생성 프로그램

프로그램명 : ZPROJECT18_002

```

⊞ * &-----*
  * & Report ZPROJECT18_002
  * &-----*
  * &
  * &-----*
REPORT ZPROJECT18_002 MESSAGE-ID ZEDM18.

INCLUDE ZPROJECT18_002_CLS.
INCLUDE ZPROJECT18_002_TOP.
INCLUDE ZPROJECT18_002_SCR.
INCLUDE ZPROJECT18_002_F01.
INCLUDE ZPROJECT18_002_PBO.
INCLUDE ZPROJECT18_002_PAI.

START-OF-SELECTION.
PERFORM CHECK_PARAMETERS.
PERFORM INSERT_HEADER.

⊞ IF GS_ZEDT18_017-ZEKKO_EBELN IS INITIAL.
  MESSAGE I001.
⊙ ELSE.
  SET SCREEN 100.
⊞ ENDIF.
```

2.3 PO 생성 프로그램

프로그램명 : ZPROJECT18_002 (ZPROJECT18_002_CLS)

```

*-----*
*&  Include      ZPROJECT18_002_CLS
*&-----*
CLASS EVENT DEFINITION.
  PUBLIC SECTION.
    METHODS HANDLE_DATA_FINISHED FOR EVENT DATA_CHANGED_FINISHED
                                     OF CL_GUI_ALV_GRID
                                     IMPORTING E_MODIFIED ET_GOOD_CELLS.
ENDCLASS.

CLASS EVENT IMPLEMENTATION.
  METHOD HANDLE_DATA_FINISHED.
    PERFORM ALV_HANDLE_DATA_FINISHED USING E_MODIFIED ET_GOOD_CELLS.
  ENDMETHOD.
ENDCLASS.
```

2.3 PO 생성 프로그램

프로그램명 : ZPROJECT18_002 (ZPROJECT18_002_TOP)

```
*&-----*  
*& Include      ZPROJECT18_002_TOP  
*&-----*  
  
TABLES : ZEDT18_015, ZEDT18_016, ZEDT18_017, ZEDT18_018, ZEDT18_SH_008.  
  
DATA : GS_ZEDT18_017 LIKE ZEDT18_017,  
       GT_ZEDT18_017 LIKE TABLE OF GS_ZEDT18_017.  
  
DATA : GS_ZEDT18_018 LIKE ZEDT18_018,  
       GT_ZEDT18_018 LIKE TABLE OF GS_ZEDT18_018.  
  
DATA : GS_ZEDT18_016 LIKE ZEDT18_016.  
  
DATA : GC_DOCKING TYPE REF TO CL_GUI_DOCKING_CONTAINER.  
DATA : GC_GRID TYPE REF TO CL_GUI_ALV_GRID.  
  
DATA : GS_FIELDCAT TYPE LVC_S_FCAT,  
       GT_FIELDCAT TYPE LVC_T_FCAT.  
  
DATA : GS_SORT TYPE LVC_S_SORT,  
       GT_SORT TYPE LVC_T_SORT.  
  
DATA : GS_LAYOUT TYPE LVC_S_LAYO.  
  
DATA : GS_VARIANT TYPE DISVARIANT.  
  
DATA : OK_CODE TYPE SY-UCOMM.  
  
DATA : GO_EVENT TYPE REF TO EVENT.  
  
DATA : GV_EBELP TYPE INT2.  
DATA : GV_BPRME TYPE ZEDT18_018-ZEKPO_BPRME.  
DATA : GV_MEINS TYPE C LENGTH 10.
```


2.3 PO 생성 프로그램

프로그램명 : ZPROJECT18_002 (ZPROJECT18_002_SCR)

```

*-----*
* Include      ZPROJECT18_002_SCR
*-----*
SELECTION-SCREEN BEGIN OF BLOCK B1 WITH FRAME.
  PARAMETERS : P_BUKRS LIKE ZEDT18_017-ZEKKO_BUKRS DEFAULT '1100'.
  PARAMETERS : P_EKORG LIKE ZEDT18_017-ZEKKO_EKORG DEFAULT '1100'.
  PARAMETERS : P_BEDAT LIKE ZEDT18_017-ZEKKO_BEDAT DEFAULT SY-DATUM.
  PARAMETERS : P_LIFNR TYPE C LENGTH 10.
SELECTION-SCREEN END OF BLOCK B1.
```

2.3 PO 생성 프로그램

프로그램명 : ZPROJECT18_002 (ZPROJECT18_002_F01)-1

```
*-----*
*& Include      ZPROJECT18_002_F01
*&-----*
*&-----*
*& Form CHECK_PARAMETERS
*&-----*
FORM CHECK_PARAMETERS .
  IF P_BUKRS = '' OR P_EKORG = '' OR P_BEDAT = '' OR P_LIFNR = '' .
    MESSAGE '조건을 전부 입력해주세요.' TYPE 'I'.
    STOP.
  ENDIF.

  SELECT COUNT(*) FROM ZEDT18_015 WHERE ZLFA_LIFNR = P_LIFNR.
  IF SY-DBCNT = 0.
    MESSAGE '해당 구매처번호는 존재하지 않습니다.' TYPE 'I'.
    STOP.
  ENDIF.
ENDIF.

*-----*
*& Form INSERT_HEADER
*&-----*
FORM INSERT_HEADER .
  SELECT COUNT(*) FROM ZEDT18_017.
  GS_ZEDT18_017-ZEKKO_EBELN = SY-DBCNT + 1.
  GS_ZEDT18_017-ZEKKO_BUKRS = P_BUKRS.
  GS_ZEDT18_017-ZEKKO_EKGRP = '1100'.
  GS_ZEDT18_017-ZEKKO_EKORG = P_EKORG.
  GS_ZEDT18_017-ZEKKO_LIFNR = P_LIFNR.
  GS_ZEDT18_017-ZEKKO_BEDAT = P_BEDAT.

  DATA : LS_ZEDT18_015 LIKE ZEDT18_015.
  SELECT SINGLE * FROM ZEDT18_015 INTO CORRESPONDING FIELDS OF LS_ZEDT18_015 WHERE ZLFA_LIFNR = P_LIFNR.
  GS_ZEDT18_017-ZEKKO_WAERS = LS_ZEDT18_015-ZLFM_WAERS.
  * 실행 후 user command add를 사용하기 전에 미리 초기화
  GV_EBELP = 0.
ENDIF.
```

```
*-----*
*& Form CREATE_OBJECT
*&-----*
FORM CREATE_OBJECT .
  CREATE OBJECT GC_DOCKING
  EXPORTING
    REPID              = SY-REPID
    DYNNR              = SY-DYNNR
    EXTENSION          = 2000.
  IF SY-SUBRC <> 0.
    ENDIF.

  CREATE OBJECT GC_GRID
  EXPORTING
    I_PARENT           = GC_DOCKING.
  IF SY-SUBRC <> 0.
    ENDIF.
ENDIF.

*-----*
*& Form SET_FIELDCAT
*&-----*
FORM SET_FIELDCAT .
  CLEAR : GS_FIELDCAT, GT_FIELDCAT.
  GS_FIELDCAT-COL_POS = 1.
  GS_FIELDCAT-FIELDNAME = 'ZEKPO_EBELP'.
  GS_FIELDCAT-COLTEXT = '물류'.
  APPEND GS_FIELDCAT TO GT_FIELDCAT.

  CLEAR : GS_FIELDCAT.
  GS_FIELDCAT-COL_POS = 2.
  GS_FIELDCAT-FIELDNAME = 'ZEKPO_MATNR'.
  GS_FIELDCAT-COLTEXT = '재고코드'.
  GS_FIELDCAT-REF_TABLE = 'ZEDT18_018'.
  GS_FIELDCAT-REF_FIELD = 'ZEKPO_MATNR'.
  GS_FIELDCAT-EDIT = 'X'.
  GS_FIELDCAT-f4availabl = 'X'.
  APPEND GS_FIELDCAT TO GT_FIELDCAT.
```

2.3 PO 생성 프로그램

프로그램명 : ZPROJECT18_002 (ZPROJECT18_002_F01)-1

```
*-----*
*& Include      ZPROJECT18_002_F01
*&-----*
*&-----*
*& Form CHECK_PARAMETERS
*&-----*
FORM CHECK_PARAMETERS .
  IF P_BUKRS = '' OR P_EKORG = '' OR P_BEDAT = '' OR P_LIFNR = '' .
    MESSAGE '조건을 전부 입력해주세요.' TYPE 'I'.
    STOP.
  ENDIF.

  SELECT COUNT(*) FROM ZEDT18_015 WHERE ZLFA_LIFNR = P_LIFNR.
  IF SY-DBCNT = 0.
    MESSAGE '해당 구매처번호는 존재하지 않습니다.' TYPE 'I'.
    STOP.
  ENDIF.
ENDIF.

*-----*
*& Form INSERT_HEADER
*&-----*
FORM INSERT_HEADER .
  SELECT COUNT(*) FROM ZEDT18_017.
  GS_ZEDT18_017-ZEKKO_EBELN = SY-DBCNT + 1.
  GS_ZEDT18_017-ZEKKO_BUKRS = P_BUKRS.
  GS_ZEDT18_017-ZEKKO_EKGRP = '1100'.
  GS_ZEDT18_017-ZEKKO_EKORG = P_EKORG.
  GS_ZEDT18_017-ZEKKO_LIFNR = P_LIFNR.
  GS_ZEDT18_017-ZEKKO_BEDAT = P_BEDAT.

  DATA : LS_ZEDT18_015 LIKE ZEDT18_015.
  SELECT SINGLE * FROM ZEDT18_015 INTO CORRESPONDING FIELDS OF LS_ZEDT18_015 WHERE ZLFA_LIFNR = P_LIFNR.
  GS_ZEDT18_017-ZEKKO_WAERS = LS_ZEDT18_015-ZLFM_WAERS.
  * 실행 후 user command add를 사용하기 전에 미리 초기화
  GV_EBELP = 0.
ENDIF.
```

```
*-----*
*& Form CREATE_OBJECT
*&-----*
FORM CREATE_OBJECT .
  CREATE OBJECT GC_DOCKING
  EXPORTING
    REPID              = SY-REPID
    DYNNR              = SY-DYNNR
    EXTENSION          = 2000.
  IF SY-SUBRC <> 0.
    ENDIF.

  CREATE OBJECT GC_GRID
  EXPORTING
    I_PARENT           = GC_DOCKING.
  IF SY-SUBRC <> 0.
    ENDIF.
ENDIF.

*-----*
*& Form SET_FIELDCAT
*&-----*
FORM SET_FIELDCAT .
  CLEAR : GS_FIELDCAT, GT_FIELDCAT.
  GS_FIELDCAT-COL_POS = 1.
  GS_FIELDCAT-FIELDNAME = 'ZEKPO_EBELP'.
  GS_FIELDCAT-COLTEXT = '물류'.
  APPEND GS_FIELDCAT TO GT_FIELDCAT.

  CLEAR : GS_FIELDCAT.
  GS_FIELDCAT-COL_POS = 2.
  GS_FIELDCAT-FIELDNAME = 'ZEKPO_MATNR'.
  GS_FIELDCAT-COLTEXT = '재고코드'.
  GS_FIELDCAT-REF_TABLE = 'ZEDT18_018'.
  GS_FIELDCAT-REF_FIELD = 'ZEKPO_MATNR'.
  GS_FIELDCAT-EDIT = 'X'.
  GS_FIELDCAT-f4availabl = 'X'.
  APPEND GS_FIELDCAT TO GT_FIELDCAT.
```

2.3 PO 생성 프로그램

프로그램명 : ZPROJECT18_002 (ZPROJECT18_002_F01)-2

```
CLEAR : GS_FIELDCAT.  
GS_FIELDCAT-COL_POS = 3.  
GS_FIELDCAT-FIELDNAME = 'ZMAKT_MAKTX'.  
GS_FIELDCAT-COLTEXT = '자재명'.  
GS_FIELDCAT-EDIT = 'X'.  
APPEND GS_FIELDCAT TO GT_FIELDCAT.
```

```
CLEAR : GS_FIELDCAT.  
GS_FIELDCAT-COL_POS = 4.  
GS_FIELDCAT-FIELDNAME = 'ZEKPO_MENGE'.  
GS_FIELDCAT-COLTEXT = 'PO수량'.  
GS_FIELDCAT-EDIT = 'X'.  
APPEND GS_FIELDCAT TO GT_FIELDCAT.
```

```
CLEAR : GS_FIELDCAT.  
GS_FIELDCAT-COL_POS = 5.  
GS_FIELDCAT-FIELDNAME = 'ZEKPO_MEINS'.  
GS_FIELDCAT-COLTEXT = '단위'.  
GS_FIELDCAT-EDIT = 'X'.  
APPEND GS_FIELDCAT TO GT_FIELDCAT.
```

```
CLEAR : GS_FIELDCAT.  
GS_FIELDCAT-COL_POS = 6.  
GS_FIELDCAT-FIELDNAME = 'ZEKPO_BPRME'.  
GS_FIELDCAT-COLTEXT = '단가'.  
GS_FIELDCAT-EDIT = 'X'.  
APPEND GS_FIELDCAT TO GT_FIELDCAT.
```

```
CLEAR : GS_FIELDCAT.  
GS_FIELDCAT-COL_POS = 7.  
GS_FIELDCAT-FIELDNAME = 'ZEKPO_WAERS'.  
GS_FIELDCAT-COLTEXT = '통화'.  
APPEND GS_FIELDCAT TO GT_FIELDCAT.
```

```
CLEAR : GS_FIELDCAT.  
GS_FIELDCAT-COL_POS = 8.  
GS_FIELDCAT-FIELDNAME = 'ZEKPO_MWSKZ'.  
GS_FIELDCAT-COLTEXT = '세금코드'.  
APPEND GS_FIELDCAT TO GT_FIELDCAT.
```

```
CLEAR : GS_FIELDCAT.  
GS_FIELDCAT-COL_POS = 9.  
GS_FIELDCAT-FIELDNAME = 'ZEKPO_PRDAT'.  
GS_FIELDCAT-COLTEXT = '납품일'.  
APPEND GS_FIELDCAT TO GT_FIELDCAT.
```

```
CLEAR : GS_FIELDCAT.  
GS_FIELDCAT-COL_POS = 10.  
GS_FIELDCAT-FIELDNAME = 'ZEKPO_WERKS'.  
GS_FIELDCAT-COLTEXT = '출력'.  
APPEND GS_FIELDCAT TO GT_FIELDCAT.
```

```
CLEAR : GS_FIELDCAT.  
GS_FIELDCAT-COL_POS = 11.  
GS_FIELDCAT-FIELDNAME = 'ZEKPO_LGORT'.  
GS_FIELDCAT-COLTEXT = '저장위치'.  
APPEND GS_FIELDCAT TO GT_FIELDCAT.
```

ENDFORM.

```
*-----*  
*      Form  SET_SORT      *  
*-----*  
*      text      *  
*-----*  
* --> p1      text      *  
* <-- p2      text      *  
*-----*
```

```
FORM SET_SORT .  
  CLEAR : GS_SORT, GT_SORT.  
  GS_SORT-SPOS = '1'.  
  GS_SORT-FIELDNAME = 'ZEKPO_EBELP'.  
  GS_SORT-UP = 'X'.  
  APPEND GS_SORT TO GT_SORT.  
ENDFORM.
```

2.3 PO 생성 프로그램

프로그램명 : ZPROJECT18_002 (ZPROJECT18_002_F01)-3

```
*&-----*
*&      Form  SET_LAYOUT
*&-----*
*      text
*-----*
* --> p1      text
* <-- p2      text
*-----*

FORM SET_LAYOUT .
  CLEAR : GS_LAYOUT.
  GS_LAYOUT-ZEBRA = 'X'.

  CLEAR GS_VARIANT.
  GS_VARIANT-REPORT = SY-REPID.
  GS_VARIANT-USERNAME = SY-UNAME.
ENDFORM.

*&-----*
*&      Form  CLASS_EVENT
*&-----*
*      text
*-----*
* --> p1      text
* <-- p2      text
*-----*

FORM CLASS_EVENT .
  CALL METHOD GC_GRID->REGISTER_EDIT_EVENT
    EXPORTING
      I_EVENT_ID = CL_GUI_ALV_GRID=>MC_EVT_MODIFIED.
  IF SY-SUBRC <> 0.
    * Implement suitable error handling here
  ENDIF.

  CREATE OBJECT GO_EVENT.

  SET HANDLER GO_EVENT->HANDLE_DATA_FINISHED FOR GC_GRID.
ENDFORM.

*&-----*
*&      Form  CALL_ALV
*&-----*
*      text
*-----*
* --> p1      text
* <-- p2      text
*-----*

FORM CALL_ALV .
  CALL METHOD GC_GRID->SET_TABLE_FOR_FIRST_DISPLAY
    EXPORTING
      IS_VARIANT      = GS_VARIANT
      I_SAVE          = 'X'
      IS_LAYOUT       = GS_LAYOUT
    CHANGING
      IT_OUTTAB       = GT_ZEDT18_018
      IT_FIELDCATALOG = GT_FIELDCAT.
  IF SY-SUBRC <> 0.
    * Implement suitable error handling here
  ENDIF.
ENDFORM.

*&-----*
*&      Form  ALV_HANDLE_DATA_FINISHED
*&-----*
FORM ALV_HANDLE_DATA_FINISHED USING P_MODIFIED
                                     P_GOOD_CELLS TYPE LVC_T_MODI.

  DATA : LS_MODI TYPE LVC_S_MODI.
  LOOP AT P_GOOD_CELLS INTO LS_MODI.
    IF LS_MODI-FIELDNAME = 'ZEKPO_MATNR'.
      READ TABLE GT_ZEDT18_018 INTO GS_ZEDT18_018 INDEX LS_MODI-ROW_ID.
      SELECT * INTO CORRESPONDING FIELDS OF GS_ZEDT18_016 FROM ZEDT18_016
        WHERE ZMARA_MATNR = GS_ZEDT18_018-ZEKPO_MATNR.
      ENDSELECT.
      GS_ZEDT18_018-ZEKPO_PRDAT = GS_ZEDT18_017-ZEKKO_BEDAT + GS_ZEDT18_016-ZEINE_APLFZ.
      GS_ZEDT18_018-ZEKPO_MEINS = GS_ZEDT18_016-ZMARA_MEINS.
      GS_ZEDT18_018-ZEKPO_BPRME = GS_ZEDT18_016-ZEINE_NETPR.
      GS_ZEDT18_018-ZMAKT_MAKTX = GS_ZEDT18_016-ZMAKT_MAKTX.
      GS_ZEDT18_018-ZEKKO_WAERS = GS_ZEDT18_016-ZEINE_WAERS.
      MODIFY GT_ZEDT18_018 FROM GS_ZEDT18_018 INDEX LS_MODI-ROW_ID.
    ENDIF.
  ENDLOOP.
  PERFORM REFRESH.
ENDFORM.
```

2.3 PO 생성 프로그램

프로그램명 : ZPROJECT18_002 (ZPROJECT18_002_F01)-4

```
*-----*
* Form REFRESH
*-----*
FORM REFRESH .
  DATA : LS_STABLE TYPE LVC_S_STBL.
  LS_STABLE-ROW = 'X'.
  LS_STABLE-COL = 'X'.
  CALL METHOD GC_GRID->REFRESH_TABLE_DISPLAY
    EXPORTING
      IS_STABLE = LS_STABLE .
  IF SY-SUBRC <> 0.
  ENDIF.
ENDFORM.

*-----*
* Form ADD_ROW
*-----*
FORM ADD_ROW .
  CLEAR : GS_ZEDT18_018.
  * 헤더와 동일한 구매 오더 번호
  GS_ZEDT18_018-ZEKPO_EBELN = GS_ZEDT18_017-ZEKKO_EBELN.
  * 품목 생성 (자동 10씩 증가)
  GV_EBELP = GV_EBELP + 10.
  GS_ZEDT18_018-ZEKPO_EBELP = GV_EBELP.
  * 자재마스터와 같은 통화 입력(앞서 헤더와 자재마스터 데이터를 일치시켜 놓음)
  GS_ZEDT18_018-ZEKKO_WAERS = GS_ZEDT18_017-ZEKKO_WAERS.
  * 헤더에는 세금코드가 없기 때문에 구매처 번호를 이용해서 가져옴
  DATA : LV_MWSKZ TYPE C LENGTH 2.
  SELECT ZLFM_MWSKZ INTO LV_MWSKZ FROM ZEDT18_015 WHERE ZLFA_LIFNR = GS_ZEDT18_017-ZEKKO_LIFNR.
  ENDSELECT.
  GS_ZEDT18_018-ZEKPO_MWSKZ = LV_MWSKZ.
  * 납품일은 헤더의 증빙일 + 자재마스터의 납품소요 시간
  DATA : LV_APLFZ TYPE N LENGTH 5.
  GS_ZEDT18_018-ZEKPO_PRDAT = GS_ZEDT18_017-ZEKKO_BEDAT.
  * BREAK-POINT.
  * 플랜트 1100 고정
  GS_ZEDT18_018-ZEKPO_WERKS = '1100'.
  * 저장위치 1101 고정
  GS_ZEDT18_018-ZEKPO_LGORT = '1101'.
  APPEND GS_ZEDT18_018 TO GT_ZEDT18_018.
  PERFORM REFRESH.
ENDFORM.
```

2.3 PO 생성 프로그램

프로그램명 : ZPROJECT18_002 (ZPROJECT18_002_PBO)

```
*-----*
*& Include      ZPROJECT18_002_PBO
*&-----*
*&-----*
*&      Module  STATUS_0100  OUTPUT
*&-----*
*      text
*-----*

MODULE STATUS_0100 OUTPUT.
  SET PF-STATUS 'STATUS_0100'.
  SET TITLEBAR '품목추가'.
ENDMODULE.

*&-----*
*&      Module  ALV_DISPLAY  OUTPUT
*&-----*
*      text
*-----*

MODULE ALV_DISPLAY OUTPUT.
  IF GC_DOCKING IS INITIAL.
    PERFORM CREATE_OBJECT.
    PERFORM SET_FIELDCAT.
    PERFORM SET_SORT.
    PERFORM SET_LAYOUT.
    PERFORM CLASS_EVENT.
    PERFORM CALL_ALV.
  ELSE.
    PERFORM REFRESH.
  ENDIF.
ENDMODULE.
```

2.3 PO 생성 프로그램

프로그램명 : ZPROJECT18_002 (ZPROJECT18_002_PAI)

```

*&-----
*& Include          ZPROJECT18_002_PAI
*&-----
*&
*& Module  USER_COMMAND_0100  INPUT
*&-----
*      text
*-----
MODULE USER_COMMAND_0100 INPUT.

IF OK_CODE = 'ADD'.
    PERFORM ADD_ROW.
ELSEIF OK_CODE = 'DELETE'.
    DATA : LT_SELECTED TYPE LVC_T_ROW.
    DATA : LS_SELECTED TYPE LVC_S_ROW.
    CALL METHOD GC_GRID->GET_SELECTED_ROWS
        IMPORTING
            ET_INDEX_ROWS = LT_SELECTED[].

    LOOP AT LT_SELECTED INTO LS_SELECTED.
        DELETE GT_ZEDT18_018 INDEX LS_SELECTED-INDEX.
    ENDLOOP.
ELSEIF OK_CODE = 'SAVE'.
    INSERT ZEDT18_017 FROM GS_ZEDT18_017.
    INSERT ZEDT18_018 FROM TABLE GT_ZEDT18_018.
    MESSAGE '정상적으로 저장되었습니다.' TYPE 'I'.
    LEAVE PROGRAM.
ENDIF.
ENDMODULE.

*&-----
*& Module  EXIT_COMMAND INPUT
*&-----
*      text
*-----
MODULE EXIT_COMMAND INPUT.
CASE OK_CODE.
WHEN 'BACK' OR 'EXIT'.
    LEAVE TO SCREEN 0.
WHEN 'CANC'.
    LEAVE PROGRAM.
ENDCASE.

ENDMODULE.
```


2.3 PO 생성 프로그램

프로그램명 : ZPROJECT18_002 (ZPROJECT18_002_PAI)

```

*&-----
*& Include          ZPROJECT18_002_PAI
*&-----
*&
*& Module  USER_COMMAND_0100  INPUT
*&-----
*
*      text
*-----
MODULE USER_COMMAND_0100 INPUT.

IF OK_CODE = 'ADD'.
    PERFORM ADD_ROW.
ELSEIF OK_CODE = 'DELETE'.
    DATA : LT_SELECTED TYPE LVC_T_ROW.
    DATA : LS_SELECTED TYPE LVC_S_ROW.
    CALL METHOD GC_GRID->GET_SELECTED_ROWS
        IMPORTING
            ET_INDEX_ROWS = LT_SELECTED[].

    LOOP AT LT_SELECTED INTO LS_SELECTED.
        DELETE GT_ZEDT18_018 INDEX LS_SELECTED-INDEX.
    ENDLOOP.
ELSEIF OK_CODE = 'SAVE'.
    INSERT ZEDT18_017 FROM GS_ZEDT18_017.
    INSERT ZEDT18_018 FROM TABLE GT_ZEDT18_018.
    MESSAGE '정상적으로 저장되었습니다.' TYPE 'I'.
    LEAVE PROGRAM.
ENDIF.
ENDMODULE.

*&-----
*& Module  EXIT_COMMAND  INPUT
*&-----
*
*      text
*-----
MODULE EXIT_COMMAND INPUT.
CASE OK_CODE.
WHEN 'BACK' OR 'EXIT'.
    LEAVE TO SCREEN 0.
WHEN 'CANC'.
    LEAVE PROGRAM.
ENDCASE.

ENDMODULE.
```

2.4 PO 생성 화면

초기화면



CancelMore 

회사코드	 1100
구매조직	1100
증빙일	2023.06.18
구매처	

2.4 PO 생성 화면

PO 아이템 추가

☒

 Cancel More ▾

	품목	자재코드	자재명	PO수량	단위	단가	통화	세금코드	납품일	플랜트	저장위치
☐	10			0		0.00	KRW	V1		1100	1101
☐	20			0		0.00	KRW	V1		1100	1101
☐	30			0		0.00	KRW	V1		1100	1101

자재코드 (1) 17 Entries found

Restrictions

자재	자재명
1	물리
10	일반강자취집
11	플그레인머스
12	싸루전드
13	케첩
14	말대
15	포장용기
16	컵
17	비닐
2	사이다
3	환타
4	양상추
5	토마토

17 Entries found

- 품목 추가 시 품목, 통화, 세금코드, 플랜트, 저장위치 자동 기입
- 자재코드 Search Help 가능

2.4 PO 생성 화면

PO 아이템 추가

✓

+ 품목추가
 ⊗ 품목삭제
 👁 PO생성
 Cancel
More ▾

🔍
↺
✂
📄
📄 ▾
↻
📄 +
📄 -
📄
☰
☷
🔍
🔍
🔍 ▾
Σ ▾
½ ▾
📄
📄 ▾
📄 ▾
👁 ▾
📊
📄

☐	품목	자재코드	자재명	PO수량	단위	단가	통화	세금코드	납품일	플랜트	저장위치
☐	10	1	콜라	0	L	500.00	KRW	V1	2023.06.19	1100	1101
☐		20		0		0.00	KRW	V1		1100	1101
☐		30		0		0.00	KRW	V1		1100	1101

- 자재코드 입력 시 자재명, 단위, 단가, 납품일 자동 기입

PO 아이템 삭제

- 품목삭제 버튼 클릭 시 원하는 행 삭제

감사합니다