

Departure Procedure

- All rwys:** SPEC VIS - Climb in visual conditions to cross the aprt at or above **2200**. Continue climbing hdg **180°** to **4200**. Then climb between **183°** CCW to **312°** to remain clear of CYD106.
- Rwy 07 – ½:** Requires a minimum climb gradient of **300** ft/NM to **3500**. Climb between hdg **100°** CW to **181°** to remain clear of CYD106.
Note: Trees to 216 ASL abeam departure end of rwy, 250' LEFT and RIGHT of rwy centreline, and aprx 0.2 NM past departure end of rwy, 450' LEFT and RIGHT of rwy centreline.
- Rwy 11 – ½:** Requires a minimum climb gradient of **300** ft/NM to **3500**. Climb between hdg **094°** CW to **181°** to remain clear of CYD106.
Note: Trees to 162 ASL abeam departure end of rwy, 200' RIGHT of rwy centreline, and aprx 0.3 NM past departure end of rwy, 700' LEFT of rwy centreline.
- Rwy 16 – ½:** Requires a minimum climb gradient of **270** ft/NM to **3200**. Climb between hdg **181°** CCW to **122°** to remain clear of CYD106.
Note: Trees to 178 ASL aprx 500' past departure end of rwy, 300' LEFT and 500' RIGHT of rwy centreline.
- Rwy 25 – ½:** Requires a minimum climb gradient of **410** ft/NM to **5500**. Climb between hdg **178°** CCW to **074°** to remain clear of CYD106.
Note: Trees to 174 ASL abeam departure end of rwy, 300' LEFT and RIGHT of rwy centreline.
- Rwy 29 – ½:** Requires a minimum climb gradient of **250** ft/NM to **3600**. Climb between hdg **173°** CCW to **109°** to remain clear of CYD106.
Note: Trees to 208 ASL abeam departure end of rwy, 450' LEFT and RIGHT of rwy centreline.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
250 FT/NM	380	500	590	670	750	840	1050	1250
270 FT/NM	410	540	630	720	810	900	1130	1350
300 FT/NM	450	600	700	800	900	1000	1250	1500
410 FT/NM	620	820	960	1100	1230	1370	1710	2050