

RNAV (GNSS) X RWY 21 OPS SPEC

RESTRICTED INSTRUMENT PROCEDURE

This procedure requires a missed approach climb gradient of **420 ft/NM** to **5500** feet and the aerodrome visual surfaces are not assessed.

The following conditions apply to this procedure:

- A minimum climb gradient of **420 ft/NM** to **5500** feet must be maintained during the missed approach procedure.
- The aircraft weight is not greater than that necessary to meet the published climb gradient on the missed approach.
- When computing the aircraft weight, make corrections for the pressure altitude, ambient temperature, wind components and any gradient loss associated with a turn at the planned time of approach.

Aerodrome visual surfaces not assessed (Obstacle Limitation Surfaces not assessed).

When starting the descent from the landing minima, pilots are cautioned that a specific obstacle-free environment is not provided on this IFR procedure. The following provisions are attached to this RIP:

- Flight Crew must be familiar with the aerodrome environment, including local area obstacles, terrain, and aerodrome layout;
- The required visual references to descend below MDA/DA should include the obstacle(s) and terrain in the approach area of the runway; and
- All visual references required by the pilot to continue the approach to a safe landing should be distinctly visible and identifiable to the pilot.

RNAV (GNSS) X RWY 21 OPS SPEC

CYDL

EFF 20 FEB 25

REGULATORY REVIEW 6 JUL 2028

CYDL-IAP-3L