

## CYMH

55 51.1

55 50.5

52 18.4

52 18.4

VAR 19° N  
2024  
ANNUAL RATE  
OF CHANGE 13° E

| DEPARTURE CLIMB RATE V/V (FPM) |     |      |      |      |      |      |      |      |
|--------------------------------|-----|------|------|------|------|------|------|------|
| GROUND SPEED                   | 90  | 120  | 140  | 160  | 180  | 200  | 250  | 300  |
| 400 FT/NM                      | 600 | 800  | 940  | 1070 | 1200 | 1340 | 1670 | 2000 |
| 500 FT/NM                      | 750 | 1000 | 1170 | 1340 | 1500 | 1670 | 2090 | 2500 |

CYMH  
N52 18.17  
W55 50.87

#### \*DEPARTURE PROCEDURE

**Rwy 11** - ½ - Requires a minimum climb gradient of **500** ft/NM to **300**. Climb hdg **107°** to **900** BPOC.

**Note:** Trees to 170 ASL abeam departure end of rwy, LEFT and RIGHT of rwy centreline.

or

SPEC VIS - Climb in visual conditions to cross the apt at or above **1000** BPOC.

**Rwy 29** - ½ - Requires a minimum climb gradient of **400** ft/NM to **400**. Climb hdg **287°** to **700** BPOC.

**Note:** Trees to 187 ASL abeam departure end of rwy, LEFT and RIGHT of rwy centreline.

or

SPEC VIS - Climb in visual conditions to cross the apt at or above **1000** BPOC.

52 18

52 18

55 51.1

55 50.5

Source of Canadian Civil Aeronautical Data: © 2026 NAV CANADA All rights reserved

CYMH