



DEPARTURE PROCEDURE

Departure Procedure

- Rwys 11, 29:** NOT ASSESSED
- Rwy 01 – ½:** Climb between hdg **039°** CCW to **191°** to remain clear of MISTY1 MOA and CYR518. When CYA513 is active, climb between hdg **039°** CCW to **239°** to remain clear of MISTY1 MOA, CYR518 and CYA513.
Note: Trees to 361 ASL aprx 350' past departure end of rwy.
Tower to 386 ASL aprx 0.2 NM past departure end of rwy, 200' RIGHT of rwy centreline.
- Rwy 06 – ½:** Climb between hdg **036°** CCW to **244°** to remain clear of MISTY1 MOA, CYR518 and CYA513.
- Rwy 19 – ½:** Requires a minimum climb gradient of **210 ft/NM** to **1200**. Climb between hdg **209°** CW to **009°** to remain clear of MISTY1 MOA and CYR518. When CYA513 is active: Requires a minimum climb gradient of **210 ft/NM** to **1200**. Climb between hdg **248°** CW to **009°** to remain clear of MISTY1 MOA, CYR518 and CYA513.
Note: Trees to 384 ASL aprx 0.4 NM past departure end of rwy, 300' RIGHT of rwy centreline.
or
SPEC VIS – Climb in visual conditions to cross the aprt at or above **3500** BPOC. When CYA513 is active: SPEC VIS NOT AUTHORIZED.
- Rwy 24 – ½:** Climb between hdg **194°** CW to **038°** to remain clear of MISTY1 MOA and CYR518. When CYA513 is active, climb between hdg **264°** CW to **038°** to remain clear of MISTY1 MOA, CYR518 and CYA513.
Note: Trees to 367 ASL aprx 0.3 NM past departure end of rwy, 650' RIGHT of rwy centreline.
Possible ship to 450 ASL transiting canal aprx 0.8 NM past departure end of rwy.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
210 FT/NM	320	420	490	560	630	700	880	1050

