



DEPARTURE PROCEDURE

Departure Procedure

Rwy 18 – ½: Requires a minimum climb gradient of **230 ft/NM** to **3200**. When Mont Wright blasting area is active. Requires a minimum climb gradient of **230 ft/NM** to **3200**. Climb between heading **227°** CCW to **360°** to **10500** BPOC to remain clear of blasting areas. When any other blasting area defined for Wabush within the CFS Caution is active: Climb between heading **212°** CCW to **066°** to **6100** BPOC to remain clear of blasting areas.

Note: Trees to 1854 ASL aprx 0.1 NM past departure end of rwy.

or

SPEC VIS: Climb in visual conditions to cross the aprt at or above **3200** BPOC. When Mont Wright is active: Climb in visual conditions to cross the aprt at or above **3200**, then on a heading **221°** CCW to **305°** to MEA BPOC. SPEC VIS not auth when any other defined blasting area for Wabush as described within the CFS Caution section is active.

Rwy 36 – ½: Requires a minimum climb gradient of **380 ft/NM** to **4000**. When Mont Wright is blasting area is active: Climb between heading **297°** CW to **179°** to **9900** BPOC to remain clear of blasting areas. Procedure not auth when any other blasting area defined for Wabush within the CFS Caution is active.

Notes: Powerlines 1894 ASL aprx 0.3NM past departure end of rwy.

or

SPEC VIS: Climb in visual conditions to cross the aprt at or above **3200** BPOC. When Mont Wright is active: Climb in visual conditions to cross the aprt at or above **3200**, then on a heading **221°** CCW to **305°** to MEA BPOC. SPEC VIS not auth when any other defined blasting area for Wabush as described within the CFS Caution section is active.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
230 FT/NM	350	460	540	620	690	770	960	1150
380 FT/NM	570	760	890	1020	1140	1270	1590	1900

Source of Canadian Civil Aeronautical Data: © 2026 NAV CANADA All rights reserved

