



DEPARTURE PROCEDURE

Departure Procedure

- All rwys:** Departure procedure not authorized when blasting area active (OCSL by NOTAM), SFC to **2000**, 1.8 NM SE of aerodrome.
- Rwy 06 – ½:** Climb hdg **054°** to **1200** BPOC.
Note: Terrain to 144 ASL aprox 0.2 NM past departure end of rwy, 400' RIGHT of centreline.
- Rwy 15 – ½:** Requires a minimum climb gradient of **400** ft/NM to **1000**. NO RIGHT turn below **2000**.
Note: Trees to 243 ASL aprox 500' past departure end of rwy.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1700** BPOC.
- Rwy 24 – ½:** Requires a minimum climb gradient of **250** ft/NM to **1500**. NO LEFT turn below **2300**.
Note: Trees to 220 ASL aprx 0.1 NM past departure end of rwy.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **1700** BPOC.
- Rwy 33 – ½:** Climb hdg **328°** to **1300** BPOC.
Note: Trees to 167 ASL aprox 150' past departure end of rwy, 450' LEFT of rwy centreline.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
250 FT/NM	380	500	590	670	750	840	1050	1250
400 FT/NM	600	800	940	1070	1200	1340	1670	2000

Source of Canadian Civil Aeronautical Data: © 2026 NAV CANADA All rights reserved

