

Departure Route Description

Unless otherwise assigned by ATC:

- All rws:** Maintain **3000**.
- Rwy 14:** Depart rwy 14, climb hdg **141°** to **1500**. Continue climb hdg **141°** or as assigned. Expect radar vectors to OAKVL (or as assigned) then proceed via depicted route.
- Rwy 32:** Requires a minimum climb gradient of **340 ft/NM** to **1800**. Depart rwy 32, climbing RIGHT turn hdg **191°** or as assigned. Expect radar vectors to OAKVL (or as assigned) then proceed via depicted route.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
340 FT/NM	510	680	800	910	1020	1140	1420	1700

ERIE TRANSITION: (OAKVL3.ERI)
FOXEE TRANSITION: (OAKVL3.FOXEE)
AIRRA TRANSITION: (OAKVL3.AIRRA)

Communication Failure

On recognition of failure 5 minutes or less after take-off and in IFR weather conditions proceed as follows:

1. Select transponder code 7600;
2. Climb to **3100** on assigned heading;
3. Proceed on course and maintain **4000** or last assigned altitude whichever is higher, then;
4. Climb to flight planned altitude 5 minutes after recognition of the communication failure.