

Departure Route Description

All rwys: Do not exceed 250 kt until above **10000**.

Rwy 15 – ½: Requires a minimum climb gradient of **270** ft/NM to **5000**. Climb hdg **148°** to **3700**. Then climbing **RIGHT** turn direct to **ALTAG**. As required, shuttle climb to **MEA BPOC**.

Note: Trees to 3159 ASL abeam departure end of rwy, 400' **LEFT** of rwy centreline and aprx 0.4 NM past departure end of rwy.

Rwy 33 – ½: Requires a minimum climb gradient of **390** ft/NM to **3600**. Climb hdg **328°** to **3600**. Then climbing **LEFT** turn direct to **ALTAG**. As required, shuttle climb to **MEA BPOC**.

Note: Tower to 3187 ASL aprx 50' past departure end of rwy, 400' **LEFT** of rwy centreline. Trees to 3190 ASL abeam departure end of rwy aprx 400' **RIGHT** of rwy centreline.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
270 FT/NM	410	540	630	720	810	900	1130	1350
390 FT/NM	590	780	910	1040	1170	1300	1630	1950

Source of Canadian Civil Aeronautical Data: © 2026 NAV CANADA All rights reserved