

Departure Route Description

Rwy 06L: Requires a minimum climb gradient of **270 ft/NM to 1100**. Climb hdg **062°** for vectors to assigned route. Maintain **3000** or as assigned.

Rwy 06R: Requires a minimum climb gradient of **260 ft/NM to 1100**. Climb hdg **062°** for vectors to assigned route. Maintain **3000** or as assigned.

Rwy 24L: Requires a minimum climb gradient of **440** ft/NM to **300**. Climb hdg **242°** for vectors to assigned route. Maintain **3000** or as assigned.

Rwy 24R: Climb hdg **242°** for vectors to assigned route. Maintain **3000** or as assigned.

Rwy 28: Requires a minimum climb gradient of **440 ft/NM** to **400**. Climb hdg **220°** for vectors to assigned route. Maintain **3000** or as assigned.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
260 FT/NM	390	520	610	700	780	870	1090	1300
270 FT/NM	410	540	630	720	810	900	1130	1350
440 FT/NM	660	880	1030	1180	1320	1470	1840	2200

Communication Failure

1. Select transponder code 7600;
2. Climb to flight planned altitude 5 minutes after take-off, and;
3. Proceed on course 5 minutes after selecting 7600.