

Departure Procedure

Rwy 06L – ½: Climb hdg **040°** to **1100**. No RIGHT turn below **6000** BPOC.

Rwy 06R – ½: Climb hdg **040°** to **1100**. No RIGHT turn below **6000** BPOC.

Rwy 10 – ½: Climb hdg **100°** to **800**. Then climbing LEFT turn hdg **062°** to **1200**.
No RIGHT turn below **7600** BPOC.

Note: Building to 135 ASL aprx 0.2 NM past departure end of rwy, aprx 440' RIGHT of rwy centreline.

Trees to 151 ASL aprx 0.4 NM past departure end of rwy, aprx 300' RIGHT of rwy centreline.

Rwy 24L – ½: Requires a minimum climb gradient of **440** ft/NM to **300**. Climb hdg **242°** to **1000**. Climb between hdg **091°** CCW to **137°** to remain clear of CYA621(H) and CYA623(H).

or

SPEC VIS – Climb in visual conditions to cross the aprt at or above **4800** BPOC.

Rwy 24R – ½: Climb hdg **242°** to **1000**. Climb between hdg **091°** CCW to **137°** to remain clear of CYA621(H) and CYA623(H).

Note: Lightpoles to 121 ASL aprx 0.2 NM past departure end of rwy, aprx 350' LEFT of rwy centreline.

Trees to 157 ASL aprx 0.3 NM past departure end of rwy, aprx 700' RIGHT of rwy centreline.

Rwy 28 – ½: Requires a minimum climb gradient of **440** ft/NM to **400**. Climb hdg **220°** to **1600**. NO LEFT turn below **5100** BPOC.

or

SPEC VIS – Climb in visual conditions to cross the aprt at or above **4800** BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
440 FT/NM	660	880	1030	1180	1320	1470	1840	2200