

Departure Route Description

- All rwsys:** Maintain **3000**. Expect clearance to flight planned altitude/flight level 10 minutes after departure.
- Rwy 02:** Climb hdg **015°** or as assigned for vectors to assigned route.
- Rwy 06:** Climb hdg **060°** to **600**. Then climbing LEFT turn hdg **020°** or as assigned for vectors to assigned route.
- Rwy 11:** Departure Procedure NOT authorized when CYR605 active above **1200**. Climb hdg **105°** or as assigned for vectors to assigned route.
- Rwy 20:** Climb hdg **195°** or as assigned for vectors to assigned route.
- Rwy 24:** Climb hdg **240°** or as assigned for vectors to assigned route
- Rwy 29:** Requires a minimum climb gradient of **270 ft/NM** to **400**. Climb hdg **285°** or as assigned for vectors to assigned route.
- Note:** Rwy 29 departure procedure not authorized when blasting area defined for St-Jean within the CFS Caution is active.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
270 FT/NM	410	540	630	720	810	900	1130	1350

Communication Failure

- On recognition of failure proceed as follows:
1. Select transponder code 7600;
 2. Climb to flight planned altitude 5 minutes after take-off, then;
 3. Proceed on course 5 minutes after selecting 7600