

Departure Route Description

Rwy 04: Climb hdg **042°** to **3000** ASL, then climbing RIGHT turn direct XIDEB, then track **223°** to DUDSO, then maintain **6000** or as assigned.

Rwys 13L & 13R: Climb hdg **132°** to **3000** ASL, then climbing RIGHT turn direct XIDEB, then track **223°** to DUDSO, then maintain **6000** or as assigned.

Rwy 22: Climb hdg **222°** to **3000** ASL, then climb direct XIDEB, then track **223°** to DUDSO, then maintain **6000** or as assigned.

Rwys 31L & 31R: Climb hdg **312°** to **3000** ASL, then climbing LEFT turn direct XIDEB, then track **223°** to DUDSO, then maintain **6000** or as assigned.

Communication Failure

Transponder mode A/3 code 7600. On recognition of communications failure 3 minutes or less after take-off and in IFR weather conditions proceed as follows:

- 1. Upon reaching **6000** ASL or last assigned altitude, whichever is higher, proceed on course;
- 2. Maintain this altitude for 3 minutes after take-off; then
- 3. Climb to flight planned altitude; not above FL190 until 25 NM outbound.

Note: If communication failure occurs more than 3 minutes after take-off, comply with the appropriate procedure for communication failure enroute.

Source of Canadian Civil Aeronautical Data: © 2026 NAV CANADA All rights reserved