

Departure Route Description

- All rws:** Climb to and maintain **5000** or flight planned altitude, whichever is lower. Anticipate radar vectors to filed/assigned route. Expect clearance to flight planned altitude/flight level within 10 minutes after departure.
- Rwy 11:** Requires a minimum climb gradient of **420** ft/NM to **1600**. Climb hdg **106°** or as assigned by ATC.
- Rwy 18:** Requires a minimum climb gradient of **440** ft/NM to **1500**. Climb hdg **179°** or as assigned by ATC.
- Rwy 29:** Requires a minimum climb gradient of **260** ft/NM to **1500**. Climb hdg **286°** or as assigned by ATC.
- Rwy 36:** Climb hdg **359°** or as assigned by ATC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
260 FT/NM	390	520	610	700	780	870	1090	1300
420 FT/NM	630	840	980	1120	1260	1400	1750	2100
440 FT/NM	660	880	1030	1180	1320	1470	1840	2200

Communication Failure

On recognition of failure 10 minutes or less after take-off and in IFR weather conditions proceed as follows:

1. Select transponder code 7600;
2. Upon reaching last assigned altitude proceed directly on course;
3. Maintain last assigned altitude for 10 minutes after take-off, then;
4. Climb to flight planned altitude.

Note: If communication failure occurs more than 10 minutes after take-off, comply with the appropriate procedure for communication failure enroute.