

DEPARTURE PROCEDURE

CYZT

Departure Procedure

Rwy 11: NORTH WESTBOUND: SPEC VIS – Climb in visual conditions to cross the apt at or above **1600**. Continue climbing OBD “YZT” **R-299 to 3000** BPOC
 SOUTH EASTBOUND: SPEC VIS – Climb in visual conditions to cross the apt at or above **1600**. Continue climbing OBD “YZT” **R-104 to 4900** BPOC

Rwy 26: NORTH WESTBOUND: SPEC VIS – Climb in visual conditions to cross the apt at or above **1600**. Continue climbing OBD “YZT” **R-299 to 3000** BPOC.
 SOUTH EASTBOUND: SPEC VIS – Climb in visual conditions to cross the apt at or above **1600**. Continue climbing OBD “YZT” **R-104 to 4900** BPOC.

Rwy 29 – ½: Requires a minimum climb gradient of **320 ft/NM to 1000**. Climb hdg **293°** to intercept OBD “YZT” **R-292 to 3000** BPOC.

or

NORTH WESTBOUND: SPEC VIS – Climb in visual conditions to cross the apt at or above **1600**. Continue climbing OBD “YZT” **R-299 to 3000** BPOC.

SOUTH EASTBOUND: SPEC VIS – Climb in visual conditions to cross the apt at or above **1600**. Continue climbing OBD “YZT” **R-104 to 4900** BPOC

Note: Terrain to 59 ASL abeam departure end of rwy, 500' LEFT of rwy centreline.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
320 FT/NM	480	640	750	860	960	1070	1340	1600

DEPARTURE PROCEDURE

EFF 14 MAY 26

CYZT