

Departure Route Description

All rwsy: Maintain **7000** or as assigned. Expect radar vectors to filed/assigned route.

Rwy 08: Climb hdg **075°** to **7000** for vectors.

Rwy 17: Climb hdg **165°** to **7000** for vectors.

Rwy 26: Requires a minimum climb gradient of **260** ft/NM to **4800**. Climb hdg **255°** to **7000** for vectors.

Rwy 35: Departure not authorized when CYA228(H) active. Requires a minimum climb gradient of **230** ft/NM to **4900**. Climb hdg **345°** to **7000** for vectors.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
230 FT/NM	350	460	540	620	690	770	960	1150
260 FT/NM	390	520	610	700	780	870	1090	1300

Communication Failure

On recognition of failure 10 minutes or less after take-off and in IFR weather conditions, proceed as follows:

- 1. Select transponder code 7600;
- 2. Upon reaching the last assigned altitude proceed directly on course;
- 3. Maintain last assigned altitude for 10 minutes after take-off, then;
- 4. Climb to flight planned altitude;
- 5. For west or southwest bound flights, proceed direct to BOTAG and shuttle to **8900** BPOC.

Note: If communication failure occurs more than 10 minutes after take-off, comply with the appropriate procedure for Communication Failure enroute.