

Departure Route Description

All rwys: Maintain **4000** or flight planned altitude, whichever is lower. Expect radar vectors to filed/assigned route. Expect clearance to flight planned altitude/flight level within 10 minutes after departure.

Rwy 07: Climb hdg **074°** for vectors. No turns below **1800** unless assigned by ATC.

Rwy 12: Requires a minimum climb gradient of **450 ft/NM** to **1100**. Do NOT exceed 180 kt prior to completion of initial LEFT turn. Climb hdg **125°** to **1100**. Then climbing LEFT turn hdg **080°** for vectors.

Rwy 25: Climb hdg **254°** for vectors. No turns below **1700** unless assigned by ATC.

Rwy 30: Climb hdg **305°** for vectors. No turns below **1700** unless assigned by ATC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
450 FT/NM	680	900	1050	1200	1350	1500	1880	2250

Note: Refer to Noise Abatement Procedures for additional requirements.

Communication Failure

On recognition of failure 10 minutes or less after take-off and in IFR weather conditions proceed as follows:

1. Select transponder code 7600;
2. Upon reaching last assigned altitude proceed via depicted route;
3. Maintain last assigned altitude for 10 minutes after take-off, then;
4. Climb to flight planned altitude.

Note: If failure occurs more than 10 minutes after take-off, comply with the appropriate procedure for communication failure enroute.