

Departure Route Description

Unless otherwise assigned by ATC:

- Rwy 08:** Requires a minimum climb gradient of **380** ft/NM to **1200**. Maintain **3000**. Climb track **082°** to LODRA. Then climb hdg **090°** and expect vectors to DAVSI.
- Rwy 26:** Requires a minimum climb gradient of **400** ft/NM to **800**. Maintain **2000**. Climb hdg **262°** to **800**. Climbing **LEFT** turn direct to EMDOS. Then continue hdg **150°** and expect vectors to DAVSI.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
380 FT/NM	570	760	890	1020	1140	1270	1590	1900
400 FT/NM	600	800	940	1070	1200	1340	1670	2000

- MIVOK TRANSITION:
IPTOS TRANSITION:
MIGLO TRANSITION:
OLABA TRANSITION:
- (BOMET7.MIVOK)
(BOMET7.IPTOS)
(BOMET7.MIGLO)
(BOMET7.OLABA)

Communication Failure

On recognition of failure 5 minutes or less after take-off and in IFR weather conditions proceed as follows:

1. Select transponder code 7600;
2. Climb to **3100** on assigned heading;
3. Proceed on course and maintain **4000** or last assigned altitude whichever is higher, then;
4. Climb to flight planned altitude 5 minutes after recognition of the communication failure.