

AERODROME CHART (HIGH INTENSITY RUNWAY OPERATIONS – HIRO)

LDA for High Intensity Runway Operations				
From threshold rwy:	To exit point	LDA in ft	Preferred exit for med/heavy jet transport	Preferred exit for prop/ turboprop transport
11	A C G F1 F/U	3373 5000 5165 6000 8000	F/U	F1
17L	D1 D3 D5 S Q B	4154 6549 8261 11,979 13,475 13,795	D3 D5	D3
17R	A1 C2 C1 A3 C3 C/A	3976 5840 6415 7489 8516 12,675	C1 A3 C3	C1 A3
29	C A J2 W/J	3200 4853 6606 8000	J2 J	J2
35L	C3 A3 C1 C2 A1 C4 C6 A/C	4154 5181 6255 6830 8684 9369 10,984 12,675	C2 C4	C2
35R	D2 D4 D6 Z V D	4156 6462 8265 10,205 13,475 13,795	D4 D6	D2 D4

Pilots may plan their arrivals using the above table of threshold-to-exit-point distances. The distances are measured from the landing threshold to the point of the intersection of the runway centreline and the extended exit taxiway centreline.

During HIRO operations, the Control Tower may nominate the rwy exit. Compliance with ATC nomination of rwy exit is at the pilot's discretion and should be acknowledged.

REMARK: For detailed information on High Intensity Runway Operations, pilots may refer to AIP RAC 4.4.10