

DEPARTURE PROCEDURE

Departure Procedure

Rwy 05 – ½: Requires a minimum climb gradient of **360** ft/NM to **2700**.

Note: Fence to 575 ASL aprx 300' past departure end of rwy, 550' RIGHT of rwy centreline.

Rwy 06L – ½: Requires a minimum climb gradient of **400** ft/NM to **2700**.

Note: Building to 612 ASL aprx 0.3 NM past departure end of rwy, 1010' LEFT of rwy centreline.

Rwy 06R – ½: Requires a minimum climb gradient of **390** ft/NM to **2700**.

Rwy 15L – ½: Requires a minimum climb gradient of **390** ft/NM to **3000**.

Note: Tower to 656 ASL aprx 0.6 NM past departure end of rwy, 1300' LEFT of rwy centreline.

Rwy 15R – ½: Requires a minimum climb gradient of **380** ft/NM to **3000**.

Rwy 23 – ½:

Note: Light poles to 609 ASL aprx 0.3 NM past departure end of rwy, 450' RIGHT of rwy centreline.

Rwy 24L – ½: Requires a minimum climb gradient of **270** ft/NM to **1700**.

Rwy 24R – ½: Requires a minimum climb gradient of **260** ft/NM to **1700**.

Rwy 33L – ½: Requires a minimum climb gradient of **250** ft/NM to **900**.

Note: Buildings to 607 ASL aprx 0.3 NM past departure end of rwy, 1000' LEFT of rwy centreline.

Rwy 33R – ½: Climb hdg **327°** to **2100** BPOC.

Note: Trees to 610 ASL aprx 0.3 NM past departure end of rwy, 1000' RIGHT of rwy centreline.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
250 FT/NM	380	500	590	670	750	840	1050	1250
260 FT/NM	390	520	610	700	780	870	1090	1300
270 FT/NM	410	540	630	720	810	900	1130	1350
360 FT/NM	540	720	840	960	1080	1200	1500	1800
380 FT/NM	570	760	890	1020	1140	1270	1590	1900
390 FT/NM	590	780	910	1040	1170	1300	1630	1950
400 FT/NM	600	800	940	1070	1200	1340	1670	2000