






TRANSITION LEVEL BY ATC
TRANSITION ALTITUDE 3000 FT AMSL

- Missed Approach:
- Track 049° MAG and climb to 2000 FT AMSL.
Inform ATC.
- Missed Approach in case of communication failure:
- Track 049° MAG and climb to 3000 FT AMSL;
- When reaching 3000 FT AMSL, turn left to intercept
EEL R-228 and proceed to OMFAR.
- After arriving over OMFAR hold or descend to 2000 FT
AMSL in an outbound turn, intercept final approach
and execute the instrument approach procedure
again.



GS IN KT		60	80	100	120	140	160	180		
VERTICAL SPEED		320 FT/MIN	425 FT/MIN	530 FT/MIN	635 FT/MIN	745 FT/MIN	850 FT/MIN	955 FT/MIN		
OCA (OCH) ELEV THR 05: 13.3 FT							MSA BASED ON EEL VOR/DME			
ACFT CAT	VOR MAPT: THR	CIRCLING*	* Circling approaches shall be executed south-east of the AD, unless otherwise instructed by ATC.		THR 05 530639.9N 0063339.2E GG511 530252.1N 0062546.7E					
A	440 (422)	450 (432)								
B		520 (502)								
C		620 (602)								
D		850 (832)								
CEILING AND VISIBILITY MINIMA			DIRECTIONS ARE MAGNETIC DISTANCES IN NM ALTITUDES AND ELEVATIONS IN FEET							
TAKE-OFF	DAY:	NA							NIGHT:	NA
LANDING	DAY:								NIGHT:	