

TWR 118.205 Rotterdam Tower
119.705
122.180 Rotterdam Delivery
ATIS 128.565 Rotterdam Info

AD ELEV -14

VAR 2° E (2025)

ANNUAL RATE OF CHANGE 10' E

ROTTERDAM / RSV
(110.900) / CH46X
515740.3N 0042652.2E

LOC ROS 109.100

DTHR 197 M
ELEV -15 FT
GUND 143 FT

CWY

Precision Approach Lighting System (CAT I)

V6

V5

Anemometer

Meteo

PAPI
MEHT 51 FT
Glide angle 3.0°

TWY V

CAUTION ⑤

Compass swing area

Fire brigade practice ground

ROTTERDAM / ROS
(109.100) / CH28X
515719.9N 0042601.1E

GP 331.400

ARP
51575N
0042614E

Anemometer

PAPI
MEHT 51 FT
Glide angle 3.0°

DTHR 195 M
ELEV -14 FT
GUND 143 FT

CWY

Precision Approach Lighting System (CAT I)

VDF

LOC RSV 110.900

LH2 storage facility

CAUTION ④

TWY V

CAUTION ③

V2

V1

FIRE STATION

ACL: APRON -15

FUEL STATION

JET AVIATION

F-apron

J-apron

TWR 122.1

**DIRECTIONS ARE MAGNETIC
ELEVATIONS IN FEET AMSL
DIMENSIONS IN METRES**

LEGEND

- ATC service BDry
- BLAST FENCE
- Ⓚ INTERMEDIATE HLDG PSN UNLIGHTED
- ⑫ MAX WING SPAN
- ⊘ NO-ENTRY: RWY entry prohibited at this point
- X NOT IN USE
- ∞ RWY GUARD LIGHTS
- ≡≡≡ RWY HLDG PSN PATTERN A
- ▨ SOLAR FARM
- STOP BAR

SCALE 1 : 12 500

metres 0 100 200 300 400 500

feet 0 500 1000 1500

PHYSICAL CHARACTERISTICS				
RWY	DIRECTION	BEARING STRENGTH	SURFACE	THR COORDINATES
06	055°	PCN 70/F/D/W/T	ASPH	515711N 0042550E
24	235°	PCN 70/F/D/W/T	ASPH	515743N 0042710E

CAUTION:

- Follow-me service is mandatory for aircraft with wingspan > 36 M, for details see AD 2.20.
- Simultaneous use of TWY N and TWY Y is not allowed for aircraft with wingspan > 36 M.
- Between TWY V1 and TWY V3 aircraft with wingspan > 36 M must strictly adhere to follow-me instructions to stay clear of obstacles.
- Runway entry via TWY V3 not allowed.
- TWYs V2, V3, V4 and V5 MAX wingspan 36 M (limited outer main gear wheel span up to but not including 9 M).
- TWY V4 not available between SS and SR.