

Departure Route Description

- All rws:** Maintain **3000**. Anticipate radar vector to filed/assigned route. Expect clearance to flight planned altitude/flight level within 10 minutes after departure.
- Rwy 04:** Climb hdg **041°** to **2000**. Then climbing LEFT turn hdg **015°** or as assigned by ATC.
- Rwy 13:** Climb hdg **129°** to **2000**. Then climbing LEFT turn hdg **120°** or as assigned by ATC.
- Rwy 18:** Requires a minimum climb gradient of **250 ft/NM** to **2000**. Climb hdg **184°** to **2000**, then climbing LEFT turn hdg **110°** or as assigned by ATC.
- Rwy 22:** Climb hdg **221°** or as assigned by ATC.
- Rwy 31:** Requires a minimum climb gradient of **250 ft/NM** to **1200**. Climb hdg **309°** to **1200**. Then climbing RIGHT turn hdg **345°** or as assigned by ATC
- Rwy 36:** Climb hdg **004°** or as assigned by ATC.

Note: When TWR CLSD, CLNC may be obtained from WG TML at 204-983-4121.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
250 FT/NM	380	500	590	670	750	840	1050	1250

Communication Failure

On recognition of a failure 10 minutes or less after take-off and in IFR weather conditions proceed as follows:

1. Select transponder code 7600;
2. Upon reaching assigned altitude proceed directly on course;
3. Maintain last assigned altitude until 10 minutes after take-off, then;
4. Climb to flight planned altitude.

Note: If communication failure occurs more than 10 minutes after take-off, comply with the appropriate procedure for communication failure enroute.