

Departure Procedure

- Rwy 08 – ½:

Requires a minimum climb gradient of **350** ft/NM to **7500**. When CYA226(T) or CYA227(T) or CYA228(H) active, climb between hdg **349°** CW to **246°**.

or

SPEC VIS: Climb visual conditions to cross the aprt at or above **5000**. Then intercept OBD "YYC" **R-250** to BOTAG at 27.6 DME (YYC). Shuttle climb to **9100** BPOC. Left hand turns. Do not exceed 265 kt.
- Rwy 17 – ½:

Requires a minimum climb gradient of **300** ft/NM to **9700**. Climb between hdg **251°** CCW to **344°** to avoid CYA226(T), CYA227(T) and CYA228(H).

or

SPEC VIS: Climb visual conditions to cross the aprt at or above **5000**. Then intercept OBD "YYC" **R-250** to BOTAG at 27.6 DME (YYC). Shuttle climb to **9100** BPOC. Left hand turns. Do not exceed 265 kt.
- Rwy 26 – ½:

Requires a minimum climb gradient of **360** ft/NM to **8100**. When CYA226(T) or CYA227(T) active, climb between hdg **235°** CCW to **075°**. When CYA226(T) or CYA227(T) NOT active, climb between hdg **288°** CCW to **075°** to avoid CYA228(H).

or

SPEC VIS: Climb visual conditions to cross the aprt at or above **5000**. Then intercept OBD "YYC" **R-250** to BOTAG at 27.6 DME (YYC). Shuttle climb to **9100** BPOC. Left hand turns. Do not exceed 265 kt.
- Rwy 35 – ½:

Requires a minimum climb gradient of **300** ft/NM to **6500**. When CYA226(T), CYA227(T), CYA228(H) active, climb between hdg **006°** CW to **165°**. When CYA226(T), CYA227(T), CYA228(H) NOT active, climb between hdg **255°** CW to **165°**.

or

SPEC VIS: Climb visual conditions to cross the aprt at or above **5000**. Then intercept OBD "YYC" **R-250** to BOTAG at 27.6 DME (YYC). Shuttle climb to **9100** BPOC. Left hand turns. Do not exceed 265 kt.

DEPARTURE CLIMB RATE V/V (FPM)

| GROUND SPEED | 90  | 120 | 140 | 160 | 180  | 200  | 250  | 300  |
|--------------|-----|-----|-----|-----|------|------|------|------|
| 300 FT/NM    | 450 | 600 | 700 | 800 | 900  | 1000 | 1250 | 1500 |
| 350 FT/NM    | 530 | 700 | 820 | 940 | 1050 | 1170 | 1460 | 1750 |
| 360 FT/NM    | 540 | 720 | 840 | 960 | 1080 | 1200 | 1500 | 1800 |