

100

123 53 123 52.5 123 52

49 03.8

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
400 FT/NM	600	800	940	1070	1200	1340	1670	2000

* DEPARTURE PROCEDURE

Rwy 16 - Refer to SID.
or
SPEC VIS - Climb visual over apt to **2000**. Continue climb INBD track **342°** to "YCD" NDB. Then shuttle climb INBD track **191°** (max **200** kt, LEFT turns) to **MEA** BPOC.

Rwy 34 - ½ - Requires a minimum climb gradient of **400** ft/NM to **1600**. Climb INBD track **342°** to "YCD" NDB. Then shuttle climb INBD track **191°** (max **200** kt, LEFT turns) to **MEA** BPOC.
Note: Trees to 156 ASL aprx 200' past departure end of rwy, 300' LEFT of rwy centreline. Pole to 149 ASL aprx 0.1 NM past departure end of rwy, 650' RIGHT of rwy centreline. Trees to 208 ASL aprx 0.3 NM past departure end of rwy.
or
SPEC VIS - Climb in visual conditions to cross the apt at or above **2000**. Continue climb INBD track **342°** to "YCD" NDB. Then shuttle climb INBD track **191°** (max **200** kt, LEFT turns) to **MEA** BPOC.

49 03.4

49 03

123 53 123 52.5 123 52

AW 91 ELEV 75

Threshold 16 displaced 197'.

Taxiway G and Apron II day use only, rstd to 5,000 lbs

CYCD N49 03.27 W123 52.21

ANNUAL RATE OF CHANGE 9' W

VAR 17° E 2015

6602 x 150

Grass Tie Down Area

FSS

AS 344°

ELEV 93

Threshold 34 displaced 1002'.

P2 - Rwy 34 - 3.5° & offset 8° right OCL 3 NM.

RUNWAY LEVEL OF SERVICE

RVO LVO

RWY 34: (¼ sm) NOT AUTHORIZED

TAKE-OFF MINIMA

Rwys 16; 34: *

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2026 NAV CANADA All rights reserved

CYCD