

Departure Route Description

Rwy 34 – ½: Requires a minimum climb gradient of **360** ft/NM to **600**. Climb to and maintain **3000**. Do not exceed 240 kt until IMADU.

Note: Aircraft unable to meet the required climb gradient should refer to Nanaimo Departure Procedure.
Trees to 141 ASL aprx. 0.1 NM past departure end of rwy, 300' **LEFT** and **RIGHT** of rwy centreline. Trees to 233 ASL aprx. 0.3 NM past departure end of rwy.

DEPARTURE CLIMB RATE V/V (FPM)								
GROUND SPEED	90	120	140	160	180	200	250	300
360 FT/NM	540	720	840	960	1080	1200	1500	1800

ILATI TRANSITION: Climb direct to IMADU, then climbing **RIGHT** turn direct to ILATI.
(IMADU1.ILATI)

UQQ TRANSITION: Climb direct to IMADU, then track **305°** to ESTOT, then track **288°**
(IMADU1.UQQ) to IKNOS, then track **302°** to "UQQ" TACAN.

Communication Failure

On recognition of failure 5 minutes or less after take-off and in IFR weather conditions, proceed as follows:

- 1. Select transponder code 7600;
- 2. Upon reaching the end of the depicted route proceed directly on course;
- 3. Maintain last assigned altitude until 5 mins after take-off, then; climb to flight planned altitude.

Note: If communication failure occurs more than 5 minutes after take-off, comply with appropriate procedure for communication failure enroute.