

Departure Route Description

Rwy 16 – ½: Requires a minimum climb gradient of **500** ft/NM to **2100**. Climb to and maintain **3000**.

Note: Aircraft unable to meet the required climb gradient should refer to Nanaimo Departure Procedure.

Trees to 250 ASL within 0.5NM of departure end of rwy, RIGHT or rwy centre line. Hazard Beacon to 245 ASL approx. 0.4NM past departure end of rwy, 660' RIGHT of rwy centreline.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
500 FT/NM	750	1000	1170	1340	1500	1670	2090	2500

KATUB TRANSITION: Do not exceed 210kt prior to DASOG. Climb track **164°** to **(LADY2.KATUB)** UKROT, then track **114°** to GABOD, then track **064°** to SILGI, then track **334°** to DASOG, then track **310°** to KATUB.

ILATI TRANSITION: Do not exceed 210kt prior to ILATI. Climb track **164°** to **(LADY2.ILATI)** UKROT, then track **114°** to GABOD, then track **064°** to SILGI, then track **092°** to ILATI.

Communication Failure

On recognition of failure 5 minutes or less after take-off and in IFR weather conditions, proceed as follows:

- 1. Select transponder code 7600;
- 2. Upon reaching the end of the depicted route proceed directly on course;
- 3. Maintain last assigned altitude until 5 mins after take-off, then; climb to flight planned altitude.

Note: If communication failure occurs more than 5 minutes after take-off, comply with appropriate procedure for communication failure enroute.