



DEPARTURE PROCEDURE

Departure Procedure

Rwy 01 – ½:

Note:

Trees to 965 ASL abeam departure end of rwy, 410' LEFT of rwy centreline. Powerpole to 979 ASL abeam departure end of rwy, 430' RIGHT of rwy centreline. Trees to 981 ASL aprx 0.1 NM past departure end of rwy, 200' RIGHT of rwy centreline.

Rwy 09 – ½:

Requires a minimum climb gradient of 250 ft/NM to 1400.

Note:

Powerline and trees to 956 ASL aprx 0.1 NM past departure end of rwy. Trees to 1011 ASL aprx 0.6 NM past departure end of rwy, 590' RIGHT of rwy centreline.

or

SPEC VIS - Climb in visual conditions to cross the aprt at or above 1700 BPOC.

Rwy 19 – ½:

Note:

Trees to 936 ASL abeam departure end of rwy, 440' LEFT of rwy centreline. Trees to 932 ASL aprx 0.2 NM past departure end of rwy, 160' LEFT of rwy centreline.

Rwy 27 – ½:

Note:

Trees to 968 ASL abeam departure end of rwy, 460' LEFT of rwy centreline. Trees to 995 ASL aprx 0.3 NM past departure end of rwy, 660' RIGHT of rwy centreline. Trees to 1011 ASL aprx 0.6 NM past departure end of rwy, 1410' RIGHT of rwy centreline.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
250 FT/NM	380	500	590	670	750	840	1050	1250

DEPARTURE PROCEDURE

CYHS

EFF 25 JAN 24

CYHS-DP

Canada Air Pilot

Effective 0901Z 14 MAY 2026 to 0901Z 9 JUL 2026

Source of Canadian Civil Aeronautical Data: © 2026 NAV CANADA All rights reserved