

DEPARTURE PROCEDURE

Departure Procedure

All rwys: All rwys departure procedures not authorized when blasting area defined for St-Jean within the CFS Caution is active.

Rwy 02 – ½: Climb between hdg **355°** CCW to **195°** to remain clear of CYR605, CYA621 and CYA623.

Note: Trees to 174 ASL aprx 0.1 NM past departure end of rwy. Tower to 276 ASL aprx 0.5 NM past departure end of rwy, 900' RIGHT of rwy centreline.

Rwy 06 – ½: Climb between hdg **023°** CCW to **240°** to remain clear of CYR605, CYA621 and CYA623.

Note: Trees to 200 ASL aprx 0.1 NM past departure end of rwy. Tower to 247 ASL aprx 0.8 NM past departure end of rwy, 600' LEFT of rwy centreline.

Rwy 11 – ½: Climb between hdg **131°** CW to **285°** to remain clear of CYR605, CYA621 and CYA623.

Note: Trees to 203 ASL aprx 250' past departure end of rwy, 200' LEFT and RIGHT of rwy centerline and aprx 0.2 NM past departure end of rwy.

Rwy 20 – ½: Climb between hdg **128°** CW to **015°** to remain clear of CYR605, CYA621 and CYA623.

Note: Trees to 207 ASL aprx 0.4 NM past departure end of rwy, 500' LEFT of rwy centreline.

Rwy 24 – ½: Climb between hdg **128°** CW to **028°** to remain clear of CYR605, CYA621 and CYA623.

Note: Trees to 217 ASL aprx 0.2 NM past departure end of rwy, 400' LEFT and RIGHT of rwy centreline.

Rwy 29 – ½: Requires a minimum climb gradient of **270 ft/NM** to **400**. Climb between hdg **128°** CW to **028°** to remain clear of CYR605, CYA621 and CYA623.

Note: Trees to 259 ASL aprx 0.1 NM past departure end of rwy, both LEFT and RIGHT of rwy centreline.

or

SPEC VIS – Climb in visual conditions to cross the aprt at or above **700**, then on a heading between **021°** CCW to **138°** to MEA BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
270 FT/NM	410	540	630	720	810	900	1130	1350

DEPARTURE PROCEDURE

EFF 16 MAY 24

CYJN