

Departure Route Description

- All rwsy:** Maintain **9000** or as assigned. Contact Vancouver Centre after passing **4000**. Expect clearance to flight planned altitude/flight level 5 minutes after departure.
- Rwy 16 - ½:** Requires a minimum climb gradient of **410** ft/NM to **4000**. Climb hdg **160°**, intercept INBD track **232°** to "YWB" NDB. Then climb OBD track **246°** from "YWB" NDB for vectors to filed/assigned route.
- Note:** Trees to 1470 ASL aprx 0.1 NM past departure end of rwy, 500' LEFT and RIGHT of rwy centreline
- Rwy 34 - ½:** Requires a minimum climb gradient of **490** ft/NM to **3500**. Climb INBD track **330°** to "LW" NDB. Then climb OBD track **330°** from "LW" NDB for vectors to filed/assigned route.
- Aircraft unable to meet the required climb gradient should refer to Kelowna Departure Procedure.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
410 FT/NM	620	820	960	1100	1230	1370	1710	2050
490 FT/NM	740	980	1150	1310	1470	1640	2050	2450

Communication Failure

- On recognition of failure 10 minutes or less after take-off and in IFR weather conditions, proceed as follows:
- 1. Select transponder code 7600;
 - 2. Maintain last assigned transition waypoint;
 - 3. Upon reaching assigned transition waypoint, proceed directly on course;
 - 4. Climb to flight planned altitude.
- Note:** If communication failure occurs more than 10 minutes after take-off, comply with the appropriate procedure for communication failure enroute.