

This aeronautical information/data is published for OPS SPEC use only

KELOWNA, BC

CYLW

RNAV (GNSS) V RWY 16

495722N 1192240W VAR 15°E

MISA RW16

RESTRICTED

LPV NOT AUTH for aircraft with wingspan greater than 118'.
As required, shuttle descent to 8100 at MITAN.

MISSED APPROACH CLIMB RATE V/V (FPM)								
GROUND SPEED	90	120	140	160	180	200	250	300
380 FT/NM	570	760	890	1020	1140	1270	1590	1900

CYA122(A)(H) SFC TO 6200 CONT DAYLIGHT

MISA RW16

MISA RW16

WTMAN
IWP
7350 6600

TATVI
FAWP
4200

3.20%

4200

3100 (LNAV ONLY)

2840 (MDA)

160°

XOVTO
SDWP
3190

XEVIM
SDWP
2850 (LNAV ONLY)

RW16
MAWP

ELEV 1420
TDZE 1409

TCH 52'

9.4 2.8 1.0 1.1

MISSED APPROACH
Do not exceed 250 kt until EPRIP. Requires a minimum climb gradient of 380 ft/NM to 4400. Climb track 160° to EPRIP. Climbing RIGHT turn track 217° to VEPTO. Then climb track 228° to 9000 to MISIR. As required shuttle climb.

RASS: When using CYFF add 110'.			CATEGORY	A	B	C	D
			LPV	1660	(251)	1	
Knots	ft/min	Min:Sec	LNAV	2620	(1211)	3	
70	400		CIRCLING	* 2840	(1420)	3	
90	510						
110	620						
130	740						
150	850						

RNAV (GNSS) V RWY 16

EFF 17 APR 25

REGULATORY REVIEW 30 SEP 2027

CYLW-IAP-3F

CYLW

Source of Canadian Civil Aeronautical Data: © 2026 NAV CANADA All rights reserved

RESTRICTED