

CYMU

76 31.5 76 30.7

ANNUAL RATE OF CHANGE 12' E

56 32.4

AS 02 ELEV 251

203°

Down 1.0% first 690'

3521 x 100

gravel

CYMU N56 32.17 W76 31.10

AS 02 ELEV 247

203°

Down 0.5% first 590'

56 32

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
460 FT/NM	690	920	1080	1230	1380	1540	1920	2300

TAKE-OFF MINIMA

Runws 02, 20: *

SCALE IN FEET

1000 0 1000

* DEPARTURE PROCEDURE
Rwy 02 - ½ - Requires a minimum climb gradient of **460 ft/NM** to **1200**.
 Climb hdg **023°** to **1900 BPOC**.
Note: Terrain to 313 ASL abeam departure end of rwy, 500' RIGHT of rwy centerline.
 or
SPEC VIS - Climb in visual conditions to cross the apt at or above **1600 BPOC**.
Rwy 20 - ½ - Climb hdg **203°** to **1500 BPOC**.
Note: Terrain to 392 ASL aprx 0.4 NM past departure end of rwy, LEFT of rwy centerline.

Source of Canadian Civil Aeronautical Data: © 2026 NAV CANADA All rights reserved

CYMU