

PAR (DND)

ATIS – 118.25 260.0	TML – 124.5 322.8 PAR – 119.4 336.0	TWR – 126.2 226.5 236.6 255.7 ADVSY Cold Lake – 126.2	GND – 121.9 275.8	ELEV 1775
---------------------	--	---	----------------------	-----------

14-06Z (DT 13-05Z) Mon-Fri, clsd Sat/Sun & Hol. Hrs may vary without notice.
Preventive maint Wed 01-07Z (DT 00-06Z) dur VFR Hol altn Thu.
MINIMUM SAFE ALTITUDE WITHIN 25 NM OF AERODROME **3800'** ASL.

Precision Approach Radar (PAR)

Rwy	G/S	TCH	GPI	TDZE	DA	VIS & RVR	HAT
13L	3.0°	46'	880	1772	1972	½	200
13R	3.0°	59'	1122	1771	1971	½	200
22	3.0°	44'	850	1767	1967	½	200
31R	3.0°	44'	850	1775	1975	½ RVR 26	200

Missed Approach

Rwy	Procedure
13L	Climb heading 129° to 5000' . LEFT turn direct Cold Lake NDB or R-093 at 15 DME as appropriate.
13R	Climb heading 129° to 5000' . LEFT turn direct Cold Lake NDB or R-093 at 15 DME as appropriate.
22	Climb heading 219° to 5000' . LEFT turn to Cold Lake NDB or R-093 at 15 DME as appropriate.
31R	Climb heading 309° to 5000' . RIGHT turn direct Cold Lake NDB or R-093 at 15 DME as appropriate.

PAR (DND)

EFF 21 MAR 24

CYOD